

Tooling by
DIJET[®]
INDEXABLE TOOLS


2026~2027



- All cutter-holders are supplied without Inserts , Wrench & MOLY.
- Specifications for the products listed in this catalog are subject to change without notice due to replacement or modification.

ABOUT STOCK

- : Stocked Items ○: Stock in JAPAN ◎: Soon to be stocked *: To be discontinued

CUTTING STYLE ICON**COATING ICON****TYPE OF MACHINING****OTHERS**

G-BODY is a GN surface-hardening treatment on thermal resistant high strength steel giving a hardness over 65HRC and secures insert pocket and holder against thermal deformation improving body durability.








Carbide shank provides much lower deflection than steel shank, that enables maximum tool life and highest productivity.










INDEXABLE TOOLS













MILLING TOOLS QUICK GUIDE | Modular Head Type

Type	Item Code	Shape / Tool dia.	Cutting edge angle / Max.DOC	Applications	
HIGH FEED COPY MILLING	SKS-GII	O.D. 0 Tolerance -0.1 Insert N, E, M Class 		     	
	MSG Type				
	A043	Ø25-42			
HIGH FEED COPY MILLING	SKS-GII-09	O.D. 0 Tolerance -0.1 Insert E Class 		     	
	MSG-09 Type				
	A054	Ø20-42			
HIGH FEED COPY MILLING	SKS EXTREME	O.D. -0.05 Tolerance -0.15 Insert M Class 		     	
	MEX-05 Type				
	A062	Ø20-40			
HIGH FEED COPY MILLING	SKS EXTREME	O.D. -0.05 Tolerance -0.15 Insert M Class 		     	
	MEX-07 Type				
	A064	Ø32-42			
HIGH FEED COPY MILLING	QM GII	Insert M Class 		    	
	MXG-07 Type				
	A075	Ø10-16			





Type	Item Code	Shape / Tool dia.	Cutting edge angle / Max.DOC	Applications	
HIGH FEED COPY MILLING	QM MAX GII	 Insert M_{Class} Ø16-42	 RE1.2	     	
	MXG Type				
	A083				
HIGH FEED COPY MILLING	QM MAX	 Insert H, M_{Class} Ø16-42	High Feed O.D. Tolerance -0.06 -0.14  RE1.2~RE2.0 Shoulder Milling O.D. Tolerance -0.03 -0.11  RE0.4~RE2.0	      	
	MQX Type				
	A094				
HIGH FEED COPY MILLING	QM MILL	 Insert H, M_{Class} Ø10-32	High Feed O.D. Tolerance -0.05 -0.15  RE1.0~RE2.0 Shoulder Milling O.D. Tolerance -0.02 -0.12  RE0.2~RE0.8	      	
	MPM Type				
	A108				
SHOULDER MILLING	HIGH PRECISION QM MILL	O.D. Tolerance 0 -0.03  Insert H, M_{Class} Ø10-16	 RE0.2~RE0.8	 	
	MPT Type				
	A108				
SHOULDER MILLING	EXTREME SAP	O.D. Tolerance -0.04 -0.1  Insert G_{Class} Ø16-40	 RE0.4~RE1.6	    	
	MSX-11 Type				
	A118				

MILLING TOOLS QUICK GUIDE | Modular Head Type

Type	Item Code	Shape / Tool dia.	Cutting edge angle / Max.DOC	Applications	
SHOULDER MILLING	EXTREME SAP	O.D. -0.05 Tolerance -0.15 Insert G _{Class}		     	
	MSX-17 Type				
	A122	Ø25-40			
SHOULDER MILLING	SIC-EVO	O.D. -0.05 Tolerance -0.15 Insert E, M _{Class}		     	
	SSV Type				
	A136	Ø25-40			
FINISHING COPY MILLING	MIRROR BALL	O.D. ± 0.008 Tolerance Insert F _{Class}		  	
	MBX Type				
	A145	Ø10-30			
FINISHING COPY MILLING	MIRROR RADIUS	O.D. -0.002 Tolerance -0.018 Insert F _{Class}		    	
	MRX Type				
	A155	Ø10-32			
FINISHING UP & DOWN MILLING	BACK & FORTH CUTTER	O.D. $+0.1$ Tolerance -0.3 Insert G _{Class}		 	WEB CATALOGUE 
	MPF Type				
	Available only on WEB CATALOGUE	Ø30-40			






Type	Item Code	Shape / Tool dia.	Cutting edge angle / Max.DOC	Applications	
FINISHING COPY MILLING	DIEMASTER 5G	O.D. 0.0 Tolerance -0.05 Insert H Class 		  	
	MXF Type				
	A169	Ø16-42			
ROUGHING COPY MILLING	SWING BALL	Tool dia. O.D. Tolerance φ16 0 -0.1 φ20, φ25 -0.01 -0.11 φ30 -0.05 -0.15 		  	WEB CATALOGUE 
	MSWX Type	Insert G Class			
	Available only on WEB CATALOGUE	Ø16-30			
ROUGHING COPY MILLING	SWING BALL	O.D. -0.05 Tolerance -0.15 Insert G Class 		  	WEB CATALOGUE 
	MSW Type				
	Available only on WEB CATALOGUE	Ø32			
COPY MILLING	SUPER DIEMASTER	O.D. 0 Tolerance -0.1 Insert G.M Class 		  	
	SDH Type				
	A175	Ø15-42			
COPY MILLING	EXTREME DIEMASTER	O.D. 0 Tolerance -0.1 Insert M Class 		  	WEB CATALOGUE 
	MTX Type				
	Available only on WEB CATALOGUE	Ø32-40			

MILLING TOOLS QUICK GUIDE | Modular Head Type








Type	Item Code	Shape / Tool dia.	Cutting edge angle / Max.DOC	Applications	
FOR ALUMINIUM ALLOY	AERO CHIPPER	O.D. Tolerance 0 - 0.1 Insert E Class		    	
	MAM Type				
	A193	Ø16-42			
FOR ALUMINIUM ALLOY	AERO CHIPPER	O.D. Tolerance - 0.04 - 0.1 Insert G Class		     	
	MAL Type				
	A194	Ø20-40			
FINISHING SIDE & BOTTOM FACE	BACK DRAFT CUTTER	O.D. Tolerance 0 - 0.1 Insert H Class	Bottom Finishing  Side Finishing 	    	WEB CATALOGUE 
	MDB Type				
	Available only on WEB CATALOGUE	Ø20-40			

Type	Item Code	Shape / Tool dia.	Cutting edge angle / Max.DOC	Applications	
FOR HIGH EFFICIENCY MACHINING	CARBIDE SHANK				
	MSN Type	MSN Type Ø10-32			
	A208	 MSN-S Type Ø9.8-32			




MILLING TOOLS QUICK GUIDE | Shank Type



Type	Item Code	Shape / Tool dia.	Cutting edge angle / Max.DOC	Applications	
HIGH FEED COPY MILLING	SKS-GII-09	 O.D. — 0 Tolerance — 0.1 Insert E Class Ø25-40	 0.9 RE1.2	   	
	SKG-09 Type				
	A055				
HIGH FEED COPY MILLING	SKS EXTREME	 O.D. — 0.05 Tolerance — 0.15 Insert M Class Ø20-33	 1.5 RE2.0	    	
	EXSKS-05 Type				
	A063				
HIGH FEED COPY MILLING	SKS EXTREME	 O.D. — 0.05 Tolerance — 0.15 Insert M Class Ø32-40	 2 RE2.0	    	
	EXSKS-07 Type				
	A065				
HIGH FEED COPY MILLING	QM GII	 O.D. — 0.05 Tolerance — 0.15 Insert M Class Ø10-14	 0.5 RE1.0	    	
	GMX-07 Type				
	A076				
HIGH FEED COPY MILLING	QM MAX GII	 O.D. — 0.05 Tolerance — 0.15 Insert M Class Ø16-32	 1 RE1.2	    	
	GMX Type				
	A082				

MILLING TOOLS QUICK GUIDE | Shank Type

Type	Item Code	Shape / Tool dia.	Cutting edge angle / Max.DOC	Applications
HIGH FEED COPY MILLING	QM MAX	 Insert H,M Class Ø16-25	High Feed O.D. Tolerance -0.06 -0.14  Shoulder Milling O.D. Tolerance -0.03 -0.11 	     
	QXPS Type			
	A093			
HIGH FEED COPY MILLING	QM MILL	 Insert H,M Class Ø10-14	High Feed O.D. Tolerance -0.05 -0.15  Shoulder Milling O.D. Tolerance -0.02 -0.12 	     
	PME Type			
	A107			
SHOULDER MILLING	EXTREME SAP	O.D. Tolerance -0.03 -0.11 Insert G Class  Ø16-40	 RE0.4~RE1.6	    
	EXSAP-11 Type			
	A117			
SHOULDER MILLING	EXTREME SAP	O.D. Tolerance -0.05 -0.15 Insert G Class  Ø25-40	 RE0.4~RE3.0	    
	EXSAP-17 Type			
	A121			
SHOULDER MILLING	SIC-EVO	O.D. Tolerance -0.05 -0.15 Insert E,M Class  Ø25-40	 RE0.4 ~ RE5.0	     
	SSV Type			
	A137			






MILLING TOOLS QUICK GUIDE | Shank Type







Type	Item Code	Shape / Tool dia.	Cutting edge angle / Max.DOC	Applications									
SHOULDER MILLING	SIC-EVO	Insert M Class  Ø32-40	 43 ~ 57	Face Milling Copy Milling Pocket Milling Helical Interpolation Slotting Shoulder Milling 									
	SSVL Type												
	A138												
FINISHING COPY MILLING	MIRROR BALL	O.D. Tolerance ±0.008 Insert F Class  Ø6-12	 R3~R6	Copy Milling Pocket Milling Slotting									
	BNM Type												
	A144												
FINISHING COPY MILLING	MIRROR RADIUS	O.D. Tolerance -0.002 / -0.018 Insert F Class  Ø6-12	 RE0~RE3.0 1° (RNM) 3° (HRM/FRM)	Face Milling Copy Milling Pocket Milling Helical Interpolation Shoulder Milling									
	RNM Type												
	A154												
ROUGHING COPY MILLING	SWING BALL	<table><tr><th>Tool dia.</th><th>O.D.</th></tr><tr><td>φ16</td><td>0 - 0.1</td></tr><tr><td>φ20, φ25</td><td>-0.01 - 0.11</td></tr><tr><td>φ30</td><td>-0.05 - 0.15</td></tr></table> Insert G Class  Ø16-30	Tool dia.	O.D.	φ16	0 - 0.1	φ20, φ25	-0.01 - 0.11	φ30	-0.05 - 0.15	 R8~R15	Copy Milling Shoulder Milling Slotting	WEB CATALOGUE 
	Tool dia.		O.D.										
	φ16		0 - 0.1										
φ20, φ25	-0.01 - 0.11												
φ30	-0.05 - 0.15												
SWBX Type													
Available only on WEB CATALOGUE													
ROUGHING COPY MILLING	SWING BALL	O.D. Tolerance -0.05 / -0.15 Insert G Class  Ø32-50	 R16~R25	Copy Milling Shoulder Milling Slotting	WEB CATALOGUE 								
	SWB Type												
	Available only on WEB CATALOGUE												

Type	Item Code	Shape / Tool dia.	Cutting edge angle / Max.DOC	Applications	
FOR ALUMINIUM ALLOY	AERO CHIPPER	 O.D. 0 Tolerance -0.1 Insert G Class		     	
	ALXM Type				
	A195				
FINISHING SIDE & BOTTOM FACE	BACK DRAFT CUTTER	 O.D. 0 Tolerance -0.1 Insert H Class	Bottom Finishing Side Finishing 	    	WEB CATALOGUE 
	DBD Type				






Available only on WEB CATALOGUE

MILLING TOOLS QUICK GUIDE | Bore Type






Type	Item Code	Shape / Tool dia.	Cutting edge angle / Max.DOC	Applications	
HIGH FEED COPY MILLING	SKS-II	O.D. Tolerance: -0.05 / -0.15 Insert: N, E, M Class 		     	
	SKG Type				
	A042	Ø50-100			
HIGH FEED COPY MILLING	SKS-II-09	O.D. Tolerance: -0.05 / -0.15 Insert: E Class 		     	
	SKG-09 Type				
	A054	Ø40-80			
HIGH FEED COPY MILLING	SKS EXTREME	O.D. Tolerance: -0.05 / -0.15 Insert: M Class 		     	
	EXSKS-05 Type				
	A062	Ø40-63			
HIGH FEED COPY MILLING	SKS EXTREME	O.D. Tolerance: -0.05 / -0.15 Insert: M Class 		     	
	EXSKS-07 Type				
	A064	Ø50-100			
HIGH FEED COPY MILLING	SKS EXTREME	O.D. Tolerance: 0 / -0.2 Insert: M Class 		     	
	EXSKS-09 Type				
	A066	Ø50-160			

Type	Item Code	Shape / Tool dia.	Cutting edge angle / Max.DOC	Applications	
HIGH FEED COPY MILLING	QM MAX GII	O.D. Tolerance — 0.05 — 0.15 Insert M Class  Ø40-66		     	
	GMX Type				
	A081				
HIGH FEED COPY MILLING	QM MAX	Insert H, M Class  Ø40-66	High Feed O.D. Tolerance — 0.05 — 0.15  RE1.2 Shoulder Milling O.D. Tolerance — 0.02 — 0.12  RE0.4~RE2.0	      	
	QXP Type				
	A092				
SHOULDER MILLING	EXTREME SAP	Tool dia. O.D. Tolerance Ⅲ φ63 — 0.03 — 0.11 φ80 — 0.02 — 0.12 Insert G Class  Ø40-80		    	
	EXSAP-11 Type				
	A116				
SHOULDER MILLING	EXTREME SAP	Tool dia. O.D. Tolerance Ⅲ φ80 — 0.05 — 0.15 φ100 0 — 0.2 Insert G Class  Ø50-125		     	
	EXSAP-17 Type				
	A120				
SHOULDER MILLING	SHOULDER 6	Tool dia. O.D. Tolerance Ⅲ φ80 — 0.05 — 0.15 φ100 0 — 0.2 Insert M Class  Ø50-160		   	
	EXSIX Type				
	A131				





MILLING TOOLS QUICK GUIDE | Bore Type






Type	Item Code	Shape / Tool dia.	Cutting edge angle / Max.DOC	Applications	
SHOULDER MILLING	SIC-EVO	Tool dia. O.D. Tolerance $\leq \varnothing 80$ - 0.05 - 0.15 $\varnothing 100$ - 0.025 - 0.175 Insert E, M Class 	 15 RE0.4 ~ RE5.0	     	
	SSV Type				
	A136	Ø40-125			
SHOULDER MILLING	SIC-EVO	O.D. Tolerance ± 0.2 Insert M Class 	 57 ~ 71	      	
	SSVL Type				
	A138	Ø50-80			
SUPER FINISHING FOR FLAT FACE	FINISH JET MILL	O.D. Tolerance ± 0.2 Insert H Class 	Super Finishing Corner Finishing  0.05~0.3 0.05~0.3 3.5°		WEB CATALOGUE 
	FJM Type				
	Available only on WEB CATALOGUE	Ø80-250			
FINISHING UP & DOWN MILLING	BACK & FORTH CUTTER	O.D. Tolerance $+0.1$ -0.3 Insert G Class 	 3 0.05~0.5	 	WEB CATALOGUE 
	PFC Type				
	Available only on WEB CATALOGUE	Ø50-80			
FINISHING COPY MILLING	DIEMASTER 5G	O.D. Tolerance 0.0 - 0.5 Insert H Class 	 0.5 RE 1.0	  	
	XFG Type				
	A168	Ø50-66			

MILLING TOOLS QUICK GUIDE | Bore Type

Type	Item Code	Shape / Tool dia.	Cutting edge angle / Max.DOC	Applications	
COPY MILLING	SUPER DIEMASTER	 O.D. Tolerance 0 -0.2 Insert G,M Class Ø50-80	 RE6.0~RE8.0	   	
	HDM Type				
	A174				
COPY MILLING	EXTREME DIEMASTER	 O.D. Tolerance 0 -0.2 Insert M Class Ø50-63	 RE6.0	   	WEB CATALOGUE 
	EXTDM Type				
	Available only on WEB CATALOGUE				
FOR HEAVY MACHINING	PNS-REBORN	 Insert M Class Ø50-250	HIGH FEED  FACE MILLING  2.5 5.0	 	
	PNS Type				
	A182				
FOR HEAVY MACHINING	HEPTA MILL	 O.D. Tolerance -0.025 -0.175 Insert H,M Class Ø50-200	 12 5 12	     	
	HEP Type				
	A186				
FOR ALUMINIUM ALLOY	AERO CHIPPER	 O.D. Tolerance 0 -0.1 Insert E Class Ø40-80	 8 RE0.4~RE2.0	     	
	AMX Type				
	A192				

MILLING TOOLS QUICK GUIDE | Bore Type

Type	Item Code	Shape / Tool dia.	Cutting edge angle / Max.DOC	Applications	
FOR ALUMINIUM ALLOY	AERO CHIPPER	O.D. Tolerance 0 -0.1 Insert G Class 	 RE0.2~RE4.0	     	
	ALX Type				
	A194	Ø50-63			
FINISHING SIDE & BOTTOM FACE	BACK DRAFT CUTTER	O.D. Tolerance 0 -0.1 Insert H Class 	Bottom Finishing  Side Finishing 	    	WEB CATALOGUE 
	DBD Type Available only on WEB CATALOGUE	Ø50-80			
ROUGHING COPY MILLING	RADIUS MILL	O.D. Tolerance -0.05 -0.15 Insert M Class 	 RE10	    	WEB CATALOGUE 
	WDR Type Available only on WEB CATALOGUE	Ø50-63			

Type	Item Code	Shape / Tool dia.	Barrel R	Applications	
5 - AXIS	MIRROR BARREL	O.D. -0.002 Tolerance -0.018 Insert F_{Class} 		    	
	KRM Type				
	A027	Ø16-30			
5 - AXIS	MIRROR BARREL	O.D. ± 0.008 Tolerance Insert F_{Class} 		  	
	TNM Type				
	A028	Ø16-20			
5 - AXIS	MIRROR BARREL	O.D. ± 0.008 Tolerance Insert F_{Class} 		   	
	TPM Type				
	A029	Ø16-20			
5 - AXIS	MIRROR BARREL	O.D. ± 0.008 Tolerance Insert F_{Class} 		    	
	LRM Type				
	A030	Ø16-30			
5 - AXIS	HIGH PRECISION QM MAX	O.D. 0 Tolerance -0.03 Insert H_MClass 		 	
	MQT Type				
	A032	Ø16-35			

DESIGNATION SYSTEM FOR MILLING INSERT



1 Shape

Symbol	Shape	Nose angle	Figure
H	Hexagonal	120°	
O	Octagonal	135°	
P	Pentagonal	108°	
S	Square	90°	
T	Triangular	60°	
C	Rhombic	80°	
D		55°	
E		75°	
M		86°	
V		35°	
L	Rectangular	90°	
A	Parallelogram	85°	
R	Round	—	
W	Special design	others	
X			
Y			
Z			

2 Relief angle

Symbol	Relief angle
B	5°
C	7°
D	15°
E	20°
F	25°
G	30°
N	0°
P	11°
O	others

3 Accuracy

Tolerance (mm)

Symbol	Corner height	Thickness	I.C. dia.
C	±0.013	±0.025	±0.025
E	±0.025	±0.025	±0.025
G	±0.025	±0.13	±0.025
H	±0.013	±0.025	±0.013
K	±0.013	±0.025	±0.05~±0.13
L	±0.025	±0.025	±0.05~±0.13
M	±0.08~±0.18	±0.13	±0.05~±0.13
N	±0.08~±0.18	±0.025	±0.05~±0.13
U	±0.13~±0.38	±0.13	±0.08~±0.25

Inscribed circle	Tolerance on I.C. dia. K, L, M (class)	Tolerance on corner height M (class)
6.35	±0.05	±0.08
9.525		
12.7	±0.08	±0.13
15.875	±0.1	±0.15
19.05		

4 Groove

Symbol	Shape	Symbol	Shape
N		U	
R		B	
F		H	
W		C	
T		J	
Q		X	others

04 15 ZP E R - S M

6

Insert thickness

7

Corner configuration

7

8

Corner configuration / Corner angle

9

Cutting edge condition

10

Feed direction

11

Classification I

12

Classification II

5 Cutting edge length

Symbol	length (ℓ)	Symbol	length (ℓ)
H		C M D V E	
O		L	
S		A	
T		R	

6 Thickness

Symbol	Thickness (mm)
02	2.38
T2	2.78
03	3.18
T3	3.97
04	4.76
05	5.56
06	6.35
07	7.94
09	9.52

7 Corner configuration

Symbol	Corner radius (mm)
02	0.2
04	0.4
08	0.8
12	1.2
15	1.5
16	1.6
20	2.0
25	2.5
30	3.0
32	3.2
40	4.0

8 Corner angle


Symbol	Clearance
D	15°
E	20°
F	25°
G	30°
P	11°



9 Symbols of major cutting edge

Symbol	Condition of cutting edge	Shape
F	Sharp edge	
E	Round honing	
T	Angle honing	
S	Combination Honing	

Symbol	Corner angle
A	45°
E	75°
P	90°
Z	others
MO	Round



10 Feed direction

Symbol	Hand
R	Right
L	Left
N	Neutral

11 Classification I

Symbol	Work
P	Steel
M	Stainless Steel
K	Cast iron
N	Non ferrous material
S	Heat resistant alloy
H	Hardened material

12 Classification II

Symbol	Application
L	Light cutting
M	Medium cutting
H	Heavy cutting

HIGH FEED TOOLS LINE-UP

HIGH STRENGTH INSERT WITH
SHARPNESS & STABILITY.
RELIABLE EVEN AT HIGH FEED RATE &
HIGH DEPTH OF CUT.
DEVELOPED FOR HIGH METAL REMOVAL
MACHINING.

$$ap \leq 3\text{mm}$$

Rigidity

SKS SERIES

SKS SERIES

SKS EXTREME EXSKS 09 Type



- 6 cutting edges
- High metal removal
- Max.ap = 3mm
- Machine type: BT50
- Program R : R3.5

SKS EXTREME EXSKS 07 Type



- 6 cutting edges
- Excellent balance of stability and sharpness
- Max.ap = 2mm
- Machine type: BT50
- Program R : R3.0

SKS GII SKG/MSG Type



- 4 cutting edges
- For High feed & High D.O.C. machining
- Max.ap = 1.5-2.5mm
- Machine type: BT40-50
- Program R : R2.0-R4.0

SKS EXTREME EXSKS 05 Type



- 6 cutting edges
- For High feed machining with multi-flutes
- Max.ap = 1.5mm
- Machine type: BT40-50
- Program R : R2.5

ADVANCED 3-D SHAPED CUTTING EDGE
INSERT WITH LOW CUTTING FORCE
GEOMETRY . MULTI-FLUTES
SPEC. HOLDER . DEVELOPED FOR HIGH
SPEED MACHINING EVEN ON SMALL
SIZED MACHINE.

$$ap \leq 1\text{mm}$$

QM SERIES

Low cutting force

QM SERIES

QM MAX GII GMX/MXG Type



- 4 cutting edges
- Machining wide variety of materials
- Max.ap = 1.0mm
- Machine type: BT40-50
- Program R : R1.5

QM MAX QXP/MQX Type



- 2 cutting edges
- Multiple insert choices for wide range of applications
- Max.ap = 1.0mm
- Machine type: BT40-50
- Program R : R1.5

QM GII GMX07/MXG07 Type



- 4 cutting edges
- Machining wide variety of materials
- Max.ap = 0.5mm
- Machine type: BT30-40
- Program R : R1.0

QM MPM/PME Type



- 2 cutting edges
- For roughing to finishing
- low cutting force
- Max.ap = 0.4mm
- Machine type: BT30-40
- Program R : R1.0

● Range of Tool Dia.

Product	No. of corners	Insert spec.	Max. ap(mm)	DC (mm)																
				10	12	16	20	25	32	40	50	52	63	66	80	100	125	160		
QM	2	single sided	0.4	←→																
QM G II	4	double sided	0.5	←→																
QM MAX	2	single sided	1.0			←→														
QM MAX G II	4	double sided	1.0			←→														
EXSKS 05	6	double sided	1.5			←→														
SKSG II	4	single sided	0.9-2.5			←→														
EXSKS 07	6	double sided	2.0					←→												
EXSKS 09	6	double sided	3.0						←→											

SHOULDER MILLING TOOLS LINE-UP

■ Shoulder Milling Series

SIC-EVO (ZOMT16)
QM MAX (ZPMT10)
QM MILL (ZOMT06)



- Single-sided 2 cutting edge insert
- Excellent chips control design
- Reliable even for long overhang machining

SHOULDER EXTREME
EXSAP-11 type
EXSAP-17 type



- Double-sided 4 cutting edge insert
- G class ground insert gives good surface finish on bottom & side wall

SHOULDER 6
EXSIX type



- Double-sided 6 cutting edge insert
- High cutting edge strength
- For heavy roughing process

Range of Tool Dia.

Product	No. of corners	Insert spec.	MAX. ap (mm)	Tool Dia. (mm)													
				10	16	20	25	32	40	50	52	63	66	80	100	125	160
QM MILL	2	Single sided	5	← Ø10~Ø32 →													
QM MAX	2	Single sided	9		← Ø16~Ø66 →												
SIC-EVO	2	Single sided	15				← Ø25~Ø125 →										
EXSAP-11	4	Double sided	10		← Ø16~Ø80 →												
EXSAP-17	4	Double sided	15				← Ø25~Ø125 →										
EXSIX	6	Double sided	10							← Ø50~Ø160 →							

Selection Guide

Product	Cutting Force	Chip Control	Surface Finish	Wall Accuracy	Cutting Edge Strength	No. of Cutting Edges
SIC-EVO (ZOMT16) QM MAX (ZPMT10) QM MILL (ZOMT06)	★★★★	★★★★	★★	★★	★	★
EXSAP11 EXSAP17	★★	★★	★★★★	★★★★	★★	★★
EXSIX	★★	★★	★	★★	★★★★	★★★★

Modular Head Series

■ PROPER MOUNTING OF MODULAR HEADS

1 Cleaning



Remove dirt and chips with air from the connecting thread and face of modular head and MSN/MGN shank holder.

2 Initial Tightening



Tighten by hand until the head and the shank holder faces touch.

3 Final Tightening



Tighten slowly with torque control spanner wrench or DIJET DS type spanner wrench and confirm that there is no gap.

- Attention)
1. Final tightening without initial tightening causes connecting thread damage.
 2. Only use DS type spanner wrench using Solid modular head (SMSA/SMSR/SMAL type)

Attention

1. Only use torque control spanner wrench or DIJET DS type spanner wrench.
In case of choosing torque control spanner wrench, confirm that the wrench size is matched to the dimensions W & C of each modular head.



Torque control spanner



Spanner wrench (DS type)

2. Only apply gentle pressure on wrench.
3. Confirm there is no gap between MSN/MGN shank holder and modular head

■ Steel modular heads

Thread	Tightening torque	Spanner size(W)
M6	8.0N·m	8 [☆] 10
M8	16N·m	12 [☆]
M10	16N·m	14, 15
M12	20N·m	17, 19
M16	25N·m	22, 26

■ Solid modular heads(SMSA/SMSR/SMAL)


Thread	Tightening torque	Spanner size(W)	Cat.No. 
M8	10~11N·m	14	DS-14
M10	10~11N·m	14	DS-14
M10	10~16N·m	17	DS-17
M12	15~20N·m	19, 22	DS-19, DS-22
M16	20~25N·m	27	DS-27

Note) Modular heads are supplied without spanner wrench

SELECTION OF MSN CARBIDE SHANK HOLDER

When using modular head over $\varnothing 16\text{mm}$, please select MSN carbide shank with a diameter ($\varnothing D1$) at least 1mm smaller than modular head ($\varnothing Dc$).

Wrong selection can cause damage to the carbide shank.



Caution for mounting in shrink fit holder.

When you use a carbide shank and a modular head on a shrink fit holder, please shrink fit only the carbide shank without mounting the modular head. Mount the modular head on the shank after shrink fit operation is complete.

In case of shrink fit MSN shank + modular head together, it will be difficult to loosen due to heat

5-AXIS Series

TECHNOLOGY

Designs that allow you to machine freely & quickly


Advanced machining technology that enables high-precision and high efficiency

A line-up that supports machining of complex shapes found in the Die&Mould and Aerospace industries.

5
axis

KRM
TYPE

Insert for "MIRROR BARREL"



Radius form accuracy
on the outer periphery
 $\pm 0.010\text{mm}$

Corner radius accuracy
of inserts within
 $\pm 0.010\text{mm}$

Cat.No.	Grade		Dimensions (mm)					
	JC8015	DH102	DC	RE	BR	L	S	C
KRM-160-R10-BR50	●	●	16	1	50	12	4	5.7
KRM-200-R10-BR60	●	●	20	1	60	15	5	6.8
KRM-250-R10-BR60	●	●	25	1	60	18.5	6	7.3
KRM-300-R10-BR60	●	●	30	1	60	22.5	7	9.1

MRX
TYPE


Modular Type

Through
coolant
hole

5
axis

Accuracy of MRX after combined O.D. run out: below $15\mu\text{m}$ (Target below $10\mu\text{m}$).

When using KRM type insert/Corner radius accuracy: within $\pm 0.010\text{mm}$. Radius form accuracy on the outer periphery: within $\pm 0.010\text{mm}$.



Cat.No.	Stock	Dimensions (mm)						Insert	Parts	
		DC	LF	DCSFMS	MD	C	W		Screw	Wrench
MRX-160-M8	●	16	23	15	M8	8	12	RNM-160/170... FRM-160/170... /HRM-160/170... /KRM-160...	FSW-4013H	A-15
MRX-200-M10	●	20	30	18.5	M10	9	14	RNM-200... FRM-200/210... /HRM-200/220... /KRM-200...	FSW-5016H	A-20W
MRX-250-M12	●	25	35	24	M12	10	17	— /FRM-250... /KRM-250...	FSW-6020	A-30
MRX-300-M16	○	30	43	29	M16	12.5	22	— /FRM-300... /KRM-300...	KSW-8025	A-30


Clamp screw	Torque(N·m)
FSW-4013H	3.0
FSW-5016H	4.0
FSW-6020	6.0
KSW-8025	6.0

5-AXIS Series

TNM Type

5
axisTNM
TYPE

Insert for "MIRROR BARREL"




Corner radius accuracy
of inserts within
 $\pm 0.010\text{mm}$

Cat.No.	Grade		Dimensions (mm)					
	JC8015	FZ15	DC	RE	BR	L	S	C
TNM-160-NR6BR32	●	●	16	6	32	18	4	1
TNM-200-NR8BR40	●	●	20	8	40	21	5	1

Through
coolant
hole5
axisMTP
TYPE

MIRROR BARREL Modular Type

Accuracy of MTP after combined O.D. run out: below $15\text{ }\mu\text{m}$ (Target below $10\text{ }\mu\text{m}$).
When using TNM type insert / Radius form accuracy on the outer periphery: within $\pm 0.010\text{mm}$.




Cat.No.	Stock	Dimensions (mm)						Insert	Parts	
		DC	LF	DCSFMS	MD	C	W		Screw	Wrench
MTP-160-M8	●	16	29	15	M8	8	12	TPM-160... TNM-160...	FSW-4013H	A-15
MTP-200-M10	●	20	36	19	M10	9	14	TPM-200... TNM-200...	FSW-5016H	A-20W

Clamp screw	Torque(N·m)
FSW-4013H	3.0
FSW-5016H	4.0

5
axis

TPM
TYPE

Insert for "MIRROR BARREL"



Radius form accuracy
on the outer periphery
±0.010mm

Radius accuracy
of inserts within
±0.010mm

Cat.No.	Grade		Dimensions (mm)						
	JC8015	DH102	DC	RE	BR	L	S	C	θ°
TPM-160-NR2T30BR400	●	●	16	2	400	17	4	1	30°
TPM-200-NR2T30BR500	●	●	20	2	500	20	5	1	30°

Through
coolant
hole


5
axis

MTP
TYPE

MIRROR BARREL Modular Type

Accuracy of MTP after combined O.D. run out: below 15 μm (Target below 10μm).

When using TPM type insert / Corner Radius accuracy: within ±0.010mm. Radius form accuracy on the outer periphery: within ±0.010mm.



Cat.No.	Stock	Dimensions (mm)						Insert	Parts	
		DC	LF	DCSFMS	MD	C	W		Screw	Wrench
MTP-160-M8	●	16	28	15	M8	8	12	TPM-160... TNM-160...	FSW-4013H	A-15
MTP-200-M10	●	20	35	19	M10	9	14	TPM-200... TNM-200...	FSW-5016H	A-20W




Clamp screw	Torque(N·m)
FSW-4013H	3.0
FSW-5016H	4.0

5-AXIS Series

LRM Type

LRM
TYPE

Insert for "MIRROR BARREL"


5
axisRadius form accuracy
on the bottom
 $\pm 0.010\text{mm}$ Corner radius accuracy
of inserts within
 $\pm 0.010\text{mm}$

Cat.No.	Grade		Dimensions (mm)					
	JC8015	DH102	DC	RE	BR	L	S	C
LRM-160-R20-BR32	●	●	16	2	32	12	4	2
LRM-200-R30-BR40	●	●	20	3	40	15	5	2
LRM-250-R30-BR50	●	●	25	3	50	18.5	6	2.5
LRM-300-R30-BR60	●	●	30	3	60	22.5	7	3

Through
coolant
hole5
axisMBX
TYPE

Modular Type

Accuracy of MBX after combined O.D. run out: below $15\mu\text{m}$ (Target below $10\mu\text{m}$).
When using LRM type insert/Corner radius accuracy: within $\pm 0.010\text{mm}$. Radius form accuracy on the front edge: within $\pm 0.010\text{mm}$.



Cat.No.	Stock	Dimensions (mm)						Insert		Parts	
		DC	LF	DCSFMS	MD	C	W			Screw	Wrench
MBX-160-M8	●	16	23	15	M8	8	12	BNM-160...	LRM-160...	FSW-4013H	A-15
MBX-200-M10	●	20	30	19	M10	9	14	BNM-200...	LRM-200...	FSW-5016H	A-20W
MBX-250-M12	●	25	35	24	M12	10	17	BNM-250...	LRM-250...	FSW-6020	A-30
MBX-300-M16	●	30	43	29	M16	12.5	22	BNM-300...	LRM-300...	KSW-8025	A-30

Clamp screw	Torque(N.m)
FSW-4013H	3.0
FSW-5016H	4.0
FSW-6020	6.0
KSW-8025	6.0

MQT
TYPE

High precision "QM MAX"



- 3 different angled bodies (0°, 3°, and 5°) that cover a range of tapered walls from 0° ~ 8°
- Possible to use even on 3 axis machine with 3° or 5° angled body ; A03 type or A05 type
- High tolerance insert-pocket for the ground inserts
- High efficiency with multi flutes



Fig.1





Fig.2




Inclination angle θ°	Cat.No.	Stock	No. of inserts	Dimensions (mm)						Parts		Insert	Fig.	
				DC	LF	DCSFMS	MD	C	W	Screws	Wrench			
0°	MQT-2016A00-M8	●	2	16	23	14	M8	8	12	TSW-2556H	A-08	XP**100308ZER-R YPHW1003**Z*R-** ZPMT1003**ZER-PL	1	
	MQT-4020A00-M10	●	4	20	30	18	M10	9	14				1	
	MQT-5025A00-M12	●	5	25	35	22.5	M12	10	17	DSW-2563H			1	
	MQT-6032A00-M16	●	6	32	43	29	M16	12	22				1	
	MQT-6035A00-M16	●	6	35	43	29	M16	12	22				1	
3°	MQT-2016A03-M8	●	2	16	23	14	M8	8	12	TSW-2556H			2	
	MQT-2020A03-M10	●	2	20	30	18	M10	9	14				2	
5°	MQT-2016A05-M8	●	2	16	23	14	M8	8	12					2
	MQT-2020A05-M10	●	2	20	30	18	M10	9	14					2

Clamp screw	Torque(N.m)
TSW-2556H	1.1
DSW-2563H	


MQT TYPE

Insert


For tapered wall finishing
(XPHW100308ZER-R)
(XPHT100308ZER-R)




For finishing side face
(YPHW1003**ZER-15)
(YPHW100308ZER-F)
(YPHW100308ZTR-F1)



Shoulder milling insert
(for semi-finishing to finishing)
ZPMT1003**ZER-PL*



CBN Insert



Type	Cat.No.	Tolerance	PVD Coating				Cermet	CBN	Dimensions (mm)				
			DH102	JC8015	JC8050	JC8118			RE	L	W1	S	AN
For Tapered wall finishing	XPHW100308ZER-R	H	●	●			●		0.8	10.06	6	3.35	11°
	XPHT100308ZER-R	H		●			●		0.8	10.06	6	3.35	11°
For Finishing side face	YPHW100303ZER-15	H	●	●			●		0.3	10.06	6	3.35	11°
	YPHW100308ZER-15	H	●				●		0.8	10.06	6	3.35	11°
	YPHW100308ZER-F	H		●					0.8	10.06	6	3.35	11°
	YPHW100308ZTR-F1	H						○	0.8	10.06	6	3.35	11°
Shoulder milling insert (for semi-finishing to finishing)	ZPMT100304ZER-PL	M	●		●	●	●		0.4	10.08	6	3.4	11°
	ZPMT100308ZER-PL	M	●		●	●	●		0.8	10.08	6	3.4	11°
	ZPMT100320ZER-PL	M	●		●	●	●		2	10.08	6	3.4	11°

■ Recommended Cutting Conditions

● KRM Type - Side finishing




Material	Grade	Tool dia. (mm)															
		16				20				25				30			
		a _p (mm)	a _e (mm)	n (min ⁻¹)	v _f (mm/min)	a _p (mm)	a _e (mm)	n (min ⁻¹)	v _f (mm/min)	a _p (mm)	a _e (mm)	n (min ⁻¹)	v _f (mm/min)	a _p (mm)	a _e (mm)	n (min ⁻¹)	v _f (mm/min)
Carbon steel below 250HB	JC8015	0.8	0.15	5,970	2,390	1	0.15	4,770	1,910	1.2	0.15	3,820	1,530	1.2	0.15	3,180	1,270
Cast steel below 285HB	JC8015	0.8	0.15	5,970	2,390	1	0.15	4,770	1,910	1.2	0.15	3,820	1,530	1.2	0.15	3,180	1,270
Tool&die steel below 255HB	JC8015	0.8	0.15	5,970	2,390	1	0.15	4,770	1,910	1.2	0.15	3,820	1,530	1.2	0.15	3,180	1,270
Mold steel 30-36HRC	JC8015	0.8	0.12	5,970	2,390	1	0.12	4,770	1,910	1.2	0.15	3,820	1,530	1.2	0.15	3,180	1,270
Mold steel 38-43HRC	JC8015	0.8	0.12	5,570	1,670	1	0.12	4,460	1,340	1	0.12	3,570	1,070	1	0.12	2,970	890
Hardened die steel 42-52HRC	DH102	0.6	0.1	4,970	750	0.7	0.1	3,980	600	0.8	0.1	3,180	480	0.8	0.1	2,650	400
Hardened die steel 55-62HRC	DH102	0.5	0.1	3,980	600	0.7	0.1	3,180	480	0.7	0.1	2,550	380	0.7	0.1	2,120	320
Grey cast iron 160-260HB	DH102	0.8	0.2	6,960	3,480	1	0.2	5,570	3,340	1.2	0.2	4,460	2,680	1.2	0.2	3,710	2,230
Nodular cast iron 170-300HB	DH102	0.8	0.2	6,960	3,480	1	0.2	5,570	3,340	1.2	0.2	4,460	2,680	1.2	0.2	3,710	2,230
Austenitic stainless steel	JC8015	0.8	0.12	5,570	2,230	1	0.12	4,460	1,780	1.2	0.12	3,570	1,430	1.2	0.12	2,970	1,190
Ferritic&Martensitic stainless steel	JC8015	0.8	0.12	5,570	2,230	1	0.12	4,460	1,780	1.2	0.12	3,570	1,430	1.2	0.12	2,970	1,190
Titanium alloy (Ti-6Al-4V) 35-43HRC	JC8015	0.5	0.1	1,990	480	0.6	0.1	1,590	380	0.7	0.1	1,270	320	0.7	0.1	1,060	270
Heat resistant alloy (INCO718) 35-43HRC	JC8015	0.5	0.1	1,590	380	0.6	0.1	1,270	300	0.7	0.1	1,020	260	0.7	0.1	850	210

Note

1. Please adjust cutting conditions according to machine rigidity or work rigidity.
2. These parameters are for overhang length 3Dc. See right table for longer application.
3. In case of chatter occurring, recommended to reduce ap or rpm and keep feed per tooth.
4. Use air blow.

Overhang (ℓ/Dc)	n (min ⁻¹)	v _f (mm/min)
~ 3Dc	100%	100%
3Dc ~ 5Dc	70%	70%
5Dc ~ 10Dc	50%	50%

Please refer to chart and formula below to calculate a_p.



$$a_p = 2 \sqrt{(R^2 - (R - H)^2)}$$

Pick amount a _p (mm)		Cusp height (mm)									
Cat.No.	R	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.010
KRM-160-R10-BR50	50	0.63	0.89	1.10	1.26	1.41	1.55	1.67	1.79	1.90	2.00
KRM-200-R10-BR60	60	0.69	0.98	1.20	1.39	1.55	1.70	1.83	1.96	2.08	2.19
KRM-250-R10-BR60											
KRM-300-R10-BR60											

Recommended Cutting Conditions

● TNM Type - Side finishing with Barrel R



● Side finishing with Tip R



Material	Grade	Tool dia. (mm)							
		16				20			
		ap (mm)	ae (mm)	n (min ⁻¹)	Vf (mm/min)	ap (mm)	ae (mm)	n (min ⁻¹)	Vf (mm/min)
Carbon steel below 250HB	JC8015	~1	0.2	6,960	2,780	~1	0.2	5,570	2,230
Cast steel below 285HB	JC8015	~1	0.2	6,960	2,780	~1	0.2	5,570	2,230
Tool&die steel below 255HB	JC8015	~1	0.2	6,960	2,780	~1	0.2	5,570	2,230
Mold steel 30-36HRC	JC8015	~1	0.2	6,960	2,780	~1	0.2	5,570	2,230
Mold steel 38-43HRC	JC8015	~1	0.2	5,970	2,390	~1	0.2	4,770	1,910
Hardened die steel 42-52HRC	JC8015	~1	0.1	4,970	1,490	~1	0.1	3,980	1,190
Grey cast iron 160-260HB	JC8015	~1	0.2	6,960	2,780	~1	0.2	5,570	2,230
Nodular cast iron 170-300HB	JC8015	~1	0.2	6,960	2,780	~1	0.2	5,570	2,230
Austenitic stainless steel	JC8015	~1	0.2	6,960	2,090	~1	0.2	5,570	1,670
Ferritic&Martensitic stainless steel	JC8015	~1	0.2	6,960	2,090	~1	0.2	5,570	1,670
Titanium alloy (Ti-6Al-4V) 35-43HRC	JC8015	~0.4	0.15	4,970	1,490	~0.4	0.15	3,980	1,190
Heat resistant alloy (INCO718) 35-43HRC	JC8015	~0.4	0.1	3,980	800	~0.4	0.1	3,180	640
Aluminum alloy	FZ15	~1.5	0.25	9,980	4,980	~1.5	0.25	7,960	4,780


Note

1. Please adjust cutting conditions according to machine rigidity or work rigidity.
2. These parameters are for overhang length 3Dc. See right table for longer application.
3. In case of chatter occurring, recommended to reduce ap or rpm and keep feed per tooth.
4. Use air blow.

Overhang (ℓ/Dc)	n (min ⁻¹)	Vf (mm/min)
~ 3Dc	100%	100%
3Dc ~ 5Dc	70%	70%
5Dc ~ 10Dc	50%	50%

Please refer to chart and formula below to calculate ap.

$$a_p = 2 \sqrt{(R^2 - (R - H)^2)}$$



Pick amount ap (mm)		Cusp height (mm)									
Cat.No.	R	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.010
TNM-160-NR6BR32	32	0.51	0.72	0.88	1.01	1.13	1.24	1.34	1.43	1.52	1.60
TNM-200-NR8BR40	40	0.57	0.80	0.98	1.13	1.26	1.39	1.50	1.60	1.70	1.79

Recommended Cutting Conditions

TPM Type - with Barrel R



Material	Grade	Tool dia. (mm)							
		16				20			
		a_p (mm)	a_e (mm)	n (min ⁻¹)	V_f (mm/min)	a_p (mm)	a_e (mm)	n (min ⁻¹)	V_f (mm/min)
Carbon steel below 250HB	JC8015	~4	0.15	13,930	4,180	~5	0.2	11,140	3,340
Cast steel below 285HB	JC8015	~4	0.15	13,930	4,180	~5	0.2	11,140	3,340
Tool&die steel below 255HB	JC8015	~4	0.15	13,930	4,180	~5	0.2	11,140	3,340
Mold steel 30-36HRC	JC8015	~3.5	0.12	11,940	3,580	~4.5	0.1	9,550	2,870
Mold steel 38-43HRC	JC8015	~3	0.12	9,950	2,990	~4	0.1	7,960	2,390
Hardened die steel 42-52HRC	JC8015	~2.5	0.1	6,960	1,390	~3	0.1	5,570	1,110
Hardened die steel 55-62HRC	JC8015	~2	0.1	5,970	1,190	~2.5	0.1	4,770	950
Grey cast iron 160-260HB	JC8015	~4	0.15	13,930	5,570	~5	0.2	11,140	4,460
Nodular cast iron 170-300HB	JC8015	~4	0.15	13,930	4,180	~5	0.2	11,140	3,340
Austenitic stainless steel	JC8015	~3	0.12	11,940	3,580	~4	0.1	9,550	2,870
Ferritic&Martensitic stainless steel	JC8015	~3	0.12	11,940	3,580	~4	0.1	9,550	2,870
Titanium alloy (Ti-6Al-4V) 35-43HRC	JC8015	~2.5	0.1	5,970	1,190	~3	0.1	4,770	950
Heat resistant alloy (INCO718) 35-43HRC	JC8015	~2.5	0.1	3,980	800	~3	0.1	3,180	640

Note

1. Please adjust cutting conditions according to machine rigidity or work rigidity.
2. These parameters are for overhang length 3Dc. See right table for longer application.
3. In case of chatter occurring, recommended to reduce a_p or rpm and keep feed per tooth.
4. Use air blow.

with Tip R




	Tool dia. (mm)							
	16				20			
	a_p (mm)	a_e (mm)	n (min ⁻¹)	V_f (mm/min)	a_p (mm)	a_e (mm)	n (min ⁻¹)	V_f (mm/min)
	0.1	0.2	15,920	1,590	0.1	0.2	12,730	1,530
	0.1	0.2	15,920	1,590	0.1	0.2	12,730	1,530
	0.1	0.2	15,920	1,590	0.1	0.2	12,730	1,530
	0.1	0.2	14,920	1,490	0.1	0.2	11,940	1,430
	0.1	0.2	13,930	1,390	0.1	0.2	11,140	1,110
	0.08	0.2	9,950	1,000	0.08	0.2	7,960	960
	0.08	0.2	8,950	900	0.08	0.2	7,160	860
	0.12	0.2	16,910	1,690	0.12	0.2	13,530	1,620
	0.12	0.2	15,920	1,590	0.12	0.2	12,730	1,530
	0.1	0.2	14,920	1,490	0.1	0.2	11,940	1,430
	0.1	0.2	14,920	1,490	0.1	0.2	11,940	1,430
	0.06	0.2	5,970	600	0.06	0.2	4,770	570
	0.05	0.2	3,980	400	0.05	0.2	3,180	380

Overhang (ℓ/Dc)	n (min ⁻¹)	V_f (mm/min)
~ 3Dc	100%	100%
3Dc ~ 5Dc	70%	70%
5Dc ~ 10Dc	50%	50%

Please refer to chart and formula below to calculate a_p .

$$a_p = 2 \sqrt{(R^2 - (R - H)^2)}$$



Pick amount a_p (mm)		Cusp height (mm)									
Cat.No.	R	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.010
TPM-160-NR2T30BR400	400	1.79	2.53	3.10	3.58	4.00	4.38	4.73	5.06	5.73	5.66
TPM-200-NR2T30BR500	500	2.00	2.83	3.46	4.00	4.47	4.90	5.66	6.00	6.32	

■ Recommended Cutting Conditions



● LRM Type

Material	Grade	Tool dia. (mm)															
		16				20				25				30			
		ap (mm)	ae (mm)	n (min ⁻¹)	Vf (mm/min)	ap (mm)	ae (mm)	n (min ⁻¹)	Vf (mm/min)	ap (mm)	ae (mm)	n (min ⁻¹)	Vf (mm/min)	ap (mm)	ae (mm)	n (min ⁻¹)	Vf (mm/min)
Carbon steel below 250HB	JC8015	0.15	~0.6	7,960	4,780	0.15	~0.7	6,370	4,460	0.15	~0.8	5,730	4,010	0.15	~0.8	4,770	3,340
Cast steel below 285HB	JC8015	0.15	~0.6	7,960	4,780	0.15	~0.7	6,370	4,460	0.15	~0.8	5,730	4,010	0.15	~0.8	4,770	3,340
Tool&die steel below 255HB	JC8015	0.15	~0.6	7,960	4,780	0.15	~0.7	6,370	4,460	0.15	~0.8	5,730	4,010	0.15	~0.8	4,770	3,340
Mold steel 30-36HRC	JC8015	0.1	~0.6	7,960	3,980	0.1	~0.7	6,370	3,820	0.1	~0.8	5,730	3,440	0.1	~0.8	4,770	2,860
Mold steel 38-43HRC	JC8015	0.1	~0.6	6,960	3,480	0.1	~0.7	5,570	3,340	0.1	~0.8	5,090	3,050	0.1	~0.8	4,240	2,540
Hardened die steel 42-52HRC	DH102	0.1	~0.5	5,970	2,390	0.1	~0.6	4,770	2,390	0.1	~0.7	4,460	2,230	0.1	~0.7	3,710	1,860
Hardened die steel 55-62HRC	DH102	0.1	~0.5	4,970	1,990	0.1	~0.6	3,980	1,590	0.1	~0.7	3,820	1,530	0.1	~0.7	3,180	1,270
HSS 55-62HRC	DH102	0.05	~0.25	3,980	1,190	0.05	~0.25	3,180	950	0.05	~0.25	2,550	770	0.05	~0.25	2,120	640
Grey cast iron 160-260HB	DH102	0.15	~0.6	7,960	4,780	0.15	~0.7	6,370	4,460	0.15	~0.8	5,730	4,010	0.15	~0.8	4,770	3,340
Nodular cast iron 170-300HB	DH102	0.15	~0.6	6,960	4,180	0.15	~0.7	5,570	3,900	0.15	~0.8	5,730	4,010	0.15	~0.8	4,770	3,340
Austenitic stainless steel	JC8015	0.15	~0.6	7,960	3,980	0.15	~0.7	6,370	3,820	0.15	~0.8	5,730	3,440	0.15	~0.8	4,770	2,860
Ferritic&Martensitic stainless steel	JC8015	0.15	~0.6	7,960	3,980	0.15	~0.7	6,370	3,820	0.15	~0.8	5,730	3,440	0.15	~0.8	4,770	2,860
Titanium alloy (Ti-6Al-4V) 35-43HRC	JC8015	0.1	~0.6	4,970	1,990	0.1	~0.7	3,980	1,990	0.1	~0.8	3,180	1,590	0.1	~0.8	2,650	1,330
Heat resistant alloy (INCO718) 35-43HRC	JC8015	0.1	~0.25	3,980	1,190	0.1	~0.3	3,180	1,270	0.1	~0.3	2,550	1,020	0.1	~0.3	2,120	850


Note

1. Please adjust cutting conditions according to machine rigidity or work rigidity.
2. These parameters are for overhang length 3Dc. See right table for longer application.
3. In case of chatter occurring, recommended to reduce ap or rpm and keep feed per tooth.
4. Use air blow.

Overhang (ℓ/Dc)	n (min ⁻¹)	Vf (mm/min)
~ 3Dc	100%	100%
3Dc ~ 5Dc	70%	70%
5Dc ~ 10Dc	50%	50%

Please refer to chart and formula below to calculate ap.

$$ae = 2 \sqrt{(R^2 - (R - H)^2)}$$



Pick amount ap (mm)		Cusp height (mm)									
Cat.No.	R	0.001	0.002	0.003	0.004	0.005	0.006	0.007	0.008	0.009	0.010
LRM-160-R20-BR32	32	0.51	0.72	0.88	1.01	1.13	1.24	1.34	1.43	1.52	1.60
LRM-200-R30-BR40	40	0.57	0.80	0.98	1.13	1.26	1.39	1.50	1.60	1.70	1.79
LRM-250-R30-BR50	50	0.63	0.89	1.10	1.26	1.41	1.55	1.67	1.79	1.90	2.00
LRM-300-R30-BR60	60	0.69	0.98	1.20	1.39	1.55	1.70	1.83	1.96	2.08	2.19

■ Definition of edge shape for programming

- When using taper holder (MQT-***A03/05 type)

Fig.1 XPHW/T





Fig.2 YPHW



- Dimensions when using XPHW / T insert


available tilt angle	Cat.No	Dimensions (mm)			Fig
		φDc	Ra	Rh	
1°~6°	MQT-2016A03-M8	15.5	R64.19	8.76	1
3°~8°	MQT-2016A05-M8	15.5	R64.34	10.98	1
1°~6°	MQT-2020A03-M10	19.5	R63.34	8.67	1
3°~8°	MQT-2020A05-M10	19.5	R63.46	10.85	1

- Dimensions when using YPHW insert

available tilt angle	Cat.No	Dimensions (mm)	Fig
		φDc	
3°	MQT-2016A03-M8	16	2
5°	MQT-2016A05-M8	16	2
3°	MQT-2020A03-M10	20	2
5°	MQT-2020A05-M10	20	2

- When using straight holder (MQT-***A00 type)

Fig.3 XPHW/T



- Dimensions when using XPHW/T insert

available tilt angle	Cat.No	Dimensions (mm)			Fig
		φDc	Ra	Rh	
0°~3°	MQT-2016A00-M8	16	R63.27	5.48	3
0°~3°	MQT-4020A00-M10	20	R64.29	5.48	3
0°~3°	MQT-5025A00-M12	25	R63.26	5.48	3
0°~3°	MQT-6032A00-M16	32	R62.41	5.48	3
0°~3°	MQT-6035A00-M16	35	R62.16	5.48	3

- Dimensions when using YPHW insert

available tilt angle	Cat.No	Dimensions (mm)	Fig
		φDc	
0°	MQT-2016A00-M8	16	-
0°	MQT-4020A00-M10	20	-
0°	MQT-5025A00-M12	25	-
0°	MQT-6032A00-M16	32	-
0°	MQT-6035A00-M16	35	-

■ Recommended Cutting Conditions

● MQT Type - with XPHW/T insert for finishing side wall + MSN shank

Material	Grade		Tool dia. (mm)				
			16 2N	20 2N	20 4N	25 5N	32 6N
Carbon steel below 250HB	JC8015 XPHT (XPHW) (CX75)	ap(mm)	≤ 1.5	≤ 1.5	≤ 1.5	≤ 1.5	≤ 1.5
		ae(mm)	< 0.12	< 0.12	< 0.12	< 0.12	< 0.12
		n(min ⁻¹)	12,000	9,600	9,600	7,640	5,460
		vf(mm/min)	4,800	3,840	7,680	7,640	6,550
Tool & die steel below 255HB	JC8015 XPHT (XPHW) (CX75)	ap(mm)	≤ 1.5	≤ 1.5	≤ 1.5	≤ 1.5	≤ 1.5
		ae(mm)	< 0.12	< 0.12	< 0.12	< 0.12	< 0.12
		n(min ⁻¹)	10,000	8,000	8,000	6,400	4,500
		vf(mm/min)	4,000	3,200	6,400	6,400	5,460
Mold steel 30-36HRC	JC8015 XPHT (XPHW) (DH102)	ap(mm)	≤ 1.2	≤ 1.2	≤ 1.2	≤ 1.2	≤ 1.2
		ae(mm)	< 0.12	< 0.12	< 0.12	< 0.12	< 0.12
		n(min ⁻¹)	9,000	7,200	7,200	5,730	4,090
		vf(mm/min)	3,600	2,880	5,740	5,730	4,910
Mold steel 38-43HRC	DH102 XPHW (JC8015)	ap(mm)	≤ 1.0	≤ 1.0	≤ 1.0	≤ 1.0	≤ 1.0
		ae(mm)	< 0.12	< 0.12	< 0.12	< 0.12	< 0.12
		n(min ⁻¹)	8,000	6,400	6,400	5,100	3,640
		vf(mm/min)	3,200	2,560	5,120	5,100	4,370
Hardened die steel 42-52HRC	DH102 XPHW (JC8015)	ap(mm)	≤ 1.0	≤ 1.0	≤ 1.0	≤ 1.0	≤ 1.0
		ae(mm)	< 0.10	< 0.10	< 0.10	< 0.10	< 0.10
		n(min ⁻¹)	5,000	4,000	4,000	3,180	2,280
		vf(mm/min)	1,500	1,200	2,400	2,380	2,050
Hardened die steel 55-62HRC	DH102 XPHW	ap(mm)	≤ 1.0	≤ 1.0	≤ 1.0	≤ 1.0	≤ 1.0
		ae(mm)	< 0.10	< 0.10	< 0.10	< 0.10	< 0.10
		n(min ⁻¹)	3,600	2,860	2,860	2,300	1,640
		vf(mm/min)	720	570	1,140	1,150	980
Grey & Nodular cast iron below 300HB	JC8015 XPHW (XPHT) (DH102)	ap(mm)	≤ 1.5	≤ 1.5	≤ 1.5	≤ 1.5	≤ 1.5
		ae(mm)	< 0.12	< 0.12	< 0.12	< 0.12	< 0.12
		n(min ⁻¹)	12,000	9,600	9,600	7,640	5,460
		vf(mm/min)	6,000	4,800	9,600	9,550	8,190
Stainless steel below 250HB	JC8015 XPHT (XPHW)	ap(mm)	≤ 1.2	≤ 1.2	≤ 1.2	≤ 1.2	≤ 1.2
		ae(mm)	< 0.12	< 0.12	< 0.12	< 0.12	< 0.12
		n(min ⁻¹)	10,000	8,000	8,000	6,400	4,550
		vf(mm/min)	4,000	3,200	6,400	6,400	5,460

Note

- Figures to be adjusted according to machine rigidity or work rigidity.
- In case of chatter occurring, recommended to reduce ap or rpm and keep feed per tooth.
- Use air blow.

Cusp height : XPHT / XPHW

Cusp height (μm)	0.50	0.71	0.97	1.27	1.61	1.98	2.40	2.86	3.35	3.89	4.46	5.08	5.73	6.43	7.16	7.94
ap (mm)	0.5	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2.0

SKS-GII

**SKG / MSG type, innovative High Feed Cutter
achieved extremely excellent metal removal rate !**

Feature 1

Provides stability even milling of deep cavities.

Feature 2

4 corner positive insert **with low cutting forces.**

Feature 3

Flat top insert

SKG-10 type insert : Max ap=1.5mm
(using insert SPNW10-type)



SKG-14 type insert : Max ap=2.5mm
(using insert SPNW14-type)



Feature 4

Chip breaker insert

Optimized cutting edge for machining of difficult to cut materials
like titanium alloy.

Effective for machining that requires reduced cutting loads or
long overhang application.



SM breaker for
difficult to cut materials



PM breaker for
mold steel

Feature 5

Insert grades for a wide range of materials
<JC8118> <JC8050> <JC7550> <DS150>



JC8118
for **mold steel, hardned steel**
from 38HRC upto 50HRC



JC8050
for **mold steel, general steel**
below 36HRC



JC7550
for **Titanium alloy, stainless steel**



DS150
for **Titanium alloy**

Application

ISO	P					M					K				S				H		
	P01	P10	P20	P30	P40	M01	M10	M20	M30	M40	K01	K10	K20	K30	S01	S10	S20	S30	H01	H10	H20
Range			JC8118									JC8118								JC8118	
				JC8050													DS150				
										JC7550								JC7550			

Feature 6

Excellent chip evacuation

SKG10
TYPE**Bore Type**Through
coolant
hole**G-
Body**


Face Milling

Copy Milling

Pocket Milling

Helical Interpolation

Plunge Milling



Cat.No.	Stock	No. of inserts	Dimensions (mm)								Arbor set bolt	Weight (kg)	Inserts
			DCX	LF	DCSFMS	DCB	DCCB	KWW	KDP	CBDP			
SKG-4050R-10-22	●	4	50	50	40	22	14	10.4	6.3	20	M10X1.5X35★	0.3	SPNW10.. SPET10.. SPMT10..
SKG-5050R-10-22	●	5	50	50	40	22	14	10.4	6.3	20	M10X1.5X35★	0.3	
SKG-5052R-10-22	●	5	52	50	40	22	16.6	10.4	6.3	20	M10	0.3	
SKG-5063R-10-22	○	5	63	50	48	22	17	10.4	6.3	20	M10	0.5	
SKG-5063R-10-27	○	5	63	50	48	27	20	12.4	7	22	M12X1.75X30★	0.5	
SKG-6063R-10-22	●	6	63	50	48	22	17	10.4	6.3	20	M10	0.5	
SKG-6063R-10-27	●	6	63	50	48	27	20	12.4	7	22	M12X1.75X30★	0.5	
SKG-6066R-10-27	●	6	66	50	50	27	20	12.4	7	22	M12X1.75X30★	0.6	
SKG-6080R-10-27	●	6	80	50	60	27	20	12.4	7	22	M12X1.75X30★	0.9	

Screw	Torque(N.m)	Wrench
TSW-3509H	3.0	A-15T

MSG10
TYPE

Modular Type

Through
coolant
hole

**G-
Body**


Face Milling

Copy Milling

Pocket Milling

Helical Interpolation

Plunge Milling



Cat.No.	Stock	No. of inserts	Dimensions (mm)						Insert
			DCX	LF	DCSFMS	MD	C	W	
MSG-2025-10-M12	●	2	25	35	23	M12	11	19	SPNW10.. SPET10.. SPMT10..
MSG-3032-10-M16	●	3	32	43	28	M16	12	22	
MSG-3035-10-M16	○	3	35	43	30	M16	14	26	
MSG-4040-10-M16	●	4	40	43	32	M16	14	26	
MSG-4042-10-M16	●	4	42	43	32	M16	14	26	

Screw	Torque(N.m)	Wrench
TSW-3509H	3.0	A-15T

SKG/MSG10
TYPE

Insert



Fig. 1





Fig. 2




Fig. 3





Fig. 4



Cat.No.	Tolerance	PVD Coating				Dimensions (mm)				Fig.
		DS150	JC7550	JC8050	JC8118	RE	IC	S	AN	
SPNW100415ZTR	N			●	●	1.5	10	4.46	11°	1
SPET100415ZPER-SM	E	●	●			1.5	10	4.46	11°	2
SPMT100415ZPER-SM	M	●	●			1.5	10	4.46	11°	3
SPMT100415ZPTR-PM	M			●	●	1.5	10	4.46	11°	4

SKG14
TYPE**Bore Type**Through
coolant
hole**G-
Body**


Face Milling

Copy Milling

Pocket Milling

Helical Interpolation

Plunge Milling



Cat.No.	Stock	No. of inserts	Dimensions (mm)								Arbor set bolt	Weight (kg)	Inserts
			DCX	LF	DCSFMS	DCB	DCCB	KWW	KDP	CBDP			
SKG-4050R-14-22	●	4	50	50	40	22	14	10.4	6.3	19.05	M10X1.5X35★	0.3	SPNW14.. SPMT14..
SKG-4052R-14-22	●	4	52	50	42	22	17	10.4	6.3	19.05	M10X1.5X35★	0.3	
SKG-4063R-14-22	●	4	63	50	48	22	17	10.4	6.3	20	M10	0.5	
SKG-4063R-14-27	●	4	63	50	48	27	20	12.4	7	22	M12X1.75X35★	0.5	
SKG-5066R-14-27	●	5	66	50	50	27	20	12.4	7	22	M12X1.75X35★	0.5	
SKG-5080R-14-27	●	5	80	50	60	27	37	12.4	7	22	M12X1.75X35★	0.8	
SKG-6100R-14-32	●	6	100	63	70	32	45	14.4	8	25	M16	1.6	

Screw	Torque(N.m)	Wrench
CSW-513H	5.5	A-20

SKG14
TYPE

Insert



Fig. 1




Fig. 2






Fig. 3



Cat.No.	Tolerance	PVD Coating				Dimensions (mm)				Fig.
		DS150	JC7550	JC8050	JC8118	RE	IC	S	AN	
SPNW140515ZTR	N			●	●	1.5	13.7	5.56	11°	1
SPMT140520ZPER-SM	M	●	●			2	13.7	5.56	11°	2
SPMT140520ZPTR-PM	M			●	●	2	13.7	5.56	11°	3


Definition of corner shape for programming

● SPNW100415ZTR




Corner radius for programming	Over cut	Remains
R2.5	0	0.99
R3.0 (Standard)	0	0.84
R3.5	0.09	0.71
R4.0	0.23	0.59

● SPE(M)T100415ZPER-SM SPMT100415ZPTR-PM




Corner radius for programming	Over cut	Remains
R2.5 (Standard)	0	0.77
R3.0	0.09	0.68
R3.5	0.25	0.60
R4.0	0.43	0.52

● SPNW140515ZTR



Corner radius for programming	Over cut	Remains
R3.5	0	1.60
R4.0 (Standard)	0	1.46
R4.5	0.06	1.32
R5.0	0.17	1.19


● SPMT140520ZPER-SM SPMT140520ZPTR-PM




Corner radius for programming	Over cut	Remains
R3.5 (Standard)	0	1.35
R4.0	0.02	1.25
R4.5	0.14	1.12
R5.0	0.29	1.05

Recommended Data for Profile Milling

Ramping



Helical interpolation



- Calculation of tool pass dia.

$$\phi_{dc} = \phi D_h - \phi D_c$$

Tool pass dia. Bore dia. Tool Dia.

- Depth of cut per one circuit should not exceed max. depth of cut A_p
- Down cutting is recommended, tool pass rotation should be counterclockwise


- In case of ramping and helical interpolation, apply 70% or less feed (V_f) from standard cutting condition table.

● SPNW100415ZTR / SPNW140515ZTR


Cat.No.	Tool dia. (mm)	Effective Cutting dia. (mm)	Max. depth of cut: a_p (mm)	Ramping		Helical interpolation	
				Max. ramping angle θ	Total cutting length at Max. (a_p): L (mm)	Min. Bore dia. D_h min. (mm)	Max. Bore dia. D_h max. (mm)
MSG-2025-10	25	9.8	1.5	1°	85.9	36	48
MSG-3032-10	32	16.8	1.5	1°	85.9	50	62
MSG-3035-10	35	19.8	1.5	1°	85.9	56	70
MSG-4040-10	40	24.8	1.5	1°	85.9	66	78
MSG-4042-10	42	26.8	1.5	1°	85.9	70	82
SKG-*050R-10	50	34.8	1.5	1°	85.9	86	98
SKG-5052R-10	52	36.8	1.5	1°	85.9	90	102
SKG-*063R-10	63	47.8	1.5	0°45'	114.6	112	124
SKG-6066R-10	66	50.8	1.5	0°45'	114.6	118	130
SKG-6080R-10	80	64.8	1.5	0°30'	171.9	146	158
SKG-4050R-14	50	28.4	2.5	1°	143.2	80	98
SKG-4052R-14	52	30.4	2.5	1°	143.2	84	102
SKG-*063R-14	63	41.4	2.5	0°45'	191	106	124
SKG-5066R-14	66	44.4	2.5	0°45'	191	112	130
SKG-5080R-14	80	58.4	2.5	0°30'	286.5	140	158
SKG-6100R-14	100	78.4	2.5	0°20'	430	180	198
SKG-6125R-14	125	103.4	2.5	0°20'	430	230	248
SKG-7160R-14	160	138.4	2.5	0°15'	573	300	318

Recommended Data for Profile Milling

Ramping



Helical interpolation



- Calculation of tool pass dia.

$$\phi D_c = \phi D_h - \phi D_c$$

Tool pass dia. Bore dia. Tool Dia.

- Depth of cut per one circuit should not exceed max. depth of cut A_p
- Down cutting is recommended, tool pass rotation should be counterclockwise

- In case of ramping and helical interpolation, apply 70% or less feed (V_f) from standard cutting condition table.

- SPE (M) T100415ZPER-SM, SPMT100415ZPTR-PM

- SPMT140520ZPER-SM, SPMT140520ZPTR-PM

Cat.No.	Tool dia. (mm)	Effective Cutting dia. (mm)	Max. depth of cut : a_p (mm)	Ramping		Helical interpolation	
				Max. ramping angle θ	Total cutting length at Max. (a_p) : L (mm)	Min. Bore dia. D_h min. (mm)	Max. Bore dia. D_h max. (mm)
MSG-2025-10	25	10	1.0	1°	57.3	36	48
MSG-3032-10	32	17	1.0	1°	57.3	50	62
MSG-3035-10	35	20	1.0	1°	57.3	56	70
MSG-4040-10	40	25	1.0	1°	57.3	66	78
MSG-4042-10	42	27	1.0	1°	57.3	70	82
SKG-*050R-10	50	35	1.0	1°	57.3	86	98
SKG-5052R-10	52	37	1.0	1°	57.3	90	102
SKG-*063R-10	63	48	1.0	0°45'	76.4	112	124
SKG-6066R-10	66	51	1.0	0°45'	76.4	118	130
SKG-6080R-10	80	65	1.0	0°30'	114.6	146	158
SKG-4050R-14	50	28.8	1.8	1°	103.1	80	98
SKG-4052R-14	52	30.8	1.8	1°	103.1	84	102
SKG-*063R-14	63	41.8	1.8	0°45'	137.5	106	124
SKG-5066R-14	66	44.8	1.8	0°45'	137.5	112	130
SKG-5080R-14	80	58.8	1.8	0°30'	206.3	140	158
SKG-6100R-14	100	78.8	1.8	0°20'	206.3	180	198
SKG-6125R-14	125	123.8	1.8	0°20'	206.3	230	248
SKG-7160R-14	160	138.8	1.8	0°15'	412.5	300	318

■ Recommended Cutting Conditions | SKSGII 10

Material	Insert	Grade	V_c (m/min)	f_z (mm/t)	ap (mm)	ae (mm)
Carbon Steel below 250HB	SPNW SPMT-PM	JC8050 (JC8118)	180 (130-180)	1.8 (1.4-1.8)	0.5-1.5	0.7 Dc
Tool & Die Steel below 255HB	SPNW SPMT-PM	JC8050 (JC8118)	180 (130-180)	1.8 (1.4-1.8)	0.5-1.5	0.7 Dc
Mold Steel 30-36HRC	SPNW SPMT-PM	JC8050 (JC8118)	180 (130-180)	1.8 (1.4-1.8)	0.5-1.5	0.7 Dc
Mold Steel 38-43HRC	SPNW SPMT-PM	JC8118 (JC8050)	110 (80-110)	1.5 (1.2-1.5)	0.5-1.2	0.6 Dc
Hardened Die Steel 42-52HRC	SPNW	JC8118	100	1.4 (1.0-1.4)	0.3-1.0	0.5 Dc
Grey & Nodular Cast Iron	SPNW SPMT-PM	JC8118	180 (160-180)	1.5 (1.5-1.8)	0.5-1.5	0.7 Dc
Stainless Steel	SPMT-SM SPET-SM	JC7550	150 (100-150)	1.4 (0.9-1.4)	0.5-1.0	0.6 Dc
Titanium Alloy	SPMT-SM SPET-SM	DS150	60	0.6 (0.4-0.6)	0.4-1.0	0.6 Dc

Note

1. Please adjust cutting conditions according to machine rigidity or work rigidity. (the above table is guide for cutting on a BT50 machine.)
 2. In case of chatter occurring, recommended to reduce ap or rpm and keep feed per tooth.
 3. ap should be reduced when using on low rigidity machine.
 4. Use air blow.
- ★ $ap \leq 1.0$ when using SPMT/SPET insert.

■ Recommended Cutting Conditions | SKSGII 14

Material	Insert	Grade	Vc (m/min)	fz (mm/t)	ap (mm)	ae (mm)
Carbon Steel below 250HB	SPNW SPMT-PM	JC8050 (JC8118)	150 (100-150)	108 (1.4-1.8)	0.6-2.0	0.7 Dc
Tool & Die Steel below 255HB	SPNW SPMT-PM	JC8050 (JC8118)	150 (100-150)	1.8 (1.4-1.8)	0.6-2.0	0.7 Dc
Mold Steel 30-36HRC	SPNW SPMT-PM	JC8050 (JC8118)	150 (100-150)	1.8 (1.4-1.8)	0.6-2.0	0.7 Dc
Mold Steel 38-43HRC	SPNW SPMT-PM	JC8118 (JC8050)	100 (80-100)	1.5 (1.4-1.5)	0.7-1.6	0.6 Dc
Hardened Die Steel 42-52HRC	SPNW	JC8118	90 (70-90)	1.2 (0.7-1.2)	0.5-1.0	0.5 Dc
Grey & Nodular Cast Iron	SPNW SPMT-PM	JC8118	180 (160-180)	1.8 (1.4-1.8)	0.6-2.0	0.7 Dc
Stainless Steel	SPMT-SM	JC7550	150 (100-150)	1.3 (1.0-1.3)	0.7-1.5	0.6 Dc
Titanium Alloy	SPMT-SM	DS150	60	0.6 (0.4-0.6)	0.7-1.3	0.6 Dc


Note

1. Please adjust cutting conditions according to machine rigidity or work rigidity. (the above table is guide for cutting on a BT50 machine.)
 2. In case of chatter occurring, recommended to reduce ap or rpm and keep feed per tooth.
 3. ap should be reduced when using on low rigidity machine.
 4. Use air blow.
- ★ap ≤1.8 when using SPMT insert.

Specifically designed for high-efficiency machining of difficult-to-cut materials

Feature 1 Multi-edge design for high-efficiency machining.


SKG-09 type



7 inserts

SKG-7050R-09-22

Conventional




4 inserts

SKG-4050R-10-22


Achieved Max $ap=0.9$ mm even if difficult-to-cut materials such as titanium alloy, stainless steel, and heat-resistant alloy.

Feature 2 Optimized cutting edge design for sharpness and low cutting resistance. Ideal for difficult-to-cut materials.


SKG-09 type



Conventional







Feature 3 Precision-ground insert with 4 cutting edges ensures excellent run-out accuracy and longer tool life.



Feature 4 Insert Lineup

Wear resistance

Fracture resistance

SDEW090312ZER
(JC7518/**DS217**/DS118)SDET090312ZDER-SM
(DS118)SDEW090312ZER
(JC7550/**DS250**/DS150)SDET090312ZDER-SM
(JC7550/**DS250**/DS150)

● Application

※ SDSS (Super Duplex Stainless Steel)

Insert	Titanium alloy	Inconel	SUS630	SUS316	※ SDSS
SDEW090312ZER (JC7518)			◎	☆	◎
SDEW090312ZER (JC7550)			●	◎	●
SDEW090312ZER (DS217)	◎	◎	◎	☆	◎
SDEW090312ZER (DS250)			●	◎	●
SDEW090312ZER (DS118)	◎				
SDEW090312ZER (DS150)	●				
SDET090312ZDER-SM (JC7550)			●	●	●
SDET090312ZDER-SM (DS250)			●	●	●
SDET090312ZDER-SM (DS150)	●				
SDET090312ZDER-SM (DS118)	●				

◎ : First Choice ● : Unstable machining ☆ : Light load machining

Feature 5 DS2 coating

- Advanced PVD technology provides high durability and superior surface smoothness.
- New multilayer technology achieves both high hardness and strong adhesion.
- Provides excellent tool life, especially when machining stainless steel.

● Properties of DIJET PVD coating

	DS2 Coating	DS1 Coating	JC7500 Coating
Composition	TiAlSiN	TiB ₂	AlTiCrN
Hardness (GPa)	36 – 38	33 – 35	27 – 28
Oxidation temperature (°C)	1100 – 1200	900 – 1000	1000 – 1100
Coefficient of friction (N)	0.3	0.4	0.5

Nano-composite layer


Provides high hardness and excellent wear resistance

Multilayer coating technology

Reduces cracking

Advanced Adhesion Layer

Developed with the latest PVD coating technology


Carbide substrate

SKS-GII 09

SKG09/MSG09 Type

SKG09
TYPE

Bore Type





Cat.No.	Stock	No. of inserts	Dimensions (mm)								Arbor set bolt	Weight (kg)	Insert
			DCX	LF	DCSFMS	DCB	DCCB	KWW	KDP	CBDP			
SKG-5040R-09-16	●	5	40	40	37	16	13.5	8.4	5.6	18	M8	0.21	SDEW090312ZER SDET090312ZDER-SM
SKG-7050R-09-22	●	7	50	50	40	22	16.5	10.4	6.3	20	M10	0.35	
SKG-7052R-09-22	●	7	52	50	40	22	16.5	10.4	6.3	20	M10	0.37	
SKG-8063R-09-22	●	8	63	50	48	22	17	10.4	6.3	20	M10	0.58	
SKG-8066R-09-27	●	8	66	50	50	27	20	12.4	7	22	M12X1.75X30★	0.60	
SKG-9080R-09-27	●	9	80	50	60	27	20	12.4	7	22	M12X1.75X30★	0.97	

Screw	Torque(N.m)	Wrench
DSW-307H	2.1	A-10

Through
coolant
holeMSG09
TYPE

Modular Type




Cat.No.	Stock	No. of inserts	Dimensions (mm)						Parts	Insert
			DCX	LF	DCSFMS	MD	C	W		
MSG-2020-09-M10	●	2	20	30	19	M10	9	14	DSW-306H	SDEW090312ZER SDET090312ZDER-SM
MSG-2022-09-M10	○	2	22	30	19	M10	9	14	DSW-307H	
MSG-3025-09-M12	●	3	25	35	23	M12	11	19	DSW-307H	
MSG-4028-09-M12	○	4	28	35	23.6	M12	11	19	DSW-307H	
MSG-4032-09-M16	●	4	32	43	28	M16	12	22	DSW-307H	
MSG-5035-09-M16	●	5	35	43	29	M16	12	22	DSW-307H	
MSG-5040-09-M16	●	5	40	43	32	M16	14	26	DSW-307H	
MSG-5042-09-M16	●	5	42	43	32	M16	14	26	DSW-307H	

Screw	Torque(N.m)	Wrench
DSW-306H	1.8	A-10
DSW-307H	2.1	A-10


Through
coolant
holeSKG09
TYPE

Shank Type



Cat.No.	Stock	No. of inserts	Dimensions (mm)					Insert
			DCX	LH	LF	DN	DCON	
SKG-3025-60-09-S25	○	3	25	60	140	23	25	SDEW090312ZER SDET090312ZDER-SM
SKG-3025-100-09-S25	○	3	25	100	180	23	25	
SKG-4032-70-09-S32	○	4	32	70	150	28	32	
SKG-4032-120-09-S32	○	4	32	120	200	28	32	
SKG-5035-70-09-S32	○	5	35	70	150	31	32	
SKG-5035-120-09-S32	○	5	35	120	200	31	32	
SKG-5040-45-09-S32	○	5	40	45	150	31.6	32	
SKG-5040-45E-09-S32	○	5	40	45	220	31.6	32	

Screw	Torque(N.m)	Wrench
DSW-307H	2.1	A-10



Cat.No.	Stock	No. of inserts	Dimensions (mm)				Insert
			DCX	LH	LF	DCON	
SKGS-3025-09-30-S25+A	*	3	25	30	100	25	SDEW090312ZER SDET090312ZDER-SM
SKGS-4032-09-35-S32+A	*	4	32	35	120	32	
SKGS-5035-09-35-S32+A	*	5	35	35	120	32	
SKGS-5040-09-35-S32+A	*	5	40	35	120	32	
SKGS-5042-09-35-S32+A	*	5	42	35	120	32	

Screw	Torque(N.m)	Wrench
DSW-307H	2.1	A-10

SKG/MSG09
TYPE

Insert



Fig. 1






Fig. 2




Cat.No.	Tolerance	PVD Coating						Dimensions (mm)				Fig.
		DS118	DS150	JC7518	DS217	DS250	JC7550	RE	IC	S	AN	
SDEW090312ZER	E	●	●	●	●	●	●	1.2	9	3.4	15°	1
SDET090312ZDER-SM	E	●	●			●	●	1.2	9	3.4	15°	2

GRADE MARKING




JC7550/DS250/DS150



JC7518/DS217/DS118

Definition of corner shape for programming


■ SDET090312ZDER-SM
SDEW090312ZER




Corner radius for programming	Remains	Over cut	Max.ap	W	Cutting edge angle	Actual corner RE
1.5	0.81	0	0.9	7.1	10°	1.2
2.0 (Standard)	0.73	0				
2.5	0.65	0.08				

Recommended Data for Profile Milling

Ramping



Helical interpolation



- Calculation of tool pass dia.

$$\phi_{dc} = \phi_{Dh} - \phi_{Dc}$$

Tool pass dia. Bore dia. Tool dia.

- Depth of cut per one circuit should not exceed max. depth of cut Ap
- Down cutting is recommended, tool pass rotation should be counterclockwise

- In case of ramping and helical interpolation, apply 70% or less feed (Vf) from standard cutting condition table.

Tool dia.	Effective cutting dia.	Max.depth of cut : ap	Ramping		Helical interpolation	
			Max.ramping angle θ	Total cutting length at Max.ap : L(mm)	Min.Bore dia. (mm)	Max.Bore dia. (mm)
20	5.6	0.9	1°	51.6	27	38
22	7.7	0.9	1°	51.6	31	42
25	10.7	0.9	1°	51.6	37	48
28	13.7	0.9	1°	51.6	43	54
32	17.6	0.9	1°	51.6	51	62
35	20.6	0.9	1°	51.6	57	68
40	25.7	0.9	1°	51.6	67	78
42	27.7	0.9	1°	51.6	71	82
50	35.6	0.9	1°	51.6	87	98
52	37.6	0.9	1°	51.6	91	102
63	48.7	0.9	0°45'	68.8	113	124
66	51.7	0.9	0°45'	68.8	119	130
80	65.7	0.9	0°30'	103.1	147	158

■ Recommended Cutting Conditions | SKG09 / MSG09 type

Material	Insert	Grade	Vc (m/min)	fz (mm/t)	ap (mm)	ae (mm)
Carbon Steel below 250HB	SDET09**-SM (SDEW09**)	JC7550 (JC7518)	180 (150-180)	1.2 (1.0-1.2)	0.3-0.8	0.6 Dc
Tool & Die Steel below 255HB	SDET09**-SM (SDEW09**)	JC7550 (JC7518)	150 (125-150)	1.2 (1.0-1.2)	0.3-0.8	0.6 Dc
Mold Steel 30-36HRC	SDET09**-SM (SDEW09**)	JC7550 (JC7518)	150 (125-150)	1.2 (1.0-1.2)	0.3-0.8	0.6 Dc
Austenitic Stainless Steel	SDEW09** (SDET09**-SM)	DS250 DS217	150 (125-150)	1.0 (0.8-1.0)	0.3-0.8	0.6 Dc
Martensitic Stainless Steel	SDEW09** (SDET09**-SM)	DS250 DS217	190 (155-190)	1.0 (0.8-1.0)	0.3-0.8	0.6 Dc
Precipitation Hardening Stainless Steel	SDEW09** (SDET09**-SM)	DS217 (DS250)	100 (85-100)	0.7 (0.6-0.7)	0.3-0.8	0.6 Dc
Super Duplex Stainless Steel	SDEW09** (SDET09**-SM)	DS217 DS250	70 (60-70)	0.5 (0.4-0.5)	0.3-0.8	0.4-0.6 Dc
Titanium Alloy	SDEW09** (SDET09**-SM)	DS118 (DS150)	60 (50-60)	0.6 (0.5-0.6)	0.3-0.8	0.6 Dc
Heat Resistant Alloy	SDEW09** (SDET09**-SM)	DS217 (DS250)	30 (25-30)	0.6 (0.5-0.6)	0.2-0.5	0.4-0.6 Dc

Note)

1. Please adjust cutting conditions according to machine rigidity or work rigidity.
(the above table is guide for cutting on a BT50 machine.)
2. In case of chatter occurring, recommended to reduce ap or rpm and keep feed per tooth.
3. ap should be reduced when using on low rigidity machine.
4. Use air blow.
5. Wet cutting is recommended for machining Super Duplex, Titanium Alloy, Heat Resistant Alloy.




High-feed milling tools with double sided inserts which achieve ultimate high-feed machining

Feature 1 Economical double-sided insert
(with 6 cutting edges)




Feature 2 Strong Clamping System
Dovetail-shaped binding faces in pocket prevents movement of inserts from the cutting force with a single screw




Feature 3

ISO	P					M					K				H		
	P01	P10	P20	P30	P40	M01	M10	M20	M30	M40	K01	K10	K20	K30	H01	H10	H20
Applicable range			JC8050					JC8050									
		JC8118										JC8118				JC8118	
			DS250					DS250									
			JC7560					JC7560									

	DS2 Coating	JC8000 (DV Coating)	JC7500 Coating
Composition	TiAlSiN	AlTiCrN	AlTiCrN
Hardness (GPa)	36-38	32-34	27-28
Oxidation temperature (°C)	1100-1200	1000-1200	1000-1100
Coefficient of friction	0.3	0.65	0.5





EXSKS-05 type

Multi-blade specifications with small diameters result in high feed machining possibilities.

- Bore type $\varnothing 40$ – $\varnothing 63$
- Modular type $\varnothing 20$ – $\varnothing 40$
- Shank type $\varnothing 20$ – $\varnothing 33$


WNMU050320ZER-PM

- For general applications
- Grade : JC8118 / JC8050



WNMU050320ZER-PL

- Low cutting force
- Sharp cutting edge
- Grade : JC8118/JC8050/DS250




EXSKS-07 type

Specifications achieve both insert strength and sharpness allowing stable high-feed machining.

- Bore type $\varnothing 50$ – $\varnothing 100$
- Modular type $\varnothing 32$ – $\varnothing 42$
- Shank type $\varnothing 32$ – $\varnothing 40$



WNMU070620ZER-PM

- For general applications
- Grade : JC8118 / JC8050



WNMU070620ZER-PL

- Low cutting force
- Sharp cutting edge
- Grade : JC8118/JC8050/DS250




EXSKS-09 type

Larger diameters using thick high-rigid inserts can achieve high-feed machining with larger depth of cut.

- Bore type $\varnothing 50$ – $\varnothing 160$

WNMU090720ZER-PM


- Suitable for face milling and pocket machining, with ap=1.4mm or more
- Grade : JC8118/JC8050/JC7560





WNMU090828ZER-PL

- Suitable for pocket machining with ap = 0.6 - 1.2 mm
- Optimized cutting edges reduce fluctuations during corner machining
- Grade : JC8118/JC8050



EXSKS-05
TYPE**Bore Type**

Cat.No.	Stock	No. of inserts	Dimensions (mm)								Arbor set bolt	Weight (kg)	Insert
			DCX	LF	DCSFMS	DCB	DCCB	KWW	KDP	CDBP			
EXSKS-5040R-05-16	●	5	40	45	35	16	13.5	8.4	5.8	19	M8	0.25	WNMU050320ZER-PM WNMU050320ZER-PL
EXSKS-7050R-05-22	●	7	50	50	40	22	16.5	10.4	6.3	20	M10	0.39	
EXSKS-7052R-05-22	●	7	52	50	40	22	16.5	10.4	6.3	20	M10	0.41	
EXSKS-8063R-05-22	●	8	63	50	48	22	17	10.4	6.3	20	M10	0.65	

MEX-05
TYPE**Modular Type**


Cat.No.	Stock	No. of inserts	Dimensions (mm)						Insert
			DCX	LF	DCSFMS	MD	C	W	
MEX-2020-05-M10	●	2	20	30	18	M10	9	14	WNMU050320ZER-PM WNMU050320ZER-PL
MEX-2021-05-M10	○	2	21	30	18	M10	9	14	
MEX-2025-05-M12	●	2	25	35	23	M12	11	19	
MEX-3025-05-M12	●	3	25	35	23	M12	11	19	
MEX-3026-05-M12	○	3	26	35	23	M12	11	19	
MEX-3028-05-M12	○	3	28	28	23	M12	11	19	
MEX-4030-05-M16	○	4	30	43	27	M16	12	22	
MEX-3032-05-M16	●	3	32	43	29	M16	12	22	
MEX-4032-05-M16	●	4	32	43	29	M16	12	22	
MEX-4033-05-M16	○	4	33	43	29	M16	12	22	
MEX-4035-05-M16	●	4	35	43	29	M16	12	22	
MEX-5040-05-M16	●	5	40	43	32	M16	14	26	

Screw	Torque(N.m)	Wrench
TSW-307H	2.1	A-10

Through coolant hole

EXSKS-05 TYPE

Shank Type



Cat.No.	Stock	No. of inserts	Dimensions (mm)							Inserts
			DCX	LU	LH	LF	DN	BHTA	DCON	
EXSKS-2020-05-50-S20	●	2	20	20	50	130	18	1°	20	WNMU050320ZER-PM WNMU050320ZER-PL
EXSKS-2020-05-80-S20	○	2	20	20	80	160	18	0.5°	20	
EXSKS-2021-05-50-S20	○	2	21	20	50	130	18	1°	20	
EXSKS-2021-05-80-S20	○	2	21	20	80	160	18	0.5°	20	
EXSKS-3025-05-60-S25	●	3	25	25	60	140	23	1°	25	
EXSKS-3025-05-100-S25	○	3	25	25	100	180	23	0.5°	25	
EXSKS-3026-05-60-S25	○	3	26	25	60	140	23	1°	25	
EXSKS-3026-05-100-S25	○	3	26	25	100	180	23	0.5°	25	
EXSKS-4032-05-70-S32	●	4	32	30	70	150	29	1.5°	32	
EXSKS-4032-05-120-S32	○	4	32	30	120	200	29	0.5°	32	
EXSKS-4033-05-70-S32	○	4	33	30	70	150	29	1.5°	32	
EXSKS-4033-05-120-S32	○	4	33	30	120	200	29	0.5°	32	

Screw	Torque(N.m)	Wrench
TSW-307H	2.1	A-10

Insert

Fig.1







Fig.2



Cat.No.	Tolerance	PVD coated			Dimensions (mm)			Fig.
		JC8118	JC8050	DS250	RE	IC	S	
WNMU050320ZER-PM	M	●	●		2	7.7	3.9	1
WNMU050320ZER-PL	M	●	●	●	2	7.7	3.9	2


GRADE MARKING



EXSKS-07
TYPE**Bore Type**

Cat.No.	Stock	No. of inserts	Dimensions (mm)								Arbor set bolt	Weight (kg)	Insert
			DCX	LF	DCSFMS	DCB	DCCB	KWW	KDP	CBDP			
EXSKS-5050R-07-22	●	5	50	50	40	22	16.5	10.4	6.3	20	M10	0.38	WNMU070620ZER-PM WNMU070620ZER-PL
EXSKS-5052R-07-22	●	5	52	50	40	22	16.5	10.4	6.3	20	M10	0.40	
EXSKS-6063R-07-22	●	6	63	50	48	22	17	10.4	6.3	20	M10	0.64	
EXSKS-6066R-07-27+A	●	6	66	50	48	27	20	12.4	7	22	M12X1.75X35★	0.64	
EXSKS-7080R-07-27	●	7	80	55	65	27	20	12.4	7	22	M12X1.75X35★	1.23	
EXSKS-8100R-07-32	●	8	100	50	85	32	26	14.4	8	25	M16X2X25★	1.76	

Screw	Torque(N.m)	Wrench
TSW-410H	3.5	A-15T

MEX-07
TYPE**Modular Type**

Cat.No.	Stock	No. of inserts	Dimensions (mm)						Insert
			DCX	LF	DCSFMS	MD	C	W	
MEX-2032-07-M16	●	2	32	43	29	M16	12	22	WNMU070620ZER-PM WNMU070620ZER-PL
MEX-3035-07-M16	●	3	35	43	29	M16	12	22	
MEX-4040-07-M16	●	4	40	43	32	M16	14	26	
MEX-4042-07-M16	●	4	42	43	32	M16	14	26	

Screw	Torque(N.m)	Wrench
TSW-410H	3.5	A-15

EXSKS-07 TYPE

Shank Type

Through coolant hole



Fig.1 DCX=Ø32





Fig.2 DCX=Ø35, 40



Cat.No.	Stock	No. of inserts	Dimensions (mm)							Fig.	Insert
			DCX	LU	LH	LF	DN	BHTA	DCON		
EXSKS-2032-07-70-S32	○	2	32	30	70	150	29	1.5°	32	1	WNMU070620ZER-PM WNMU070620ZER-PL
EXSKS-2032-07-120-S32	○	2	32	30	120	200	29	0.6°	32	1	
EXSKS-3035-07-40-S32	○	3	35	40	-	150	31	-	32	2	
EXSKS-3035-07-40L-S32	○	3	35	40	-	200	31	-	32	2	
EXSKS-4040-07-50-S32	○	4	40	50	-	150	35	-	32	2	
EXSKS-4040-07-50L-S32	○	4	40	50	-	200	35	-	32	2	

Screw	Torque(N.m)	Wrench
TSW-410H	3.5	A-15

Insert

Fig.1








Fig.2




Cat.No.	Tolerance	PVD coated			Dimensions (mm)			Fig.
		JC8118	JC8050	DS250	RE	IC	S	
WNMU070620ZER-PM	M	●	●		2	11.2	6.4	1
WNMU070620ZER-PL	M	●	●	●	2	11.2	6.4	2

GRADE MARKING






JC8050/DS250



JC8118

EXSKS-09
TYPE

Bore Type


Fig.1
Through coolant holeFig.2
Without coolant holeFig.3
Through coolant holeSet bolt built into
the cutter body

Cat.No.	Stock	No. of inserts	Dimensions (mm)								Arbor set bolt	Weight (kg)	Fig.	Inserts
			DCX	LF	DCSFMS	DCB	DCCB	KWW	KDP	CBDB				
EXSKS-3050R-22	○	3	50	55	40	22	9.6	10.4	6.3	19	M10×1.5×25	0.4	3	WNMU090720ZER-PM WNMU090828ZER-PL
EXSKS-4050R-22	●	4	50	55	40	22	9.6	10.4	6.3	19	M10×1.5×25	0.3	3	
EXSKS-4052R-22	●	4	52	50	40	22	17	10.4	6.3	20	M10	0.4	1	
EXSKS-4063R-22	○	4	63	50	48	22	17	10.4	6.3	20	M10	0.5	1	
EXSKS-5063R-22	●	5	63	50	48	22	17	10.4	6.3	20	M10	0.5	1	
EXSKS-5063R-27	●	5	63	50	48	27	20	12.4	7	22	M12×1.75×30	0.5	1	
EXSKS-5066R-27	●	5	66	50	48	27	20	12.4	7	22	M12×1.75×30	0.5	1	
EXSKS-6080R-27	●	6	80	55	65	27	37	12.4	7	22	M12×1.75×40	0.9	1	
EXSKS-7100R-32	●	7	100	70	85	32	26	14.4	8	32	M16×2×45	1.9	1	
EXSKS-8125R-40	●	8	125	70	100	40	32	16.4	9	35	M20×2.5×45	3.9	1	
EXSKS-9160R-40	●	9	160	55	100	40	85	16.4	9	35	M20	3.9	2	


Screw	Torque(N.m)	Wrench
CSW-513H	5.5	A-20

Insert

WNMU090720ZER-PM



WNMU090828ZER-PL




Cat.No.	Tolerance	PVD coated			Dimensions (mm)			
		JC8118	JC8050	JC7560	IC	S	BS	RE
WNMU090720ZER-PM	M	●	●	●	14	7.66	1.94	2
WNMU090828ZER-PL	M	●	●		13.91	8.66	1.37	2.8

Note) When using PL inserts, tool dia. will be smaller than PM insert.
In case dia. Ø100 holder, tool dia. is 0.06mm smaller.
In case dia. Ø125 holder, tool dia. is 0.11mm smaller.
In case dia. Ø160 holder, tool dia. is 0.15mm smaller


GRADE MARKING

WNMU090720ZER-PM




JC8050 JC8118 JC7560

WNMU090828ZER-PL





JC 8050 JC 8118

EXSKS-05
TYPE**Definition of corner shape for programming**

Corner radius for programming	Remains	Over cut
R2.0	0.59	0
R2.5 (Std.)	0.5	0
R3.0	0.41	0.13

(mm)

Attention for profile milling

- Calculation of tool pass dia.

$$\varnothing_{dc} = \varnothing_{Dh} - \varnothing_{Dc}$$

Tool pass dia. Bore dia. Tool dia.


- Depth of cut per one circuit should not exceed max. depth of cut ap.
- Down cutting is recommended, so tool pass rotation should be counterclockwise.
- To obtain a flat bottom surface when helical milling, it requires to remove "the uncut part" in the center of the work material at a final pass.

- ◎ In case of ramping and helical interpolation, apply 70% or less feed speed from standard cutting condition table.
- ◎ In case of drilling, apply 50% or less Z axis feed speed from standard cutting condition table.
- ◎ Long consecutive chips may come out in case of drilling, confirm the safe condition sufficiently.

Cat. No.	Tool dia. (mm)	EFF. Cutting dia. (mm)	Max. depth of cut (mm) ap	Ramping		Helical interpolation			Max. drilling depth Z (mm)
				Max. ramping angle θ°	Total cutting length at Max ap	Min. bore dia. Dh min (mm)	Max. bore dia. Dh min (mm)	Dh min (mm)	
EXSKS-*020/MEX-*020	20	10	1.5	2.8	31	28	36	31	0.4
EXSKS-*021/MEX-*021	21	11	1.5	2.6	34	30	38	33	0.4
EXSKS-*025/MEX-*025	25	15	1.5	1.8	48	38	46	41	0.4
EXSKS-*026/MEX-*026	26	16	1.5	1.7	51	40	48	43	0.4
MEX-*028	28	18	1.5	1.5	58	44	52	47	0.4
MEX-*030	30	20	1.5	1.3	67	48	56	51	0.4
EXSKS-*032/MEX-*032	32	22	1.5	1.2	72	52	60	55	0.4
EXSKS-*033/MEX-*033	33	23	1.5	1.1	79	54	62	57	0.4
MEX-*035	35	25	1.5	1	86	58	66	61	0.4
EXSKS-*040/MEX-*040	40	30	1.5	0.8	108	68	76	71	0.4
EXSKS-*050	50	40	1.5	0.6	144	88	96	91	0.4
EXSKS-*052	52	42	1.5	0.6	144	92	100	95	0.4
EXSKS-*063	63	53	1.5	0.5	172	114	122	117	0.4

EXSKS-07
TYPE

Definition of corner shape for programming




Corner radius for programming	Remains	Over cut
R3.0 (Std.)	0.8	0
R3.5	0.73	0.06
R4.0	0.66	0.21


(mm)

Attention for profile milling

Ramping



Helical interpolation



- Calculation of tool pass dia.

$$\varnothing_{dc} = \varnothing_{Dh} - \varnothing_{Dc}$$

Tool pass dia. Bore dia. Tool dia.


- Depth of cut per one circuit should not exceed max. depth of cut ap.
- Down cutting is recommended, so tool pass rotation should be counterclockwise.
- To obtain a flat bottom surface when helical milling, it requires to remove "the uncut part" in the center of the work material at a final pass.

- In case of ramping and helical interpolation, apply 70% or less feed speed from standard cutting condition table.
- In case of drilling, apply 50% or less Z axis feed speed from standard cutting condition table.
- Long consecutive chips may come out in case of drilling, confirm the safe condition sufficiently.

Cat. No.	Tool dia. (mm)	EFF. Cutting dia. (mm)	Max. depth of cut (mm) ap	Ramping		Helical interpolation			Max. drilling depth Z (mm)
				Max. ramping angle °	Total cutting length at Max ap	Min. bore dia. Dh min (mm)	Max. bore dia. Dh min (mm)	Dh min (mm)	
EXSKS-*032/MEX-*032	32	15	2	2.2	53	41	60	48	0.5
EXSKS-*035/MEX-*035	35	18	2	2.1	55	47	66	54	0.5
EXSKS-*040/MEX-*040	40	23	2	2	58	57	76	64	0.5
MEX-*042	42	25	2	1.8	64	61	80	68	0.5
EXSKS-*050	50	33	2	1.5	77	77	96	84	0.5
EXSKS-*052	52	35	2	1.2	96	81	100	88	0.5
EXSKS-*063	63	46	2	1	115	103	122	110	0.5
EXSKS-*080	80	63	2	0.8	144	137	156	144	0.5
EXSKS-*100	100	83	2	0.5	230	178	198	183	0.6

EXSKS-09
TYPE


Definition of corner shape for programming




Insert	W	Corner radius for programming	Remains	Over cut
WNMU090720ZER-PM	8.2	R3.0	1.41	0
		R3.5	1.30	0
		R4.0	1.19	0.025
Insert	W	Corner radius for programming	Remains	Over cut
WNMU090828ZER-PL	8.4	R3.0	1.18	0
		R3.5	1.06	0
		R4.0	0.95	0.010

Attention for profile milling

Ramping



Helical interpolation



- Calculation of tool pass dia.

$$\varnothing dc = \varnothing Dh - \varnothing Dc$$

Tool pass dia. Bore dia. Tool dia.

- Depth of cut per one circuit should not exceed max. depth of cut ap.
- Down cutting is recommended, so tool pass rotation should be counterclockwise.
- To obtain a flat bottom surface when helical milling, it requires to remove "the uncut part" in the center of the work material at a final pass.

- In case of ramping and helical interpolation, apply 70% or less feed speed from standard cutting condition table.
- In case of drilling, apply 50% or less Z axis feed speed from standard cutting condition table.
- Long consecutive chips may come out in case of drilling, confirm the safe condition sufficiently.

WNMU090720ZER-PM

Cat. No.	Tool dia. (mm)	EFF. Cutting dia. (mm)	Max. depth of cut (mm) ap	Ramping		Helical interpolation			Max. drilling depth Z (mm)
				Max. ramping angle θ°	Total cutting length at Max ap	Min. bore dia. Dh min (mm)	Max. bore dia. Dh min (mm)	Dh min (mm)	
EXSKS-*050	50	33	3	2.5	69	73	96	81	1.1
EXSKS-*052	52	35	3	2.4	72	77	100	85	1.2
EXSKS-*063	63	46	3	1.8	96	99	122	107	1.2
EXSKS-*066	66	49	3	1.7	102	105	128	113	1.2
EXSKS-*080	80	63	3	1.3	133	133	156	141	1.3
EXSKS-*100	100	83	3	1	172	173	196	181	1.3
EXSKS-*125	125	108	3	0.9	191	223	246	231	1.3
EXSKS-*160	160	143	3	0.7	246	293	316	301	1.7

WNMU090828ZER-PL

Cat. No.	Tool dia. (mm)	EFF. Cutting dia. (mm)	Max. depth of cut (mm) ap	Ramping		Helical interpolation			Max. drilling depth Z (mm)
				Max. ramping angle θ°	Total cutting length at Max ap	Min. bore dia. Dh min (mm)	Max. bore dia. Dh min (mm)	Dh min (mm)	
EXSKS-*050	50	33	2	2.3	50	74	96	82	1
EXSKS-*052	52	35	2	2.2	53	78	100	86	1
EXSKS-*063	63	46	2	1.8	64	100	122	108	1.2
EXSKS-*066	66	49	2	1.7	68	106	128	114	1.2
EXSKS-*080	80	63	2	1.3	89	134	156	142	1.3
EXSKS-*100	99.94	83	2	1	115	174	195	182	1.3
EXSKS-*125	124.89	108	2	0.9	128	224	245	232	1.4
EXSKS-*160	159.85	142	2	0.7	164	294	315	302	1.6

■ Recommended Cutting Conditions | EXSKS-05 (Bore type)

Material	Grade	Vc (m/min)	fz (mm/t)	ap (mm)	ae (mm)
Carbon Steel below 250HB	JC8050 (JC8118)	160 (120-160)	1.2 (0.8-1.2)	0.4-1.0	0.7 Dc
Tool & Die Steel below 255HB	JC8050 (JC8118)	150 (110-150)	1.2 (0.8-1.2)	0.4-1.0	0.7 Dc
Mold Steel 30-36HRC	JC8118 (JC8050)	150 (110-150)	1.2 (0.8-1.2)	0.4-1.0	0.7 Dc
Mold Steel 38-43HRC	JC8118 (JC8050)	110 (80-110)	1.0 (0.8-1.0)	0.4-0.8	0.6 Dc
Hardened Die Steel 42-52HRC	JC8118	100 (70-100)	0.8 (0.6-0.8)	0.5-0.7	0.5 Dc
Grey Cast Iron	JC8118 (JC8050)	180 (130-180)	1.4 (0.9-1.4)	0.5-1.0	0.7 Dc
Nodular Cast Iron	JC8118 (JC8050)	160 (110-160)	1.2 (0.8-1.2)	0.5-1.0	0.7 Dc
Austenitic Stainless Steel	JC8050 (DS250)	130 (90-130)	1.0 (0.8-1.0)	0.4-0.8	0.5 Dc
Martensitic Stainless Steel	JC8118 (DS250)	150 (100-150)	1.2 (1.0-1.2)	0.5-1.0	0.5 Dc

■ Recommended Cutting Conditions | MEX-05 (Modular type)

Material	Grade	Vc (m/min)	fz (mm/t)	ap (mm)	ae (mm)
Carbon Steel below 250HB	JC8050 (JC8118)	200 (160-200)	1.2 (1.0-1.2)	0.4-0.8	0.7 Dc
Tool & Die Steel below 255HB	JC8050 (JC8118)	180 (140-180)	1.2 (1.0-1.2)	0.4-0.8	0.7 Dc
Mold Steel 30-36HRC	JC8118 (JC8050)	180 (140-180)	1.2 (1.0-1.2)	0.4-0.8	0.7 Dc
Mold Steel 38-43HRC	JC8118 (JC8050)	130 (80-130)	1.0 (0.8-1.2)	0.4-0.6	0.6 Dc
Hardened Die Steel 42-52HRC	JC8118	100 (70-100)	0.8 (0.6-0.8)	0.5-0.6	0.5 Dc
Grey Cast Iron	JC8118 (JC8050)	200 (160-200)	1.4 (1.0-1.4)	0.5-1.0	0.7 Dc
Nodular Cast Iron	JC8118 (JC8050)	180 (140-180)	1.2 (1.0-1.2)	0.5-1.0	0.7 Dc
Austenitic Stainless Steel	JC8050 (DS250)	150 (110-150)	1.0 (0.8-1.0)	0.4-0.6	0.5 Dc
Martensitic Stainless Steel	JC8118 (DS250)	170 (130-170)	1.2 (1.0-1.2)	0.5-0.8	0.5 Dc

Note

1. Please adjust cutting conditions according to machine rigidity or work rigidity. (the above table is guide for cutting on a BT50 machine.)
2. In case of chatter occurring, recommended to reduce ap or rpm and keep feed per tooth.
3. ap should be reduced when using on low rigidity machine.
4. Use air blow.

■ Recommended Cutting Conditions | EXSKS-07 (Bore type)

Material	Grade	Vc (m/min)	fz (mm/t)	ap (mm)	ae (mm)
Carbon Steel below 250HB	JC8050	150 (120-150)	1.5 (1.1-1.5)	0.5-1.5	0.7 Dc
Tool & Die Steel below 255HB	JC8050	130 (100-130)	1.5 (1.1-1.5)	0.5-1.5	0.7 Dc
Mold Steel 30-36HRC	JC8118	130 (100-130)	1.5 (1.1-1.5)	0.5-1.5	0.7 Dc
Mold Steel 38-43HRC	JC8118	110 (80-110)	1.3 (1.0-1.3)	0.4-1.2	0.6 Dc
Hardened Die Steel 42-52HRC	JC8118	90 (70-90)	1.0 (0.8-1.0)	0.4-1.0	0.5 Dc
Grey Cast Iron	JC8118	150 (120-150)	1.5 (1.1-1.5)	0.5-2.0	0.7 Dc
Nodular Cast Iron	JC8118	130 (100-130)	1.5 (1.1-1.5)	0.5-1.5	0.7 Dc
Austenitic Stainless Steel	JC8050 (DS250)	110 (80-110)	1.3 (1.0-1.3)	0.4-1.2	0.5 Dc
Martensitic Stainless Steel	JC8118 (DS250)	130 (100-130)	1.3 (1.0-1.3)	0.5-1.5	0.5 Dc

■ Recommended Cutting Conditions | MEX-07 (Modular type)

Material	Grade	Vc (m/min)	fz (mm/t)	ap (mm)	ae (mm)
Carbon Steel below 250HB	JC8050	200 (160-200)	1.5 (1.3-1.5)	0.5-1.0	0.7 Dc
Tool & Die Steel below 255HB	JC8050	180 (140-180)	1.5 (1.3-1.5)	0.5-1.0	0.7 Dc
Mold Steel 30-36HRC	JC8118	180 (140-180)	1.5 (1.3-1.5)	0.5-1.0	0.7 Dc
Mold Steel 38-43HRC	JC8118	130 (90-130)	1.2 (1.0-1.2)	0.4-0.8	0.6 Dc
Hardened Die Steel 42-52HRC	JC8118	100 (70-100)	1.0 (0.8-1.0)	0.4-0.8	0.5 Dc
Grey Cast Iron	JC8118	200 (160-200)	1.5 (1.4-1.5)	0.5-1.5	0.7 Dc
Nodular Cast Iron	JC8118	170 (130-170)	1.5 (1.3-1.5)	0.5-1.0	0.7 Dc
Austenitic Stainless Steel	JC8050 (DS250)	150 (110-150)	1.2 (1.0-1.2)	0.4-0.8	0.5 Dc
Martensitic Stainless Steel	JC8118 (DS250)	170 (130-170)	1.2 (1.0-1.2)	0.5-1.0	0.5 Dc

Note

1. Please adjust cutting conditions according to machine rigidity or work rigidity. (the above table is guide for cutting on a BT50 machine.)
2. In case of chatter occurring, recommended to reduce ap or rpm and keep feed per tooth.
3. ap should be reduced when using on low rigidity machine.
4. Use air blow.

Recommended Cutting Conditions | EXSKS-09 (Bore type)

Material	Grade	Vc (m/min)	fz (mm/t)	ap (mm)	ae (mm)
Carbon Steel below 250HB	JC7560 JC8050 (JC8118)	150 (100-150)	2.0 (1.0-2.0)	0.4-2.0	0.7 Dc
Tool & Die Steel below 255HB	JC7560 JC8050 (JC8118)	150 (100-150)	2.0 (1.0-2.0)	0.4-2.0	0.7 Dc
Mold Steel 30-36HRC	JC7560 JC8050 (JC8118)	130 (90-130)	2.0 (1.0-2.0)	0.4-2.0	0.7 Dc
Mold Steel 38-43HRC	JC8118 (JC8050)	110 (70-110)	1.0 (0.5-1.0)	0.4-1.5	0.6 Dc
Hardened Die Steel 42-52HRC	JC8118	80 (60-80)	1.0 (0.5-1.0)	0.4-1.5	0.5 Dc
Grey Cast Iron	JC8118	190 (100-190)	2.0 (1.0-2.0)	0.4-2.5	0.7 Dc
Nodular Cast Iron	JC8118	190 (100-190)	2.0 (1.0-2.0)	0.4-2.5	0.7 Dc
Stainless Steel	JC8050 (JC7560)	150 (100-150)	1.5 (1.0-1.5)	0.4-2.0	0.5 Dc

Note

1. Please adjust cutting conditions according to machine rigidity or work rigidity. (the above table is guide for cutting on a BT50 machine.)
2. In case of chatter occurring, recommended to reduce ap or rpm and keep feed per tooth.
3. ap should be reduced when using on low rigidity machine.
4. Use air blow.


High-Feed Milling Cutter

Multi-Blade Design with **Double-Sided Compact Inserts** for High Productivity

Feature 1

Lineup from Ø10, featuring economical double-sided inserts with four cutting edges.

1. Economical Double-Sided Inserts



2. Lineup from Ø10 – Insert size 07



- ✓ Tool diameter **Ø10**–Ø16 mm
- ✓ Max. depth of cut: **0.5 mm**
- ✓ **Modular type**: Ø10–Ø16 mm
- Shank type**: Ø10–Ø14 mm

Feature 2

High-Rigidity Design for Stable, Reliable Machining.

1. Increased insert rigidity



NEW

MXG07
ENMU07...

MPM

EOMT06...



2. M2 Fine-Pitch Screw

Fine-pitch
M2 screw



NEW

MXG07

Coarse-pitch
M1.8 screw




MPM
(Conventional model)


3. High-Rigidity Body Design

NEW

MXG07



MPM



Body rigidity improved by 44%

MXG07
TYPE**Modular Type**Through
coolant
hole



Face Milling

Copy Milling

Pocket Milling

Helical Interpolation

Slotting



Cat.No.	Stock	No. of inserts	Dimensions (mm)						Insert
			DCX	LF	DCSFMS	MD	C	W	
MXG-2010-07-M6	●	2	10	18	9.5	M6	6.5	8	ENMU07T207ZER-PM
MXG-3012-07-M6	●	3	12	20	11.2	M6	6.5	8	
MXG-3013-07-M6	●	3	13	20	11.2	M6	6.5	8	
MXG-4016-07-M8	●	4	16	23	15	M8	8	12	

Screw	Torque(N.m)	Wrench
TSW-2044H	0.5	A-06

GMX07
TYPE

Shank Type

Through
coolant
hole


Face Milling

Copy Milling

Pocket Milling

Helical Interpolation

Slotting




Type	Cat.No.	Stock	No. of inserts	Dimensions (mm)					Insert
				DCX	LH	LF	DN	DCON	
Standard	GMX2010-07-20-S10+A	●	2	10	20	80	9.2	10	ENMU07T207ZER-PM
	GMX3012-07-20-S12+A	●	3	12	20	80	11.2	12	
	GMX3014-07-20-S12+A	●	3	14	20	80	11.8	12	
Long shank	GMX2011-07-20-S10-LS+A	●	2	11	20	120	9.6	10	
	GMX3013-07-20-S12-LS+A	●	3	13	20	120	11.6	12	
	GMX3014-07-20-S12-LS+A	●	3	14	20	120	11.8	12	

Screw	Torque(N.m)	Wrench
TSW-2044H	0.5	A-06


GMX07/MXG07
TYPE

Insert




Cat.No.	Tolerance	PVD Coating		Dimensions (mm)			
		JC8050	JC8118	RE	L	W1	S
ENMU07T207ZER-PM	M	●	●	0.7	7	4.25	2.85

Definition of corner shape for programming



Recommended Data for Profile Milling



- Calculation of tool pass dia.

$$\phi_{dc} = \phi_{Dh} - \phi_{Dc}$$

Tool pass dia. Bore dia. Tool dia.

- Depth of cut per one circuit should not exceed max. depth of cut a_p
- Down cutting is recommended, tool pass rotation should be counterclockwise

- In case of ramping and helical interpolation, apply 70% or less feed (V_f) from standard cutting condition table
- Drilling is not recommended.

ENMU07T207ZER-PM

Tool dia. (mm)	Effective Cutting dia. (mm)	Max. depth of cut APMX (mm)	Ramping		Helical interpolation		
			Max.ramping angle RMPX θ°	Total cutting length at APMX : L(mm)	Through hole Min. bore dia. Dh (mm)	Blind hole,flat bottom Min. bore dia. Dh (mm)	Through hole Max. bore dia. Dh (mm)
10	5.5	0.5	1.1	26.0	15	16	19
12	7.5	0.5	1.2	23.9	19	20	23
13	8.4	0.5	1.1	26.0	21	22	25
16	11.4	0.5	0.9	31.8	27	28	31

■ Recommended Cutting Conditions | GMX07/MXG07 type

Material	Insert	Grade	Vc (m/min)	fz (mm/t)	ap (mm)	ae (mm)
Carbon Steel below 250HB	ENMU07...-PM	JC8050	165	1.0	0.3	0.5-0.6 Dc
Tool & Die Steel below 255HB	ENMU07...-PM	JC8050	150	1.0	0.3	0.5-0.6 Dc
Mold Steel 30-36HRC	ENMU07...-PM	JC8050	150	1.0	0.3	0.5-0.6 Dc
Mold Steel 38-43HRC	ENMU07...-PM	JC8118	120	0.9	0.3	0.5-0.6 Dc
Hardened Die Steel 42-52HRC	ENMU07...-PM	JC8118	90	0.6	0.25	0.5-0.6 Dc
Grey Cast Iron	ENMU07...-PM	JC8118	200	1.0	0.3	0.5-0.6 Dc
Nodular Cast Iron	ENMU07...-PM	JC8118	200	1.0	0.3	0.5-0.6 Dc
Stainless Steel	ENMU07...-PM	JC8050	165	1.0	0.3	0.5-0.6 Dc

Note:

1. These parameters represent stable machining at lengths 3×D.
Please adjust cutting conditions according to machine rigidity or work rigidity.
2. In case of chatter occurring, recommended to reduce ap or rpm and keep feed per tooth.
3. ap should be reduced when using on low rigidity machine.
4. Use air blow.


Achieving high metal removal rates!

High efficiency machining for versatile applications



Feature 1

Optimized cutting edge for a wide range of applications



Feature 2

Economical double sided insert with 4 cutting edges for various types of materials;
Carbon steel, Hardened material <upto 62HRC>, Stainless steel, Titanium alloy

● Line up



● Insert grades

ISO	P					M					K				S				H		
	P01	P10	P20	P30	P40	M01	M10	M20	M30	M40	K01	K10	K20	K30	S01	S10	S20	S30	H01	H10	H20
Range																					

GMX10
TYPE

Bore Type

Through
coolant
hole

**G-
Body**


Face Milling

Copy Milling

Pocket Milling

Helical Interpolation

Slotting



Cat.No	Stock	No. of inserts	Dimensions (mm)								Weight (kg)	Inserts
			DCX	LF	DCSFMS	DCB	DCCB	KWW	KDP	CBDP		
GMX-6040R-16+A	●	6	40	45	35	16	13.5	8.4	5.6	19	0.24	ENMU100412ZER-** ENM*100312ZER-**
GMX-6042R-16+A	●	6	42	45	35	16	13.5	8.4	5.6	19	0.25	
GMX-7050R-22	●	7	50	50	40	22	17	10.4	6.3	20	0.35	
GMX-7052R-22	●	7	52	50	40	22	17	10.4	6.3	20	0.40	
GMX-7063R-22	●	7	63	50	48	22	17	10.4	6.3	20	0.64	
GMX-7066R-27	●	7	66	50	48	27	20	12.4	7	22	0.66	


Screw	Torque(N.m)	Wrench
TSW-2567H	1.1	A-08

QM MAX GII

GMX10/MXG10 Type

GMX10
TYPE

Shank Type

Through
coolant
hole

Cat.No.	Stock	No. of inserts	Dimensions (mm)							Insert
			DCX	LU	LH	LF	DN	BHTA	DCON	
GMX-2016-30-S16	●	2	16	16	30	100	14	3.5°	16	ENMU100412ZER-** ENM*100312ZER-**
GMX-2016-50-S16	●	2	16	16	50	150	14	1.2°	16	
GMX-3020-50-S20	●	3	20	20	50	130	17.2	2.3°	20	
GMX-3020-80-S20	●	3	20	20	80	160	17.2	1°	20	
GMX-4025-60-S25	●	4	25	25	60	140	22	2°	25	
GMX-4025-100-S25	●	4	25	25	100	180	22	0.9°	25	
GMX-5032-70-S32	●	5	32	30	70	150	29	1.5°	32	
GMX-5032-120-S32	●	5	32	30	120	200	29	0.6	32	

Screw	Torque(N.m)	Wrench
TSW-2567H	1.1	A-08

MXG10
TYPE**Modular Type**Through
coolant
hole**G-
Body**


Face Milling

Copy Milling

Pocket Milling

Helical Interpolation

Slotting




Cat.No.	Stock	No. of inserts	Dimensions (mm)						Insert
			DCX	LF	DCSFMS	MD	C	W	
MXG-2016-M8	●	2	16	23	14	M8	8	12	ENMU100412ZER-** ENM*100312ZER-**
MXG-2017-M8	●	2	17	23	14	M8	8	12	
MXG-3020-M10	●	3	20	30	18	M10	9	14	
MXG-3021-M10	●	3	21	30	18	M10	9	14	
MXG-3022-M10	○	3	22	30	18	M10	9	14	
MXG-3025-M12	●	3	25	35	22	M12	11	19	
MXG-4025-M12	●	4	25	35	22	M12	11	19	
MXG-4026-M12	●	4	26	35	22.5	M12	11	19	
MXG-4028-M12	○	4	28	35	23.6	M12	11	19	
MXG-5030-M16	●	5	30	43	27	M16	12	22	
MXG-5032-M16	●	5	32	43	29	M16	12	22	
MXG-5035-M16	●	5	35	43	29	M16	12	22	
MXG-6040-M16	●	6	40	43	32	M16	14	26	
MXG-6042-M16	●	6	42	43	32	M16	14	26	

Screw	Torque(N.m)	Wrench
TSW-2567H	1.1	A-08


GMX10/MXG10
TYPE

Insert



ENMU100412ZER-PH




ENMU100412ZER-SL



ENMU100312ZER-HL




ENMQ100312ZER




Cat.No.	Tolerance	PVD Coating								Dimensions (mm)			
		DH102	JC7518	JC7550	JC7560	JC8050	JC8118	DS118	DS150	RE	L	W1	S
ENMU100412ZER-PH	M				●	●	●			1.2	10	6	4
ENMU100412ZER-SL	M		●	●				●	●	1.2	10	6	4
ENMU100312ZER-HL	M	●								1.2	10	6	3.2
ENMQ100312ZER	M	●								1.2	10	6	3.2

GRADE MARKING


ENMU100412ZER-PH



JC8118




JC8050




JC7560

ENMU100412ZER-SL



JC7518/DS118




JC7550/DS150

■ Insert selection guide

Materials	Grade	Cat.No.			
		ENMU100412ZER-PH	ENMU100412ZER-SL	ENMU100312ZER-HL	ENMQ100312ZER
Chip breaker		For general milling	Low cutting force	For Hardened materials	Flat top insert
Carbon steel (S50C, S55C) below 250HB	JC8118	○			
	JC8050	◎			
	JC7560	●			
	JC7550				
	JC7518		☆		
	DH102				
	DS118				
	DS150				
Tool & die steel (SKD61, SKD11) below 255HB	JC8118	○			
	JC8050	◎			
	JC7560	●			
	JC7550				
	JC7518		☆		
	DH102				
	DS118				
	DS150				
Mold steel (HPM7, PX5, P20) 30 - 36HRC	JC8118	○			
	JC8050	◎			
	JC7560	●			
	JC7550				
	JC7518		☆		
	DH102				
	DS118				
	DS150				
Mold steel (NAK80, HPM1, P21) 38 - 43HRC	JC8118	◎			
	JC8050	●			
	JC7560				
	JC7550				
	JC7518		☆		
	DH102				
	DS118				
	DS150				
Hardened die steel (SKD61, DAC, DHA) 42 - 52HRC	JC8118	◎			
	JC8050				
	JC7560				
	JC7550				
	JC7518		☆		
	DH102			●	
	DS118				
	DS150				
Hardened die steel (SKD11, SLD, DC11) 55 - 62HRC	JC8118	×			
	JC8050	×			
	JC7560	×			
	JC7550		×		
	JC7518		×		
	DH102			○	◎
	DS118				
	DS150				
Grey cast iron (FC, FCD) below 300HB	JC8118	◎			
	JC8050	○			
	JC7560	●			
	JC7550				
	JC7518				
	DH102				
	DS118				
	DS150				
Stainless steel (SUS304) below 250HB	JC8118	●			
	JC8050				
	JC7560				
	JC7550		○		
	JC7518				
	DH102				
	DS118				
	DS150		◎		
Titanium alloy (Ti-6Al-4V)	JC8118	●			
	JC8050				
	JC7560				
	JC7550		○		
	JC7518				
	DH102				
	DS118				
	DS150		◎		
Heat resistant alloy (INCO718)	JC8118	●			
	JC8050				
	JC7560				
	JC7550				
	JC7518		○		
	DH102				
	DS118		◎		
	DS150				

◎ : First choice ○ : For general milling ● : For unstable milling ☆ : For light cutting resistance × : Not recommended

Definition of Corner Shape for Programming



Cat.No.	W	Corner radius for programming	Remains	Over cut
ENMU100412ZER-PH	3.1	1.0	0.51	0
ENMU100412ZER-SL		1.5 (Standard)	0.36	0
		2.0	0.22	0.05


(mm)

Cat.No.	W	Corner radius for programming	Remains	Over cut
ENMU100312ZER-HL	3.3	1.0	0.55	0
ENMQ100312ZER		1.5 (Standard)	0.41	0
		2.0	0.26	0.04


(mm)

Recommended Data for Profile Milling

Ramping



Helical interpolation



- Calculation of tool pass dia.

$$\varphi dc = \varphi Dh - \varphi Dc$$

Tool pass dia. Bore dia. Tool dia.

- Depth of cut per one circuit should not exceed max. depth of cut a_p
- Down cutting is recommended, tool pass rotation should be counterclockwise

- In case of ramping and helical interpolation, apply 70% or less feed (V_f) from standard cutting condition table
- In case of drilling, apply 50% or less Z axis feed (F) from standard cutting condition table
- Long consecutive chips may result in case of drilling, confirm safe operating conditions

Cat.No.	Tool dia.	Effective Cutting dia.		Max. depth of cut: ap	Ramping	
		Insert			Ramping Max. ramping Angle θ	Max. depth of cut (ap) Total cutting length: L (mm)
		ENMU100412ZER-※※	ENM※100312ZER-※※			
MXG-2016-M8	16	10.1	9.6	0.7	1°36'	25.1
MXG-2017-M8	17	11	10.5	0.7	1°36'	25.1
MXG-3020-M10	20	13.9	13.5	1	1°30'	38.2
MXG-3021-M10	21	14.9	14.5	1	1°30'	38.2
MXG-※025-M12	25	18.9	18.4	1	1°12'	47.7
MXG-4026-M12	26	19.9	19.4	1	1°12'	47.7
MXG-5030-M16	30	23.9	23.4	1	0°54'	63.6
MXG-5032-M16	32	25.8	25.4	1	0°54'	63.6
MXG-5035-M16	35	28.8	28.4	1	0°42'	81.8
MXG-6040-M16	40	33.8	33.4	1	0°30'	114.5
MXG-6042-M16	42	35.8	35.4	1	0°30'	114.5
GMX-2016-※※-S16	16	10.1	9.6	0.7	1°36'	25.1
GMX-3020-※※-S20	20	13.9	13.5	1	1°30'	38.2
GMX-4025-※※-S25	25	18.9	18.4	1	1°12'	47.7
GMX-5032-※※-S32	32	25.8	25.4	1	0°54'	63.6
GMX-7050R-※※	50	43.8	43.4	1	0°24'	143.2
GMX-7052R-22	52	45.8	45.4	1	0°24'	143.2
GMX-7063R-※※	63	56.8	56.4	1	0°18'	190.9
GMX-7066R-※※	66	59.8	59.4	1	0°18'	190.9

Cat.No.	Tool dia.	Helical interpolation			Max.drilling depth : Z	
		Min.Bore dia.		Max. Bore dia.	Insert	
		Insert			ENMU100412ZER-※※	ENM※100312ZER-※※
		ENMU100412ZER-※※	ENM※100312ZER-※※		ENMU100412ZER-※※	ENM※100312ZER-※※
MXG-2016-M8	16	22	21	30	0.3	0.2
MXG-2017-M8	17	24	23	32	0.3	0.2
MXG-3020-M10	20	30	29	38	0.4	0.2
MXG-3021-M10	21	32	31	40	0.4	0.2
MXG-※025-M12	25	40	39	48	0.5	0.3
MXG-4026-M12	26	42	41	50	0.5	0.3
MXG-5030-M16	30	50	49	58	0.6	0.4
MXG-5032-M16	32	54	53	62	0.6	0.4
MXG-5035-M16	35	60	59	68	0.6	0.4
MXG-6040-M16	40	70	69	78	0.7	0.5
MXG-6042-M16	42	74	73	82	0.7	0.5
GMX-2016-※※-S16	16	22	21	30	0.3	0.2
GMX-3020-※※-S20	20	30	29	38	0.4	0.2
GMX-4025-※※-S25	25	40	39	48	0.5	0.3
GMX-5032-※※-S32	32	54	53	62	0.6	0.4
GMX-7050R-※※	50	90	89	98	0.8	0.6
GMX-7052R-22	52	94	93	102	0.8	0.6
GMX-7063R-※※	63	116	115	124	0.8	0.6
GMX-7066R-※※	66	122	121	130	0.8	0.6

■ Recommended Cutting Conditions | GMX10 / MXG10 type

Material	Insert	Grade	Vc (m/min)	fz (mm/t)	ap (mm)	ae (mm)
Carbon Steel below 250HB	-PH	JC8050 (JC7560)	180 (130-180)	1.2	0.4-1.0	0.7 Dc
Tool & Die Steel below 255HB	-PH	JC8050 (JC7560)	180 (130-180)	1.2	0.4-1.0	0.7 Dc
Mold Steel 30-36HRC	-PH	JC8050 (JC7560)	160 (130-160)	1.2	0.4-1.0	0.7 Dc
Mold Steel 38-43HRC	-PH	JC8118 (JC8050)	100 (70-100)	1.1 (0.8-1.1)	0.3-0.8	0.7 Dc
Hardened Die Steel 42-52HRC	-PH (-SL)	JC8118 (JC7518)	90 (70-90)	1.1 (0.8-1.1)	0.1-0.6	0.6 Dc
Hardened Die Steel 55-62HRC	ENMQ.. (ENMU..-HL)	DH102	80 (60-80)	0.3 (0.25-0.3)	0.1-0.2	0.4 Dc
Grey Cast Iron	-PH	JC8118 (JC8050)	200 (150-200)	1.5 (1.2-1.5)	0.4-1.0	0.7 Dc
Nodular Cast Iron	-PH	JC8118 (JC8050)	200 (150-200)	1.5 (1.2-1.5)	0.4-1.0	0.7 Dc
Austenitic Stainless Steel	-SL	JC7550 (JC7518)	120 (100-120)	1.0 (0.8-1.0)	0.3-0.8	0.6 Dc
Precipitationhardening Stainless Steel	-SL (-PH)	JC7550 (JC8050)	100 (90-100)	0.7 (0.6-0.7)	0.2-0.6	0.6 Dc
Duplex Stainless Steel	-SL (-PH)	JC7550 (JC8050)	100 (90-100)	0.3 (0.2-0.3)	0.3-0.8	0.6 Dc
Titanium Alloy	-SL	DS150 (DS118)	60 (50-60)	0.7 (0.6-0.7)	0.3-0.7	0.6 Dc
Heat Resistant Alloy	-SL	JC7518 (JC7550)	30 (20-30)	0.3	0.2~0.7	0.6 Dc

Note

1. Please adjust cutting conditions according to machine rigidity or work rigidity. (the above table is guide for cutting on a BT50 machine.)
2. In case of chatter occurring, recommended to reduce ap or rpm and keep feed per tooth.
3. ap should be reduced when using on low rigidity machine.
4. Use air blow.

QM *Quick & Mini* MAX

New generation high feed mill "QM MAX"

Modular Type
φ16~φ42

Bore Type
φ40~φ66



Shank Type
φ16~φ25



Low cutting force geometry

Unique 3D geometry insert provides stable cutting and less power consumption.

Multi - flutes specification


High speed and high efficient machining.

Vibration free

Control vibration with combination of MSN carbide shank holder

Insert Line-Up


High feed insert



EPMT100312ZER

EPMT100312ZER

High feed insert for unfavorable conditions




EPMW100312ZER

EPMW100312ZTR

EPMW100312ZTR

For high hardened steel

EPHW1003...ZTR
(R1.6, 2.0)

Shoulder insert for aluminum

ZPMT1003...ZER-NL
(R0.4, 0.8, 2.0)


Shoulder insert for general steel

ZPMT1003...ZER-PL
(R0.4, 0.8, 1.6, 2.0)

Shoulder insert for Ti alloy

ZPMT1003...ZER-SL
(R0.4, 0.8, 2.0)

"Mirror Insert" for finishing side & bottom face



YPHW1003...ZER-...

CBN insert



YPHW100308ZTR-F1

A variety of inserts all fit into the same body.


Multi-purpose cutter that can high feed, square up and finish.

QXP
TYPE


Bore Type




● High feed




● Shoulder milling



● High feed (QXP-8066R)



● Shoulder milling (QXP-8066R)



Cat.No.	Stock	No. of inserts	Dimensions (mm)								Insert
			DCX	LF	DCSFMS	DCB	DCCB	KWW	KDP	CBDP	
QXP-6040R-16	●	6	40	45	35	16	14	8.4	5.6	18	EP**1003**Z*R ZPMT1003**ZER** YPHW1003**Z*R**
QXP-7040R-16	●	7	40	45	35	16	14	8.4	5.6	18	
QXP-7050R-22	●	7	50	50	40	22	17	10.4	6.3	20	
QXP-8050R-22	●	8	50	50	40	22	17	10.4	6.3	20	
QXP-8052R-22	●	8	52	50	40	22	17	10.4	6.3	20	
QXP-8063R-22	●	8	63	50	48	22	17	10.4	6.3	20	
QXP-8066R-27	●	8	66	50	48	27	20	12.4	7	22	

Screw	Torque(N.m)	Wrench
DSW-2563H	1.1	A-08

QXPS
TYPE

Shank Type

Through
coolant
hole

Face Milling


Shoulder Milling

Slotting

Copy Milling

Pocket Milling

Helical Interpolation



Cat.No	Stock	No. of inserts	Dimensions (mm)					Parts		Insert
			DCX	LH	LF	DN	DCON	Screw	Wrench	
QXPS2016S16+A	●	2	16	30	100	15	16	TSW-2556H	A-08	EP**1003**Z*R ZPMT1003**ZER-** YPHW1003**Z*R-**
QXPS3020S20+A	●	3	20	50	130	18.85	20			
QXPS4025S25+A	●	4	25	60	140	23.6	25	DSW-2563H		



Screw	Torque(N.m)
TSW-2556H	1.1
DSW-2563H	

QM MAX

MQX/QXP Type

MQX
TYPE

Modular Type




Cat.No.	Stock	No. of inserts	Dimensions (mm)						Parts		Insert
			DCX	LF	DCSFMS	MD	C	W	Screw	Wrench	
MQX-2016-M8	●	2	16	23	14	M8	8	12	TSW-2556H	A-08	EP**1003**Z*R ZPMT1003**ZER-** YPHW1003**Z*R-**
MQX-2017-M8	●	2	17	23	14	M8	8	12			
MQX-3020-M10	●	3	20	30	18	M10	9	14			
MQX-4020-M10	●	4	20	30	18	M10	9	14			
MQX-4021-M10	●	4	21	30	18	M10	9	14			
MQX-4025-M12	●	4	25	35	22.5	M12	10	17	DSW-2563H		
MQX-5025-M12	●	5	25	35	22.5	M12	10	17			
MQX-4026-M12	●	4	26	35	22.5	M12	10	17			
MQX-5026-M12	●	5	26	35	22.5	M12	10	17			
MQX-5028-M12	○	5	28	35	23.6	M12	10	17			
MQX-5030-M16	○	5	30	43	27	M16	12	22			
MQX-5032-M16	●	5	32	43	29	M16	12	22			
MQX-6032-M16	●	6	32	43	29	M16	12	22			
MQX-5035-M16	●	5	35	43	29	M16	12	22			
MQX-6035-M16	●	6	35	43	29	M16	12	22			
MQX-6040-M16	●	6	40	43	32	M16	14	26			
MQX-7040-M16	●	7	40	43	32	M16	14	26			
MQX-6042-M16	●	6	42	43	32	M16	14	26			

Screw	Torque(N.m)
TSW-2556H	1.1
DSW-2563H	


MQX/QXP TYPE

Insert


High feed insert
(EPMT1003 * * ZER)




Shoulder insert for general steel
(ZPMT1003 * * ZER-PL)




Shoulder insert for Ti alloy
(ZPMT1003 * * ZER-SL)





High feed insert for unfavorable conditions
(EPMW100312ZER)




"Mirror Insert" for finishing side & bottom face
(YPHW1003 * * ZER-15) (YPHW100308ZTR-F1) (YPHW100308ZER-F)




High feed insert for unfavorable conditions
(EPMW100312ZTR)




For high hardened steel
(EPHW1003 * * ZTR)




CBN insert



Shoulder insert for aluminum
(ZPMT1003 * * ZER-NL)




"Mirror Insert" for finishing side & bottom face
(YPHW100320ZER-24)




Type	Cat. No.	Tolerance	PVD coating									Uncoated	Cermet	CBN	Dimensions (mm)				
			JC8118	DH102	JC7518	JC7550	JC7560	JC8015	JC8050	DS118	DS150	FC18	CX75	JBN795	L	S	W1	RE	AN
High feed insert	EPMT100312ZER	M	●			●	●		●	●	●				10	3.2	6	1.2	11°
	EPMT100320ZER	M	●												10	3.2	6	2.0	11°
High feed insert for unfavorable conditions	EPMW100312ZER	M	●						●						10	3.2	6	1.2	11°
	EPMW100312ZTR	M	●				●		●						10	3.2	6	1.2	11°
For high hardened steel	EPHW100316ZTR	H	●	●											10	3.2	6	1.6	11°
	EPHW100320ZTR	H	●	●											10	3.2	6	2.0	11°
Shoulder insert for aluminum	ZPMT100304ZER-NL	M										●			10.08	3.4	6	0.4	11°
	ZPMT100308ZER-NL	M										●			10.08	3.4	6	0.8	11°
	ZPMT100320ZER-NL	M										●			10.08	3.4	6	2.0	11°
Shoulder insert for general steel	ZPMT100304ZER-PL	M	●	●					●				●		10.08	3.4	6	0.4	11°
	ZPMT100308ZER-PL	M	●	●					●				●		10.08	3.4	6	0.8	11°
	ZPMT100316ZER-PL	M	●						●						10.08	3.4	6	1.6	11°
	ZPMT100320ZER-PL	M	●	●					●				●		10.08	3.4	6	2.0	11°
Shoulder insert for Ti alloy	ZPMT100304ZER-SL	M			●					●					10.08	3.4	6	0.4	11°
	ZPMT100308ZER-SL	M			●					●					10.08	3.4	6	0.8	11°
	ZPMT100320ZER-SL	M			●					●					10.08	3.4	6	2.0	11°
"Mirror Insert" for finishing side & bottom face	YPHW100303ZER-15	H		●				●					●		10.06	3.35	6	0.3	11°
	YPHW100308ZER-15	H		●									●		10.06	3.35	6	0.8	11°
	YPHW100308ZER-F	H						●							10.06	3.35	6	0.8	11°
	YPHW100308ZTR-F1	H											○		10.06	3.35	6	0.8	11°
	YPHW100320ZER-24	H		●				●							10.06	3.35	6	2.0	11°

GRADE MARKING

● EPMT1003... / EPMW1003...




JC8118/DS118




JC8050/JC7560/DS150

● EPHW1003...




JC8118




DH102

● ZPMT1003...


JC8118/JC7518
DS118/FC18

DH102




JC8050/CX75

● YPHW100303ZER-15




DH102/CX75




JC8015

● YPHW100308ZER-15




DH102/CX75

● YPHW100308ZER-F




JC8015

● YPHW100320ZER-24



DH102



JC8015

Insert selection guide

Material	Carbon steel (S50C, S55C) below 250HB						Tool & die steel (SKD61, SKD11) below 255HB						Mold steel (HPM7, PX5, P20) 30-36HRC						Mold steel (NAK80, HPM1, P21) 38-43HRC					
Cat.No. Grade	JC8118	JC8050	JC7560	DH102	DS118	DS150	JC8118	JC8050	JC7560	DH102	DS118	DS150	JC8118	JC8050	JC7560	DH102	DS118	DS150	JC8118	JC8050	JC7560	DH102	DS118	DS150
EPMT1003 * * ZER	☆	☆	☆				☆	☆	☆				☆	☆	☆				☆	☆				
EPMW100312ZER																				○				
EPMW100312ZTR	○	○	◎				○	○	◎				○	○	◎				◎	○				
EPHW100316ZTR																								

Material	Hardened die steel (SKD61, DAC, DHA) 42-52 HRC						Hardened die steel (SKD11, SLD, DC11) 55-62HRC						Grey cast iron (FC, FCD) below 300HB						Stainless steel (SUS304) below 250HB					
Cat.No. Grade	JC8118	JC8050	JC7560	DH102	DS118	DS150	JC8118	JC8050	JC7560	DH102	DS118	DS150	JC8118	JC8050	JC7560	DH102	DS118	DS150	JC8118	JC8050	JC7560	DH102	DS118	DS150
EPMT1003 * * ZER	☆						×	×					○							◎	○			
EPMW100312ZER	○						○						◎							●				
EPMW100312ZTR	●						●						●		○									
EPHW100316ZTR	◎									◎														


Material	Titanium alloy (Ti-6Al-4V)						Heat resistant alloy (INC0718)					
Cat.No. Grade	JC8118	JC8050	JC7560	DH102	DS118	DS150	JC8118	JC8050	JC7560	DH102	DS118	DS150
EPMT1003 * * ZER	○	○	●		○	◎	◎	○	○		○	○
EPMW100312ZER		●						●				
EPMW100312ZTR												
EPHW100316ZTR												

- EPMT Type : with chip breaker
- EPMW Type : without chip breaker

- ◎ : First choice
- : For general milling
- : For unstable milling
- ☆ : For light cutting force
- ×


Definition of corner shape for programming

- EPMT/W Type
(RE=R1.2)




Corner radius for programming R	Over cut	Remains
R1.0	0	0.57
R1.5 (Std.)	0	0.45
R2.0	0.04	0.33
R2.5	0.21	0.21
R3.0	0.40	0.09

- EPMT Type
(RE=R2.0)



Corner radius for programming R	Over cut	Remains
R1.0	0	0.51
R1.5	0	0.31
R2.0 (Std.)	0	0.13
R2.5	0.12	0.04
R3.0	0.32	0


- EPHW Type




Corner radius for programming R	Over cut	Remains
R1.0	0	0.42
R1.5 (Std.)	0	0.33
R2.0	0.01	0.23
R2.5	0.17	0.14
R3.0	0.37	0.05

Recommended Data for Profile Milling

Ramping



Helical interpolation



- Calculation of tool pass dia.

$$\phi D_c = \phi D_h - \phi D_c$$

Tool pass dia. Bore dia. Tool Dia.

- Depth of cut per one circuit should not exceed max. depth of cut A_p
- Down cutting is recommended, tool pass rotation should be counterclockwise

- In case of ramping and helical interpolation, apply 70% or less feed (V_f) from standard cutting condition table
- In case of drilling, apply 50% or less Z axis feed (F) from standard cutting condition table
- Long consecutive chips may result in case of drilling, confirm safe operating conditions

EPM*100312ZER

Cat.No.	Tool dia.	Effective Cutting dia.	Max.depth of cut : a_p	Ramping		Helical interpolation		Max.drilling depth Z(mm)
				Max.ramping angle θ	Max.depth of cut (a_p) Total cutting length L (mm)	Min.Bore dia.	Max.Bore dia.	
QXP-*040R-16	40	34.1	1	0.5	114.6	70	78	0.6
QXP-*050R-* *	50	44.1	1	0.4	143.2	90	98	0.6
QXP-8052R-22	52	46.1	1	0.35	163.7	94	102	0.6
QXP-8063R-* *	63	57.1	1	0.3	191	116	124	0.6
QXP-8066R-* *	66	60.1	1	0.3	191	122	130	0.6
QXPS2016S16+A	16	10.2	0.8	1.8	25.5	22	30	0.6
QXPS3020S20+A	20	14.1	0.8	1.4	32.7	30	38	0.6
QXPS4025S25+A	25	19.1	0.8	1	45.8	40	48	0.6
MQX-*016-M8	16	10.2	0.8	1.8	25.5	22	30	0.6
MQX-*017-M8	17	11.2	0.8	1.6	28.6	24	32	0.6
MQX-*020-M10	20	14.1	0.8	1.4	32.7	30	38	0.6
MQX-*021-M10	21	15.1	0.8	1.3	35.3	32	40	0.6
MQX-*025-M12	25	19.1	0.8	1	45.8	40	48	0.6
MQX-*026-M12	26	20.1	0.8	0.95	48.2	42	50	0.6
MQX-*028-M12	28	22.1	0.8	0.85	53.9	46	54	0.6
MQX-*030-M16	30	24.1	0.8	0.8	57.3	50	58	0.5
MQX-*032-M16	32	26.1	0.8	0.7	65.5	54	62	0.5
MQX-*035-M16	35	29.1	0.8	0.6	76.4	60	68	0.5
MQX-*040-M16	40	34.1	0.8	0.5	91.7	70	78	0.6
MQX-*042-M16	42	36.2	0.8	0.45	101.9	74	82	0.6

Recommended Data for Profile Milling

EPMT100320ZER

Cat.No.	Tool dia.	Effective Cutting dia.	Max.depth of cut : ap	Ramping		Helical interpolation		Max.drilling depth Z(mm)
				Max.ramping angle θ	Max.depth of cut (ap) Total cutting length L (mm)	Min.Bore dia.	Max.Bore dia.	
QXP- * 040R-16	40	35.1	1	0.55	104.2	72	78	0.7
QXP- * 050R- * *	50	45.1	1	0.4	143.2	92	98	0.7
QXP-8052R-22	52	47.2	1	0.4	143.2	96	102	0.7
QXP-8063R- * *	63	58.2	1	0.3	191	118	124	0.7
QXP-8066R- * *	66	61.2	1	0.3	191	124	130	0.7
QXPS2016S16+A	16	11.2	0.8	2.3	19.9	24	30	0.7
QXPS3020S20+A	20	15.1	0.8	1.5	30.6	32	38	0.7
QXPS4025S25+A	25	20.1	0.8	1.1	41.7	42	48	0.6
MQX- * 016-M8	16	11.2	0.8	2.3	19.9	24	30	0.7
MQX- * 017-M8	17	12.2	0.8	2	22.9	26	32	0.7
MQX- * 020-M10	20	15.1	0.8	1.5	30.6	32	38	0.7
MQX- * 021-M10	21	16.1	0.8	1.4	32.7	34	40	0.7
MQX- * 025-M12	25	20.1	0.8	1.1	41.7	42	48	0.6
MQX- * 026-M12	26	21.1	0.8	1	45.8	44	50	0.6
MQX- * 028-M12	28	23.1	0.8	0.9	50.9	48	54	0.6
MQX- * 030-M16	30	25.1	0.8	0.85	53.9	52	58	0.6
MQX- * 032-M16	32	27.1	0.8	0.75	61.1	56	62	0.6
MQX- * 035-M16	35	30.1	0.8	0.65	70.5	62	68	0.6
MQX- * 040-M16	40	35.1	0.8	0.55	83.3	72	78	0.7
MQX- * 042-M16	42	37.1	0.8	0.55	83.3	76	82	0.7

EPMW100312ZTR

Cat.No.	Tool dia.	Effective Cutting dia.	Max.depth of cut : ap	Ramping		Helical interpolation		Max.drilling depth Z(mm)
				Max.ramping angle θ	Max.depth of cut (ap) Total cutting length L (mm)	Min.Bore dia.	Max.Bore dia.	
QXP- * 040R-16	40	34.1	1	0.4	143.2	70	78	0.6
QXP- * 050R- * *	50	44.1	1	0.3	191	90	98	0.6
QXP-8052R-22	52	46.1	1	0.25	229.2	94	102	0.6
QXP-8063R- * *	63	57.1	1	0.2	286.5	116	124	0.6
QXP-8066R- * *	66	60.1	1	0.2	286.5	122	130	0.6
QXPS2016S16+A	16	10.2	0.8	1.7	27	22	30	0.6
QXPS3020S20+A	20	14.1	0.8	1.3	35.3	30	38	0.6
QXPS4025S25+A	25	19.1	0.8	0.9	50.9	40	48	0.6
MQX- * 016-M8	16	10.2	0.8	1.7	27	22	30	0.6
MQX- * 017-M8	17	11.2	0.8	1.5	30.6	24	32	0.6
MQX- * 020-M10	20	14.1	0.8	1.3	35.3	30	38	0.6
MQX- * 021-M10	21	15.1	0.8	1.2	38.2	32	40	0.6
MQX- * 025-M12	25	19.1	0.8	0.9	50.9	40	48	0.6
MQX- * 026-M12	26	20.1	0.8	0.85	53.9	42	50	0.6
MQX- * 028-M12	28	22.1	0.8	0.75	61.1	46	54	0.6
MQX- * 030-M16	30	24.1	0.8	0.7	65.5	50	58	0.5
MQX- * 032-M16	32	26.1	0.8	0.6	76.4	54	62	0.5
MQX- * 035-M16	35	29.1	0.8	0.5	91.7	60	68	0.5
MQX- * 040-M16	40	34.1	0.8	0.4	114.6	70	78	0.6
MQX- * 042-M16	42	36.2	0.8	0.35	131	74	82	0.6

Recommended Data for Profile Milling

EPHW100316ZTR

Cat.No.	Tool dia.	Effective Cutting dia.	Max.depth of cut : ap	Ramping		Helical interpolation		Max.drilling depth Z(mm)
				Max.ramping angle θ	Max.depth of cut (ap) Total cutting length L (mm)	Min.Bore dia.	Max.Bore dia.	
QXP- * 040R-16	40	34.1	0.6	0.3	114.6	70	78	0.6
QXP- * 050R- * *	50	44.1	0.6	0.2	171.9	90	98	0.6
QXP-8052R-22	52	46.1	0.6	0.2	171.9	94	102	0.6
QXP-8063R- * *	63	57.1	0.6	0.15	229.2	116	124	0.6
QXP-8066R- * *	66	60.1	0.6	0.15	229.2	122	130	0.6
QXPS2016S16+A	16	10.2	0.6	1.1	31.2	22	30	0.6
QXPS3020S20+A	20	14.1	0.6	0.8	43	30	38	0.6
QXPS4025S25+A	25	19.1	0.6	0.55	62.5	40	48	0.6
MQX- * 016-M8	16	10.2	0.6	1.1	31.2	22	30	0.6
MQX- * 017-M8	17	11.2	0.6	1	34.4	24	32	0.6
MQX- * 020-M10	20	14.1	0.6	0.8	43	30	38	0.6
MQX- * 021-M10	21	15.1	0.6	0.7	49.1	32	40	0.6
MQX- * 025-M12	25	19.1	0.6	0.55	62.5	40	48	0.6
MQX- * 026-M12	26	20.1	0.6	0.5	68.8	42	50	0.6
MQX- * 028-M12	28	22.1	0.6	0.45	76.4	46	54	0.6
MQX- * 030-M16	30	24.1	0.6	0.4	85.9	50	58	0.5
MQX- * 032-M16	32	26.1	0.6	0.4	85.9	54	62	0.5
MQX- * 035-M16	35	29.1	0.6	0.35	98.2	60	68	0.5
MQX- * 040-M16	40	34.1	0.6	0.3	114.6	70	78	0.6
MQX- * 042-M16	42	36.2	0.6	0.25	137.5	74	82	0.6

ZPMT100304ZER- **

Cat.No.	Tool dia.	Effective Cutting dia.	Max.depth of cut : ap	Ramping		Helical interpolation		Max.drilling depth Z(mm)
				Max.ramping angle θ	Max.depth of cut (ap) Total cutting length L (mm)	Min.Bore dia.	Max.Bore dia.	
QXP- * 040R-16	40	39	1	0.95	60.3	75.6	78.4	0.6
QXP- * 050R- * *	50	49	1	0.7	81.8	95.6	98.4	0.6
QXP-8052R-22	52	51	1	0.65	88.1	99.6	102.4	0.6
QXP-8063R- * *	63	62	1	0.55	104.2	121.6	124.4	0.6
QXP-8066R- * *	66	65	1	0.5	114.6	127.6	130.4	0.6
QXPS2016S16+A	16	15	0.8	3	15.3	27.6	30.4	0.6
QXPS3020S20+A	20	19	0.8	2.4	19.1	35.6	38.4	0.6
QXPS4025S25+A	25	24	0.8	1.7	27	45.6	48.4	0.6
MQX- * 016-M8	16	15	0.8	3	15.3	27.6	30.4	0.6
MQX- * 017-M8	17	16	0.8	3.2	14.3	29.6	32.4	0.6
MQX- * 020-M10	20	19	0.8	2.4	19.1	35.6	38.4	0.6
MQX- * 021-M10	21	20	0.8	2.2	20.8	37.6	40.4	0.6
MQX- * 025-M12	25	24	0.8	1.7	27	45.6	48.4	0.6
MQX- * 026-M12	26	25	0.8	1.6	28.6	47.6	50.4	0.6
MQX- * 028-M12	28	27	0.8	1.5	30.6	51.6	54.4	0.6
MQX- * 030-M16	30	29	0.8	1.3	35.3	55.6	58.4	0.5
MQX- * 032-M16	32	31	0.8	1.2	38.2	59.6	62.4	0.5
MQX- * 035-M16	35	34	0.8	1.1	41.7	65.6	68.4	0.5
MQX- * 040-M16	40	39	0.8	0.95	48.2	75.6	78.4	0.6
MQX- * 042-M16	42	41	0.8	0.85	53.9	79.6	82.4	0.6

Recommended Data for Profile Milling

ZPMT100308ZER-**-**

Cat.No.	Tool dia.	Effective Cutting dia.	Max.depth of cut : ap	Ramping		Helical interpolation		Max.drilling depth Z(mm)
				Max.ramping angle θ	Max.depth of cut (ap) Total cutting length L (mm)	Min.Bore dia.	Max.Bore dia.	
QXP- * 040R-16	40	38.2	1	0.95	60.3	74.8	77.6	0.6
QXP- * 050R- * *	50	48.2	1	0.7	81.8	94.8	97.6	0.6
QXP-8052R-22	52	50.2	1	0.65	88.1	98.8	101.6	0.6
QXP-8063R- * *	63	61.2	1	0.55	104.2	120.8	123.6	0.6
QXP-8066R- * *	66	64.2	1	0.5	114.6	126.8	129.6	0.6
QXPS2016S16+A	16	14.2	0.8	3	15.3	26.8	29.6	0.6
QXPS3020S20+A	20	18.2	0.8	2.4	19.1	34.8	37.6	0.6
QXPS4025S25+A	25	23.2	0.8	1.7	27	44.8	47.6	0.6
MQX- * 016-M8	16	14.2	0.8	3	15.3	26.8	29.6	0.6
MQX- * 017-M8	17	15.2	0.8	3.2	14.3	28.8	31.6	0.6
MQX- * 020-M10	20	18.2	0.8	2.4	19.1	34.8	37.6	0.6
MQX- * 021-M10	21	19.2	0.8	2.2	20.8	36.8	39.6	0.6
MQX- * 025-M12	25	23.2	0.8	1.7	27	44.8	47.6	0.6
MQX- * 026-M12	26	24.2	0.8	1.6	28.6	46.8	49.6	0.6
MQX- * 028-M12	28	26.2	0.8	1.5	30.6	50.8	53.6	0.6
MQX- * 030-M16	30	28.2	0.8	1.3	35.3	54.8	57.6	0.5
MQX- * 032-M16	32	30.2	0.8	1.2	38.2	58.8	61.6	0.5
MQX- * 035-M16	35	33.2	0.8	1.1	41.7	64.8	67.6	0.5
MQX- * 040-M16	40	38.2	0.8	0.95	48.2	74.8	77.6	0.6
MQX- * 042-M16	42	40.2	0.8	0.85	53.9	78.8	81.6	0.6

ZPMT100320ZER-**-**

Cat.No.	Tool dia.	Effective Cutting dia.	Max.depth of cut : ap	Ramping		Helical interpolation		Max.drilling depth Z(mm)
				Max.ramping angle θ	Max.depth of cut (ap) Total cutting length L (mm)	Min.Bore dia.	Max.Bore dia.	
QXP- * 040R-16	40	35.8	1	0.95	60.3	70	75.2	0.6
QXP- * 050R- * *	50	45.8	1	0.7	81.8	90	95.2	0.6
QXP-8052R-22	52	47.8	1	0.65	88.1	94	99.2	0.6
QXP-8063R- * *	63	58.8	1	0.55	104.2	116	121.2	0.6
QXP-8066R- * *	66	61.8	1	0.5	114.6	122	127.2	0.6
QXPS2016S16+A	16	11.8	0.8	3	15.3	22	27.2	0.6
QXPS3020S20+A	20	15.8	0.8	2.4	19.1	30	35.2	0.6
QXPS4025S25+A	25	20.8	0.8	1.7	27	40	45.2	0.6
MQX- * 016-M8	16	11.8	0.8	3	15.3	22	27.2	0.6
MQX- * 017-M8	17	12.8	0.8	3.2	14.3	24	29.2	0.6
MQX- * 020-M10	20	15.8	0.8	2.4	19.1	30	35.2	0.6
MQX- * 021-M10	21	16.8	0.8	2.2	20.8	32	37.2	0.6
MQX- * 025-M12	25	20.8	0.8	1.7	27	40	45.2	0.6
MQX- * 026-M12	26	21.8	0.8	1.6	28.6	42	47.2	0.6
MQX- * 028-M12	28	23.8	0.8	1.5	30.6	46	51.2	0.6
MQX- * 030-M16	30	25.8	0.8	1.3	35.3	50	55.2	0.5
MQX- * 032-M16	32	27.8	0.8	1.2	38.2	54	59.2	0.5
MQX- * 035-M16	35	30.8	0.8	1.1	41.7	60	65.2	0.5
MQX- * 040-M16	40	35.8	0.8	0.95	48.2	70	75.2	0.6
MQX- * 042-M16	42	37.8	0.8	0.85	53.9	74	79.2	0.6

Recommended Data for Profile Milling

YPHW100303ZER-15

Cat.No.	Tool dia.	Effective Cutting dia.	Max.depth of cut : ap	Ramping		Helical interpolation		Max.drilling depth Z(mm)
				Max.ramping angle θ	Max.depth of cut (ap) Total cutting length L (mm)	Min.Bore dia.	Max.Bore dia.	
QXP- * 040R-16	40	39.3	0.3	1	17.2	77	78.7	0.3
QXP- * 050R- * *	50	49.3	0.3	0.75	22.9	97	98.7	0.3
QXP-8052R-22	52	51.3	0.3	0.7	24.6	101	102.7	0.3
QXP-8063R- * *	63	62.3	0.3	0.6	28.6	123	124.7	0.3
QXP-8066R- * *	66	65.3	0.3	0.55	31.3	129	130.7	0.3
QXPS2016S16+A	16	15.3	0.3	1.3	13.2	29	30.7	0.2
QXPS3020S20+A	20	19.3	0.3	2.1	8.2	37	38.7	0.3
QXPS4025S25+A	25	24.3	0.3	1.8	9.5	47	48.7	0.3
MQX- * 016-M8	16	15.3	0.3	1.3	13.2	29	30.7	0.2
MQX- * 017-M8	17	16.3	0.3	1.7	10.1	31	32.7	0.3
MQX- * 020-M10	20	19.3	0.3	2.1	8.2	37	38.7	0.3
MQX- * 021-M10	21	20.3	0.3	2.4	7.2	39	40.7	0.3
MQX- * 025-M12	25	24.3	0.3	1.8	9.5	47	48.7	0.3
MQX- * 026-M12	26	25.3	0.3	1.7	10.1	49	50.7	0.3
MQX- * 028-M12	28	27.3	0.3	1.6	10.7	53	54.7	0.3
MQX- * 030-M16	30	29.3	0.3	1.4	12.3	57	58.7	0.3
MQX- * 032-M16	32	31.3	0.3	1.3	13.2	61	62.7	0.3
MQX- * 035-M16	35	34.3	0.3	1.2	14.3	67	68.7	0.3
MQX- * 040-M16	40	39.3	0.3	1	17.2	77	78.7	0.3
MQX- * 042-M16	42	41.3	0.3	0.9	19.1	81	82.7	0.3

YPHW100308ZER-15

Cat.No.	Tool dia.	Effective Cutting dia.	Max.depth of cut : ap	Ramping		Helical interpolation		Max.drilling depth Z(mm)
				Max.ramping angle θ	Max.depth of cut (ap) Total cutting length L (mm)	Min.Bore dia.	Max.Bore dia.	
QXP- * 040R-16	40	38.3	0.3	1	17.2	75	77.7	0.3
QXP- * 050R- * *	50	48.3	0.3	0.75	22.9	95	97.7	0.3
QXP-8052R-22	52	50.3	0.3	0.7	24.6	99	101.7	0.3
QXP-8063R- * *	63	61.3	0.3	0.6	28.6	121	123.7	0.3
QXP-8066R- * *	66	64.3	0.3	0.55	31.3	127	129.7	0.3
QXPS2016S16+A	16	14.3	0.3	1.4	12.3	27	29.7	0.2
QXPS3020S20+A	20	18.3	0.3	2.2	7.8	35	37.7	0.3
QXPS4025S25+A	25	23.3	0.3	1.9	9	45	47.7	0.3
MQX- * 016-M8	16	14.3	0.3	1.4	12.3	27	29.7	0.2
MQX- * 017-M8	17	15.3	0.3	1.8	9.5	29	31.7	0.3
MQX- * 020-M10	20	18.3	0.3	2.2	7.8	35	37.7	0.3
MQX- * 021-M10	21	19.3	0.3	2.5	6.9	37	39.7	0.3
MQX- * 025-M12	25	23.3	0.3	1.9	9	45	47.7	0.3
MQX- * 026-M12	26	24.3	0.3	1.8	9.5	47	49.7	0.3
MQX- * 028-M12	28	26.3	0.3	1.7	10.1	51	53.7	0.3
MQX- * 030-M16	30	28.3	0.3	1.5	11.5	55	57.7	0.3
MQX- * 032-M16	32	30.3	0.3	1.4	12.3	59	61.7	0.3
MQX- * 035-M16	35	33.3	0.3	1.2	14.3	65	67.7	0.3
MQX- * 040-M16	40	38.3	0.3	1	17.2	75	77.7	0.3
MQX- * 042-M16	42	40.3	0.3	0.9	19.1	79	81.7	0.3

Recommended Data for Profile Milling

YPHW100320ZER-24

Cat.No.	Tool dia.	Effective Cutting dia.	Max.depth of cut : ap	Ramping		Helical interpolation		Max.drilling depth Z(mm)
				Max.ramping angle θ	Max.depth of cut (ap) Total cutting length L (mm)	Min.Bore dia.	Max.Bore dia.	
QXP- *040R-16	40	35.9	0.3	1.1	15.6	70.2	75.3	0.3
QXP- *050R- * *	50	45.9	0.3	0.9	19.1	90.2	95.3	0.3
QXP-8052R-22	52	47.9	0.3	0.85	20.2	94.2	99.3	0.3
QXP-8063R- * *	63	58.9	0.3	0.65	26.4	116.2	121.3	0.3
QXP-8066R- * *	66	61.9	0.3	0.65	26.4	122.2	127.3	0.3
QXPS2016S16+A	16	11.9	0.3	1.9	9	22.2	27.3	0.3
QXPS3020S20+A	20	15.9	0.3	2.5	6.9	30.2	35.3	0.3
QXPS4025S25+A	25	20.9	0.3	2.2	7.8	40.2	45.3	0.3
MQX- *016-M8	16	11.9	0.3	1.9	9	22.2	27.3	0.3
MQX- *017-M8	17	12.9	0.3	2.2	7.8	24.2	29.3	0.3
MQX- *020-M10	20	15.9	0.3	2.5	6.9	30.2	35.3	0.3
MQX- *021-M10	21	16.9	0.3	2.8	6.1	32.2	37.3	0.3
MQX- *025-M12	25	20.9	0.3	2.2	7.8	40.2	45.3	0.3
MQX- *026-M12	26	21.9	0.3	2	8.6	42.2	47.3	0.3
MQX- *028-M12	28	23.9	0.3	1.8	9.5	46.2	51.3	0.3
MQX- *030-M16	30	25.9	0.3	1.6	10.7	50.2	55.3	0.3
MQX- *032-M16	32	27.9	0.3	1.5	11.5	54.2	59.3	0.3
MQX- *035-M16	35	30.9	0.3	1.4	12.3	60.2	65.3	0.3
MQX- *040-M16	40	35.9	0.3	1.1	15.6	70.2	75.3	0.3
MQX- *042-M16	42	37.9	0.3	1.1	15.6	74.2	79.3	0.3

■ Recommended Cutting Conditions

Material		High Feed		Shoulder Milling	Side Finishing	Bottom Finishing
		EPMT / EPMW	EPHW	ZPMT		
Carbon Steel below 250HB	Grade	JC7560 (JC8050 JC8118)	-	JC8050 (JC8118)	JC8050 (JC8118)	JC8050 (JC8118)
	Vc	130 - 180	-	130 - 160	190 - 320	90 - 180
	fz	0.7 - 0.9	-	0.12 - 0.15	0.18 - 0.30	0.1 - 0.15
	ap	0.4 - 1.0	-	~5.0	~5.0	~0.2
	ae	0.7 Dc	-	~0.16 Dc	~0.2	0.4 - 1.0 Dc
Tool & Die Steel below 255HB	Grade	JC7560 (JC8050 JC8118)	-	JC8050 (JC8118)	JC8050 (JC8118)	JC8050 (JC8118)
	Vc	130 - 180	-	120 - 150	180 - 300	80 - 160
	fz	0.7 - 0.9	-	0.12 - 0.15	0.15 - 0.25	0.1 - 0.15
	ap	0.4 - 1.0	-	~5.0	~5.0	~0.2
	ae	0.7 Dc	-	~0.16 Dc	~0.2	0.4 - 1.0 Dc
Mold Steel 30-36HRC	Grade	JC8118 (JC7560 JC8050)	-	JC8118 (JC8050)	JC8118 (JC8050)	JC8118 (JC8050)
	Vc	130 - 180	-	120 - 150	180 - 300	80 - 160
	fz	0.7 - 1.0	-	0.12 - 0.15	0.15 - 0.25	0.1 - 0.15
	ap	0.4 - 1.0	-	~5.0	~5.0	~0.2
	ae	0.7 Dc	-	~0.16 Dc	~0.2	0.4 - 1.0 Dc
Mold Steel 38-43HRC	Grade	JC8118 (JC8050)	-	JC8118 (JC8050)	JC8118 (JC8050)	JC8118 (JC8050)
	Vc	70 - 100	-	100 - 120	150 - 250	70 - 140
	fz	0.6 - 0.7	-	0.1 - 0.12	0.15 - 0.25	0.1 - 0.15
	ap	0.3 - 0.8	-	~4.0	~4.0	~0.2
	ae	0.6 Dc	-	~0.15 Dc	~0.2	0.4 - 1.0 Dc
Hardened Die Steel 42-52HRC	Grade	JC8118	JC8118	JC8118 (DH102)	JC8118 (DH102)	JC8118 (DH102)
	Vc	60 - 70	70 - 90	80 - 100	120 - 210	75 - 100
	fz	0.5	0.5 - 0.8	0.09 - 0.12	0.12 - 0.20	0.1 - 0.12
	ap	0.2 - 0.6	0.1 - 0.3	~3.5	~3.5	~0.2
	ae	0.6 Dc	0.6 Dc	~0.14 Dc	~0.2	0.4 - 1.0 Dc
Hardened Die Steel 55-62HRC	Grade	-	DH102	DH102	DH102	DH102
	Vc	-	60 - 80	50 - 70	100 - 180	50 - 70
	fz	-	0.2 - 0.3	0.1	0.09 - 0.15	0.08 - 0.1
	ap	-	0.1 - 0.2	~2.5	~2.5	~0.15
	ae	-	0.4 Dc	~0.14 Dc	~0.15	0.4 - 1.0 Dc
Grey & Nodular Cast Iron below 300HB	Grade	JC8118	-	JC8118 (DH102)	JC8118 (DH102)	JC8118 (DH102)
	Vc	110 - 150	-	120 - 150	160 - 280	90 - 180
	fz	0.8 - 1.2	-	0.16 - 0.2	0.18 - 0.30	0.12 - 0.18
	ap	0.4 - 1.0	-	~5.0	~5.0	~0.2
	ae	0.7 Dc	-	~0.2 Dc	~0.2	0.4 - 1.0 Dc
Stainless Steel	Grade	JC8050 (JC7560)	-	JC8050 (JC8118 JC7518)	JC8050 (JC8118 JC7518)	JC8050 (JC8118 JC7518)
	Vc	130 - 150	-	120 - 150	180 - 300	80 - 160
	fz	0.6 - 0.8	-	0.12 - 0.15	0.15 - 0.25	0.1 - 0.15
	ap	0.3 - 0.8	-	~5.0	~5.0	~0.2
	ae	0.6 Dc	-	~0.16 Dc	~0.2	0.4 - 1.0 Dc
Titanium Alloy	Grade	DS150 (JC8050 DS118)	-	DS118 (JC7518)	DS118 (JC7518)	DS118 (JC7518)
	Vc	50 - 60	-	50 - 60	60 - 100	25 - 50
	fz	0.4	-	0.12 - 0.15	0.15 - 0.25	0.1 - 0.12
	ap	0.2 - 0.8	-	~5.0	~5.0	~0.2
	ae	0.6 Dc	-	~0.15 Dc	~0.2	0.4 - 1.0 Dc
Heat Resistant Alloy	Grade	JC8118 (JC8050)	-	JC7518	JC7518	JC7518
	Vc	20 - 30	-	25 - 30	30 - 50	15 - 30
	fz	0.3	-	0.11 - 0.15	0.15 - 0.25	0.1 - 0.12
	ap	0.2 - 0.8	-	~5.0	~5.0	~0.2
	ae	0.6 Dc	-	~0.15 Dc	~0.20	0.4 - 1.0 Dc
Aluminium	Grade	-	-	FC18	FC18	FC18
	Vc	-	-	300 - 600	420 - 700	300 - 600
	fz	-	-	0.16 - 0.2	0.18 - 0.30	0.1 - 0.15
	ap	-	-	~5.0	~5.0	~0.3
	ae	-	-	~0.4 Dc	~0.3	0.4 - 1.0 Dc

■ Recommended Cutting Conditions

Material		Contouring	Side Finishing	Bottom Finishing	Vertical Side Finishing	Side Finishing	Bottom Finishing	Vertical Side Finishing
		YPHW-24	YPHW-15			YPHW-F (CBN)		
Carbon Steel below 250HB	Grade	-	JC8015 (DH102)	DH102	JC8015 (DH102)	-	-	-
	Vc	-	450 - 650	170 - 260	350 - 450	-	-	-
	fz	-	0.1 - 0.15	0.18 - 0.25	0.08 - 0.18	-	-	-
	ap	-	0.7 - 2.0	~0.2	Pf 0.5 - 1.12	-	-	-
	ae	-	~0.2	~0.6 Dc	~0.2	-	-	-
Tool & Die Steel below 255HB	Grade	-	JC8015 (DH102)	DH102	JC8015 (DH102)	-	-	-
	Vc	-	350 - 450	150 - 240	300 - 400	-	-	-
	fz	-	0.1 - 0.15	0.18 - 0.25	0.08 - 0.18	-	-	-
	ap	-	0.7 - 2.0	~0.2	Pf 0.5 - 1.12	-	-	-
	ae	-	~0.2	~0.6 Dc	~0.2	-	-	-
Mold Steel 30-36HRC	Grade	-	JC8015 (DH102)	DH102	JC8015 (DH102)	-	-	-
	Vc	-	350 - 450	140 - 220	250 - 350	-	-	-
	fz	-	0.1 - 0.15	0.17 - 0.2	0.07 - 0.15	-	-	-
	ap	-	0.7 - 2.0	~0.2	Pf 0.5 - 1.12	-	-	-
	ae	-	~0.2	~0.6 Dc	~0.2	-	-	-
Mold Steel 38-43HRC	Grade	JC8015 (DH102)	JC8015 (DH102)	DH102	JC8015 (DH102)	-	-	-
	Vc	220	350 - 400	150 - 200	180 - 250	-	-	-
	fz	0.25	0.08 - 0.12	0.1 - 0.12	0.07 - 0.12	-	-	-
	ap	0.15 - 0.4	0.7 - 2.0	~0.2	Pf 0.5 - 1.12	-	-	-
	ae	~0.4 Dc	~0.2	~0.6 Dc	~0.2	-	-	-
Hardened Die Steel 42-52HRC	Grade	JC8015 (DH102)	JC8015 (DH102)	DH102	DH102 (JC8015)	JBN795	JBN795	JBN795
	Vc	160	170 - 200	60 - 100	120 - 170	400 - 450	300 - 350	400 - 450
	fz	0.25	0.08 - 0.1	0.1	0.06 - 0.1	0.07 - 0.08	0.06 - 0.08	0.07 - 0.08
	ap	0.1 - 0.25	~1.5	~0.2	Pf 0.5 - 1.12	~1.2	~0.08	Pf 0.5 - 1.12
	ae	~0.4 Dc	~0.2	~0.6 Dc	~0.15	~0.1	~0.6 Dc	~0.1
Hardened Die Steel 55-62HRC	Grade	DH102	DH102	DH102	-	JBN795	JBN795	-
	Vc	100	150 - 180	50 - 70	-	300 - 400	200	-
	fz	0.2	0.08 - 0.1	0.05 - 0.07	-	0.06 - 0.08	0.05 - 0.06	-
	ap	0.1 - 0.2	~1.0	~0.2	-	~1.2	~0.06	-
	ae	~0.3 Dc	~0.2	~0.4 Dc	-	~0.1	~0.6 Dc	-
Grey Cast Iron	Grade	-	JC8015 (DH102)	DH102	JC8015 (DH102)	JBN795	JBN795	JBN795
	Vc	-	450 - 550	130 - 200	450 - 550	750	700	750
	fz	-	0.1 - 0.15	0.1 - 0.2	0.1 - 0.15	0.1 - 0.135	0.1 - 0.12	0.1 - 0.135
	ap	-	0.7 - 2.0	~0.2	Pf 0.5 - 1.12	~1.5	~0.1	Pf 0.5 - 1.12
	ae	-	~0.2	~0.6 Dc	~0.2	~0.1	~0.6 Dc	~0.1
Nodular Cast Iron	Grade	-	JC8015 (DH102)	DH102	JC8015 (DH102)	JBN795	-	JBN795
	Vc	-	450 - 550	130 - 200	450 - 550	700	-	700
	fz	-	0.1 - 0.15	0.1 - 0.2	0.1 - 0.15	0.1 - 0.135	-	0.1 - 0.135
	ap	-	0.7 - 2.0	~0.2	Pf 0.5 - 1.12	~1.5	-	Pf 0.5
	ae	-	~0.2	~0.6 Dc	~0.2	~0.1	-	~0.1
Stainless Steel	Grade	-	JC8015 (DH102)	JC8015 (DH102)	-	-	-	-
	Vc	-	350 - 450	130 - 180	-	-	-	-
	fz	-	0.1 - 0.15	0.1 - 0.15	-	-	-	-
	ap	-	0.7 - 2.0	~0.2	-	-	-	-
	ae	-	~0.2	~0.6 Dc	-	-	-	-
Titanium Alloy	Grade	-	JC8015 (DH102)	DH102	-	-	-	-
	Vc	-	70 - 90	30 - 50	-	-	-	-
	fz	-	0.08 - 0.12	0.1 - 0.15	-	-	-	-
	ap	-	0.7 - 2.0	~0.2	-	-	-	-
	ae	-	~0.2	~0.6 Dc	-	-	-	-

Note

1. Please adjust cutting conditions according to machine rigidity or work rigidity.
2. In case of chatter occurring, recommended to reduce ap or rpm and keep feed per tooth.
3. ap should be reduced when using on low rigidity machine.
4. Use air blow.
5. When using Endmill type, reduce cutting conditions by 10-20%.

Low cutting force geometry

- Unique 3D geometry insert provides stable cutting and less power consumption.
- BT30 Capable of running on low horse power & compact machines.





Multi - flutes specification

- High speed and high efficient machining.

Vibration free

- Control vibration with combination of MSN carbide shank holder for longer tool life.

Low cutting force geometry High feed machining with Multi-flutes specification



Adopted G-Body

Possible to use even for finishing applications

Insert Line-Up

A variety of inserts all fit into the same body.

High feed insert



EOMT0602...ZER (R1.0, 2.0)

High feed insert for unfavorable conditions




EOMW060210ZER

Shoulder insert



ZOMT0602...ZER-PL (R0.2,0.4,0.8)

For high hardened steel



EOHW0602...ZTR (R1.0, 2.0)


"Mirror Insert" for finishing side & bottom face



YOHW0602...ZER-12


PME
TYPE

Shank Type




■ PME type (Through coolant hole)

● High feed




● Shoulder milling




■ PME-LS type (No coolant hole)

● High feed



● Shoulder milling



Type	Cat.No.	Stock	No. of inserts	Dimensions (mm)					Insert
				DCX	LH	LF	DN	DCON	
Standard	PME2010S10	●	2	10	20	80	9.3	10	EO**0602**Z*R ZOMT0602**ZER YOHW0602**ZER-12
	PME3012S12	●	3	12			11.2	12	
	PME3014S12	●		14			13.15		
Long shank	PME2011S10-LS	●	2	11	33	120	10.3	10	
	PME3013S12-LS	●	3	13	39		12.2	12	
	PME3014S12-LS	●		14	42		13.15		



Screw	Torque(N.m)	Wrench
DSW-1840H	0.4	A-06

QM MILL

MPM/PME Type

MPM
TYPE

Modular Type




Cat.No.	Stock	No. of inserts	Dimensions (mm)						Insert
			DCX	LF	DCSFMS	MD	C	W	
MPM-2010-M6	●	2	10	18	9.5	M6	6.5	8	EO**0602**Z*R ZOMT0602**ZER YOHW0602**ZER-12
MPM-2011-M6	●		11		9.7	M6			
MPM-3012-M6	●	3	12	20	11.2	M6			
MPM-3013-M6	●		13		11.5	M6			
MPM-3015-M8	○	4	15	23	14	M8	8	12	
MPM-4016-M8	●		16		15	M8			
MPM-4017-M8	●		17			M8			
MPM-4018-M8	○		18			M8			
MPM-5020-M10	●	5	20	30	19	M10	9	14	
MPM-5021-M10	●		21		M10				
MPM-6025-M12	●	6	25	35	23.6	M12	10	17	
MPM-7030-M16	●	7	30	43	29	M16	12	22	
MPM-8032-M16	●	8	32			M16			

MPT
TYPE

High Precision "QM MILL"

High tolerance insert-pocket for the ground inserts




Cat.No.	Stock	No. of inserts	Dimensions (mm)						Insert
			DC	LF	DCSFMS	MD	C	W	
MPT-2010A00-M6	●	2	10	18	9.5	M6	6.5	8	ZOMT0602**ZER YOHW0602**ZER-12
MPT-2011A00-M6	○		11		9.7				
MPT-3012A00-M6	●	3	12	20	11.2				
MPT-3013A00-M6	○		13		11.5				
MPT-4016A00-M8	●	4	16	23	15	M8	8	12	



Screw	Torque(N.m)	Wrench
DSW-1840H	0.4	A-06

Insert


High feed insert



High feed insert for unfavorable conditions






For high hardened steel



Shoulder insert



"Mirror Insert" for finishing side & bottom face




Type	Cat.No.	Tolerance	PVD coating							Dimensions (mm)				
			DH102	DS118	DS150	JC7560	JC8015	JC8050	JC8118	RE	L	W1	S	AN
High feed insert	EOMT060210ZER	M		●	●	●		●	●	1.0	6.5		2.5	13°
	EOMT060220ZER			●	●			●	●	2.0				
High feed insert for unfavorable conditions	EOMW060210ZER					●		●	●	1.0				
High hardened steel	EOHW060210ZTR	H	●						●	1.0	6.62	4.3	2.7	
	EOHW060220ZTR		●						●	2.0				
Shoulder milling insert	ZOMT060202ZER-PL	M						●	●	0.2				
	ZOMT060204ZER-PL							●	●	0.4				
	ZOMT060208ZER-PL								●	●	0.8			
MIRROR INSERT for finishing side & bottom face	YOHW060203ZER-12	H	●				●			0.3	6.5		2.6	
	YOHW060205ZER-12		●				●			0.5				
	YOHW060208ZER-12		●					●						0.8


GRADE MARKINGS



JC8118/DS118



JC8050/JC7560/DS150



MAGNETIZER



- Magnetizing and demagnetizing a wrench can easily be done by inserting the tip into the magnetizer and rubbing lightly.
- Do not use in the vicinity of the equipment that can be influenced with magnetism.

Cat.No.	Stock
MAGNETISER	○

■ Insert selection guide

Material	Carbon steel (S50C, S55C) below 250HB						Tool & die steel (SKD61, SKD11) below 255HB					
Cat.No. \ Grade	JC8118	JC8050	JC7560	DH102	DS118	DS150	JC8118	JC8050	JC7560	DH102	DS118	DS150
EOMT0602*0ZER	☆	☆	☆				☆	☆	☆			
EOMW060210ZER	○	○	◎				○	○	◎			
EOHW0602*0ZTR												

Material	Mold steel (HPM7, PX5, KPM30) 30-36HRC						Mold steel (NAK80, HPM1) 38-43HRC					
Cat.No. \ Grade	JC8118	JC8050	JC7560	DH102	DS118	DS150	JC8118	JC8050	JC7560	DH102	DS118	DS150
EOMT0602*0ZER	☆	☆	☆				☆	☆				
EOMW060210ZER	○	○	◎				◎	○				
EOHW0602*0ZTR												


Material	Hardened die steel (SKD61, DAC, DHA) 42-52HRC						Hardened die steel (SKD11, SLD, DC11) 55-62HRC					
Cat.No. \ Grade	JC8118	JC8050	JC7560	DH102	DS118	DS150	JC8118	JC8050	JC7560	DH102	DS118	DS150
EOMT0602*0ZER	☆						×	×				
EOMW060210ZER	○	●					○					
EOHW0602*0ZTR	◎						●			◎		

Material	Cast iron (FC, FCD) below 300HB						Stainless steel (SUS304) below 250HB					
Cat.No. \ Grade	JC8118	JC8050	JC7560	DH102	DS118	DS150	JC8118	JC8050	JC7560	DH102	DS118	DS150
EOMT0602*0ZER	○							◎	○			
EOMW060210ZER	◎		●					●				
EOHW0602*0ZTR												


Material	Titanium alloy (Ti-6Al-4V)						Heat resistant alloy (INCO718)					
Cat.No. \ Grade	JC8118	JC8050	JC7560	DH102	DS118	DS150	JC8118	JC8050	JC7560	DH102	DS118	DS150
EOMT0602*0ZER	○	○	◎		○	◎	◎	○	○		○	○
EOMW060210ZER			●					●				
EOHW0602*0ZTR												

◎: First choice ○: For general milling ●: For unstable milling ☆: For light cutting force ×: Not recommended

Definition of corner shape for programming



Recommended Data for Profile Milling



- Calculation of tool pass dia.

$$\phi_{dc} = \phi_{Dh} - \phi_{Dc}$$

Tool pass dia. Bore dia. Tool Dia.

- Depth of cut per one circuit should not exceed max. depth of cut a_p
- Down cutting is recommended, tool pass rotation should be counterclockwise

- In case of ramping and helical interpolation, apply 70% or less feed (V_f) from standard cutting condition table
- In case of drilling, apply 50% or less Z axis feed (F) from standard cutting condition table
- Long consecutive chips may result in case of drilling, confirm safe operating conditions

Cat.No.	Tool dia. (mm)	Effective cutting dia. (mm)	Max.depth of cut: a_p (mm)	Ramping		Helical interpolation	
				Max. ramping angle θ	Max. depth of cut (a_p) Total cutting length L (mm)	Min. Bore dia. (mm)	Max. Bore dia. (mm)
MPM-2010-M6	10	6.6	0.3	2°18'	7.5	15	18
MPM-2011-M6	11	7.6	0.3	1°54'	9	17	20
MPM-3012-M6	12	8.5	0.3	1°36'	10.7	19	22
MPM-3013-M6	13	9.5	0.3	1°24'	12.3	21	24
MPM-3015-M8	15	11.5	0.4	1°12'	19.1	25	28
MPM-4016-M8	16	12.5	0.4	1°	22.9	27	30
MPM-4017-M8	17	13.5	0.4	0°54'	25.5	29	32
MPM-4018-M8	18	14.5	0.4	0°51'	27.0	31	34
MPM-5020-M10	20	16.5	0.4	0°45'	30.6	35	38
MPM-5021-M10	21	17.5	0.4	0°42'	32.7	37	40
MPM-6025-M12	25	21.5	0.4	0°30'	45.8	45	48
MPM-7030-M16	30	26.5	0.4	0°27'	50.9	55	58
MPM-8032-M16	32	28.5	0.4	0°24'	57.3	59	62
PME2010S10	10	6.6	0.3	2°18'	7.5	15	18
PME2011S10-LS	11	7.6	0.3	1°54'	9	17	20
PME3012S12	12	8.5	0.3	1°36'	10.7	19	22
PME3013S12-LS	13	9.5	0.3	1°24'	12.3	21	24
PME3014S12 (-LS)	14	10.5	0.3	1°18'	13.2	23	26

Recommended Cutting Conditions

Material		High Feed		Side Finishing	Bottom Finishing
		EOMT / EOMW	EOHW	YOHW	YOHW
Carbon Steel below 250HB	Grade	JC7560 (JC8050 JC8118)	-	JC8015 (DH102)	JC8015 (DH102)
	Vc	95 - 120	-	280 - 400	160 - 250
	fz	0.5 - 0.9	-	0.1 - 0.15	0.14 - 0.2
	ap	0.2 - 0.4	-	~1.2	~0.12
	ae	0.7 Dc	-	~0.1	0.6 Dc
Tool & Die Steel below 255HB	Grade	JC7560 (JC8050 JC8118)	-	JC8015 (DH102)	JC8015 (DH102)
	Vc	90 - 110	-	250 - 360	150 - 230
	fz	0.5 - 0.9	-	0.1 - 0.15	0.13 - 0.18
	ap	0.15 - 0.4	-	~1.0	~0.12
	ae	0.7 Dc	-	~0.1	0.6 Dc
Mold Steel 30-36HRC	Grade	JC8118 (JC7560 JC8050)	-	JC8015 (DH102)	JC8015 (DH102)
	Vc	90 - 110	-	250 - 360	150 - 230
	fz	0.5 - 0.9	-	0.1 - 0.15	0.13 - 0.18
	ap	0.2 - 0.4	-	~1.0	~0.12
	ae	0.7 Dc	-	~0.1	0.6 Dc
Mold Steel 38-43HRC	Grade	JC8118 (JC8050)	-	DH102 (JC8015)	DH102 (JC8015)
	Vc	70 - 90	-	200 - 280	130 - 200
	fz	0.5 - 0.7	-	0.08 - 0.12	0.08 - 0.12
	ap	0.2 - 0.3	-	~1.0	~0.12
	ae	0.6 Dc	-	~0.1	0.6 Dc
Hardened Die Steel 42-52HRC	Grade	JC8118	JC8118	DH102 (JC8015)	DH102 (JC8015)
	Vc	50 - 70	70 - 90	140 - 200	90 - 120
	fz	0.45 - 0.6	0.3 - 0.6	0.08 - 0.1	0.08 - 0.1
	ap	0.15 - 0.3	0.1 - 0.25	~0.8	~0.1
	ae	0.6 Dc	0.6 Dc	~0.1	0.4 Dc
Hardened Die Steel 55-62HRC	Grade	-	DH102	DH102	DH102
	Vc	-	70 - 80	100 - 150	50 - 70
	fz	-	0.27 - 0.3	0.08 - 0.1	0.06 - 0.08
	ap	-	0.1 - 0.15	~0.5	~0.1
	ae	-	0.4 Dc	~0.1	0.4 Dc
Grey & Nodular Cast Iron below 300HB	Grade	JC8118	-	JC8015 (DH102)	JC8015 (DH102)
	Vc	120 - 150	-	280 - 400	130 - 200
	fz	0.5 - 0.9	-	0.1 - 0.15	0.1 - 0.15
	ap	0.2 - 0.4	-	~1.2	~0.15
	ae	0.7 Dc	-	~0.12	0.6 Dc
Stainless Steel	Grade	JC8050 (JC7560)	-	JC8015 (DH102)	JC8015 (DH102)
	Vc	95 - 120	-	250 - 360	150 - 230
	fz	0.5 - 0.9	-	0.1 - 0.15	0.13 - 0.18
	ap	0.15 - 0.4	-	~1.0	~0.12
	ae	0.6 Dc	-	~0.1	0.6 Dc
Titanium Alloy	Grade	DS150 (JC7560 JC8050 DS118)	-	JC8015 (DH102)	JC8015 (DH102)
	Vc	50 - 60	-	55 - 80	30 - 50
	fz	0.4 - 0.5	-	0.08 - 0.12	0.09 - 0.12
	ap	0.15 - 0.3	-	~1.0	~0.12
	ae	0.6 Dc	-	~0.1	0.6 Dc
Heat Resistant Alloy	Grade	JC8118 (JC8050)	-	-	-
	Vc	25 - 30	-	-	-
	fz	0.3 - 0.4	-	-	-
	ap	0.15 - 0.3	-	-	-
	ae	0.6 Dc	-	-	-

Note

1. Please adjust cutting conditions according to machine rigidity or work rigidity.
2. In case of chatter occurring, recommended to reduce ap or rpm and keep feed per tooth.
3. ap should be reduced when using on low rigidity machine.
4. Use air blow.

■ Recommended Cutting Conditions

Material		Shoulder Milling ZOMT	Side Finishing ZOMT	Bottom Finishing ZOMT
Carbon Steel below 250HB	Grade	JC8050 (JC8118)	JC8050 (JC8118)	JC8050 (JC8118)
	Vc	128 - 160	145 - 240	90 - 180
	fz	0.06 - 0.08	0.07 - 0.13	0.1 - 0.15
	ap	~4.0	~4.0	~0.15
	ae	~0.15 Dc	~0.1	~0.6 Dc
Tool & Die Steel below 255HB	Grade	JC8050 (JC8118)	JC8050 (JC8118)	JC8050 (JC8118)
	Vc	120 - 150	130 - 215	80 - 160
	fz	0.04 - 0.06	0.07 - 0.13	0.1 - 0.15
	ap	~4.0	~4.0	~0.15
	ae	~0.15 Dc	~0.1	~0.6 Dc
Mold Steel 30-36HRC	Grade	JC8118 (JC8050)	JC8118 (JC8050)	JC8118 (JC8050)
	Vc	120 - 150	130 - 215	80 - 160
	fz	0.03 - 0.05	0.07 - 0.13	0.1 - 0.15
	ap	~4.0	~4.0	~0.15
	ae	~0.15 Dc	~0.1	~0.6 Dc
Mold Steel 38-43HRC	Grade	JC8118 (JC8050)	JC8118 (JC8050)	JC8118 (JC8050)
	Vc	90 - 120	110 - 185	70 - 140
	fz	0.03 - 0.05	0.05 - 0.1	0.1 - 0.15
	ap	~3.0	~3.0	~0.15
	ae	~0.13 Dc	~0.1	~0.6 Dc
Hardened Die Steel 42-52HRC	Grade	JC8118	JC8118	JC8118
	Vc	80 - 100	90 - 120	75 - 100
	fz	0.03 - 0.05	0.05 - 0.07	0.1 - 0.12
	ap	~2.5	~2.5	~0.1
	ae	~0.12 Dc	~0.1	~0.6 Dc
Grey & Nodular Cast Iron below 300HB	Grade	JC8118	JC8118	JC8118
	Vc	120 - 150	125 - 210	90 - 180
	fz	0.06 - 0.08	0.07 - 0.15	0.12 - 0.18
	ap	~4.0	~4.0	~0.15
	ae	~0.15 Dc	~0.1	~0.6 Dc
Stainless Steel	Grade	JC8050	JC8050	JC8050
	Vc	120 - 150	130 - 215	80 - 160
	fz	0.04 - 0.06	0.07 - 0.13	0.1 - 0.15
	ap	~4.0	~4.0	~0.15
	ae	~0.15 Dc	~0.1	~0.6 Dc

Note

1. Please adjust cutting conditions according to machine rigidity or work rigidity.
2. In case of chatter occurring, recommended to reduce ap or rpm and keep feed per tooth.
3. ap should be reduced when using on low rigidity machine.
4. Use air blow.

EXTREME SAP

EXSAP/MSX TYPE



Facemill type



Modular head type



Shank type


Various line up

Capable of a variety of applications such as facemilling, slotting and plunging

Arc-shaped cutting edge trajectory

Due to the arc-geometry on peripheral cutting edge, cusp height can be smaller even in case of large ap.

Achieves high efficient & high precision machining for side walls.



Strong clamping system

Due to unique clamping system that holds insert in place, it is possible to achieve high efficient machining in roughing application.


High precision G class periphery ground

capable of semi-finishing



Double sided 4 cutting edge insert

■ EXSAP-11 type



High speed machining
with multi flutes & small insert

Accuracy of tool diameter : 0-0.1mm
Achieves higher precision on semi-finishing process



Grade: **JC8050**
JC8118

PM breaker for general steel (up to 50HRC)



Grade: **JC7550**
JC7518
DS118
DS150

SL breaker for hard to cut material
such as Titanium alloy, Heat resistant alloy

■ EXSAP-17 type



Max.depth of cut (ap)=15mm
From roughing to semi-finishing

High rigidity insert
Achieves high precision machining even when using
large ap



Grade: **JC8050**
JC8118

PM breaker for general steel (up to 50HRC)

■ Insert grades


ISO	P					M					K				S			
	P01	P10	P20	P30	P40	M01	M10	M20	M30	M40	K01	K10	K20	K30	S01	S10	S20	S30
Range			JC8118					JC8118					JC8118			DS118		
				JC8050					JC8050								DS150	
			JC7518					JC7518									JC7518	
				JC7550					JC7550								JC7550	

EXTREME SAP

EXSAP11/MSX11 Type

EXSAP-11
TYPE

Bore Type



Cat.No.	Stock	No. of inserts	Dimensions (mm)								Arbor set bolt	Weight (kg)	Inserts
			DC	LF	DCSFMS	DCB	DCCB	KWW	KDP	CBDP			
EXSAP-6040R-11-16	●	6	40	40	35	16	14	8.4	5.6	18	M8	0.22	ZNGU1105**ZER-**
EXSAP-7050R-11-22	●	7	50	40	47	22	16.5	10.4	6.3	20	M10	0.38	
EXSAP-7052R-11-22	●	7	52	40	47	22	16.5	10.4	6.3	20	M10	0.39	
EXSAP-7063R-11-22	●	7	63	40	50	22	17	10.4	6.3	20	M10	0.53	
EXSAP-7063R-11-27	●	7	63	50	50	27	20	12.4	7	22	M12X1.75X30	0.62	
EXSAP-8080R-11-27	●	8	80	50	56	27	20	12.4	7	22	M12X1.75X30	0.99	

Screw	Torque(N.m)	Wrench
TSW-307H	2.1	A-10

EXSAP-11
TYPE**Shank Type**Through
coolant
hole


Face Milling

Shoulder Milling

Slotting

Helical Interpolation

Plunge Milling



Cat.No.	Stock	No. of inserts	Dimensions (mm)					Insert
			DC	LH	LF	DN	DCON	
EXSAP-2016-11-30-S16	○	2	16	30	90	14.6	16	ZNGU1105**ZER-**
EXSAP-2016-11-50-S16	●	2	16	50	110	14.6	16	
EXSAP-3020-11-50-S20	●	3	20	50	130	18.3	20	
EXSAP-3020-11-80-S20	○	3	20	80	160	18.3	20	
EXSAP-3025-11-60-S25	●	3	25	60	140	23.4	25	
EXSAP-3025-11-100-S25	○	3	25	100	180	23.4	25	
EXSAP-3026-11-60-S25	○	3	26	60	140	23.4	25	
EXSAP-4030-11-70-S32	○	4	30	70	150	28.4	32	
EXSAP-4030-11-120-S32	○	4	30	120	200	28.4	32	
EXSAP-4032-11-70-S32	●	4	32	70	150	29	32	
EXSAP-4032-11-120-S32	○	4	32	120	200	29	32	
EXSAP-4033-11-70-S32	○	4	33	70	150	29	32	
EXSAP-5040-11-50-S32	○	5	40	50	150	37	32	
EXSAP-5040-11-50L-S32	○	5	40	50	200	37	32	

Screw	Torque(N.m)	Wrench
TSW-307H	2.1	A-10

MSX-11
TYPE**Modular Type**Through
coolant
hole



Face Milling

Shoulder Milling

Slotting

Helical Interpolation

Plunge Milling



Cat.No.	Stock	No. of inserts	Dimensions (mm)						Insert
			DC	LF	DCSFMS	MD	C	W	
MSX-2016-11-M8	●	2	16	23	15	M8	8	12	ZNGU1105**ZER**
MSX-2017-11-M8	○	2	17	23	15	M8	8	12	
MSX-2018-11-M8	○	2	18	23	15	M8	8	12	
MSX-3020-11-M10	●	3	20	30	18	M10	9	14	
MSX-3021-11-M10	○	3	21	30	18	M10	9	14	
MSX-3025-11-M12	●	3	25	35	22	M12	11	19	
MSX-3026-11-M12	○	3	26	35	22	M12	11	19	
MSX-3028-11-M12	○	3	28	35	22	M12	11	19	
MSX-4030-11-M16	○	4	30	43	29	M16	12	22	
MSX-4032-11-M16	●	4	32	43	29	M16	12	22	
MSX-4033-11-M16	○	4	33	43	29	M16	12	22	
MSX-4035-11-M16	○	4	35	43	29	M16	12	22	
MSX-5040-11-M16	●	5	40	43	29	M16	12	22	

Screw	Torque(N.m)	Wrench
TSW-307H	2.1	A-10

EXSAP11/MSX11
TYPE

Insert



Fig 1







Fig 2




Cat.No.	Tolerance	PVD Coating						Dimensions (mm)				Fig.
		DS118	DS150	JC7518	JC7550	JC8050	JC8118	RE	L	W1	S	
ZNGU110504ZER-PM	G					●	●	0.4	11	6.3	5.6	1
ZNGU110508ZER-PM	G					●	●	0.8	11	6.3	5.6	1
ZNGU110512ZER-PM	G					○	○	1.2	11	6.3	5.6	1
ZNGU110516ZER-PM	G					●	●	1.6	11	6.3	5.6	1
ZNGU110504ZER-SL	G	●	●	●	●			0.4	11	6.3	5.6	2
ZNGU110508ZER-SL	G	●	●	●	●			0.8	11	6.3	5.6	2
ZNGU110516ZER-SL	G	●	●	●	●			1.6	11	6.3	5.6	2

 Grade markings



JC8118




JC8050




JC7518 / DS118




JC7550 / DS150



ZNGU110504ZER



ZNGU110508ZER





ZNGU110516ZER

EXTREME SAP

EXSAP17/MSX17 Type

EXSAP-17 TYPE

Bore Type



Cat.No.	Stock	No. of inserts	Dimensions (mm)								Arbor set bolt	Weight (kg)	Insert
			DC	LF	DCSFMS	DCB	DCCB	KWW	KDP	CBDP			
EXSAP-4050R-22	●	4	50	40	47	22	17	10.4	6.3	20	M10	0.38	ZNGU1709**ZER-PM ZNGU170908ZER-SM
EXSAP-5050R-22	●	5	50	40	47	22	17	10.4	6.3	20	M10	0.38	
EXSAP-5052R-22	●	5	52	40	47	22	17	10.4	6.3	20	M10	0.41	
EXSAP-5063R-22	●	5	63	40	50	22	17	10.4	6.3	20	M10	0.58	
EXSAP-7080R-27	●	7	80	50	56	27	20	12.4	7	22	M12X1.75X30	1.09	
EXSAP-7100R-32	●	7	100	50	85	32	26	14.4	8	25	M16X2X25	1.93	
EXSAP-8125R-40	●	8	125	63	100	40	32	16.4	9	32	M20X2.5X40	3.66	

Screw	Torque(N.m)	Wrench
TSW-410H	3.5	A-15T

EXSAP-17
TYPE

Shank Type

Through
coolant
hole


Face Milling

Shoulder Milling

Slotting

Helical Interpolation

Plunge Milling





Cat.No.	Stock	No. of inserts	Dimensions (mm)					Insert
			DC	LH	LF	DN	DCON	
EXSAP-2025-60-S25	●	2	25	60	140	23	25	ZNGU1709**ZER-PM ZNGU170908ZER-SM
EXSAP-2025-100-S25	○	2	25	100	180	23	25	
EXSAP-2032-70-S32	○	2	32	70	150	29	32	
EXSAP-2032-120-S32	○	2	32	120	200	29	32	
EXSAP-3032-70-S32	●	3	32	70	150	29	32	
EXSAP-3032-120-S32	○	3	32	120	200	29	32	
EXSAP-3035-40-S32	○	3	35	40	150	32	32	
EXSAP-4040-40-S32	○	4	40	40	150	37	32	

Screw	Torque(N.m)	Wrench
TSW-410H	3.5	A-15

EXTREME SAP

EXSAP17/MSX17 Type


MSX-17
TYPE**Modular Type**

Cat.No.	Stock	No. of inserts	Dimensions (mm)						Insert
			DC	LF	DCSFMS	MD	C	W	
MSX-2025-M12	●	2	25	35	22	M12	11	19	ZNGU1709**ZER-PM ZNGU170908ZER-SM
MSX-2026-M12	○	2	26	35	22	M12	11	19	
MSX-2028-M12	○	2	28	35	22	M12	11	19	
MSX-2030-M16	○	2	30	43	29	M16	12	22	
MSX-2032-M16	●	2	32	43	29	M16	12	22	
MSX-3032-M16	●	3	32	43	29	M16	12	22	
MSX-3033-M16	○	3	33	43	29	M16	12	22	
MSX-3035-M16	○	3	35	43	29	M16	12	22	
MSX-4040-M16	●	4	40	43	29	M16	12	22	

Screw	Torque(N.m)	Wrench
TSW-410H	3.5	A-15

EXSAP17/MSX17
TYPE

Insert




Cat.No.	Tolerance	PVD Coating		Dimensions (mm)			
		JC8050	JC8118	RE	L	W1	S
ZNGU170904ZER-PM	G	●	●	0.4	16.9	10	8.8
ZNGU170908ZER-PM	G	●	●	0.8	16.9	10	8.8
ZNGU170916ZER-PM	G	●	●	1.6	16.9	10	8.8
ZNGU170920ZER-PM	G	●	●	2	16.9	10	8.8
ZNGU170930ZER-PM	G	●	●	3	16.9	10	8.6

Cat.No.	Tolerance	PVD Coating	Dimensions (mm)			
		JC7550	RE	L	W1	S
ZNGU170908ZER-SM	G	●	0.8	16.9	10	8.8


Recommended Data for Profile Milling

EXSAP-11 Type

Ramping




Helical interpolation




Cat. No.	Tool dia.	Effective Cutting dia.	Max. depth of cut : ap	Ramping		Helical interpolation	
				Max. ramping angle θ	Max. depth of cut : ap Total cutting length L(mm)	Min. Bore dia.	Max. Bore dia.
MSX-2016-11-M8	16	14.1	1.5	1.0°	86	18	29.6
MSX-3020-11-M10	20	18.1	1.5	0.7°	123	26	37.6
MSX-3025-11-M12	25	23.1	1.5	0.4°	215	36	47.6
MSX-4030-11-M16	30	28.1	1.5	0.3°	286	46	57.6
MSX-4032-11-M16	32	30.1	1.5	0.3°	286	50	61.6
MSX-5040-11-M16	40	38.1	1.5	0.2°	430	66	77.6
EXSAP-2016-11-**-S16	16	14.1	1.5	1.0°	86	18	29.6
EXSAP-3020-11-**-S20	20	18.1	1.5	0.7°	123	26	37.6
EXSAP-3025-11-**-S25	25	23.1	1.5	0.4°	215	36	47.6
EXSAP-4030-11-**-S32	30	28.1	1.5	0.3°	286	46	57.6
EXSAP-4032-11-**-S32	32	30.1	1.5	0.3°	286	50	61.6
EXSAP-5040-11-**-S32	40	38.1	1.5	0.2°	430	66	77.6
EXSAP-6040R-11-16	40	38.1	1.5	0.2°	430	66	77.6
EXSAP-7050R-11-22	50	48.1	1.5	0.15°	573	86	97.6
EXSAP-7052R-11-22	52	50.1	1.5	0.15°	573	90	101.6
EXSAP-7063R-11-22	63	61.1	1.5	Not recommended			
EXSAP-7063R-11-27	63	61.1	1.5				
EXSAP-8080R-11-27	80	78.1	1.5				

EXSAP-17 Type

Ramping



Helical interpolation



Cat. No.	Tool dia.	Effective Cutting dia.	Max. depth of cut : ap	Ramping		Helical interpolation	
				Max. ramping angle θ	Max. depth of cut : ap Total cutting length L(mm)	Min. Bore dia.	Max. Bore dia.
EXSAP/MSX-2025	25	21.5	1.5	0.7°	123	34	46
MSX-2026-M12	26	22.5	1.5	0.7°	123	36	48
MSX-2028-M12	28	25.5	1.5	0.6°	143	40	52
MSX-2030-M16	30	26.5	1.5	0.6°	143	44	56
EXSAP/MSX-032	32	28.5	1.5	0.5°	172	48	60
MSX-3033-M16	33	29.5	1.5	0.5°	172	50	62
MSX-3035-M16	35	31.5	1.5	0.4°	215	54	66
MSX-4040-M16	40	36.5	1.5	0.4°	215	64	76
EXSAP-050R-22	50	46.5	1.5	0.3°	286	84	96
EXSAP-5052R-22	52	48.5	1.5	0.3°	286	88	100
EXSAP-5063R-22	63	59.5	1.5	0.2°	430	110	122
EXSAP-7080R-27	80	76.5	1.5	0.15°	573	144	156
EXSAP-7100R-32	100	96.5	Not recommended				
EXSAP-8125R-40	125	121.5					

● In case of ramping and helical interpolation, apply 80% or less feed (Vf) from standard cutting condition table

● In case of helical interpolation, recommend wet cutting by coolant through the tool

● Calculation of tool pass dia.

$$\phi_{dc} = \phi_{Dh} - \phi_{Dc}$$

Tool pass dia. Bore dia. Tool Dia.

● Depth of cut per one circuit should not exceed max. depth of cut Ap

● Down cutting is recommended, tool pass rotation should be counterclockwise

Recommended Cutting Conditions

EXSAP-11 type / Side Milling

Material	Grade	Vc	fz		Tool dia. (mm)							
					16	20	25	32	40	50	63	80
Carbon Steel below 250HB	JC8050 (JC8118)	140 - 180	0.14 - 0.20	ap	~5	~5	~6	~6	~7	~8	~9	~9
				ap x ae	~4	~5	~7.2	~9.8	~14	~24	~30	~36
Cast Steel below 285HB	JC8050 (JC8118)	140 - 180	0.14 - 0.20	ap	~5	~5	~6	~6	~7	~8	~9	~9
				ap x ae	~4	~5	~7.2	~9.8	~14	~24	~30	~36
Tool & Die Steel below 255HB	JC8050 (JC8118)	140 - 180	0.14 - 0.20	ap	~5	~5	~6	~6	~7	~8	~9	~9
				ap x ae	~4	~5	~7.2	~9.8	~14	~24	~30	~36
Mold Steel 30-36HRC	JC8118 (JC8050)	110 - 130	0.10 - 0.18	ap	~5	~5	~6	~6	~7	~8	~9	~9
				ap x ae	~4	~5	~7.2	~9.8	~14	~24	~30	~36
Mold Steel 38-43HRC	JC8118 (JC8050)	90 - 120	0.10 - 0.18	ap	~5	~5	~6	~6	~7	~8	~9	~9
				ap x ae	~3.4	~4	~6	~8	~10	~20	~24	~28
Hardened Die Steel 42-52HRC	JC8118	80 - 100	0.07 - 0.12	ap	~3	~3.5	~4	~4	~4.5	~6	~9	~9
				ap x ae	~1.6	~2	~3.2	~3.6	~4	~8	~9	~10
Grey Cast Iron below 160-260HB	JC8118 (JC8050)	160 - 200	0.14 - 0.20	ap	~5	~5	~6	~6	~7	~8	~9	~9
				ap x ae	~5	~6	~9.8	~12	~16	~28	~34	~40
Nodular Cast Iron below 170-300HB	JC8118 (JC8050)	140 - 180	0.12 - 0.20	ap	~5	~5	~6	~6	~7	~8	~9	~9
				ap x ae	~5	~6	~9.8	~12	~16	~28	~34	~40
Austenitic Stainless Steel	JC8050 (JC7550)	100 - 120	0.10 - 0.18	ap	~5	~5	~6	~6	~7	~8	~9	~9
				ap x ae	~4	~5	~7.2	~9.8	~14	~24	~30	~36
Martensitic Stainless Steel	JC8050 (JC7550)	100 - 140	0.10 - 0.18	ap	~5	~5	~6	~6	~7	~8	~9	~9
				ap x ae	~3.2	~5	~7.2	~9.8	~14	~24	~30	~36
Titanium Alloy	DS150 (JC7550)	50 - 70	0.11 - 0.13	ap	~5	~5	~6	~6	~7	~8	~9	~9
				ap x ae	~3.2	~4	~6	~8	~10	~20	~26	~30
Heat Resistant Alloy	JC7518 (JC8118)	20 - 30	0.08 - 0.10	ap	~5	~5	~6	~6	~7	~8	~9	~9
				ap x ae	~3.2	~4	~6	~8	~10	~20	~26	~30

Note

1. Please adjust cutting conditions according to machine rigidity or work rigidity.
2. In case of chatter occurring, recommended to reduce ap or rpm and keep feed per tooth.
3. ap should be reduced when using on low rigidity machine.
4. Use air blow.

Recommended Cutting Conditions

EXSAP-11 type / Face Milling

Material	Grade	Vc	fz		Tool dia. (mm)							
					16	20	25	32	40	50	63	80
Carbon Steel below 250HB	JC8050 (JC8118)	130 - 180	0.11 - 0.2	ap	~1	~1.2	~1.2	~1.5	~1.8	~2	~2	~2
				ae	~10	~12	~15	~18	~24	~30	~30	~48
Cast Steel below 285HB	JC8050 (JC8118)	130 - 180	0.11 - 0.2	ap	~1	~1.2	~1.2	~1.5	~1.8	~2	~2	~2
				ae	~10	~12	~15	~18	~24	~30	~30	~48
Tool & Die Steel below 255HB	JC8050 (JC8118)	130 - 180	0.11 - 0.2	ap	~1	~1.2	~1.2	~1.5	~1.8	~2	~2	~2
				ae	~10	~12	~15	~18	~24	~30	~30	~48
Mold Steel 30-36HRC	JC8118 (JC8050)	110 - 130	0.1 - 0.18	ap	~1	~1.2	~1.2	~1.5	~1.8	~2	~2	~2
				ae	~10	~12	~15	~18	~24	~30	~30	~48
Mold Steel 38-43HRC	JC8118 (JC8050)	90 - 120	0.1 - 0.16	ap	~0.8	~1	~1	~1.2	~1.4	~1.8	~1.8	~1.8
				ae	~10	~12	~15	~18	~24	~30	~30	~48
Hardened Die Steel 42-52HRC	JC8118	80 - 100	0.08 - 0.12	ap	~0.4	~0.5	~0.5	~0.6	~0.8	~1	~1	~1
				ae	~8	~8	~10	~12	~16	~20	~25	~32
Grey Cast Iron below 160-260HB	JC8118 (JC8050)	160 - 200	0.11 - 0.2	ap	~1	~1.2	~1.2	~1.5	~1.8	~2	~2	~2
				ae	~10	~12	~15	~18	~24	~30	~30	~48
Nodular Cast Iron below 170-300HB	JC8118 (JC8050)	130 - 180	0.11 - 0.2	ap	~1	~1.2	~1.2	~1.5	~1.8	~2	~2	~2
				ae	~10	~12	~15	~18	~24	~30	~30	~48
Austenitic Stainless Steel	JC8050 (JC7550)	100 - 120	0.11 - 0.18	ap	~1	~1.2	~1.2	~1.5	~1.8	~2	~2	~2
				ae	~6	~8	~10	~12	~16	~20	~25	~32
Martensitic Stainless Steel	JC8050 (JC7550)	100 - 150	0.11 - 0.18	ap	~1	~1.2	~1.2	~1.5	~1.8	~2	~2	~2
				ae	~10	~12	~15	~18	~24	~30	~30	~48
Titanium Alloy	DS150 (JC7550)	50 - 70	0.08 - 0.12	ap	~0.8	~1	~1	~0.8	~1.4	~1.8	~1.8	~1.8
				ae	~6	~8	~10	~12	~16	~20	~25	~32
Heat Resistant Alloy	JC7518 (JC8118)	20 - 30	0.06 - 0.11	ap	~0.8	~1	~1	~0.8	~1.4	~1.8	~1.8	~1.8
				ae	~6	~8	~10	~12	~16	~20	~25	~32

Note

1. Please adjust cutting conditions according to machine rigidity or work rigidity.
2. In case of chatter occurring, recommended to reduce ap or rpm and keep feed per tooth.
3. ap should be reduced when using on low rigidity machine.
4. Use air blow.
5. When using for slot milling, apply 50% or less feed (Vf) from standard cutting condition.

Recommended Cutting Conditions

EXSAP-17 type / Side Milling

Material	Grade	Vc	fz		Tool dia. (mm)							
					25	32	40	50	63	80	100	125
Carbon Steel below 250HB	JC8050	150 - 200	0.2 - 0.35	ap	~10	~12	~15	~15	~15	~15	~15	~15
				ap x ae	~15	~24	~30	~40	~45	~45	~45	~45
Cast Steel below 285HB	JC8050	130 - 180	0.2 - 0.35	ap	~10	~12	~15	~15	~15	~15	~15	~15
				ap x ae	~15	~24	~30	~40	~45	~45	~45	~45
Tool & Die Steel below 255HB	JC8050	150 - 200	0.2 - 0.35	ap	~10	~12	~15	~15	~15	~15	~15	~15
				ap x ae	~15	~24	~30	~40	~45	~45	~45	~45
Mold Steel 30-36HRC	JC8118	110 - 150	0.2 - 0.35	ap	~10	~12	~15	~15	~15	~15	~15	~15
				ap x ae	~15	~24	~30	~40	~45	~45	~45	~45
Mold Steel 38-43HRC	JC8118	90 - 120	0.15 - 0.25	ap	~10	~12	~15	~15	~15	~15	~15	~15
				ap x ae	~12	~18	~20	~30	~30	~30	~30	~30
Hardened Die Steel 42-52HRC	JC8118	80 - 100	0.1 - 0.2	ap	~10	~12	~12	~15	~15	~15	~15	~15
				ap x ae	~7	~8	~12	~18	~25	~25	~25	~25
Grey Cast Iron below 160-260HB	JC8118	200 - 250	0.2 - 0.35	ap	~10	~12	~15	~15	~15	~15	~15	~15
				ap x ae	~15	~24	~30	~40	~45	~45	~45	~45
Nodular Cast Iron below 170-300HB	JC8118	110 - 150	0.15 - 0.3	ap	~10	~12	~15	~15	~15	~15	~15	~15
				ap x ae	~15	~24	~30	~40	~45	~45	~45	~45
Austenitic Stainless Steel	JC8050 (JC7550)	100 - 120	0.1 - 0.2	ap	~10	~12	~15	~15	~15	~15	~15	~15
				ap x ae	~15	~24	~30	~40	~45	~45	~45	~45
Martensitic Stainless Steel	JC8118	130 - 180	0.15 - 0.3	ap	~10	~12	~15	~15	~15	~15	~15	~15
				ap x ae	~15	~24	~30	~40	~45	~45	~45	~45

Note

1. Please adjust cutting conditions according to machine rigidity or work rigidity.
2. In case of chatter occurring, recommended to reduce ap or rpm and keep feed per tooth.
3. ap should be reduced when using on low rigidity machine.
4. Use air blow.

Recommended Cutting Conditions

EXSAP-17 type / Face Milling

Material	Grade	Vc	fz		Tool dia. (mm)							
					25	32	40	50	63	80	100	125
Carbon Steel below 250HB	JC8050	110 - 150	0.20 - 0.30	ap	~3	~3.5	~3.5	~4	~4	~4	~4	~4
				ae	~25	~32	~40	~50	~63	~80	~100	~125
Cast Steel below 285HB	JC8050	110 - 150	0.20 - 0.30	ap	~3	~3.5	~3.5	~4	~4	~4	~4	~4
				ae	~25	~32	~40	~50	~63	~80	~100	~125
Tool & Die Steel below 255HB	JC8050	110 - 150	0.15 - 0.25	ap	~3	~3.5	~3.5	~4	~4	~4	~4	~4
				ae	~25	~32	~40	~50	~63	~80	~100	~125
Mold Steel 30-36HRC	JC8118	110 - 130	0.15 - 0.25	ap	~3	~3.5	~3.5	~4	~4	~4	~4	~4
				ae	~25	~32	~40	~50	~63	~80	~100	~125
Mold Steel 38-43HRC	JC8118	90 - 110	0.15 - 0.25	ap	~2	~2.5	~2.5	~3	~3	~3	~4	~4
				ae	~25	~32	~40	~50	~63	~80	~100	~125
Hardened Die Steel 42-52HRC	JC8118	70 - 90	0.10 - 0.20	ap	~1	~2	~2	~2.5	~2.5	~2.5	~4	~4
				ae	~20	~25	~32	~40	~55	~65	~80	~100
Grey Cast Iron below 160-260HB	JC8118	130 - 180	0.20 - 0.30	ap	~5	~5.5	~5.5	~6	~6	~6	~4	~4
				ae	~25	~32	~40	~50	~63	~80	~100	~125
Nodular Cast Iron below 170-300HB	JC8118	110 - 130	0.15 - 0.25	ap	~3	~3.5	~3.5	~4	~4	~4	~4	~4
				ae	~25	~32	~40	~50	~63	~80	~100	~125
Austenitic Stainless Steel	JC8050 (JC7550)	90 - 110	0.10 - 0.20	ap	~3	~3.5	~3.5	~4	~4	~4	~4	~4
				ae	~20	~25	~32	~40	~55	~65	~80	~100
Martensitic Stainless Steel	JC8118	110 - 150	0.15 - 0.25	ap	~3	~3.5	~3.5	~4	~4	~4	~4	~4
				ae	~25	~32	~40	~50	~63	~80	~100	~125

Note

1. Please adjust cutting conditions according to machine rigidity or work rigidity.
2. In case of chatter occurring, recommended to reduce ap or rpm and keep feed per tooth.
3. ap should be reduced when using on low rigidity machine.
4. Use air blow.
5. When using for slot milling, apply 50% or less feed (Vf) from standard cutting condition.

Double sided insert with 6 cutting edge

SHOULDER SIX

Unique 3D insert

Due to arc-geometry on the peripheral cutting edge, cusp height can be smaller even in case of large ap.

Achieves low cutting force

Achieves high efficient & high precision machining for side walls.



Features


This tool can accommodate an array of applications such as face milling, slotting and plunging. The unique 3D design of the insert has 6 positive axial cutting edges which decrease tool pressure.

Double - sided insert with 6 cutting edges.

The robust insert is 7.5mm in thickness allowing for stable machining and longer tool life.



ISO	P					M					K				H		
	P01	P10	P20	P30	P40	M01	M10	M20	M30	M40	K01	K10	K20	K30	H01	H10	H20
Range			JC8118					JC8118				JC8118				JC8118	
				JC8050				JC8050									



EXSIX
TYPE

Bore Type



Fig.1
Through coolant hole





Fig.2
Without coolant hole




Cat.No.	Stock	No. of inserts	Dimensions (mm)								Arbor set bolt	Weight (kg)	Insert	Fig.
			DC	LF	DCSFMS	DCB	DCCB	KWW	KDP	CBDP				
EXSIX-4050R-22	●	4	50	40	47	22	14	10.4	6.3	20	M10X1.5X25★	0.33	YCMU0907**ZER-PM	1
EXSIX-4052R-22	●		52								M10X1.5X25★	0.35		
EXSIX-5063R-22	●	5	63		50		17				M10	0.50		
EXSIX-5066R-22	●		66								M10	0.53		
EXSIX-6080R-27	●	6	80	50	56	27	20	12.4	7	22	M12X1.75X30★	0.93		2
EXSIX-7100R-32	●	7	100		85	32	26	14.4	8	25	M16X2X30★	1.88		
EXSIX-8125R-40	●	8	125	63	100	40	32	16.4	9	32	M20X2.5X40★	3.62		
EXSIX-9160R-40	●	9	160								60	35		

Screw	Torque(N.m)	Wrench
CSW-513H	5.5	A-20

SHOULDER SIX


EXSIX Type

Insert



Cat.No.	Tolerance	PVD Coating		Dimensions (mm)			
		JC8050	JC8118	RE	BS	IC	S
YCMU090708ZER-PM	M	●	●	0.8	1.41	14	7.5
YCMU090716ZER-PM		●	●	1.6	0.62		

GRADE MARKING



■ Recommended Cutting Conditions

Material	Grade	Shoulder Milling				Face Milling				Plunge Milling			
		Vc	fz	ap	ap x ae	Vc	fz	ap	ae	Vc	fz	ae	Pf
Carbon Steel below 250HB	JC8050	160 - 200	0.20 - 0.35	~9.0	~45	110 - 150	0.20 - 0.30	~4.0	~1.0Dc	180	0.25	~5	~0.5Dc
Cast Steel below 285HB	JC8050	140 - 180	0.20 - 0.35	~9.0	~45	110 - 150	0.20 - 0.30	~4.0	~1.0Dc	160	0.25	~5	~0.5Dc
Tool & Die Steel below 255HB	JC8050	160 - 200	0.20 - 0.35	~9.0	~45	110 - 150	0.15 - 0.25	~4.0	~1.0Dc	180	0.20	~5	~0.5Dc
Mold Steel 30-36HRC	JC8118	120 - 150	0.20 - 0.35	~9.0	~45	110 - 130	0.15 - 0.25	~4.0	~1.0Dc	130	0.20	~5	~0.5Dc
Mold Steel 38-43HRC	JC8118	90 - 120	0.15 - 0.25	~9.0	~30	90 - 110	0.10 - 0.25	~3.0	~1.0Dc	100	0.20	~5	~0.5Dc
Hardened Die Steel 42-52HRC	JC8118	80 - 100	0.10 - 0.20	~9.0	~25	70 - 90	0.10 - 0.20	~2.5	~0.8Dc	90	0.10	~5	~0.5Dc
Grey Cast Iron below 160-260HB	JC8118	210 - 250	0.20 - 0.35	~9.0	~45	130 - 180	0.20 - 0.30	~6.0	~1.0Dc	200	0.30	~5	~0.5Dc
Nodular Cast Iron below 170-300HB	JC8118	110 - 150	0.15 - 0.30	~9.0	~45	110 - 130	0.15 - 0.25	~4.0	~1.0Dc	130	0.20	~5	~0.5Dc
Austenitic Stainless Steel	JC8050	100 - 120	0.10 - 0.20	~9.0	~45	90 - 110	0.10 - 0.20	~4.0	~0.8Dc	110	0.15	~5	~0.5Dc
Martensitic Stainless Steel	JC8118	140 - 180	0.15 - 0.30	~9.0	~45	110 - 150	0.15 - 0.25	~4.0	~1.0Dc	160	0.20	~5	~0.5Dc

Note

1. Please adjust cutting conditions according to machine rigidity or work rigidity.
2. In case of chatter occurring, recommended to reduce ap or rpm and keep feed per tooth.
3. ap should be reduced when using on low rigidity machine.
4. Use air blow.
5. When using for slot milling, apply 50% or less feed (Vf) from standard cutting condition.
6. Ramping and helical interpolation are not recommended.


Feature 1 Arc Geometry on Peripheral Cutting Edge




The arc-shaped peripheral cutting edge minimizes cusp height even at large depth of cut (a_p), enabling high-efficiency, high-precision machining of vertical walls.

Max. depth of cut (a_p) = 15mm is possible.

Feature 2 Low Cutting Force with High-Positive Geometry



Optimized Cutting Edge Geometry



Work Material : 1.1213

Tool dia : $\phi 25$

Cutting Conditions : $V_c=200\text{m/min}$, $f_z=0.1\text{mm/t}$, $a_p=15\text{mm}$, $a_e=1\text{mm}$

Feature 3 Multi-functional indexable cutter

Usable for a wide range of applications such as face milling, slotting, pocket milling & side milling.



Shoulder Milling



Radius Milling



Slotting



Side Milling



Pocket Milling




Copy Milling



Face Milling



Helical Interpolation



Three-face insert clamping ensures stable ramping and helical interpolation.


Feature 4 Long Cutting Edge Cutter Body

New long-edge cutter body lineup enables deeper shoulder milling in both bore and shank type holders.



Long Cutting Edge Cutter Lineup

- Bore type
 - ø50 mm → Max. Depth of Cut(ap) : 57mm
 - ø63 mm → Max. Depth of Cut(ap) : 57mm
 - ø80 mm → Max. Depth of Cut(ap) : 71mm
- Shank type
 - ø32 mm → Max. Depth of Cut(ap) : 43mm
 - ø40 mm → Max. Depth of Cut(ap) : 57mm



- **Wide pocket geometry** enhances chip evacuation.
- **Coolant holes in every pocket** improve chip evacuation and prevent chip welding.

Feature 5 Insert Line-up



- For Steel

ZOMT1605...ZER-PM

(R0.4, R0.8, R1.6, R2.0, R3.0, R4.0, R5.0)



- For Aluminium alloy
- High precision periphery ground insert.

ZOET1605...ZFR-NL

(R0.4, R0.8, R1.6, R2.0, R3.0, R3.2)




Application

ISO	P					M					K				H			N			
	P01	P10	P20	P30	P40	M01	M10	M20	M30	M40	K01	K10	K20	K30	H01	H10	H20	N01	N10	N20	N30
Range	JC8118					JC8118					JC8118				JC8118						
	JC8050					JC8050												FC18			

SSV
TYPE

Bore Type

Through
coolant
hole



Cat.No.	Stock	No. of inserts	Dimensions (mm)								Max. spindle speed (min ⁻¹)	Arbor set bolt	Weight (kg)	Insert
			DC	LF	DCSFMS	DCB	DCCB	KWW	KDP	CBDP				
SSV-4040R-16	●	4	40	40	35	16	14	8.4	5.6	18	19,000	M8	0.20	ZOMT1605**ZER-PM ZOET1605**ZFR-NL
SSV-5050R-22	●	5	50	40	47	22	17	10.4	6.3	20	16,000	M10	0.33	
SSV-6063R-22	●	6	63	40	50	22	17	10.4	6.3	20	14,000	M10	0.52	
SSV-6063R-27	●	6	63	50	60	27	20	12.4	7	22	14,000	M12X1.75X30 ★	0.75	
SSV-7080R-27	●	7	80	50	60	27	20	12.4	7	22	12,000	M12X1.75X30 ★	1.08	
SSV-8100R-32	●	8	100	50	85	32	26	14.4	8	25	11,000	M16X2X30 ★	1.95	
SSV-8125R-40	●	8	125	63	100	40	32	16.4	9	32	9,600	M20X2.5X40 ★	3.73	

Note) When using inserts with corner radius RE4 or RE5, please machine the cutter body to R4 or C4.5.

Screw	Torque(N.m)	Wrench
DSW-4075H	3.6	A-15T

SSV
TYPE

Modular Type

Through
coolant
hole



Cat.No.	Stock	No. of inserts	Dimensions (mm)						Max. spindle speed (min ⁻¹)	Insert
			DC	LF	DCSFMS	MD	C	W		
SSV-2025-M12	●	2	25	35	22	M12	11	19	26,000	ZOMT1605**ZER-PM ZOET1605**ZFR-NL
SSV-2028-M12	○	2	28	35	22	M12	11	19	24,000	
SSV-3030-M16	○	3	30	43	29	M16	12	22	23,000	
SSV-3032-M16	●	3	32	43	29	M16	12	22	22,000	
SSV-3035-M16	●	3	35	43	29	M16	12	22	20,000	
SSV-4040-M16	●	4	40	43	29	M16	12	22	19,000	

Note) When using inserts with corner radius RE4 or RE5, please machine the cutter body to R4 or C4.5.

Screw	Torque(N.m)	Wrench
DSW-4075H	3.6	A-15


SSV
TYPE

Shank Type



Cat.No.	Stock	No. of inserts	Dimensions (mm)					Insert
			DC	LH	LF	DN	DCON	
SSV-2025-60-S25+A	●	2	25	60	140	23	25	ZOMT1605**ZER-PM ZOET1605**ZFR-NL
SSV-2025-100-S25+A	●	2	25	100	180	23	25	
SSV-3032-70-S32+A	●	3	32	70	150	29	32	
SSV-3032-120-S32+A	●	3	32	120	200	29	32	
SSV-4040-50L-S32+A	●	4	40	50	200	37	32	

Note) When using inserts with corner radius RE4 or RE5, please machine the cutter body to R4 or C4.5.

Through
coolant
hole

Cat.No.	Stock	No. of inserts	Dimensions (mm)					Insert
			DC	LH	LF	DN	DCON	
SSV-4040-50-S32	●	4	40	50	150	37	32	ZOMT1605**ZER-PM ZOET1605**ZFR-NL


Note) When using inserts with corner radius RE4 or RE5, please machine the cutter body to R4 or C4.5.

Screw	Torque(N.m)	Wrench
DSW-4075H	3.6	A-15

SSVL
TYPE

Bore Type

LONG CUTTING EDGE



Cat.No.	Stock	No. of Flutes	No. of Inserts	Dimensions (mm)									Arbor set bolt	Weight (kg)	Insert
				DC	LF	DCSFMS	DCB	DCCB	KWW	KDP	CBDP	APMX			
SSVL-3050R-57-22	●	3	12	50	80	47	22	16.5	10.4	6.3	20	57	ASB-M10065	0.75	ZOMT1605**ZER-PM
SSVL-4063R-57-27	●	4	16	63	80	60	27	20	12.4	7	22	57	ASB-M12065	1.27	
SSVL-5080R-71-32	●	5	25	80	95	70	32	26	14.4	8	25	71	ASB-M16070	2.47	

Note) 1. When using inserts with corner radius RE4 or RE5, please machine the cutter body to R4 or C4.5.

2. Corner radius RE0.8 is recommended for peripheral cutting edges, excluding the bottom cutting edge.


Inserts with corner radius RE0.4 can also be used.

Screw	Torque(N.m)	Wrench
DSW-4075H	3.6	A-15T

SSVL
TYPE

Shank Type

LONG CUTTING EDGE



Cat.No.	Stock	No. of Flutes	No. of Inserts	Dimensions (mm)					Insert
				DC	LF	DCON	LH	APMX	
SSVL-2032-43-S32	●	2	6	32	140	32	60	43	ZOMT1605**ZER-PM
SSVL-3040-57-S40	●	3	12	40	150	40	70	57	

Note) 1. When using inserts with corner radius RE4 or RE5, please machine the cutter body to R4 or C4.5.


2. Corner radius RE0.8 is recommended for peripheral cutting edges, excluding the bottom cutting edge.

Inserts with corner radius RE0.4 can also be used.


Screw	Torque(N.m)	Wrench
DSW-4075H	3.6	A-15T

Insert

For Steel




For Aluminium alloy




Cat.No.	Tolerance	PVD Coating		Uncoated	Dimensions (mm)			
		JC8050	JC8118		RE	L	W1	S
ZOMT160504ZER-PM	M	●	●		0.4	18	10	4.7
ZOMT160508ZER-PM	M	●	●		0.8	18	10	4.7
ZOMT160516ZER-PM	M	●	●		1.6	18	10	4.7
ZOMT160520ZER-PM	M	●	●		2.0	18	10	4.7
ZOMT160530ZER-PM	M	●	●		3.0	18	10	4.7
ZOMT160540ZER-PM	M	●	●		4.0	17	10	4.7
ZOMT160550ZER-PM	M	●	●		5.0	17	9.9	4.7
ZOET160504ZFR-NL	E			●	0.4	18	10	4.7
ZOET160508ZFR-NL	E			●	0.8	18	10	4.7
ZOET160516ZFR-NL	E			●	1.6	18	10	4.7
ZOET160520ZFR-NL	E			●	2.0	18	10	4.7
ZOET160530ZFR-NL	E			●	3.0	18	10	4.7
ZOET160532ZFR-NL	E			○	3.2	18	10	4.7


GRADE MARKINGS




ZO*T160504Z*R-**




ZO*T160508Z*R-**




ZO*T160516Z*R-**




ZO*T160520Z*R-**




ZO*T160530Z*R-**




ZOET160532ZFR-NL




ZOMT160540ZER-PM




ZOMT160550ZER-PM



JC8050



JC8118




FC18


SSV TYPE

Recommended Data for Profile Milling

Ramping



Helical interpolation



- Calculation of tool pass dia.

$$\phi_{dc} = \phi_{Dh} - \phi_{Dc}$$

Tool pass dia. Bore dia. Tool Dia.

- Depth of cut per one circuit should not exceed max. depth of cut a_p .
- Down cutting is recommended, tool pass rotation should be counterclockwise.

- In case of ramping and helical interpolation, apply 80% or less feed (V_f) from standard cutting condition table.
- In case of drilling, apply 50% or less feed (V_f) from standard cutting condition table.
- In case of helical interpolation, recommend wet cutting by coolant through the tool.
- Long chips may come out in case of drilling, confirm safe operating conditions.

Tool dia. (mm)	Effective Cutting dia. (mm)	Ramping					Helical Interpolation		Max. Drilling Depth: Z (mm)
		Max. ramping angle θ	Max Depth of Cut : a_p (mm)		Total Cutting Length at Max a_p : L(mm)		Min. Bore dia. Dh min (mm)	Max. Bore dia. Dh max (mm)	
			STEELS	ALUMINIUM	STEELS	ALUMINIUM			
25	24.7-2×R	6.2	1.5	7	13.8	64.5	31	49.2-2×R	1.4
28	27.7-2×R	5.3	1.5	7	16.2	75.5	37	55.2-2×R	1.4
30	29.7-2×R	4.8	1.5	7	17.9	83.4	41	59.2-2×R	1.4
32	31.7-2×R	4.4	1.5	7	19.5	91.0	45	63.2-2×R	1.4
35	34.7-2×R	4.3	1.5	7	19.9	93.1	51	69.2-2×R	1.4
40	39.7-2×R	3.6	1.5	7	23.8	111.3	61	79.2-2×R	1.4
50	49.7-2×R	2.4	1.5	7	35.8	167.1	81	99.2-2×R	1.4
63	62.7-2×R	1.7	1.5	7	50.5	235.9	107	125.2-2×R	1.4
80	79.7-2×R	1.2	1.5	7	71.6	334.2	141	159.2-2×R	1.4
100	99.7-2×R	0.9	1.5	7	95.5	445.6	181	199.2-2×R	1.4
125	124.7-2×R	0.65	1.5	7	132.2	617.0	231	249.2-2×R	1.4

Recommended Cutting Conditions | Shoulder Milling | SSV type

Material	Grade	Vc (m/min)	fz (mm/t)		Tool dia. (mm)							
					25	32	40	50	63	80	100	125
Carbon Steel below 250HB	JC8050	200 (160-200)	0.35 (0.20-0.35)	ap	≤ 10.0	≤ 12.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0
				ap x ae	≤ 15	≤ 24	≤ 30	≤ 40	≤ 45	≤ 45	≤ 45	≤ 45
Cast Steel below 285HB	JC8050	180 (140-180)	0.3 (0.20-0.30)	ap	≤ 10.0	≤ 12.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0
				ap x ae	≤ 15	≤ 24	≤ 30	≤ 40	≤ 45	≤ 45	≤ 45	≤ 45
Tool & Die Steel below 255HB	JC8050	200 (160-200)	0.35 (0.20-0.35)	ap	≤ 10.0	≤ 12.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0
				ap x ae	≤ 15	≤ 24	≤ 30	≤ 40	≤ 45	≤ 45	≤ 45	≤ 45
Mold Steel 30-36HRC	JC8118	150 (120-150)	0.35 (0.20-0.35)	ap	≤ 10.0	≤ 12.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0
				ap x ae	≤ 15	≤ 24	≤ 30	≤ 40	≤ 45	≤ 45	≤ 45	≤ 45
Mold Steel 38-43HRC	JC8118	120 (90-120)	0.25 (0.15-0.25)	ap	≤ 10.0	≤ 12.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0
				ap x ae	≤ 12	≤ 18	≤ 20	≤ 30	≤ 30	≤ 45	≤ 45	≤ 45
Hardened Die Steel 42-52HRC	JC8118	100 (80-100)	0.2 (0.10-0.20)	ap	≤ 10.0	≤ 12.0	≤ 12.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0
				ap x ae	≤ 8	≤ 12	≤ 12	≤ 18	≤ 25	≤ 45	≤ 45	≤ 45
Grey Cast Iron below 160-260HB	JC8118	210 (210-250)	0.35 (0.20-0.35)	ap	≤ 10.0	≤ 12.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0
				ap x ae	≤ 15	≤ 24	≤ 30	≤ 40	≤ 45	≤ 45	≤ 45	≤ 45
Nodular Cast Iron below 170-300HB	JC8118	150 (110-150)	0.3 (0.15-0.30)	ap	≤ 10.0	≤ 12.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0
				ap x ae	≤ 15	≤ 24	≤ 30	≤ 40	≤ 45	≤ 45	≤ 45	≤ 45
Austenitic Stainless Steel	JC8050	120 (100-120)	0.2 (0.10-0.20)	ap	≤ 10.0	≤ 12.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0
				ap x ae	≤ 15	≤ 24	≤ 30	≤ 40	≤ 45	≤ 45	≤ 45	≤ 45
Martensitic Stainless Steel	JC8118	180 (140-180)	0.3 (0.15-0.30)	ap	≤ 10.0	≤ 12.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0
				ap x ae	≤ 15	≤ 24	≤ 30	≤ 40	≤ 45	≤ 45	≤ 45	≤ 45
Aluminium	FC18	900 (700-900)	0.2 (0.07-0.20)	ap	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0	≤ 15.0
				ap x ae	≤ 75	≤ 75	≤ 75	≤ 75	≤ 75	≤ 75	≤ 75	≤ 75

Note

1. Please adjust cutting conditions according to machine rigidity or work rigidity.
2. In case of chatter occurring, recommended to reduce ap or rpm and keep feed per tooth.
3. ap should be reduced when using on low rigidity machine.
4. Use airflow. (For Aluminium machining Wet cutting is recommended.)

■ Recommended Cutting Conditions | Face Milling | SSV type

Material	Grade	Vc (m/min)	fz (mm/t)		Tool dia. (mm)							
					25	32	40	50	63	80	100	125
Carbon Steel below 250HB	JC8050	150 (110-150)	0.35 (0.20-0.35)	ap	≤ 3.0	≤ 3.5	≤ 3.5	≤ 4.0	≤ 4.0	≤ 4.0	≤ 4.0	≤ 4.0
				ae	≤ 25	≤ 32	≤ 40	≤ 50	≤ 63	≤ 80	≤ 100	≤ 125
Cast Steel below 285HB	JC8050	150 (110-150)	0.35 (0.20-0.35)	ap	≤ 3.0	≤ 3.5	≤ 3.5	≤ 4.0	≤ 4.0	≤ 4.0	≤ 4.0	≤ 4.0
				ae	≤ 25	≤ 32	≤ 40	≤ 50	≤ 63	≤ 80	≤ 100	≤ 125
Tool & Die Steel below 255HB	JC8050	150 (110-150)	0.30 (0.15-0.30)	ap	≤ 3.0	≤ 3.5	≤ 3.5	≤ 4.0	≤ 4.0	≤ 4.0	≤ 4.0	≤ 4.0
				ae	≤ 25	≤ 32	≤ 40	≤ 50	≤ 63	≤ 80	≤ 100	≤ 125
Mold Steel 30-36HRC	JC8118	130 (110-130)	0.30 (0.15-0.30)	ap	≤ 3.0	≤ 3.5	≤ 3.5	≤ 4.0	≤ 4.0	≤ 4.0	≤ 4.0	≤ 4.0
				ae	≤ 25	≤ 32	≤ 40	≤ 50	≤ 63	≤ 80	≤ 100	≤ 125
Mold Steel 38-43HRC	JC8118	110 (90-110)	0.25 (0.15-0.25)	ap	≤ 2.0	≤ 2.5	≤ 2.5	≤ 3.0	≤ 3.0	≤ 3.0	≤ 3.0	≤ 3.0
				ae	≤ 25	≤ 32	≤ 40	≤ 50	≤ 63	≤ 80	≤ 100	≤ 125
Hardened Die Steel 42-52HRC	JC8118	90 (70-90)	0.20 (0.10-0.20)	ap	≤ 1.5	≤ 2.0	≤ 2.0	≤ 2.5	≤ 2.5	≤ 2.5	≤ 2.5	≤ 2.5
				ae	≤ 20	≤ 26	≤ 32	≤ 40	≤ 55	≤ 65	≤ 80	≤ 100
Grey Cast Iron below 160-260HB	JC8118	200 (130-200)	0.35 (0.20-0.35)	ap	≤ 5.0	≤ 5.5	≤ 5.5	≤ 6.0	≤ 6.0	≤ 6.0	≤ 6.0	≤ 6.0
				ae	≤ 25	≤ 32	≤ 40	≤ 50	≤ 63	≤ 80	≤ 100	≤ 125
Nodular Cast Iron below 170-300HB	JC8118	130 (110-130)	0.30 (0.15-0.30)	ap	≤ 3.0	≤ 3.5	≤ 3.5	≤ 4.0	≤ 4.0	≤ 4.0	≤ 4.0	≤ 4.0
				ae	≤ 25	≤ 32	≤ 40	≤ 50	≤ 63	≤ 80	≤ 100	≤ 125
Austenitic Stainless Steel	JC8050	110 (90-110)	0.20 (0.10-0.20)	ap	≤ 3.0	≤ 3.5	≤ 3.5	≤ 4.0	≤ 4.0	≤ 4.0	≤ 4.0	≤ 4.0
				ae	≤ 20	≤ 26	≤ 32	≤ 40	≤ 55	≤ 65	≤ 80	≤ 100
Martensitic Stainless Steel	JC8118	150 (110-150)	0.30 (0.15-0.30)	ap	≤ 3.0	≤ 3.5	≤ 3.5	≤ 4.0	≤ 4.0	≤ 4.0	≤ 4.0	≤ 4.0
				ae	≤ 25	≤ 32	≤ 40	≤ 50	≤ 63	≤ 80	≤ 100	≤ 125
Aluminium	FC18	900 (700-900)	0.20 (0.07-0.20)	ap	≤ 7.0	≤ 7.0	≤ 7.0	≤ 7.0	≤ 7.0	≤ 7.0	≤ 7.0	≤ 7.0
				ae	≤ 18	≤ 22	≤ 28	≤ 35	≤ 44	≤ 56	≤ 70	≤ 87

Note

1. Please adjust cutting conditions according to machine rigidity or work rigidity.
2. In case of chatter occurring, recommended to reduce ap or rpm and keep feed per tooth.
3. ap should be reduced when using on low rigidity machine.
4. Use airflow. (For Aluminium machining Wet cutting is recommended.)

■ Recommended Cutting Conditions | Shoulder Milling | SSVL type

Material	Grade	Vc (m/min)	Tool dia. (mm)					
			32			40		
			ap(mm)	ap x ae(mm ²)	fz (mm/t)	ap(mm)	ap x ae(mm ²)	fz (mm/t)
Carbon Steel below 250HB	JC8050	160	≤ 43	≤ 86	0.23-0.27	≤ 57	≤ 171	0.23-0.27
Cast Steel below 285HB	JC8050	140	≤ 43	≤ 86	0.23-0.27	≤ 57	≤ 171	0.23-0.27
Tool & Die Steel below 255HB	JC8050	160	≤ 43	≤ 86	0.23-0.27	≤ 57	≤ 171	0.23-0.27
Mold Steel 30-36HRC	JC8118	120	≤ 43	≤ 86	0.18-0.23	≤ 57	≤ 171	0.18-0.23
Mold Steel 38-43HRC	JC8118	90	≤ 43	≤ 65	0.18-0.23	≤ 57	≤ 85	0.18-0.23
Hardened Die Steel 42-52HRC	JC8118	90	≤ 43	≤ 43	0.14-0.18	≤ 57	≤ 57	0.14-0.18
Grey Cast Iron below 160-260HB	JC8118	210	≤ 43	≤ 129	0.23-0.27	≤ 57	≤ 228	0.23-0.27
Nodular Cast Iron below 170-300HB	JC8118	130	≤ 43	≤ 129	0.18-0.23	≤ 57	≤ 228	0.18-0.23
Austenitic Stainless Steel	JC8050	100	≤ 43	≤ 86	0.14-0.18	≤ 57	≤ 171	0.14-0.18
Martensitic Stainless Steel	JC8118	150	≤ 43	≤ 86	0.18-0.23	≤ 57	≤ 171	0.18-0.23

Material	Grade	Vc (m/min)	Tool dia. (mm)					
			50			63		
			ap(mm)	ap x ae(mm ²)	fz (mm/t)	ap(mm)	ap x ae(mm ²)	fz (mm/t)
Carbon Steel below 250HB	JC8050	160	≤ 57	≤ 342	0.20-0.30	≤ 57	≤ 433	0.25-0.35
Cast Steel below 285HB	JC8050	140	≤ 57	≤ 342	0.20-0.30	≤ 57	≤ 433	0.25-0.35
Tool & Die Steel below 255HB	JC8050	160	≤ 57	≤ 239	0.20-0.30	≤ 57	≤ 302	0.25-0.35
Mold Steel 30-36HRC	JC8118	120	≤ 57	≤ 239	0.20-0.30	≤ 57	≤ 302	0.25-0.35
Mold Steel 38-43HRC	JC8118	90	≤ 57	≤ 199	0.15-0.25	≤ 57	≤ 256	0.15-0.25
Hardened Die Steel 42-52HRC	JC8118	90	≤ 57	≤ 68	0.10-0.20	≤ 57	≤ 85	0.10-0.20
Grey Cast Iron below 160-260HB	JC8118	210	≤ 57	≤ 342	0.20-0.30	≤ 57	≤ 433	0.25-0.35
Nodular Cast Iron below 170-300HB	JC8118	130	≤ 57	≤ 342	0.15-0.25	≤ 57	≤ 433	0.20-0.30
Austenitic Stainless Steel	JC8050	100	≤ 57	≤ 239	0.10-0.20	≤ 57	≤ 302	0.10-0.20
Martensitic Stainless Steel	JC8118	150	≤ 57	≤ 342	0.15-0.25	≤ 57	≤ 433	0.20-0.30

- Note) 1. Please adjust cutting conditions according to machine rigidity or work rigidity.
 2. In case of chatter occurring, recommended to reduce ap or rpm and keep feed per tooth.
 3. ap should be reduced when using on low rigidity machine.
 4. Use airblow.

BNM
TYPE

Shank Type

High Precision Indexable Ball Nose End Mill

- Ball radius accuracy (with holder): **below ± 0.010 mm.**
- Insert ball radius accuracy: **below ± 0.006 mm.**



Fig.1





Fig.2



Cat.No.	Stock	Dimensions (mm)									Parts		Inserts	Fig.
		DC	RE	LU	LH	LF	DN	BHTA	θk	DCON	Screws	Wrench		
BNMS-060017S-S06C	●	6	3	—	17	60	5.5	—	—	6	FSW-2005H	A-06	BNM-060	1
BNMS-060030T-S10C	●	6	3	15	30	80	5.5	6°	4°14'	10				2
BNMM-060035S-S06C	●	6	3	—	35	92	5.5	—	—	6				1
BNML-060017S-S06C	●	6	3	—	17	120	5.5	—	—	6				1
BNMS-080025S-S08C	●	8	4	—	25	90	7.5	—	—	8	FSW-2506H	A-07	BNM-080 RNM-080	1
BNMM-080035S-S08C	●	8	4	—	35	92	7.5	—	—	8				1
BNML-080075S-S08C	●	8	4	—	75	140	7.5	—	—	8				1
BNML-080095S-S08C	●	8	4	—	95	160	7.5	—	—	8				1
BNML-080075T-S12C	●	8	4	20	75	132	7.5	2°	1°37'	12				2
BNMS-100030S-S10C	●	10	5	—	30	100	9.5	—	—	10	FSW-3007H	A-08	BNM-100/RNM-100	1
BNMM-100043S-S10C	●	10	5	—	43	100	9.5	—	—	10				1
BNMS-120028S-S12C	●	12	6	—	28	84	11.5	—	—	12	KSW-3509	A-15	BNM-120/RNM-120	1
BNMM-120053S-S12C	●	12	6	—	53	110	11.5	—	—	12				1

Screw	Torque(N.m)
FSW-2005H	0.5
FSW-2506H	0.9
FSW-3007H	1.2
KSW-3509	3.0



MBX
TYPE**Modular Type**Through
coolant
hole

Slotting

Copy Milling

Pocket Milling

- Ball radius accuracy (with holder): **below ± 0.010 mm.**
Insert ball radius accuracy: **below ± 0.006 mm.**
- O.D. runout (with MSN carbide shank holder): below 0.015 mm.



Cat.No.	Stock	Dimensions (mm)							Parts		Inserts
		DC	RE	LF	DCSFMS	MD	C	W	Screws	Wrench	
MBX-100-M6	●	10	5	18	9.7	M6	6.5	8	FSW-3007H	A-08	BNM-100
MBX-120-M6	●	12	6	20	11.5	M6	6.5	8	KSW-3509	A-15	BNM-120
MBX-160-M8	●	16	8	23	15	M8	8	12	FSW-4013H	A-15	BNM-160
MBX-200-M10	●	20	10	30	19	M10	8	14	FSW-5016H	A-20W	BNM-200
MBX-250-M12	●	25	12.5	35	24	M12	10	17	FSW-6020	A-30	BNM-250
MBX-300-M16	●	30	15	43	29	M16	12.5	22	KSW-8025	A-30	BNM-300/320

Screw	Torque(N.m)
FSW-3007H	1.2
KSW-3509	3.0
FSW-4013H	3.0
FSW-5016H	4.0
FSW-6020	6.0
KSW-8025	6.0

■ Spanner

	Cat.No.	MD	Torque	width across flat	Thickness	Length
	DS-08	M6	8.0 N.m	8	4	85
	DS-12	M8	16 N.m	12	4	93



MIRROR BALL

BNM Type

BNM-TG
TYPE

Helical geometry

good for finishing hard material/weld up to 60 HRC



Radius accuracy
 ± 0.006 mm

Cat.No.	PVD Coating	Dimensions(mm)					
	DH102	RE	L	W1	S	C	AN
BNM-060-TG	●	3	5	6	2	—	10°
BNM-080-TG	●	4	7	8	2.4	0.5	5°
BNM-100-TG	●	5	8.5	10	2.6	1	5°
BNM-120-TG	●	6	10	12	3	1.5	5°
BNM-160-TG	●	8	12	16	4	1.5	5°
BNM-200-TG	●	10	15	20	5	2	5°
BNM-250-TG	●	12.5	18.5	25	6	2	5°
BNM-300-TG	○	15	22.5	30	7	2	5°
BNM-320-TG	●	16	32	32	7	2	5°

BNM-TS
TYPE

High Helix geometry

good for semi-finishing & finishing hard materials up to 60HRC

Radius accuracy
 ± 0.006 mm

Cat.No.	PVD Coating	Dimensions(mm)					
	DH102	RE	W1	L	S	C	AN
BNM-060-TS	●	3	6	5	2	—	10°
BNM-080-TS	●	4	8	7	2.4	0.5	5°
BNM-100-TS	●	5	10	8.5	2.6	1	5°
BNM-120-TS	●	6	12	10	3	1.5	5°
BNM-160-TS	●	8	16	12	4	1.5	5°
BNM-200-TS	●	10	20	15	5	2	5°
BNM-250-TS	●	12.5	25	18.5	6	2	5°
BNM-300-TS	○	15	30	22.5	7	2	5°
BNM-320-TS	●	16	32	23.5	7	2	5°

BNM-SS
TYPE**Sharp Helical geometry**

good for finishing and semi finishing general steel , mold steel & stainless steel


Radius accuracy
 ± 0.006 mm

Fig 1






Fig 2



Cat.No.	PVD Coating		Dimensions(mm)						Fig.
	DH108	DS108	RE	L	W1	S	C	AN	
BNM-060-SS	●	●	3	5	6	2	—	10°	1
BNM-080-SS	●	●	4	7	8	2.4	0.5	5°	1
BNM-100-SS	●	●	5	8.5	10	2.6	1	5°	1
BNM-120-SS	●	●	6	10	12	3	1	5°	1
BNM-160-SS	●	●	8	12	16	4	1	5°	1
BNM-200-SS	●	●	10	15	20	5	1	5°	2
BNM-250-SS	●	●	12.5	18.5	25	6	1	5°	2
BNM-300-SS	○	○	15	22.5	30	7	1	5°	2
BNM-320-SS	●	●	16	23.5	32	7	1	5°	2




MIRROR BALL

BNM Type


BNM
TYPE

Neutral style geometry

strictly for finishing applications

Radius accuracy
 ± 0.006 mm● DH111 ($W1 \leq 10$)● DH111 ($W1 \geq 12$)




● CBN



Cat.No.	PVD Coating	CBN	Dimensions(mm)				
	DH111	JBN245	RE	W1	L	C	S
BNM-060	●		3	6	5	—	2
BNM-080	●		4	8	7	—	2.4
BNM-100	●		5	10	8.5	—	2.6
BNM-120	●		6	12	10	—	3
BNM-160	●	○	8	16	12	0.8	4
BNM-200	●	○	10	20	15	1	5
BNM-250	●	○	12.5	25	18.5	1	6
BNM-300	○	○	15	30	22.5	1	7
BNM-320	●		16	32	23.5	—	7

BNM
TYPE**Neutral style geometry**


good for semi-finishing & finishing non-ferrous metals such as aluminium, copper

Radius accuracy
 ± 0.006 mm $W1 \leq 10$  $W1 \geq 12$ 

Cat.No.	Diamond Coating	Uncoated	Dimensions(mm)				
	JC10000	KT9	RE	W1	L	C	S
BNM-060	○	●	3	6	5	—	2
BNM-080	○	●	4	8	7	—	2.4
BNM-100	○	●	5	10	8.5	—	2.6
BNM-120	○	●	6	12	10	—	3
BNM-160	○	●	8	16	12	0.8	4
BNM-200	○	●	10	20	15	1	5

BNM-S
TYPE**Sharp Helical geometry**

good for semi-finishing & finishing non-ferrous metals such as aluminium, copper

Radius accuracy
 ± 0.006 mm

Cat.No.	Uncoated	DLC Coating	Dimensions (mm)					
	FZ05	JC20003	RE	L	W1	S	C	AN
BNM-060-S	●	○	3	5	6	2	—	10°
BNM-080-S	●	○	4	7	8	2.4	0.5	5°
BNM-100-S	●	○	5	8.5	10	2.6	1	5°
BNM-120-S	●	○	6	10	12	3	1	5°
BNM-160-S	●	○	8	12	16	4	1	5°
BNM-200-S	●	○	10	15	20	5	1	5°
BNM-250-S	○	○	12.5	18.5	25	6	1	5°
BNM-300-S	○	○	15	22.5	30	7	1	5°

■ Controlled Torque Wrenches (with replaceable blade)

Wrenches are pre-set to protect screws and bodies against damage during both the tightening and loosening process



● Controlled Torque Wrenches (with replaceable blade)

Cat. No.	Torque(N.m)	crew torque	Replacement blade	Applicable inserts
TQC-06	T6	0.5Nm	B-06	BNM-060... HRM-060..., FRM-060...
TQC-07	T7	0.9Nm	B-07	BNM-080... RNM-080..., HRM-080/090..., FRM-080...
TQC-08	T8	1.2Nm	B-08	BNM-100... RNM-100..., HRM-100/110..., FRM-100...
TQC-10	T10	2.0Nm	B-10	BNM-120... RNM-120..., HRM-120/130..., FRM-120/130...

Insert Mounting Information

1. Make sure the insert seat on body is carefully cleaned.
2. Make sure insert itself is clean, especially hole and face location.
3. Change insert screw when threads start to wear. (approximately every 10-15 inserts)
4. Do not over tighten screw, see table for torque specifications.

■ Grade Selection Guide

Material	BNM				BNM-S		BNM-SS		BNM-TG	BNM-TS
	DH111	JC10000	KT9	JBN245	FZ05	JC20003	DH108	DS108	DH102	DH102
Carbon steel below 250HB	◎☆						◎			
Tool & Die steel below 255HB	◎☆						◎			
Mold steel 30 - 36HRC	○						◎			
Mold steel 38 - 43HRC	○						◎			
Hardened die steel 42 - 52HRC	○						◎		○	○
Hardened die steel 55 - 62HRC							○		◎	◎
HSS 63 - 70HRC									◎	◎
Grey cast iron 160 - 260HB	○			★			○		◎	◎
Nodular cast iron 170 - 300HB	○			★			○		◎	◎
Austenitic stainless steel (304,316,317) 17Cr	◎☆						◎			
Ferritic & martensitic stainless steel (403,420J2,430) 13Cr	◎☆						◎			
Aluminium alloy (A5052)			◎		◎	◎				
Aluminium alloy (A7075)			◎		◎	◎				
Aluminium alloy Si below 13%			◎		◎	◎				
Copper alloy (C1100)			◎		◎	◎				
Graphite		○				◎				
Titanium alloy (Ti-6Al-4V) 35 - 43HRC	◎☆						◎	◎		
Heat resistant alloy (INCO718) 35 - 43HRC	◎☆						◎			

◎ : First choice ○ : Second choice ☆ : Wet cutting ★ : High speed machining

■ Recommended Cutting Conditions | BNM / BNM-SS / BNM-TS / BNM-TG type

Material	Grade		Tool dia. (mm)								
			6	8	10	12	16	20	25	30	32
Carbon steel below 250HB	BNM (DH111) BNM-SS (DH108)	<i>n</i> (min ⁻¹)	18,570	13,930	12,730	10,610	8,950	7,160	6,370	5,310	4,970
		<i>Vf</i> (mm/min)	5,570	4,180	5,090	4,240	5,370	5,010	4,460	3,720	3,480
		<i>ap</i> (mm)	0.1	0.1	0.15	0.15	0.15	0.15	0.15	0.15	0.15
		<i>ae</i> (mm)	0.1	0.15	0.2	0.2	0.25	0.3	0.4	0.5	0.5
Tool & Die steel below 255HB	BNM (DH111) BNM-SS (DH108)	<i>n</i> (min ⁻¹)	18,570	13,930	12,730	10,610	8,950	7,160	6,370	5,310	4,970
		<i>Vf</i> (mm/min)	5,570	4,180	5,090	4,240	5,370	5,010	4,460	3,720	3,480
		<i>ap</i> (mm)	0.1	0.1	0.15	0.15	0.15	0.15	0.15	0.15	0.15
		<i>ae</i> (mm)	0.1	0.15	0.2	0.2	0.25	0.3	0.4	0.5	0.5
Mold steel 30 - 36HRC	BNM (DH111) BNM-SS (DH108)	<i>n</i> (min ⁻¹)	18,570	13,930	12,730	10,610	8,950	7,160	6,370	5,310	4,970
		<i>Vf</i> (mm/min)	5,570	4,180	5,090	4,240	5,370	5,010	4,460	3,720	3,480
		<i>ap</i> (mm)	0.05	0.05	0.1	0.1	0.1	0.1	0.1	0.1	0.1
		<i>ae</i> (mm)	0.1	0.15	0.2	0.2	0.25	0.3	0.4	0.5	0.5
Mold steel 38 - 43HRC	BNM (DH111) BNM-SS (DH108)	<i>n</i> (min ⁻¹)	15,920	11,940	11,140	9,280	7,960	6,370	5,730	4,770	4,480
		<i>Vf</i> (mm/min)	3,180	2,390	3,340	2,780	3,980	3,820	3,440	2,860	2,690
		<i>ap</i> (mm)	0.05	0.05	0.1	0.1	0.1	0.1	0.1	0.1	0.1
		<i>ae</i> (mm)	0.1	0.15	0.2	0.2	0.25	0.3	0.4	0.5	0.5
Hardened die steel 42 - 52HRC	BNM (DH111) BNM-SS (DH108)	<i>n</i> (min ⁻¹)	13,260	9,950	9,550	7,960	6,960	5,570	5,090	4,240	3,980
		<i>Vf</i> (mm/min)	2,650	1,990	2,870	2,390	3,480	3,340	3,050	2,540	2,390
		<i>ap</i> (mm)	0.05	0.05	0.1	0.1	0.1	0.1	0.1	0.1	0.1
		<i>ae</i> (mm)	0.1	0.15	0.2	0.2	0.25	0.3	0.4	0.5	0.5
Hardened die steel 55 - 62HRC	BNM-TG (DH102) BNM-TS (DH102)	<i>n</i> (min ⁻¹)	10,610	7,960	7,960	6,630	5,970	4,770	4,460	3,710	3,480
		<i>Vf</i> (mm/min)	2,120	1,590	2,390	1,990	2,990	2,860	2,680	2,230	2,090
		<i>ap</i> (mm)	0.05	0.05	0.1	0.1	0.1	0.1	0.1	0.1	0.1
		<i>ae</i> (mm)	0.1	0.15	0.15	0.2	0.25	0.3	0.4	0.5	0.5
HSS 63 - 70HRC	BNM-TG (DH102) BNM-TS (DH102)	<i>n</i> (min ⁻¹)	7,960	5,970	6,370	5,310	4,970	3,980	3,820	3,180	2,980
		<i>Vf</i> (mm/min)	1,590	1,190	1,270	1,060	1,490	1,190	1,530	1,270	1,190
		<i>ap</i> (mm)	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05
		<i>ae</i> (mm)	0.05	0.1	0.1	0.1	0.1	0.15	0.2	0.3	0.3
Grey & Nodular cast iron below 300 HB	BNM (DH111) BNM-TG BNM-TS (DH102)	<i>n</i> (min ⁻¹)	18,570	13,930	12,730	10,610	8,950	7,160	6,370	5,310	4,970
		<i>Vf</i> (mm/min)	7,430	5,570	6,370	5,310	6,270	5,730	5,100	4,250	3,980
		<i>ap</i> (mm)	0.1	0.1	0.15	0.15	0.15	0.15	0.15	0.15	0.15
		<i>ae</i> (mm)	0.1	0.15	0.2	0.2	0.25	0.3	0.4	0.5	0.5
Stainless steel	BNM (DH111) BNM-SS (DH108)	<i>n</i> (min ⁻¹)	18,570	13,930	12,730	10,610	8,950	7,160	6,370	5,310	4,970
		<i>Vf</i> (mm/min)	5,570	4,180	5,090	4,240	5,370	5,010	4,460	3,720	3,480
		<i>ap</i> (mm)	0.1	0.1	0.15	0.15	0.15	0.15	0.15	0.15	0.15
		<i>ae</i> (mm)	0.1	0.15	0.2	0.2	0.25	0.3	0.4	0.5	0.5
Titanium alloy (Ti-6Al-4V)	BNM (DH111) BNM-SS (DS108)	<i>n</i> (min ⁻¹)	10,610	7,960	9,550	7,960	5,970	4,770	4,460	3,710	3,480
		<i>Vf</i> (mm/min)	3,180	2,390	3,820	3,180	2,990	2,860	2,680	2,230	2,090
		<i>ap</i> (mm)	0.05	0.05	0.1	0.1	0.1	0.1	0.1	0.1	0.1
		<i>ae</i> (mm)	0.1	0.15	0.15	0.2	0.25	0.3	0.4	0.5	0.5
Heat resistant alloy (INCO718)	BNM (DH111) BNM-SS (DS108)	<i>n</i> (min ⁻¹)	7,960	5,970	6,370	5,310	4,970	3,980	3,820	3,180	2,980
		<i>Vf</i> (mm/min)	1,590	1,190	1,910	1,590	1,990	1,590	1,530	1,270	1,190
		<i>ap</i> (mm)	0.05	0.05	0.1	0.1	0.1	0.1	0.1	0.1	0.1
		<i>ae</i> (mm)	0.1	0.1	0.1	0.1	0.1	0.15	0.2	0.3	0.3

Note) 1. Please adjust cutting conditions according to machine rigidity or work rigidity.
 2. These cutting conditions represent stable machining at length 3 x Dc.
 Please adjust cutting conditions according to overhang length.
 3. In case of chatter occurring, recommended to reduce ap or feed.
 4. Use air blow.

Overhang length	n (min ⁻¹)	Vf (mm/min)
~3Dc	100%	100%
3Dc~5Dc	70%	70%
5Dc~10Dc	50%	50%

■ Recommended Cutting Conditions | BNM (CBN) type

Material	Cat.No	Grade		Tool dia.(mm)			
				16	20	25	30
Grey cast iron 160- 260 HB	BNM	JBN245	n (min ⁻¹)	23,870	19,100	15,280	12,730
			Vf (mm/min)	11,940	11,460	9,170	8,910
			ap (mm)	0.05	0.05	0.05	0.05
			ae (mm)	0.25	0.3	0.4	0.5
Nodular cast iron 170- 300 HB	BNM	JBN245	n (min ⁻¹)	19,890	15,920	12,730	10,610
			Vf (mm/min)	7,960	7,960	6,370	6,370
			ap (mm)	0.05	0.05	0.05	0.05
			ae (mm)	0.25	0.3	0.4	0.5

Note

1. These cutting conditions represent on high speed machine.
2. These cutting conditions represent stable machining at length 3 x Dc.
Please adjust cutting conditions according to overhang length.
3. Use carbide shank holder.
4. For better surface finish , mist coolant is recommended.
5. Plunging is not recommended.
- 6 Please keep the stock uniform by pre-machining.

Overhang length	n (min ⁻¹)	Vf (mm/min)
~3Dc	100%	100%
3Dc~5Dc	70%	70%
5Dc~10Dc	50%	50%

■ Recommended Cutting Conditions | BNM / BNM-S type

Material	Cat.No	Grade		Tool dia.(mm)					
				6	8	10	12	16	20
Aluminium	BNM BNM-S	KT9 FZ05 JC20003	n (min ⁻¹)	23,870	17,900	15,920	13,260	10,940	8,750
			Vf (mm/min)	9,550	7,160	7,960	6,630	7,660	7,000
			ap (mm)	0.2	0.2	0.25	0.25	0.25	0.25
			ae (mm)	0.1	0.15	0.2	0.2	0.25	0.3
Copper alloy	BNM BNM-S	KT9 FZ05 JC20003	n (min ⁻¹)	23,870	17,900	15,920	13,260	10,940	8,750
			Vf (mm/min)	9,550	7,160	7,960	6,630	7,660	7,000
			ap (mm)	0.15	0.15	0.2	0.2	0.2	0.2
			ae (mm)	0.1	0.15	0.2	0.2	0.25	0.3
Graphite	BNM BNM-S	JC10000 JC20003	n (min ⁻¹)	23,870	17,900	15,920	13,260	10,940	8,750
			Vf (mm/min)	9,550	7,160	7,960	6,630	7,660	7,000
			ap (mm)	0.15	0.15	0.2	0.2	0.2	0.2
			ae (mm)	0.1	0.15	0.2	0.2	0.25	0.3

Note) 1. Please adjust cutting conditions according to machine rigidity or work rigidity.

2. These cutting conditions represent stable machining at length 3 x Dc.

Please adjust cutting conditions according to overhang length.

3. In case of chatter occurring, recommended to reduce ap or feed.

4. Use air blow.

Overhang length	n (min ⁻¹)	Vf (mm/min)
~3Dc	100%	100%
3Dc~5Dc	70%	70%
5Dc~10Dc	50%	50%

MIRROR RADIUS

RNM Type

RNM
TYPE

Shank Type

High Precision Indexable Radius End Mill

- Corner radius accuracy below $\pm 0.010\text{mm}$



Fig.1





Fig.2



Cat.No.	Stock	Dimensions (mm)								Parts		Inserts	Fig.
		DC	LU	LH	LF	DN	BHTA	θ_k	DCON	Screws	Wrench		
RNMS-060015U-S06C	●	6	—	15	60	5.7	—	—	6	FSW-2005H	A-06	RNM-060 HRM-060 FRM-060	2
RNMM-060030U-S06C	●	6	—	30	80	5.7	—	—	6				2
RNMS-080020U-S08C	●	8	—	20	70	7.6	—	—	8	FSW-2506H	A-07	RNM-080 HRM-080/090 FRM-080	2
RNMM-080040U-S08C	●	8	—	40	90	7.6	—	—	8				2
RNMM-080053T-S12C	●	8	20	53	110	7.8	2°	2°12'	12				1
RNML-080075S-S08C	●	8	—	75	140	7.8	—	—	8				2
RNMM-100050S-S10C	●	10	—	50	110	9.8	—	—	10	FSW-3007H	A-08	RNM-100 HRM-100/110 FRM-100	2
RNML-100075S-S10C	●	10	—	75	140	9.8	—	—	10				2
RNMM-120053S-S12C	●	12	—	53	110	11.8	—	—	12	KSW-3509	A-15	RNM-120 HRM-120/130 FRM-120	2
RNML-120095S-S12C	●	12	—	95	160	11.8	—	—	12				2

Screw	Torque (N.m)
FSW-2005H	0.5
FSW-2506H	0.9
FSW-3007H	1.2
KSW-3509	3.0

MRX
TYPE**Modular Type****High Precision Indexable Radius End Mill**Through
coolant
hole

Face Milling


Shoulder Milling

Copy Milling

Pocket Milling

Helical Interpolation


- RNM / Corner radius accuracy **below $\pm 0.010\text{mm}$**
- HRM / Corner radius accuracy **$\pm 0.015\text{ mm}$**
- FRM / Corner radius accuracy **$\pm 0.010\text{ mm}$**
- O.D. run out / MRX + MSN carbide shank **below $\pm 0.015\text{mm}$**



Cat.No.	Stock	Dimensions (mm)						Parts		Inserts
		DC	LF	DCSFMS	MD	C	W	Screws	Wrench	
MRX-100-M6	●	10	18	9.7	M6	6.5	8	FSW-3007H	A-08	RNM-100 HRM-100/110 FRM-100...
MRX-120-M6	●	12	20	11.5	M6	6.5	8	KSW-3509	A-15	RNM-120 HRM-120/130 FRM-120
MRX-160-M8	●	16	23	15	M8	8	12	FSW-4013H	A-15	RNM-160 HRM-160/170 FRM-160/170...
MRX-200-M10	●	20	30	18.5	M10	8	14	FSW-5016H	A-20W	HRM-200/220 FRM-200/210
MRX-250-M12	●	25	35	24	M12	10	17	FSW-6020	A-30	FRM-250
MRX-300-M16	○	30	43	29	M16	12.5	22	KSW-8025	A-30	FRM-300
MRX-320-M16	●	32	43	30	M16	12.5	22	KSW-8025	A-30	FRM-320

Screw	Torque (N.m)
FSW-3007H	1.2
KSW-3509	3.0
FSW-4013H	3.0
FSW-5016H	4.0
FSW-6020	6.0
KSW-8025	6.0

■ **Spanner**

	Cat.No.	MD	Torque	width across flat	Thickness	Length
	DS-08	M6	8.0 N.m	12	4	85
	DS-12	M8	16 N.m	12	4	93

MIRROR RADIUS

RNM Type


FRM
TYPE

High feed geometry

from Semi-finishing to finishing

Corner radius accuracy
 ± 0.010 mm

FRM-□□□-R0



Cat.No.	PVD Coating		Dimensions(mm)				
	DH102	JC8015	RE	L	W1	S	C
FRM-060-R0		●	※	5	6	2	0.8
FRM-060-R03	●	●	0.3	5	6	2	0.8
FRM-060-R05	●	●	0.5	5	6	2	0.8
FRM-060-R10	●	●	1	5	6	2	0.8
FRM-080-R0		●	※	7	8	2.4	1.2
FRM-080-R03	●	●	0.3	7	8	2.4	1.2
FRM-080-R05	●	●	0.5	7	8	2.4	1.2
FRM-080-R10	●	●	1	7	8	2.4	1.2
FRM-100-R0		●	※	8.5	10	2.6	1.5
FRM-100-R03	●	●	0.3	8.5	10	2.6	1.5
FRM-100-R05	●	●	0.5	8.5	10	2.6	1.5
FRM-100-R10	●	●	1	8.5	10	2.6	1.5
FRM-100-R20	●	●	2	8.5	10	2.6	1.5
FRM-120-R0		●	※	10	12	3	1.5
FRM-120-R03	●	●	0.3	10	12	3	1.5
FRM-120-R05	●	●	0.5	10	12	3	1.5
FRM-120-R10	●	●	1	10	12	3	1.5
FRM-120-R15	●		1.5	10	12	3	1.5
FRM-120-R20	●	●	2	10	12	3	1.5
FRM-120-R30	●		3	10	12	3	1.5
FRM-130-R05		●	0.5	10	13	3	1.5
FRM-130-R10		●	1	10	13	3	1.5


Cat.No.	PVD Coating		Dimensions(mm)				
	DH102	JC8015	RE	L	W1	S	C
FRM-160-R0		●	※	12	16	4	2
FRM-160-R03	●	●	0.3	12	16	4	2
FRM-160-R05	●	●	0.5	12	16	4	2
FRM-160-R10	●	●	1	12	16	4	2
FRM-160-R15	●		1.5	12	16	4	2
FRM-160-R20	●	●	2	12	16	4	2
FRM-160-R30	●		3	12	16	4	2
FRM-170-R03		●	0.3	12	17	4	2
FRM-170-R05		●	0.5	12	17	4	2
FRM-170-R10	●	●	1	12	17	4	2
FRM-170-R20		●	2	12	17	4	2
FRM-200-R0		●	※	15	20	5	2
FRM-200-R03	●	●	0.3	15	20	5	2
FRM-200-R05	●	●	0.5	15	20	5	2
FRM-200-R10	●	●	1	15	20	5	2
FRM-200-R15	●		1.5	15	20	5	2
FRM-200-R20	●	●	2	15	20	5	2
FRM-200-R30	●	●	3	15	20	5	2
FRM-210-R05		●	0.5	15	21	5	2
FRM-210-R10	●	●	1	15	21	5	2
FRM-210-R20		●	2	15	21	5	2
FRM-250-R03	●	●	0.3	18.5	25	6	2.5
FRM-250-R05	●	●	0.5	18.5	25	6	2.5
FRM-250-R10	●	●	1	18.5	25	6	2.5
FRM-250-R15	●		1.5	18.5	25	6	2.5
FRM-250-R20	●	●	2	18.5	25	6	2.5
FRM-250-R30	●	●	3	18.5	25	6	2.5
FRM-260-R03		●	0.3	18.5	26	6	2.5
FRM-260-R05		●	0.5	18.5	26	6	2.5
FRM-260-R10		●	1	18.5	26	6	2.5
FRM-300-R03	○	○	0.3	22.5	30	7	3
FRM-300-R05	○	○	0.5	22.5	30	7	3
FRM-300-R10	○	○	1	22.5	30	7	3
FRM-300-R20	○	○	2	22.5	30	7	3
FRM-300-R30	○	○	3	22.5	30	7	3
FRM-320-R03	●	●	0.3	23.5	32	7	3
FRM-320-R05	●	●	0.5	23.5	32	7	3
FRM-320-R10	●	●	1	23.5	32	7	3
FRM-320-R20	●	●	2	23.5	32	7	3
FRM-320-R30	●		3	23.5	32	7	3

MIRROR RADIUS

RNM Type

HRM
TYPE**High feed geometry**

from Semi-finishing to finishing


Corner radius accuracy
 ± 0.015 mm

Cat.No.	PVD Coating	Dimensions(mm)				
	JC8015	RE	L	W1	S	C
HRM-060-R05	●	0.5	5	6	2	—
HRM-060-R10	●	1	5	6	2	—
HRM-060-R15	●	1.5	5	6	2	—
HRM-080-R20	●	2	7	8	2.4	0.3
HRM-090-R20	●	2	7	9	2.4	0.3
HRM-100-R20	●	2	8.5	10	2.6	0.3
HRM-110-R20	●	2	8.5	11	2.6	0.3
HRM-120-R20	●	2	10	12	3	0.5
HRM-130-R20	●	2	10	13	3	0.5
HRM-160-R20	●	2	12	16	4	0.5
HRM-160-R30	●	3	12	16	4	0.5
HRM-170-R30	●	3	12	17	4	0.5
HRM-200-R20	●	2	15	20	5	0.5
HRM-200-R30	●	3	15	20	5	0.5
HRM-220-R30	○	3	15	22	5	0.5

Mirror Radius Oversized Insert



Recommended to use oversized insert ※ for increasing side clearance to prevent the damage of shank by sticking chips.

(※) HRM-090-R20, HRM-110-R20, HRM-130-R20,
HRM-170-R30, HRM-220-R30



RNM
TYPE**Neutral geometry**

good for finishing non-ferrous materials such as Aluminium, Copper

Corner radius accuracy
 ± 0.010 mm

Cat.No.	Diamond Coating	Uncoated	Dimensions(mm)				
	JC10000	KT9 (K10)	RE	L	W1	S	C
RNM-080-R03		○	0.3	7	8	2.4	2.7
RNM-080-R05	●	●	0.5	7	8	2.4	2.7
RNM-080-R10		●	1	7	8	2.4	2.7
RNM-100-R03		○	0.3	8.5	10	2.6	3.3
RNM-100-R05	●	●	0.5	8.5	10	2.6	3.3
RNM-100-R10	○	●	1	8.5	10	2.6	3.3
RNM-100-R15		○	1.5	8.5	10	2.6	3.3
RNM-100-R20		○	2	8.5	10	2.6	3.3
RNM-120-R03		○	0.3	10	12	3	4
RNM-120-R05	○	●	0.5	10	12	3	4
RNM-120-R10	○	●	1	10	12	3	4
RNM-120-R15		○	1.5	10	12	3	4
RNM-120-R20		●	2	10	12	3	4
RNM-160-R03		●	0.3	12	16	4	5.3
RNM-160-R05		●	0.5	12	16	4	5.3
RNM-160-R10		●	1	12	16	4	5.3
RNM-160-R15		○	1.5	12	16	4	5.3
RNM-160-R20		○	2	12	16	4	5.3
RNM-200-R03		○	0.3	15	20	5	6.7
RNM-200-R05		○	0.5	15	20	5	6.7
RNM-200-R10		●	1	15	20	5	6.7
RNM-200-R15		○	1.5	15	20	5	6.7
RNM-200-R20		○	2	15	20	5	6.7

■ Grade Selection Guide

Material	Insert	Grade	RNM		HRM	FRM	
			JC10000	KT9	JC8015	DH102	JC8015
Carbon steel below 250HB	FRM HRM	JC8015			◎		◎
Cast steel below 285HB	FRM HRM	JC8015			◎		◎
Tool & Die steel below 255HB	FRM HRM	JC8015			◎		◎
Mold steel 30 - 36HRC	FRM HRM	JC8015			◎		◎
Mold steel 38 - 43HRC	FRM HRM	JC8015			◎		◎
Hardened die steel 42 - 52HRC	FRM HRM	DH102 JC8015			○	◎	○
Hardened die steel 55 - 62HRC	FRM	DH102				◎	
HSS 63 - 70HRC	FRM	DH102				◎	
Grey & Nodular cast iron below 300HB	FRM HRM	DH102 JC8015			○	◎	○
Austenitic stainless steel (304,316,317) 17Cr	FRM HRM	JC8015			◎	○	◎
Aluminium alloy (A5052)	RNM	KT9		◎			
Copper alloy (C1100)	RNM	KT9		◎			
Graphite	RNM	JC10000	◎				
Titanium alloy (Ti-6Al-4V) 35 - 43HRC	HRM FRM	JC8015			◎		◎
Heat resistant alloy (INC0718) 35 - 43HRC	HRM FRM	JC8015			◎		◎

Note) ◎ : First choice ○ : Second choice

■ Recommended Cutting Conditions | RNM type | Side Finishing

Material	Cat.No	Grade		Tool dia.(mm)				
				8	10	12	16	20
Aluminium	RNM	KT9	$n(\text{min}^{-1})$	13,930	11,140	9,280	6,960	5,570
			$Vf(\text{mm/min})$	5,570	4,460	3,710	3,500	2,800
			$ap(\text{mm})$	0.4	0.5	0.6	0.8	1.0
			$ae(\text{mm})$	0.2	0.2	0.2	0.2	0.2
Copper alloy	RNM	KT9	$n(\text{min}^{-1})$	9,950	7,960	6,630	4,970	3,980
			$Vf(\text{mm/min})$	3,980	3,180	2,650	2,500	2,000
			$ap(\text{mm})$	0.3	0.3	0.4	0.5	0.7
			$ae(\text{mm})$	0.15	0.15	0.15	0.15	0.15
Graphite	RNM	JC10000	$n(\text{min}^{-1})$	13,930	11,140	9,280	—	—
			$Vf(\text{mm/min})$	5,570	4,460	3,710	—	—
			$ap(\text{mm})$	0.4	0.5	0.6	—	—
			$ae(\text{mm})$	0.2	0.2	0.2	—	—

■ Recommended Cutting Conditions | RNM type | Bottom Finishing

Material	Cat.No	Grade		Tool dia.(mm)				
				8	10	12	16	20
Aluminium	RNM	KT9	$n(\text{min}^{-1})$	11,940	9,550	7,960	5,970	4,770
			$Vf(\text{mm/min})$	4,780	3,820	3,180	3,580	2,860
			$ap(\text{mm})$	0.25	0.25	0.25	0.25	0.3
			$ae(\text{mm})$	1.2 (~4)	1.2 (~5)	1.5 (~5)	2.0 (~9)	2.5 (~13)
Copper alloy	RNM	KT9	$n(\text{min}^{-1})$	7,960	6,370	5,310	3,980	3,180
			$Vf(\text{mm/min})$	2,390	1,910	1,590	1,190	950
			$ap(\text{mm})$	0.2	0.2	0.2	0.2	0.25
			$ae(\text{mm})$	1.2 (~4)	1.2 (~5)	1.5 (~5)	2.0 (~9)	2.5 (~13)
Graphite	RNM	JC10000	$n(\text{min}^{-1})$	11,940	9,550	7,960	—	—
			$Vf(\text{mm/min})$	4,780	3,820	3,180	—	—
			$ap(\text{mm})$	0.25	0.25	0.25	—	—
			$ae(\text{mm})$	1.2 (~4)	1.2 (~5)	1.5 (~5)	—	—

- Note) 1. Please adjust cutting conditions according to machine rigidity or work rigidity.
 2. These cutting conditions represent stable machining at length $3 \times D_c$.
 Please adjust cutting conditions according to overhang length.
 3. In case of chatter occurring, recommended to reduce ap or feed.
 4. Use air blow.

Overhang length	$n(\text{min}^{-1})$	$Vf(\text{mm/min})$
~3Dc	100%	100%
3Dc~5Dc	70%	70%
5Dc~10Dc	50%	50%

■ Recommended Cutting Conditions | FRM type | Side Finishing

Material	Grade		Tool dia. (mm)								
			6	8	10	12/13	16/17	20/21	25/26	30	32
Carbon steel below 250HB	JC8015	n (min ⁻¹)	15,920	11,940	9,550	7,960	5,970	4,770	3,820	3,180	2,980
		Vf (mm/min)	3,980	2,990	2,870	2,390	2,390	1,910	1,530	1,270	1,190
		ap (mm)	0.2	0.3	0.3	0.3	0.4	0.5	0.8	1.0	1.2
		ae (mm)	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
Tool & Die steel below 255HB	JC8015	n (min ⁻¹)	15,920	11,940	9,550	7,960	5,970	4,770	3,820	3,180	2,980
		Vf (mm/min)	3,980	2,990	2,870	2,390	2,390	1,910	1,530	1,270	1,190
		ap (mm)	0.2	0.3	0.3	0.3	0.4	0.5	0.8	1.0	1.2
		ae (mm)	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
Mold steel 30 - 36HRC	JC8015	n (min ⁻¹)	15,920	11,940	9,550	7,960	5,970	4,770	3,820	3,180	2,980
		Vf (mm/min)	3,980	2,990	2,870	2,390	2,390	1,910	1,530	1,270	1,190
		ap (mm)	0.2	0.3	0.3	0.3	0.4	0.5	0.8	1.0	1.2
		ae (mm)	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
Mold steel 38 - 43HRC	JC8015	n (min ⁻¹)	14,850	11,140	8,910	7,430	5,570	4,460	3,570	2,970	2,790
		Vf (mm/min)	3,710	2,790	2,670	2,230	1,670	1,340	1,070	890	840
		ap (mm)	0.2	0.2	0.3	0.3	0.4	0.5	0.8	1.0	1.2
		ae (mm)	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
Hardened die steel 42 - 52HRC	DH102 JC8015	n (min ⁻¹)	13,260	9,950	7,960	6,630	4,970	3,980	3,180	2,650	2,490
		Vf (mm/min)	1,330	1,000	800	660	750	600	480	400	370
		ap (mm)	0.2	0.2	0.3	0.3	0.4	0.5	0.6	0.8	1.0
		ae (mm)	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
Hardened die steel 55 - 62HRC	DH102	n (min ⁻¹)	10,610	7,960	6,370	5,310	3,980	3,180	2,550	2,120	1,990
		Vf (mm/min)	1,060	800	640	530	600	480	380	320	300
		ap (mm)	0.2	0.2	0.3	0.3	0.4	0.5	0.6	0.8	1.0
		ae (mm)	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
HSS 63 - 70HRC	DH102	n (min ⁻¹)	7,960	5,970	4,770	3,980	2,980	2,390	1,910	1,590	1,490
		Vf (mm/min)	320	240	290	320	300	240	190	160	150
		ap (mm)	0.1	0.1	0.1	0.1	0.2	0.2	0.3	0.4	0.5
		ae (mm)	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
Grey & Nodular cast iron below 300 HB	DH102 JC8015	n (min ⁻¹)	18,570	13,930	11,140	9,280	6,960	5,570	4,460	3,710	3,480
		Vf (mm/min)	6,500	4,880	3,900	3,250	3,480	3,340	2,680	2,230	2,090
		ap (mm)	0.2	0.3	0.3	0.3	0.4	0.5	0.8	1.0	1.2
		ae (mm)	0.1	0.1	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Stainless steel	JC8015	n (min ⁻¹)	14,850	11,140	8,910	7,430	5,570	4,460	3,570	2,970	2,790
		Vf (mm/min)	4,460	3,340	2,670	2,230	2,230	1,780	1,430	1,190	1,120
		ap (mm)	0.2	0.3	0.3	0.3	0.4	0.5	0.8	1.0	1.0
		ae (mm)	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
Titanium alloy (Ti-6Al-4V)	JC8015	n (min ⁻¹)	5,310	3,980	3,180	2,650	1,990	1,590	1,270	1,060	990
		Vf (mm/min)	1,060	800	760	640	480	380	320	270	250
		ap (mm)	0.2	0.2	0.3	0.3	0.3	0.3	0.4	0.4	0.4
		ae (mm)	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
Heat resistant alloy (INCO718)	JC8015	n (min ⁻¹)	4,240	3,180	2,550	2,120	1,590	1,270	1,020	850	800
		Vf (mm/min)	850	640	610	510	380	300	260	210	200
		ap (mm)	0.2	0.2	0.3	0.3	0.3	0.3	0.4	0.4	0.4
		ae (mm)	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1

- Note) 1. Please adjust cutting conditions according to machine rigidity or work rigidity.
 2. These cutting conditions represent stable machining at length 3 x Dc.
 Please adjust cutting conditions according to overhang length.
 3. In case of chatter occurring, recommended to reduce ap or feed.
 4. Use air blow.

Overhang length	n (min ⁻¹)	Vf (mm/min)
~3Dc	100%	100%
3Dc~5Dc	70%	70%
5Dc~10Dc	50%	50%

■ Recommended Cutting Conditions | FRM type | Bottom Finishing

Material	Grade		Tool dia. (mm)								
			6	8	10	12/13	16/17	20/21	25/26	30	32
Carbon steel below 250HB	JC8015	n (min ⁻¹)	13,790	10,350	8,280	6,900	5,170	4,140	3,310	2,760	2,590
		Vf (mm/min)	3,450	3,110	2,480	2,070	2,070	1,660	1,320	1,100	1,040
		ap (mm)	0.1	0.15	0.15	0.15	0.15	0.2	0.2	0.2	0.2
		ae (mm)	1.0 (~3)	1.2 (~4)	1.2 (~5)	1.5 (~5)	2.0 (~9)	2.5 (~13)	4.0 (~18)	4.2 (~23)	4.2 (~25)
Tool & Die steel below 255HB	JC8015	n (min ⁻¹)	13,790	10,350	8,280	6,900	5,170	4,140	3,310	2,760	2,590
		Vf (mm/min)	3,450	3,110	2,480	2,070	2,070	1,660	1,320	1,100	1,040
		ap (mm)	0.1	0.15	0.15	0.15	0.15	0.2	0.2	0.2	0.2
		ae (mm)	1.0 (~3)	1.2 (~4)	1.2 (~5)	1.5 (~5)	2.0 (~9)	2.5 (~13)	4.0 (~18)	4.2 (~23)	4.2 (~25)
Mold steel 30 - 36HRC	JC8015	n (min ⁻¹)	13,790	10,350	8,280	6,900	5,170	4,140	3,310	2,760	2,590
		Vf (mm/min)	3,450	3,110	2,480	2,070	2,070	1,660	1,320	1,100	1,040
		ap (mm)	0.1	0.15	0.15	0.15	0.15	0.2	0.2	0.2	0.2
		ae (mm)	1.0 (~3)	1.2 (~4)	1.2 (~5)	1.5 (~5)	2.0 (~9)	2.5 (~13)	4.0 (~18)	4.2 (~23)	4.2 (~25)
Mold steel 38 - 43HRC	JC8015	n (min ⁻¹)	12,730	9,550	7,640	6,370	4,770	3,820	3,060	2,550	2,390
		Vf (mm/min)	3,180	2,870	2,290	1,910	1,430	1,150	920	770	720
		ap (mm)	0.1	0.15	0.15	0.15	0.15	0.2	0.2	0.2	0.2
		ae (mm)	1.0 (~3)	1.2 (~4)	1.2 (~5)	1.5 (~5)	2.0 (~9)	2.5 (~13)	4.0 (~18)	4.2 (~23)	4.2 (~25)
Hardened die steel 42 - 52HRC	DH102 JC8015	n (min ⁻¹)	10,080	7,560	6,050	5,040	3,780	3,020	2,420	2,020	1,890
		Vf (mm/min)	1,010	760	610	600	570	450	360	300	280
		ap (mm)	0.05	0.06	0.08	0.1	0.1	0.15	0.15	0.15	0.15
		ae (mm)	1.0 (~3)	1.2 (~4)	1.2 (~5)	1.5 (~5)	2.0 (~9)	2.5 (~13)	4.0 (~18)	4.2 (~23)	4.2 (~25)
Hardened die steel 55 - 62HRC	DH102	n (min ⁻¹)	6,900	5,170	4,140	3,450	2,590	2,070	1,660	1,380	1,290
		Vf (mm/min)	690	520	410	410	390	310	250	210	190
		ap (mm)	0.05	0.06	0.08	0.1	0.1	0.15	0.15	0.15	0.15
		ae (mm)	1.0 (~3)	1.2 (~4)	1.2 (~5)	1.5 (~5)	2.0 (~9)	2.5 (~13)	4.0 (~18)	4.2 (~23)	4.2 (~25)
HSS 63 - 70HRC	DH102	n (min ⁻¹)	5,310	3,980	3,180	2,650	1,990	1,590	1,270	1,060	990
		Vf (mm/min)	210	160	190	210	200	160	130	110	100
		ap (mm)	0.03	0.04	0.05	0.05	0.05	0.05	0.05	0.05	0.05
		ae (mm)	1.0 (~2)	1.2 (~3)	1.2 (~4)	1.5 (~5)	2.0 (~6)	2.5 (~8)	4.0 (~10)	4.2 (~12)	4.2 (~13)
Grey & Nodular cast iron below 300 HB	DH102 JC8015	n (min ⁻¹)	15,920	11,940	9,550	7,960	5,970	4,770	3,820	3,180	2,980
		Vf (mm/min)	4,780	4,180	3,340	3,180	2,390	1,910	1,910	1,590	1,490
		ap (mm)	0.1	0.15	0.15	0.2	0.2	0.2	0.2	0.2	0.2
		ae (mm)	1.0 (~3)	1.2 (~4)	1.2 (~5)	1.5 (~5)	2.0 (~9)	2.5 (~13)	4.0 (~18)	4.2 (~23)	4.2 (~25)
Stainless steel	JC8015	n (min ⁻¹)	12,730	9,550	7,640	6,370	4,770	3,820	3,060	2,550	2,390
		Vf (mm/min)	3,180	2,870	2,290	1,910	1,910	1,530	1,220	1,020	960
		ap (mm)	0.1	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15
		ae (mm)	1.0 (~3)	1.2 (~4)	1.2 (~5)	1.5 (~5)	2.0 (~9)	2.5 (~13)	4.0 (~18)	4.2 (~23)	4.2 (~25)
Titanium alloy (Ti-6Al-4V)	JC8015	n (min ⁻¹)	2,920	2,190	1,750	1,460	1,090	880	700	580	550
		Vf (mm/min)	580	440	350	290	220	180	140	120	110
		ap (mm)	0.1	0.15	0.15	0.15	0.15	0.2	0.2	0.2	0.2
		ae (mm)	1.0 (~3)	1.2 (~4)	1.2 (~5)	1.5 (~5)	2.0 (~9)	2.5 (~13)	4.0 (~18)	4.2 (~23)	4.2 (~25)
Heat resistant alloy (INCO718)	JC8015	n (min ⁻¹)	2,920	2,190	1,750	1,460	1,090	880	700	580	550
		Vf (mm/min)	580	440	350	290	220	180	140	120	110
		ap (mm)	0.1	0.15	0.15	0.15	0.15	0.2	0.2	0.2	0.2
		ae (mm)	1.0 (~3)	1.2 (~5)	1.2 (~5)	1.5 (~5)	2.0 (~9)	2.5 (~13)	4.0 (~18)	4.2 (~23)	4.2 (~25)

Note) 1. Please adjust cutting conditions according to machine rigidity or work rigidity.
 2. These cutting conditions represent stable machining at length 3 x Dc.
 Please adjust cutting conditions according to overhang length.
 3. In case of chatter occurring, recommended to reduce ap or feed.
 4. Use air blow.

Overhang length	n (min ⁻¹)	Vf (mm/min)
~3Dc	100%	100%
3Dc~5Dc	70%	70%
5Dc~10Dc	50%	50%

MIRROR RADIUS


HRM Type

■ Recommended Cutting Conditions | HRM type | High Feed / Semi finishing

Material		Tool dia. (mm)									
		Ø6×R1.5		Ø8×R2/Ø9×R2				Ø10×R2/Ø11×R2			
		2.5 D	5.0 D	2.5 D	5.0 D	7.5 D	10 D	2.5 D	5.0 D	7.5 D	10 D
Carbon steel below 250HB	n (min ⁻¹)	9,000	9,000	7,500	7,500	7,500	7,500	6,000	6,000	6,000	6,000
	Vf (mm/min)	8,000	7,200	8,200	6,750	6,750	6,750	7,200	6,000	6,000	6,000
	ap (mm)	0.2	0.15	0.4	0.4	0.25	0.2	0.4	0.4	0.25	0.2
	ae (mm)	2.1	2.1	2.8	2.8	2.8	2.8	4.2	4.2	4.2	4.2
Mold steel 30 - 43HRC	n (min ⁻¹)	8,500	8,500	7,100	7,100	7,100	7,100	5,700	5,700	5,700	5,700
	Vf (mm/min)	7,600	6,800	7,800	6,400	6,400	6,400	6,800	5,700	5,700	5,700
	ap (mm)	0.2	0.15	0.4	0.4	0.25	0.2	0.4	0.4	0.25	0.2
	ae (mm)	2.1	2.1	2.8	2.8	2.8	2.8	4.2	4.2	4.2	4.2
Tool & Die steel below 255HB	n (min ⁻¹)	8,500	8,500	7,100	7,100	7,100	7,100	5,700	5,700	5,700	5,700
	Vf (mm/min)	7,600	6,800	7,800	6,400	6,400	6,400	6,800	5,700	5,700	5,700
	ap (mm)	0.2	0.15	0.4	0.4	0.25	0.2	0.4	0.4	0.25	0.2
	ae (mm)	2.1	2.1	2.8	2.8	2.8	2.8	4.2	4.2	4.2	4.2
Stainless steel below 250HB	n (min ⁻¹)	8,000	8,000	6,700	6,700	6,700	6,700	5,400	5,400	5,400	5,400
	Vf (mm/min)	6,400	5,600	7,300	6,000	6,000	6,000	6,400	5,400	5,400	5,400
	ap (mm)	0.2	0.15	0.4	0.4	0.25	0.2	0.4	0.4	0.25	0.2
	ae (mm)	2.1	2.1	2.8	2.8	2.8	2.8	4.2	4.2	4.2	4.2
Hardened die steel 40 - 50HRC	n (min ⁻¹)	6,900	6,900	6,000	6,000	6,000	6,000	4,700	4,700	4,700	4,700
	Vf (mm/min)	5,500	4,800	6,600	4,800	4,800	4,800	5,600	4,700	4,700	4,700
	ap (mm)	0.15	0.1	0.2	0.2	0.15	0.1	0.2	0.2	0.15	0.1
	ae (mm)	2.1	2.1	2.8	2.8	2.8	2.8	4.2	4.2	4.2	4.2
Grey & Nodular cast iron below 300 HB	n (min ⁻¹)	7,400	7,400	6,400	6,400	6,400	6,400	5,100	5,100	5,100	5,100
	Vf (mm/min)	6,600	5,900	7,600	5,700	5,700	5,700	6,100	5,100	5,100	5,100
	ap (mm)	0.2	0.15	0.4	0.4	0.25	0.2	0.4	0.4	0.25	0.2
	ae (mm)	2.1	2.1	2.8	2.8	2.8	2.8	4.2	4.2	4.2	4.2

ap adjustment by corner radius $ap \times \text{ratio}$	Tool dia. (mm)	ap (mm)
	Ø6×R0.5	65%
	Ø6×R1.0	80%
	Ø6×R1.5	100%

- Note) 1. Please adjust cutting conditions according to machine rigidity or work rigidity.
 2. In case of chatter occurring, recommended to reduce ap or Vf .
 3. Recommended to reduce the parameters when using on low horse power machine.
 4. Use air blow.
 5. Reduce ap , n & Vf by 30% in case of cutting material 50-55HRC.
 6. Reduce Vf for better surface finish.
 7. Use angle 2°30' or below in case of ramping (see right figure).
 8. In case of slotting with over 5xDc, reduce Vf or ap appropriately.



★ Insert Mounting Information

1. Make sure the insert seat on body is carefully cleaned.
2. Make sure insert itself is clean, especially the hole and face location.
3. Change insert screw when threads starts to wear.
4. Do not over tighten screw. See table for torque specifications.

Toll dia. (mm)	Torque
ϕD_c	N·m
6	0.5
8	0.9
10	1.2
12	2.0
16	3.0
20	4.0

■ Recommended Cutting Conditions | **HRM type** | High Feed / Semi finishing

	Tool dia. (mm)											
	Ø12×R2/Ø13×R2				Ø16×R3/Ø17×R3				Ø20×R3/Ø22×R3			
	2.5 D	5.0 D	7.5 D	10 D	2.5 D	5.0 D	7.5 D	10 D	2.5 D	5.0 D	7.5 D	10 D
<i>n</i> (min ⁻¹)	5,000	5,000	5,000	5,000	3,800	3,800	3,800	3,800	3,000	3,000	3,000	3,000
<i>Vf</i> (mm/min)	6,000	5,000	5,000	5,000	4,500	3,800	3,800	3,800	3,600	3,000	3,000	3,000
<i>ap</i> (mm)	0.5	0.4	0.25	0.2	0.6	0.6	0.4	0.3	0.6	0.6	0.4	0.3
<i>ae</i> (mm)	5.6	5.6	5.6	5.6	7	7	7	7	9.8	9.8	9.8	9.8
<i>n</i> (min ⁻¹)	4,700	4,700	4,700	4,700	3,500	3,500	3,500	3,500	2,800	2,800	2,800	2,800
<i>Vf</i> (mm/min)	5,600	4,700	4,700	4,700	4,200	3,500	3,500	3,500	3,300	2,800	2,800	2,800
<i>ap</i> (mm)	0.4	0.4	0.25	0.2	0.6	0.6	0.4	0.3	0.6	0.6	0.4	0.3
<i>ae</i> (mm)	5.6	5.6	5.6	5.6	7	7	7	7	9.8	9.8	9.8	9.8
<i>n</i> (min ⁻¹)	4,700	4,700	4,700	4,700	3,500	3,500	3,500	3,500	2,800	2,800	2,800	2,800
<i>Vf</i> (mm/min)	5,600	4,700	4,700	4,700	4,200	3,500	3,500	3,500	3,300	2,800	2,800	2,800
<i>ap</i> (mm)	0.4	0.4	0.25	0.2	0.6	0.6	0.4	0.3	0.6	0.6	0.4	0.3
<i>ae</i> (mm)	5.6	5.6	5.6	5.6	7	7	7	7	9.8	9.8	9.8	9.8
<i>n</i> (min ⁻¹)	4,500	4,500	4,500	4,500	3,400	3,400	3,400	3,400	2,700	2,700	2,700	2,700
<i>Vf</i> (mm/min)	5,400	4,500	4,500	4,500	4,000	3,400	3,400	3,400	3,200	2,700	2,700	2,700
<i>ap</i> (mm)	0.4	0.4	0.25	0.2	0.6	0.6	0.4	0.3	0.6	0.6	0.4	0.3
<i>ae</i> (mm)	5.6	5.6	5.6	5.6	7	7	7	7	9.8	9.8	9.8	9.8
<i>n</i> (min ⁻¹)	4,000	4,000	4,000	4,000	3,000	3,000	3,000	3,000	2,400	2,400	2,400	2,400
<i>Vf</i> (mm/min)	4,800	4,000	4,000	4,000	3,600	3,000	3,000	3,000	2,800	2,400	2,400	2,400
<i>ap</i> (mm)	0.2	0.2	0.15	0.1	0.3	0.3	0.25	0.2	0.3	0.3	0.25	0.2
<i>ae</i> (mm)	5.6	5.6	5.6	5.6	7	7	7	7	9.8	9.8	9.8	9.8
<i>n</i> (min ⁻¹)	4,200	4,200	4,200	4,200	3,200	3,200	3,200	3,200	2,500	2,500	2,500	2,500
<i>Vf</i> (mm/min)	5,000	4,200	4,200	4,200	3,800	3,200	3,200	3,200	3,000	2,500	2,500	2,500
<i>ap</i> (mm)	0.4	0.4	0.25	0.2	0.6	0.6	0.4	0.3	0.6	0.6	0.4	0.3
<i>ae</i> (mm)	5.6	5.6	5.6	5.6	7	7	7	7	9.8	9.8	9.8	9.8

ap adjustment by corner radius ap × ratio	Tool dia. (mm)	ap (mm)	Tool dia. (mm)	ap (mm)
	Ø16×R2.0	75%	Ø20×R2.0	75%
	Ø16×R3.0	100%	Ø20×R3.0	100%

DIEMASTER 5G

Feature 1 Multiple Machining Styles

Shoulder Milling(radius)

- Side Wall Finishing




Face Milling

- Bottom Finishing



Copy Milling

- Semi-Finishing



Plunge Milling

- Plunge Finishing & Semi-Finishing

Feature 2 Available in 2 insert grades

JC8015

P

M

K

DH103

P

K

H


For general purpose


Applied to general steel, mold steel, stainless steel,
and hardened die steel up to 50 HRC

For hardened steel

Excellent wear-resistance when finishing
or semi-finishing high hardened steels

ISO	P					M					K				H		
	P01	P10	P20	P30	P40	M01	M10	M20	M30	M40	K01	K10	K20	K30	H01	H10	H20
Application Range	JC8015					JC8015					JC8015						
	DH103										DH103				DH103		

Feature 3 Economical **double-sided** insert (with 6 cutting edges)
High accuracy with H-class tolerance

Feature 4**Double-wiper insert****Wiper for face cutting and for periphery cutting****Selection Guide**

Product	Mirror Radius MRX / RNM type	High Precision QM max MQT-A00 type	Diemaster 5G XFG / MXF type
			
Tool diameter (mm)	6 - 32	16 - 35	16 - 66
Diameter tolerance	0 / -0.02	0 / -0.03	+0.01 / -0.05
Accuracy	★★★★	★★	★
Efficiency	★	★★★★	★★★
Economical	★	★★	★★★★

DIEMASTER 5G

XFG
TYPE

Bore Type


Through
coolant
hole

Face Milling

Copy Milling

Shoulder Milling

Plunge Milling



Cat.No.	Stock	No. of inserts	Dimensions (mm)								Arbor set bolt	Weight (kg)	Inserts
			DC	LF	DCSFMS	DCB	DCCB	KWW	KDP	CBDP			
XFG-6050R-22	●	6	50	50	47	22	16.5	10.4	6.3	20	M10	0.54	WNHU04T310ZER
XFG-6052R-22	●	6	52	50	47	22	16.5	10.4	6.3	20	M10	0.56	
XFG-7063R-27	●	7	63	50	48	27	20.0	12.4	7	22	M12×1.75×30★	0.69	
XFG-7066R-27	●	7	66	50	48	27	20.0	12.4	7	22	M12×1.75×30★	0.72	

Screw	Torque(N.m)	Wrench
TSW-2567H	1.1	A-08


**MXF
TYPE****Modular Type**Through
coolant
hole

Face Milling

Copy Milling



Shoulder Milling

Plunge Milling



Cat.No.	Stock	No. of inserts	Dimensions (mm)						Insert
			DC	LF	DCSFMS	MD	C	W	
MXF-2016-M8	●	2	16	23	14	M8	8	12	WNHU04T310ZER
MXF-3020-M10	●	3	20	30	18	M10	9	14	
MXF-4025-M12	●	4	25	35	22	M12	11	19	
MXF-5032-M16	●	5	32	43	29	M16	12	22	
MXF-5035-M16	●	5	35	43	29	M16	12	22	
MXF-6040-M16	●	6	40	43	32	M16	14	26	
MXF-6042-M16	●	6	42	43	32	M16	14	26	

Screw	Torque(N.m)	Wrench
TSW-2567H	1.1	A-08

Insert

Cat.No.	Tolerance	PVD coated		Dimensions (mm)		
		DH103	JC8015	RE	IC	S
WNHU04T310ZER	H	●	●	1.0	6.35	3.33

DIEMASTER 5G

● Attention



Attention to mounting head and MSN/ MGN shank arbor.

■ Tightening procedure

① Cleaning

Remove dirt and chips with air from the connecting thread and face of modular head and MSN/MGN shank arbor.

② Initial Tightening

Tighten by hand until the head and the shank arbor faces touch.

③ Final Tightening

Tighten slowly with torque control spanner wrench or DIJET DS type spanner wrench and confirm that there is no gap.

Attention: Final tightening without initial tightening cause connecting thread damage.



NOTE

Note: 1. Please gently apply pressure on wrench.

2. Please confirm that there is no gap between MSN/MGN shank arbor and modular

Thread	Tightening torque	Spanner size W (mm)
M8	16N • m	12 ☆
M10	16N • m	14, 15
M12	20N • m	17, 19
M16	25N • m	22, 26

Note: 1. Modular heads are supplied without spanner wrench.

2. In case of choosing torque control spanner wrench, confirm that the wrench size is match to the dimensions W & C of each modular head. (There are some cases that modifying the thickness of spanner wrench is necessary)

3. ☆ mark shows: DIJET have a stock of DS-8 and 12 type spanner wrenches.




Selection of "MSN Carbide shank arbor"

In case of using modular head over $\varnothing 16\text{mm}$, please select **MSN carbide shank arbor that diameter ($\varnothing D1$) is 1mm or more smaller than modular head ($\varnothing Dc$).**

A wrong selection causes damage to the carbide shank.

$$\varnothing Dc - \varnothing D1 \geq 1\text{mm}$$




Caution for the mounting to shrink fit holder.

When you use a carbide shank and a modular head on the shrink fit holder, please shrink fit the only the carbide shank without modular head. **Please mount a modular head after cooling off.**


Note: In case of shrink fit MSN shank + modular head together, it will be difficult to loose due to heat desipation.

Attention for profile milling

Ramping



Helical interpolation



● Calculation of tool pass dia.

$$\phi dc = \phi Dh - \phi Dc$$

Tool pass dia. Bore dia. Tool dia.

- Depth of cut per one circuit should not exceed max. depth of cut a_p
- Down cutting is recommended, so tool pass rotation should be counterclockwise.
- To obtain a flat bottom surface when helical milling, it requires to remove "the uncut part" in the center of work materials at final pass.

- ◎ In case of ramping and helical interpolation, apply 80% or less feed speed from standard cutting condition table.
- ◎ In case of helical interpolation, recommend wet cutting by coolant through the tool.

Cat.No.	Tool dia.	Max. Depth of cut (mm) a_p	Ramping		Helical interpolation		
			Max. ramping angle θ°	Total cutting length at Max. a_p L (mm)	Through hole Min. bore dia. D_h min (mm)	Through hole Max. bore dia. ϕD_h max (mm)	Flat bottom Min. bore dia. D_f min (mm)
MXF-2016-M8	16	0.5	0.4	72	28.2	31	29.6
MXF-3020-M10	20	0.5	0.3	95	36.2	39	37.6
MXF-4025-M12	25	0.5	0.2	143	46.2	49	47.6
MXF-5032-M16	32	0.5	0.15	191	60.2	63	61.6
MXF-5035-M16	35	0.5	0.15	191	66.2	69	67.6
MXF-6040-M16	40	0.5	0.1	286	76.2	79	77.6
MXF-6042-M16	42	0.5	0.1	286	80.2	83	81.6
XFG-6050R-22	50	0.5	0.1	286	96.2	99	97.6
XFG-6052R-22	52	0.5	0.1	286	100.2	103	101.6
XFG-7063R-27	63	0.5	※Ramping & helical interpolation is not recommended.				
XFG-7066R-27	66	0.5					

※Drilling is not recommended.

DIEMASTER 5G

■ Recommended Cutting Conditions

Material	Grade		Finishing		Semi Finishing
			Side Wall	Bottom Face	
Carbon steel below 250HB	JC8015	Vc(mm/min)	300	260	190
		fz(mm/t)	0.20	0.20	0.4 - 0.6
		ap(mm)	0.30	0.20	0.20
		ae(mm)	0.10	~ 0.7 Dc	0.5Dc
Cast steel below 285HB	JC8015	Vc(mm/min)	300	260	190
		fz(mm/t)	0.20	0.20	0.4 - 0.6
		ap(mm)	0.30	0.20	0.20
		ae(mm)	0.10	~ 0.7 Dc	0.5Dc
Tool & die steel below 255HB	JC8015	Vc(mm/min)	300	260	175
		fz(mm/t)	0.20	0.20	0.4 - 0.6
		ap(mm)	0.30	0.20	0.20
		ae(mm)	0.10	~ 0.7 Dc	0.5Dc
Mold steel 30-36 HRC	DH103 JC8015	Vc(mm/min)	300	260	175
		fz(mm/t)	0.20	0.20	0.4 - 0.6
		ap(mm)	0.30	0.20	0.20
		ae(mm)	0.10	~ 0.7 Dc	0.5Dc
Mold steel 38-43HRC	DH103 JC8015	Vc(mm/min)	280	240	160
		fz(mm/t)	0.15	0.15	0.4 - 0.6
		ap(mm)	0.30	0.20	0.20
		ae(mm)	0.10	~ 0.7 Dc	0.5Dc
Hardened die steel 42-52HRC	DH103 JC8015	Vc(mm/min)	250	190	150
		fz(mm/t)	0.08	0.08	0.4 - 0.6
		ap(mm)	0.30	0.15	0.20
		ae(mm)	0.10	~ 0.7 Dc	0.5Dc
Grey cast iron 160-260HB	DH103 JC8015	Vc(mm/min)	350	300	160
		fz(mm/t)	0.25	0.20	0.4 - 0.6
		ap(mm)	0.30	0.20	0.20
		ae(mm)	0.20	~ 0.7 Dc	0.5Dc
Nodular cast iron 170-300HB	DH103 JC8015	Vc(mm/min)	350	300	160
		fz(mm/t)	0.25	0.20	0.4 - 0.6
		ap(mm)	0.30	0.20	0.20
		ae(mm)	0.20	~ 0.7 Dc	0.5Dc
Stainless steel	JC8015	Vc(mm/min)	280	240	170
		fz(mm/t)	0.20	0.20	0.4 - 0.6
		ap(mm)	0.30	0.15	0.20
		ae(mm)	0.10	~ 0.7 Dc	0.5Dc
Titanium alloy Ti-6Al-4V 35-43HRC	JC8015	Vc(mm/min)	100	55	-
		fz(mm/t)	0.12	0.10	-
		ap(mm)	0.25 - 0.30	0.20	-
		ae(mm)	0.10	~ 0.7 Dc	-
Heat resistant alloy INCO718 35-43HRC	JC8015	Vc(mm/min)	80	55	-
		fz(mm/t)	0.12	0.10	-
		ap(mm)	0.25 - 0.30	0.20	-
		ae(mm)	0.10	~ 0.7 Dc	-

Vc : Cutting speed fz : Feed rate per tooth ap : Depth of cut ae : Width of cut

Note

1. The above cutting conditions should be adjusted according to the machine rigidity and workpiece rigidity.
2. The above cutting conditions are for a overhang length of 3Dc.
Adjust the rotation speed n (min-1) and feed rate Vf (mm/min) according to the protrusion length.
3. If chattering occurs, reduce the depth of cut to a shallower depth than the above values or lower the feed rate.
4. Remove chips by air blow. Be especially careful when machining cavities with a vertical MC.
5. When using a steel shank, reduce the rotation speed n (min-1) and feed rate Vf (mm/min) to 80% of the above conditions.


Recommended Cutting Conditions

Material	Grade		Plunging	
			Finishing	Semi Finishing
Carbon steel below 250HB	JC8015	Vc(mm/min)	400	300
		fz(mm/t)	0.10	0.15
		ae(mm)	~0.2	~2
		Pf(mm)	-	~0.15Dc
Cast steel below 285HB	JC8015	Vc(mm/min)	400	300
		fz(mm/t)	0.10	0.15
		ae(mm)	~0.2	~2
		Pf(mm)	-	~0.15Dc
Tool & die steel below 255HB	JC8015	Vc(mm/min)	350	260
		fz(mm/t)	0.10	0.15
		ae(mm)	~0.2	~2
		Pf(mm)	-	~0.15Dc
Mold steel 30-36 HRC	DH103 JC8015	Vc(mm/min)	300	220
		fz(mm/t)	0.10	0.12
		ae(mm)	~0.2	~2
		Pf(mm)	-	~0.15Dc
Mold steel 38-43HRC	DH103 JC8015	Vc(mm/min)	200	150
		fz(mm/t)	0.10	0.12
		ae(mm)	~0.2	~2
		Pf(mm)	-	~0.15Dc
Hardened die steel 42-52HRC	DH103 JC8015	Vc(mm/min)	140	100
		fz(mm/t)	0.07	0.10
		ae(mm)	~0.2	~2
		Pf(mm)	-	~0.15Dc
Grey cast iron 160-260HB	DH103 JC8015	Vc(mm/min)	500	370
		fz(mm/t)	0.10	0.15
		ae(mm)	~0.2	~2
		Pf(mm)	-	~0.15Dc
Nodular cast iron 170-300HB	DH103 JC8015	Vc(mm/min)	500	370
		fz(mm/t)	0.10	0.15
		ae(mm)	~0.2	~2
		Pf(mm)	-	~0.15Dc

Vc : Cutting speed fz : Feed rate per tooth ae : Width of cut Pf : Pick Feed

Note

1. The above cutting conditions should be adjusted according to the machine rigidity and workpiece rigidity.
2. The above cutting conditions are for a overhang length of 3Dc.
Adjust the rotation speed n (min-1) and feed rate Vf (mm/min) according to the protrusion length.
3. If chattering occurs, reduce the depth of cut to a shallower depth than the above values or lower the feed rate.
4. Remove chips by air blow. Be especially careful when machining cavities with a vertical MC.
5. When using a steel shank, reduce the rotation speed n (min-1) and feed rate Vf (mm/min) to 80% of the above conditions.




SUPER DIEMASTER

HDM/SDH Type

HDM
TYPE


Bore Type / Standard Pitch

Through
coolant
hole

Cat.No.	Stock	No. of inserts	Dimensions(mm)									Arbor set bolt	Parts		Weight (kg)	Inserts
			DCX	RE	LF	DCSFMS	DCB	DCCB	KWW	KDP	CBDP		Screw	Wrench		
HDM-3050-12R-22	●	3	50	6	50	47	22	16.5	10.4	6.3	20	M10	DSW-410H	A-15T	0.5	RD**1204MO...
HDM-4063-16R-22	●	4	63	8	50	60	22	16.5	10.4	6.3	20	M10	DSW-4512H	A-20	0.7	RD**1606MO...

HDM
TYPE

Bore Type / Fine Pitch



Cat.No.	Stock	No. of inserts	Dimensions(mm)									Arbor set bolt	Weight (kg)	Parts		Inserts
			DCX	RE	LF	DCSFMS	DCB	DCCB	KWW	KDP	CBDP			Screw	Wrench	
HDM-4050-16R-22	●	4	50	8	55	47	22	16.5	10.4	6.3	20	M10	0.4	DSW-4512H	A-20	RD**1606MO...
HDM-5050-12R-22	●	5	50	6	50	47	22	16.5	10.4	6.3	20	M10	0.4	DSW-410H	A-15T	RD**1204MO...
HDM-5052-12R-22	●	5	52	6	50	40	22	16.5	10.4	6.3	20	M10	0.5	DSW-410H	A-15T	RD**1204MO...
HDM-5063-16R-27	●	5	63	8	50	60	27	20	12.4	7	22	M12	0.7	DSW-4512H	A-20	RD**1606MO...
HDM-6063-12R-27	●	6	63	6	50	60	27	20	12.4	7	22	M12	0.8	DSW-410H	A-15T	RD**1204MO...
HDM-6080-16R-27	●	6	80	8	55	76	27	20	12.4	7	22	M12	1.3	DSW-4512H	A-20	RD**1606MO...
HDM-7080-12R-27	●	7	80	6	55	76	27	20	12.4	7	22	M12	1.4	DSW-410H	A-15T	RD**1204MO...

MD		Hexagonal wrench(mm) for Arbor set bolt
M10		8
M12		10
M16		14
M20		17
M24		19

Inserts	Screw	Clamp	Wrench
			
RD**1204MO*	DSW-410H	DCM-18	A-15T
RD**1606MO*	DSW-4512H	DCM-17	A-20



SDH
TYPE

Modular Type / Standard Pitch




Fig.1





Fig.2




Cat.No.	Stock	No. of inserts	Dimensions(mm)							Parts			Inserts	Fig.
			DCX	RE	LF	DCSFMS	MD	C	W	Screw	Clamp	Wrench		
SDH-2150-R07-M8	●	2	15	3.5	23	13.8	M8	8	12	TSW-2556H	-	A-08SD	RD**07T2MO...	1
SDH-2160-R07-M8	●	2	16	3.5	23	15	M8	8	12					
SDH-2200-R07-M10	●	2	20	3.5	30	18	M10	8	14					
SDH-2250-R10-M12	●	2	25	5	35	23	M12	10	17	CSW-408H	DCM-18	A-15	RD**1004MO...	2
SDH-2280-R10-M12	○	2	28	5	35	25	M12	10	17				RD**1204MO...	
SDH-2320-R12-M16	●	2	32	6	43	28	M16	12	22	DSW-410H			RD**1004MO...	
SDH-3320-R10-M16	●	3	32	5	43	28	M16	12	22	CSW-408H			RD**1204MO...	
SDH-2350-R12-M16	○	2	35	6	43	32	M16	12	22	DSW-410H			RD**1004MO...	
SDH-3350-R10-M16	○	3	35	5	43	32	M16	12	22	CSW-408H			RD**1004MO...	
SDH-2400-R12-M16	○	2	40	6	43	32	M16	13	26	DSW-410H			RD**1204MO...	

SDH
TYPE

Modular Type / Fine Pitch



Screw	Torque (N.m)
TSW-2556H	1.1
CSW-408H	3.6
DSW-410H	3.6



Cat.No.	Stock	No. of inserts	Dimensions(mm)							Parts		Inserts
			DCX	RE	LF	DCSFMS	MD	C	W	Screw	Wrench	
SDH-3200-R07-M10	●	3	20	3.5	30	18	M10	8	14	TSW-2556H	A-08SD	RD**07T2MO...
SDH-3220-R07-M10	○	3	22	3.5	30	20	M10	8	14			
SDH-3250-R07-M12	○	3	25	3.5	35	23	M12	10	17			
SDH-3250-R10-M12	●	3	25	5	35	23	M12	10	17	CSW-408H	A-15	RD**1004MO...
SDH-3280-R10-M12	○	3	28	5	35	25	M12	10	17			
SDH-3300-R10-M16	○	3	30	5	43	28	M16	12	22			
SDH-4300-R10-M16	●	4	30	5	43	28	M16	12	22			
SDH-4320-R10-M16	●	4	32	5	43	28	M16	12	22			
SDH-3350-R12-M16	●	3	35	6	43	32	M16	12	22	DSW-410H		RD**1204MO...
SDH-4350-R10-M16	●	4	35	5	43	32	M16	12	22	CSW-408H		RD**1004MO...
SDH-4400-R12-M16	●	4	40	6	43	32	M16	13	26	DSW-410H		RD**1204MO...
SDH-5420-R10-M16	●	5	42	5	43	32	M16	13	26	CSW-408H		RD**1004MO...

SUPER DIEMASTER


HDM/SDH Type

Insert

Standard type

Flat top inert

for General steel




Cat.No.	Tolerance	PVD Coating			Dimensions(mm)		
		DH103	JC5040	JC8015	IC	S	AN
RDMW07T2MOT	M	●	●	●	7	2.7	15°
RDMW1004MOT		●	●	●	10	4.1	
RDMW1204MOT		●	●	●	12	4.8	
RDMW1606MOT		●	●	●	16	6	

Low cutting force

Chip breaker style

for Titanium • Inconel

for Stainless steel




Cat.No.	Tolerance	PVD Coating			Dimensions(mm)			Fig.
		JC8015	JC8050	JC8118	IC	S	AN	
RDGT07T2MOE	G	●	●		7	2.7	15°	1
RDGT1004MOE		●	●		10	4.1		
RDGT1004MOT		●	●		12	4.8		
RDGT1204MOE		●	●		16	6		
RDGT1204MOT		●	●					
RDGT1606MOE		●	●					
RDGT1606MOT		●	●					
RDMT07T2MOE	M		●	○	7	2.7		2
RDMT1004MOE			●	●	10	4.1		
RDMT1004MOE-ML			●		12	4.8		
RDMT1004MOT			●	●				1
RDMT1204MOE			●	●				2
RDMT1204MOE-ML			●	●				1
RDMT1204MOT			●	●				
RDMT1606MOE			●	●	16	6		
RDMT1606MOT			●	●				

Low cutting force

Chip breaker style

for Aluminium



Cat.No.	Tolerance	Uncoated	Dimensions(mm)		
		FZ05	IC	S	AN
RDGT07T2MOF-AL	G	●	7	2.7	15°
RDGT1004MOF-AL		●	10	4.1	
RDGT1204MOF-AL		●	12	4.8	
RDGT1606MOF-AL		●	16	6	

Insert grades

ISO	P					M					K				N				S				H		
	P01	P10	P20	P30	P40	M01	M10	M20	M30	M40	K01	K10	K20	K30	N01	N10	N20	N30	S01	S10	S20	S30	H01	H10	H20
Range																									

Grade selection guide


Material	Cast iron	Carbon steel · Tool steel			Mold steel		Hardened steel	Titanium alloy Inconel		Stainless steel		Aluminium
Grade	JC8015 JC5118	JC5040	JC8118	JC8050	JC8015 JC8118	JC8050	DH103 (over 50HRC) JC8015 JC8118	JC8015 JC8118	JC8050	JC8015 JC8118	JC8050	FZ05
Cat.No.												
RDMW07T2MOT	◎	◎	○		◎		◎	○		○		
RD * T07T2MOE	☆		☆	●	☆	●		◎	●	◎	●	
RDMW1004MOT	◎	◎	○		◎		◎					
RD * T1004MOT	☆				○					○	●	
RD * T1004MOE			☆	●	☆	●		○	●	☆		
RDMT1004MOE-ML									◎		◎	
RDMW1204MOT	◎	◎	○		◎		◎					
RD * T1204MOT	☆				○					○	●	
RD * T1204MOE			☆	●	☆	●		○	●	☆		
RDMT1204MOE-ML									◎		◎	
RDMW1606MOT	◎	◎	○		◎		◎					
RD * T1606MOT	☆				○					○	●	
RD * T1606MOE			☆	●	☆	●		○	◎	☆	◎	
RDGT****MOF-AL												◎

Grade selection guide

Material	Cast iron	Carbon steel Tool steel	Mold steel	Hardened steel	Stainless steel	Aluminium
Cat.No./Grade	DH103	JC8015	JC8015	DH103	JC8015	FZ05
RDMW****MOT	◎	◎	◎	◎	◎	
RDGT****MOF-AL						◎

• RDMW type : without chip breaker • RD*T type : with chip breaker
 ◎ : First choice ○ : General cutting ● : Unstable cutting ☆ : Light cutting

Recommended Data for Profile Milling



Tool dia. (mm)	Insert dia. (R) (mm)	Effective cutting dia. ϕD_1 (mm)	Min. Bore dia. $D_h \text{ min}$ (mm)	Max. Bore dia. $D_h \text{ max}$ (mm)	Max. ramping angle: θ	Max. depth of cut: a_p (mm)	Max. depth of cut (a_p) Total cutting length: L (mm)	Max. drilling length: Z (mm)	Depth of holder face: X (mm)
15	7 (R3.5)	8	20	28	3°00'	3.5	66.8	0.4	1.0
16	7 (R3.5)	9	22	30	9°00'	3.5	22.1	1.5	2.5
20	7 (R3.5)	13	30	38	5°30'	3.5	36.3	1.5	2.5
22	7 (R3.5)	15	34	42	4°35'	3.5	43.6	1.5	2.5
25	7 (R3.5)	18	40	48	3°40'	3.5	54.6	1.5	2.5
25	10 (R5)	15	34	48	10°45'	5.0	26.3	2.5	3.5
28	10 (R5)	18	40	54	8°20'	5.0	34.1	2.5	3.5
30	10 (R5)	20	44	58	7°15'	5.0	39.3	2.5	3.5
32	10 (R5)	22	48	62	6°25'	5.0	44.4	2.5	3.5
32	12 (R6)	20	44	62	7°35'	6.0	45.1	2.5	3.5
35	10 (R5)	25	54	68	5°30'	5.0	51.9	2.5	3.5
35	12 (R6)	23	50	68	6°15'	6.0	54.7	2.5	3.5
40	12 (R6)	28	60	78	4°55'	6.0	69.7	2.5	3.5
42	10 (R5)	32	68	82	4°05'	5.0	70.0	2.5	3.5
50	12 (R6)	38	80	98	5°15'	6.0	65.2	3.5	4.5
50	16 (R8)	34	75	98	7°25'	8.0	61.4	4.0	5.0
52	12 (R6)	40	84	102	4°55'	6.0	69.7	3.5	4.5
52	16 (R8)	36	79	102	6°55'	8.0	65.9	4.0	5.0
63	12 (R6)	51	106	124	3°45'	6.0	91.5	3.5	4.5
63	16 (R8)	47	101	124	5°00'	8.0	91.4	4.0	5.0
66	12 (R6)	54	112	130	3°30'	6.0	98.1	3.5	4.5
66	16 (R8)	50	107	130	4°40'	8.0	98.0	4.0	5.0
80	12 (R6)	68	140	158	2°45'	6.0	124.9	3.5	4.5
80	16 (R8)	64	135	158	3°30'	8.0	130.7	4.0	5.0
100	16 (R8)	84	175	198	2°35'	8.0	177.3	4.0	5.0
125	16 (R8)	109	225	248	1°55'	8.0	239.1	4.0	5.0
160	16 (R8)	144	295	318	1°25'	8.0	223.5	4.0	5.0

Recommended Cutting Conditions


Material	Grade	Vc	Parameters	Insert Type			
				RD**07	RD**10	RD**12	RD**16
Carbon Steel below 250HB	JC8050 JC5040 JC8118	170 - 220	fz	~0.25	~0.30	~0.35	~0.37
			ap	~1.5	~2.0	~2.5	~4.0
			ae	0.7 Dc	0.7 Dc	0.7 Dc	0.7 Dc
Mold Steel 30-43HRC	JC8050 JC8118 JC8015	160 - 190	fz	~0.25	~0.29	~0.33	~0.34
			ap	~1.5	~2.0	~2.5	~3.5
			ae	0.6 Dc	0.6 Dc	0.6 Dc	0.6 Dc
Tool & Die Steel below 255HB	JC5040 JC8118	160 - 190	fz	~0.25	~0.30	~0.35	~0.37
			ap	~1.5	~2.0	~2.5	~4.0
			ae	0.7 Dc	0.7 Dc	0.7 Dc	0.7 Dc
Stainless Steel	JC8050 JC8015 JC8118	135 - 160	fz	~0.25	~0.26	~0.28	~0.32
			ap	~1.5	~2.0	~2.5	~4.0
			ae	0.6 Dc	0.6 Dc	0.6 Dc	0.6 Dc
Hardened Die Steel 40-50HRC	JC8015 DH103	120 - 140	fz	~0.20	~0.25	~0.25	~0.25
			ap	~0.8	~1.5	~1.5	~2.0
			ae	0.4 Dc	0.4 Dc	0.4 Dc	0.4 Dc
Grey & Nodular Cast Iron	JC8015 JC8118	170 - 220	fz	~0.25	~0.30	~0.35	~0.40
			ap	~1.5	~2.0	~2.5	~4.0
			ae	0.7 Dc	0.7 Dc	0.7 Dc	0.7 Dc
Titanium Alloy	JC8050 JC8015 JC8118	65	fz	~0.25	~0.25	~0.25	~0.25
			ap	~0.5	~0.5	~1.0	~1.5
			ae	0.6 Dc	0.6 Dc	0.6 Dc	0.6 Dc
Heat Resistant Alloy	JC8015 JC8118 JC8050	30	fz	~0.2	~0.2	~0.2	~0.25
			ap	~0.5	~0.5	~1.0	~1.5
			ae	0.6 Dc	0.6 Dc	0.6 Dc	0.6 Dc
Aluminium	FZ05	400 - 800	fz	~0.29	~0.30	~0.30	~0.39
			ap	~2.0	~3.5	~4.0	~5.5
			ae	0.6 Dc	0.6 Dc	0.6 Dc	0.6 Dc

Note


1. Please adjust cutting conditions according to machine rigidity or work rigidity.
2. In case of chatter occurring, recommended to reduce ap or Vf.
3. ap should be reduced when using on low rigidity machine.
4. Use airblow. (For cutting Aluminium, Titanium & Heat resistant alloy Wet cutting is recommended.)
5. When cutting Hard materials (50-55HRC), reduce ap, n & Vf by 30% from standard conditions.

Feature 1 Economical **double-sided** 10-edge Inserts


5 inserts available




PNMU190720AER-**MM**
DS250



PNMU190720AER-**PM**
DP117



PNMU190720AER-**PL**
DP117/DP150




PNMU190720AER-**KM**
DH103

Cat. No.	Grade	Carbon steel	Alloy steel	Pre-hardened steel	Hardened steel	Cast iron	Stainless steel
PNMU190720AER-MM	DS250	○	◎				◎
PNMU190720AER-PM	DP117			○	◎	○	
PNMU190720AER-PL	DP117			◎	○	○	
PNMU190720AER-PL	DP150	◎	○				○
PNMU190720AER-KM	DH103					◎	

◎: First choice ○: Second choice

Feature 2 Equipped with Two Different Entry Angles



45°


Large Depth of Cut

Enables **large depth of cut** and efficient machining on **high-rigidity machines**.

45° ap max=5mm



► Watch the Video



Rigid Insert Clamping

Three-face constraint provides rigidity and stability in heavy cutting.




27°

High-Feed Machining

Enables **high-feed machining** at depths of cut below 2.5 mm.

27° ap ≤ 2.5mm




Helical cutting edge


The large axial rake angle allows for smooth machining.

Feature 3 DP117 / DP150 – New PVD Coating Grades

- Improved coating toughness enhances edge stability and **reduces micro-chipping**.




- Stronger coating-substrate adhesion** improves delamination resistance by approx. 20%, ensuring stable, reliable cutting.



Application

ISO	P					M					K				H				
	P01	P10	P20	P30	P40	M01	M10	M20	M30	M40	K01	K10	K20	K30	H01	H10	H20	H30	
Application Range	NEW DP117											DH103				NEW DP117			
	NEW DP150						NEW	DP150				NEW DP117							
	DS250							DS250											

Feature 4 Two Cutter Body Types Available



Coarse Pitch
($\varnothing 100\text{mm}$ / 6 flutes)



Fine Pitch
($\varnothing 100\text{mm}$ / 9 flutes)

PNS
TYPE

Bore Type




Fig. 1


G-
BodyThrough
coolant
hole

Fig. 2





Fig. 3



Cat.No.		Stock	No. of inserts	Dimensions (mm)									Arbor set bolt	Weight (kg)	Fig.	Insert
				DC	DCX	LF	DCSFMS	DCB	DCCB	KWW	KDP	CBDP				
Coarse Pitch	PNS-3050R-19-22	●	3	50	68.4	50	47	22	17	10.4	6.3	20	M10	0.57	1	PNMU190720AER-**
	PNS-4063R-19-22	●	4	63	81.4	50	50	22	17	10.4	6.3	20	M10	0.81	1	
	PNS-5080R-19-27	●	5	80	98.3	50	56	27	20	12.4	7	22	M12×1.75×30★	1.12	1	
	PNS-6100R-19-32	●	6	100	118.3	50	85	32	26	14.4	8	25	M16×2×30★	2.04	1	
	PNS-7125R-19-40	●	7	125	143.3	63	100	40	32	16.4	9	32	M20×2.5×40★	3.81	1	
	PNS-8160R-19-40	●	8	160	178.4	63	100	40	60	16.4	9	32	M20	4.41	2	
	PNS-10200R-19-60	●	10	200	218.4	63	150	60	140	25.7	14	38	M16	6.68	3	
	PNS-12250R-19-60	●	12	250	268.4	63	150	60	170	25.7	14	38	M16	8.75	3	
Fine Pitch	PNS-4050R-19-22	●	4	50	68.4	50	47	22	17	10.4	6.3	20	M10	0.60	1	
	PNS-5063R-19-22	●	5	63	81.4	50	50	22	17	10.4	6.3	20	M10	0.82	1	
	PNS-7080R-19-27	●	7	80	98.3	50	56	27	20	12.4	7	22	M12×1.75×30★	1.11	1	
	PNS-9100R-19-32	●	9	100	118.3	50	85	32	26	14.4	8	25	M16×2×30★	2.09	1	
	PNS-11125R-19-40	●	11	125	143.3	63	100	40	32	16.4	9	32	M20×2.5×40★	3.85	1	
	PNS-12160R-19-40	●	12	160	178.4	63	100	40	60	16.4	9	32	M20	4.53	2	
	PNS-14200R-19-60	●	14	200	218.4	63	150	60	140	25.7	14	38	M16	6.90	3	
	PNS-16250R-19-60	●	16	250	268.4	63	150	60	170	25.7	14	38	M16	9.10	3	

Screw	Torque(N.m)	Wrench
CSW-513H	5.5	A-20

Insert



PNMU190720AER-MM



PNMU190720AER-PM



PNMU190720AER-PL



PNMU190720AER-KM

Fig. 1






Fig. 2




Cat.No.	Tolerance	PVD Coating				Dimensions (mm)			Fig.
		DS250	DP117	DP150	DH103	RE	IC	S	
PNMU190720AER-MM	M	●				2	19.5	7.5	1
PNMU190720AER-PM	M		●			2	19.5	7.5	1
PNMU190720AER-PL	M		●	●		2	19.5	7.5	2
PNMU190720AER-KM	M				●	2	19.5	7.5	1

GRADE MARKINGS




PNMU190720AER-PL DP117




PNMU190720AER-PL DP150

⚠ Ensure correct insert positioning before mounting



Correct – Recommended



Poor contact – Not acceptable

The indication mark on the cutter body and the corner of the insert must be in the same position when mounting the inserts.

■ Recommended Cutting Conditions | Deep face milling | PNS type ($a_p \leq 5 \text{ mm}$)

Material	Insert	Grade	V_c (m/min)	f_z (mm/t)	a_p (mm)
Carbon Steel below 250HB	PNMU190720AER-PL (PNMU190720AER-MM)	DP150 (DS250)	140 – 180	0.25 – 0.35	4.0 – 5.0
Cast Steel below 285HB	PNMU190720AER-MM (PNMU190720AER-PL)	DS250 (DP150)	120 – 160	0.25 – 0.3	4.0 – 5.0
Tool & Die Steel below 255HB	PNMU190720AER-MM (PNMU190720AER-PL)	DS250 (DP150)	90 – 130	0.2 – 0.25	3.0 – 5.0
Mold Steel 30-36HRC	PNMU190720AER-PL (PNMU190720AER-PM)	DP117 (DP150)	90 – 130	0.25 – 0.3	4.0 – 5.0
Mold Steel 38-43HRC	PNMU190720AER-PL (PNMU190720AER-PM)	DP117	80 – 120	0.2 – 0.25	3.0 – 5.0
Grey Cast Iron 160-260HB	PNMU190720AER-KM (PNMU190720AER-PL) (PNMU190720AER-PM)	DH103 (DP117)	140 – 180	0.35 – 0.4	4.0 – 5.0
Nodular Cast Iron 170-300HB	PNMU190720AER-KM (PNMU190720AER-PL) (PNMU190720AER-PM)	DH103 (DP117)	120 – 160	0.3 – 0.35	3.0 – 5.0
Austenitic Stainless Steel	PNMU190720AER-MM (PNMU190720AER-PL)	DS250 (DP150)	80 – 120	0.2 – 0.25	3.0 – 5.0
Martensitic Stainless Steel	PNMU190720AER-MM (PNMU190720AER-PL)	DS250 (DP150)	90 – 130	0.25 – 0.3	4.0 – 5.0

Note)

1. Please adjust cutting conditions according to machine rigidity or work rigidity.
2. In case of chatter occurring, recommended to reduce a_p or rpm and keep feed per tooth.
3. a_p should be reduced when using on low rigidity machine.
4. Use air blow.

■ Recommended Cutting Conditions | High feed machining | PNS type ($a_p \leq 2.5$ mm)

Material	Insert	Grade	V_c (m/min)	f_z (mm/t)	a_p (mm)
Carbon Steel below 250HB	PNMU190720AER-PL (PNMU190720AER-MM)	DP150 (DS250)	160 – 200	0.6 – 0.7	1.5 – 2.0
Cast Steel below 285HB	PNMU190720AER-MM (PNMU190720AER-PL)	DS250 (DP150)	140 – 180	0.5 – 0.6	1.5 – 2.0
Tool & Die Steel below 255HB	PNMU190720AER-MM (PNMU190720AER-PL)	DS250 (DP150)	110 – 150	0.4 – 0.5	1.0 – 2.0
Mold Steel 30-36HRC	PNMU190720AER-PL (PNMU190720AER-PM)	DP117 (DP150)	110 – 150	0.5 – 0.6	1.5 – 2.0
Mold Steel 38-43HRC	PNMU190720AER-PL (PNMU190720AER-PM)	DP117	100 – 140	0.4 – 0.5	1.0 – 2.0
Hardened Die Steel 42-52HRC	PNMU190720AER-PM (PNMU190720AER-PL)	DP117	30 – 70	0.15 – 0.2	0.5 – 0.8
Grey Cast Iron 160-260HB	PNMU190720AER-KM (PNMU190720AER-PL) (PNMU190720AER-PM)	DH103 (DP117)	170 – 200	0.7 – 0.8	2.0 – 2.5
Nodular Cast Iron 170-300HB	PNMU190720AER-KM (PNMU190720AER-PL) (PNMU190720AER-PM)	DH103 (DP117)	140 – 180	0.5 – 0.6	1.0 – 2.0
Austenitic Stainless Steel	PNMU190720AER-MM (PNMU190720AER-PL)	DS250 (DP150)	120 – 160	0.5 – 0.6	1.0 – 2.0
Martensitic Stainless Steel	PNMU190720AER-MM (PNMU190720AER-PL)	DS250 (DP150)	140 – 180	0.4 – 0.5	1.0 – 2.0

Note)

1. Please adjust cutting conditions according to machine rigidity or work rigidity.
2. In case of chatter occurring, recommended to reduce a_p or rpm and keep feed per tooth.
3. a_p should be reduced when using on low rigidity machine.
4. Use air blow.

HEPTA MILL

HEP Type

HEP
TYPE

High Feed Mill with 7 Cutting-Edge



- Max. Depth of cut 5mm at fz=1mm/tooth is possible.
- Insert with thickness 6.35mm is durable for heavy roughing.
- Heptagonal insert with unique geometry for lower cutting force.
- Multi functional cutter for ramping , pocket milling , plunging.



Fig.1




Fig.2





Fig.3



Cat.No.	Stock	No. of inserts	Dimensions (mm)									Arbor set bolt	Parts		Weight (kg)	Inserts	Fig.
			DC	DCX	LF	DCSFMS	DCB	DCCB	KWW	KDP	CBDB		Screw	Wrench			
HEP-3050R-08-22	●	3	36.7	50	65	47	22	9.6	10.4	6.3	19	M10X1.5X25	DSW-4512H	A-20	0.9	XD**080 ...	1
HEP-4063R-08-22	●	4	49.5	63	50	60	22	17	10.4	6.3	20	M10			1.1		
HEP-4063R-08-27	●	4	49.5	63	50	60	27	20	12.4	7	22	M12X1.75X30			1.1		
HEP-5080R-08-27	●	5	66.6	80	55	76	27	20	12.4	7	22	M12X1.75X40			1.9		
HEP-6100R-08-32	●	6	86.6	100	70	96	32	26	14.4	8	32	M16X2X45			3.6		
HEP-7125R-08-40	●	7	111.6	125	70	100	40	32	16.4	9	35	M20X2.5X45			5.5		
HEP-8160R-08-40	●	8	146.6	160	70	100	40	32	16.4	9	35	M20X2.5X45	A-20L		8.4		2
HEP-9200R-08-60	●	9	186.6	200	65	140	60	140	25.4	14.3	40	M16			10.2		

Screw	Torque(N.m)
DSW-4512H	6

Insert




Fig 1




Fig 3




Fig 2




Fig 4




Fig 5

Cat.No.	Tolerance	PVD Coating							Dimensions(mm)				Fig.
		JC5040	JC7550	JC7560	JC8011	JC8015	JC8050	JC8118	RE	IC	S	AN	
XDMW080620ZTR	M	●		●			●	●	2	17.5	6.35	15°	1
XDMW080635ZTR-S						●			3.5				4
XDMT080620ZER				●			●	●	2	17.341	6.5		2
XDMT080620ZER-ML			●					●					3
XDHW080610ZER-W	H				●				4	17.5	6.35		5

■ Recommended Cutting Conditions


Material	Insert	Grade	General Cutting			Unstable Cutting			ae
			Vc	fz	ap	Vc	fz	ap	
Carbon Steel below 250HB	XDMT080620ZER (XDMW080620ZTR) [XDMW080620ZTR]	JC7560 (JC5040) [JC7560]	140	~0.8	~4	120	~0.8	~4	0.7 Dc
Tool & Die Steel below 255HB	XDMT080620ZER (XDMW080620ZTR) [XDMW080620ZTR]	JC7560 (JC5040) [JC7560]	140	~0.7	~3	120	~0.7	~3	0.7 Dc
Mold Steel 30-36 HRC	XDMT080620ZER (XDMT080620ZER) [XDMW080620ZTR]	JC8118 (JC7560) [JC5040]	140	~0.7	~3	120	~0.7	~3	0.7 Dc
Mold Steel 38-43 HRC	XDMT080620ZER (XDMT080620ZER) [XDMW080620ZTR]	JC8118 (JC8015) [JC8118]	100	~0.7	~3	90	~0.7	~3	0.7 Dc
Hardened Die Steel 42-52 HRC	XDMT080620ZER (XDMT080620ZER) [XDMW080620ZTR]	JC8118 (JC8015) [JC8118]	70	~0.4	~2	70	~0.3	~2	0.4 Dc
Grey Cast Iron	XDMT080620ZTR (XDMT080620ZTR) [XDMW080635ZTR-S]	JC8015 (JC8118) [JC8015]	140	~1.0	~5	120	~1.0	~5	0.7 Dc
Nodular Cast Iron	XDMT080620ZTR (XDMT080620ZTR) [XDMW080635ZTR-S]	JC8015 (JC8118) [JC8015]	120	~0.8	~4	100	~0.7	~4	0.7 Dc
Austenitic Stainless Steel	XDMT080620ZER (XDMT080620ZER) [XDMT080620ZER-ML]	JC8050 (JC7560) [JC7550]	120	~0.5	~4	100	~0.5	~4	0.7 Dc
Titanium Alloy	XDMT080620ZER-ML (XDMT080620ZER) [XDMT080620ZER]	JC7550 JC5040 [JC8118]	60	~0.3	~3	50	~0.2	~3	0.6 Dc
Heat Resistant Alloy	XDMT080620ZER-ML (XDMT080620ZER) [XDMT080620ZER]	JC8118 (JC8118) [JC8015]	30	~0.2	~2	25	~0.2	~2	0.5 Dc

Note

1. Please adjust cutting conditions according to machine rigidity or work rigidity.
2. In case of chatter occurring, recommended to reduce ap or Vf.
3. Use airblow.
4. XDMW080635ZTR-S is recommended to cut cast steel with crusty and nonuniform surface.



High Precision and High Efficient Machining on Aerospace tooling



Through coolant hole

High Precision

Combination of high accuracy body and ground insert gives excellent side wall finish.

High Efficiency

Sharp & Unique 3D geometry insert enables high efficiency and low cutting resistance machining. Key in insert gives added security allowing high speed spindle machining.

Multi function

Capable of ramping and helical interpolation.

AMX/MAM TYPE



- Bore type
Ø40-Ø80
- Modular Head type
Ø16-Ø42

MAX.ap = 8mm

XOET0803..PDFR

grade: FZ05

RE: 0.2-2.0




grade: DS217

RE: 0.4-2.0



grade: DN103

RE: 0.2-2.0



ALX/MAL TYPE



- Bore type
Ø50-Ø63
- Modular Head type
Ø20-Ø40
- Shank type
Ø20-Ø40

MAX.ap = 15mm

XOGT1605..PDFR

grade: FZ05

RE: 0.2-4.0



XOGT1605..PDER

grade: JC5118

RE: 0.2-3.2



AERO CHIPPER

AMX/MAM Type

AMX
TYPE

Bore Type

Through
coolant
holeG-
Body



Shoulder Milling

Slotting

Copy Milling

Pocket Milling

Helical Interpolation



Cat.No.	Stock	No. of inserts	Dimensions(mm)								Max. spindle speed (min ⁻¹)	Weight (kg)	Inserts
			DC	LF	DCSFMS	DCB	DCCB	KWW	KDP	CBDP			
AMX-6040R-16	●	6	40	40	35	16	14	8.4	5.6	18	28,000	0.2	XOET0803**PDFR
AMX-7050R-22	●	7	50	40	45	22	16.5	10.4	6.3	20	24,000	0.3	
AMX-8063R-22	●	8	63	40	50	22	17	10.4	6.3	20	21,000	0.48	
AMX-9080R-22	○	9	80	40	50	22	17	10.4	6.3	20	18,000	0.68	
AMX-9080R-27	●	9	80	50	60	27	20	12.4	7	22	18,000	1.01	

Screw	Torque(N.m)	Wrench
TSW-2567H	1.1	A-08

MAM
TYPE

Modular Type

Through
coolant
hole


Shoulder Milling

Slotting

Copy Milling

Pocket Milling

Helical Interpolation



Cat.No.	Stock	No. of inserts	Dimensions(mm)						Max. spindle speed (min ⁻¹)	Parts	Inserts
			DC	LF	DCSFMS	MD	C	W		Clamp screw	
MAM-2016-M8	●	2	16	23	14	M8	8	12	40,000	TSW-2556H	XOET0803**PDFR
MAM-2018-M8	○	2	18	23	14	M8	8	12	40,000		
MAM-3020-M10	●	3	20	30	18	M10	9	14	40,000		
MAM-3022-M10	○	3	22	30	18	M10	9	14	40,000		
MAM-3025-M12	○	3	25	35	22	M12	11	19	40,000	TSW-2567H	
MAM-4025-M12	●	4	25	35	22	M12	11	19	40,000		
MAM-4028-M12	○	4	28	35	23.6	M12	11	19	36,000		
MAM-4030-M16	○	4	30	43	27	M16	12	22	34,000		
MAM-5032-M16	●	5	32	43	29	M16	12	22	33,000		
MAM-5035-M16	○	5	35	43	32	M16	14	26	31,000		
MAM-6040-M16	●	6	40	43	32	M16	14	26	28,000		
MAM-6042-M16	○	6	42	43	32	M16	14	26	27,000		

Screw	Torque(N.m)	Wrench
TSW-2556H	1.1	A-08
TSW-2567H		



AMX/MAM
TYPE

Insert

FZ05

DS217

DN103



Cat.No.	Tolerance	Uncoated	PVD Coating	DLC Coating	Dimensions (mm)				
		FZ05	DS217	DN103	RE	L	W1	S	C
XOET080302PDFR	E	●		●	0.2	12.5	6.8	3.2	1.5
XOET080304PDFR	E	●		●	0.4	12.5	6.8	3.2	1.7
XOET080304PDER	E		●		0.4	12.5	6.8	3.2	1.5
XOET080308PDFR	E	●		●	0.8	12.5	6.8	3.2	2
XOET080308PDER	E		●		0.8	12.5	6.8	3.2	1.5
XOET080316PDFR	E	●		●	1.6	12.5	6.8	3.2	2.9
XOET080320PDFR	E	●		●	2.0	12.5	6.8	3.2	3
XOET080320PDER	E		●		2.0	12.5	6.8	3.2	2.5

AERO CHIPPER

ALX/MAL Type

ALX
TYPE

Bore Type

Through
coolant
holeG-
Body



Shoulder Milling

Slotting

Copy Milling

Pocket Milling

Helical Interpolation





Cat.No.	Stock	No. of inserts	Dimensions(mm)								Max. spindle speed (min ⁻¹)	Weight (kg)	Inserts
			DC	LF	DCSFMS	DCB	DCCB	KWW	KDP	CDBP			
ALX4050R-22	●	4	50	50	45	22	16.5	10.4	6.3	20	24,000	0.4	XOGT1605**PD*R
ALX5063R-22	●	5	63	50	50	22	16.5	10.4	6.3	20	21,000	0.6	

Screw	Torque (N.m)	Wrench
DSW-4085	3.6	A-15T

MAL
TYPE

Modular Type


Through
coolant
holeG-
Body

Cat.No.	Stock	No. of inserts	Dimensions(mm)						Max. spindle speed (min ⁻¹)	Inserts
			DC	LF	DCSFMS	MD	C	W		
MAL-1020-M10	●	1	20	35	19.5	M10	9	14	15,000	XOGT1605**PD*R
MAL-2025-M12	●	2	25	35	24	M12	11	19	40,000	
MAL-2028-M12	○	2	28	35	24	M12	10	19	36,000	
MAL-2030-M16	○	2	30	43	28	M16	12	22	34,000	
MAL-2032-M16	●	2	32	43	29	M16	12	22	33,000	
MAL-2035-M16	○	2	35	43	29	M16	12	22	31,000	
MAL-3040-M16	●	3	40	43	32	M16	14	26	28,000	

Screw	Torque (N.m)	Wrench
DSW-4085	3.6	A-15


Part to be modified

R2.6



Part to be modified


C2.3



When using inserts with corner radius RE 4 (XOGT160540PDFR), Standard cutter body has to be modified with R2.6 or C2.3

ALXM TYPE

Shank Type




Cat.No.	Stock	No. of inserts	Dimensions(mm)					Max. spindle speed	Parts		Inserts
			DC	LH	LF	DN	DCON		Screw	Wrench	
ALXM1020S20	●	1	20	35	110	19.18	20	15,000	DSW-4075H	A-15	XOGT1605**PD*R
ALXM2025S25	●	2	25	50	125	24	25	40,000	DSW-4085		
ALXM2028S25	●	2	28	50	125	26.87	25	36,000			
ALXM2032S32	●	2	32	50	150	30.5	32	33,000			
ALXM2035S32	○	2	35	50	150	33.32	32	31,000			
ALXM3040S32	●	3	40	80	170	37.96	32	28,000			

Screw	Torque (N.m)
DSW-4075H	3.6
DSW-4085	3.6

ALX/MAL TYPE


Insert




Cat.No.	Tolerance	PVD Coating	Uncoated	Dimensions (mm)				
		JC5118	FZ05	RE	L	W1	S	C
XOGT160502PDFR	G		●	0.2	20.8	16.35	5	2.5
XOGT160504PDFR	G		●	0.4	21.0	16.35	5	2.4
XOGT160508PDFR	G		●	0.8	21.0	16.35	5	2.4
XOGT160512PDFR	G		●	1.2	20.9	16.35	5	2.5
XOGT160516PDFR	G		●	1.6	20.7	16.35	5	2.6
XOGT160520PDFR	G		●	2.0	20.6	16.35	5	2.8
XOGT160525PDFR	G		○	2.5	20.3	16.35	5	3.0
XOGT160530PDFR	G		●	3.0	20.1	16.35	5	3.3
XOGT160532PDFR	G		●	3.2	19.9	16.35	5	3.5
XOGT160540PDFR	G		●	4.0	19.2	16.35	5	4.3
XOGT160502PDER	G	●		0.2	20.8	16.35	5	2.5
XOGT160504PDER	G	●		0.4	21.0	16.35	5	2.4
XOGT160508PDER	G	●		0.8	21.0	16.35	5	2.4
XOGT160512PDER	G	●		1.2	20.9	16.35	5	2.5
XOGT160516PDER	G	●		1.6	20.7	16.35	5	2.6
XOGT160520PDER	G	○		2.0	20.6	16.35	5	2.8
XOGT160530PDER	G	●		3.0	20.1	16.35	5	3.3
XOGT160532PDER	G	○		3.2	19.9	16.35	5	3.5

Recommended Data for Profile Milling

Ramping



Helical interpolation



- Calculation of tool pass dia.

$$\phi D_c = \phi D_h - \phi D_c$$

Tool pass dia. Bore dia. Tool dia.

- Depth of cut per one circuit should not exceed max. depth of cut ap.
- Down cutting is recommended, so tool pass rotation should be counterclockwise.

XOET080302PDFR

Tool dia.	Eff. Cutting dia. (mm)	Max. depth of cut (mm)	Ramping		Helical interpolation			Max. drilling depth
			Max. ramping angle θ°	Total cutting length at Max. ap L	Through hole Min. bore dia. Dh min (mm)	Flat bottom Min. bore dia. Dh min (mm)	Through hole Max. bore dia. Dh max (mm)	
16	15.5	5	18.0	15.4	20	29.5	31	2.5
18	17.5	5	17.5	15.9	24	33.5	35	2.5
20	19.5	5	14.0	20.1	28	37.5	39	2.5
22	21.5	5	12.5	22.6	32	41.5	43	2.5
25	24.5	5	10.0	28.4	38	47.5	49	2.5
28	27.5	5	8.5	33.5	44	53.5	55	2.5
30	29.5	5	7.5	38.0	48	57.5	59	2.5
32	31.5	5	7.0	40.7	52	61.5	63	2.5
35	34.5	5	6.0	47.6	58	67.5	69	2.5
40 (42)	39.5 (41.5)	5	5.0	57.2	68 (72)	77.5 (81.5)	79 (83)	2.5
50	49.5	5	4.0	71.5	88	97.5	99	2.5
63	62.5	5	3.0	95.4	114	123.5	125	2.5
80	79.5	5	2.5	114.5	148	160.0	159	2.5

XOET080304PDFR

Tool dia.	Eff. Cutting dia. (mm)	Max. depth of cut (mm)	Ramping		Helical interpolation			Max. drilling depth
			Max. ramping angle θ°	Total cutting length at Max. ap L	Through hole Min. bore dia. Dh min (mm)	Flat bottom Min. bore dia. Dh min (mm)	Through hole Max. bore dia. Dh max (mm)	
16	15.1	5	18.0	15.4	20	29.0	31	2.5
18	17.1	5	17.5	15.9	24	33.0	35	2.5
20	19.1	5	14.0	20.1	28	37.0	39	2.5
22	21.1	5	12.5	22.6	32	37.0	43	2.5
25	24.1	5	10.0	28.4	38	47.0	49	2.5
28	27.1	5	8.5	33.5	44	53.0	55	2.5
30	29.1	5	7.5	38.0	48	57.0	59	2.5
32	31.1	5	7.0	40.7	52	61.0	63	2.5
35	34.1	5	6.0	47.6	58	67.0	69	2.5
40 (42)	39.1 (41.1)	5	5.0	57.2	68 (72)	77.0 (81.0)	79 (83)	2.5
50	49.1	5	4.0	71.5	88	97.0	99	2.5
63	62.1	5	3.0	95.4	114	123.0	125	2.5
80	79.1	5	2.5	114.5	148	157.5	159	2.5

XOET080308PDR

Tool dia.	Eff. Cutting dia. (mm)	Max.depth of cut (mm)	Ramping		Helical interpolation			Max. drilling depth
			Max. ramping angle θ°	Total cutting length at Max.ap L	Through hole Min. bore dia. Dh min (mm)	Flat bottom Min.bore dia. Dh min (mm)	Through hole Max. bore dia. Dh max (mm)	
16	14.3	5	18.0	15.4	20	28.5	31	2.5
18	16.3	5	17.5	15.9	24	32.5	35	2.5
20	18.3	5	14.0	20.1	28	36.5	39	2.5
22	18.3	5	12.5	22.6	32	36.5	43	2.5
25	23.3	5	10.0	28.4	38	46.5	49	2.5
28	26.3	5	8.5	33.5	44	52.5	55	2.5
30	28.3	5	7.5	38.0	48	56.5	59	2.5
32	30.3	5	7.0	40.7	52	60.5	63	2.5
35	33.3	5	6.0	47.6	58	66.5	69	2.5
40 (42)	38.3 (40.3)	5	5.0	57.2	68 (72)	76.5 (80.5)	79 (83)	2.5
50	48.3	5	4.0	71.5	88	96.5	99	2.5
63	61.3	5	3.0	95.4	114	122.5	125	2.5
80	78.3	5	2.5	114.5	148	156.5	159	2.5

XOET080316PDR

Tool dia.	Eff. Cutting dia. (mm)	Max.depth of cut (mm)	Ramping		Helical interpolation			Max. drilling depth
			Max. ramping angle θ°	Total cutting length at Max.ap L	Through hole Min. bore dia. Dh min (mm)	Flat bottom Min.bore dia. Dh min (mm)	Through hole Max. bore dia. Dh max (mm)	
16	12.7	5	18.0	15.4	20	27.0	31	2.5
18	14.7	5	17.5	15.9	24	31.0	35	2.5
20	16.7	5	14.0	20.1	28	35.0	39	2.5
22	16.7	5	12.5	22.6	32	35.0	43	2.5
25	21.7	5	10.0	28.4	38	45.0	49	2.5
28	24.7	5	8.5	33.5	44	51.0	55	2.5
30	26.7	5	7.5	38.0	48	55.0	59	2.5
32	28.7	5	7.0	40.7	52	59.0	63	2.5
35	31.7	5	6.0	47.6	58	65.0	69	2.5
40 (42)	36.7 (38.7)	5	5.0	57.2	68 (72)	75.0 (79.0)	79 (83)	2.5
50	46.7	5	4.0	71.5	88	94.5	99	2.5
63	59.7	5	3.0	95.4	114	120.5	125	2.5
80	76.7	5	2.5	114.5	148	157.5	159	2.5

XOET080320PDR

Tool dia.	Eff. Cutting dia. (mm)	Max.depth of cut (mm)	Ramping		Helical interpolation			Max. drilling depth
			Max. ramping angle θ°	Total cutting length at Max.ap L	Through hole Min. bore dia. Dh min (mm)	Flat bottom Min.bore dia. Dh min (mm)	Through hole Max. bore dia. Dh max (mm)	
16	11.9	5	18.0	15.4	20	26.5	31	2.5
18	13.9	5	17.5	15.9	24	30.5	35	2.5
20	15.9	5	14.0	20.1	28	34.5	39	2.5
22	15.9	5	12.5	22.6	32	34.5	43	2.5
25	20.9	5	10.0	28.4	38	44.5	49	2.5
28	23.9	5	8.5	33.5	44	50.5	55	2.5
30	25.9	5	7.5	38.0	48	54.5	59	2.5
32	27.9	5	7.0	40.7	52	58.5	63	2.5
35	30.9	5	6.0	47.6	58	64.5	69	2.5
40 (42)	35.9 (37.9)	5	5.0	57.2	68 (72)	74.5 (78.5)	79 (83)	2.5
50	45.9	5	4.0	71.5	88	94.5	99	2.5
63	58.9	5	3.0	95.4	114	120.5	125	2.5
80	75.9	5	2.5	114.5	148	156.5	159	2.5

AERO CHIPPER

AMX/MAM Type

■ Recommended Cutting Conditions | Shoulder Milling

● Bore Type

Material	Grade	Tool dia. (mm)									
		40					50				
		6N					7N				
		ℓ (mm)	a_p (mm)	$a_p \times a_e$ (mm)	n (mm ⁻¹)	V_f (mm/min)	ℓ (mm)	a_p (mm)	$a_p \times a_e$ (mm)	n (mm ⁻¹)	V_f (mm/min)
Aluminium Alloy 50-110HB	FZ05 DN103	100	8	80	6,000	5,400	100	8	100	5,700	5,990
		150	6	42	6,000	5,400	150	8	80	5,700	5,990
		200	5	30	4,800	4,320	200	6	60	4,600	4,830
Austenitic Stainless Steel	DS217	100	6	27	800	480	100	6	30	760	530
		150	5	18	800	480	150	6	24	760	530
		200	4	9	660	400	200	4	16	640	450
Titanium Alloy	DS217	100	6	27	530	250	100	6	30	510	290
		150	5	18	530	250	150	6	24	510	290
		200	4	9	400	190	200	4	16	380	210

Material	Grade	Tool dia. (mm)									
		63					80				
		8N					9N				
		ℓ (mm)	a_p (mm)	$a_p \times a_e$ (mm)	n (mm ⁻¹)	V_f (mm/min)	ℓ (mm)	a_p (mm)	$a_p \times a_e$ (mm)	n (mm ⁻¹)	V_f (mm/min)
Aluminium Alloy 50-110HB	FZ05 DN103	100	8	126	4,500	5,400	100	8	160	3,600	4,860
		150	8	126	4,500	5,400	150	8	160	3,600	4,860
		200	8	96	4,500	5,400	200	8	160	2,900	3,920
Austenitic Stainless Steel	DS217	100	6	36	610	490	100	6	42	480	430
		150	6	36	610	490	150	6	42	480	430
		200	6	27	610	490	200	6	36	480	430
Titanium Alloy	DS217	100	6	36	400	260	100	6	42	320	230
		150	6	36	400	260	150	6	42	320	230
		200	6	27	400	260	200	6	36	320	230

Note) 1. The figure to be adjusted according to the machine rigidity or work rigidity.

2. In case of chatter occurring, recommended to reduce the depth of cut a_p or Spindle speed

3. If machine does not have enough power, recommend to reduce the depth of cut a_p or Spindle speed and Feed speed.

4. Use of water soluble cutting oil is recommended.

Recommended Cutting Conditions | Shoulder Milling

Modular Type + MSN Type carbide shank holder

Material	Grade	Tool dia. (mm)														
		16 / 18					20 / 22					25				
		2N					3N					3N				
		ℓ (mm)	a_p (mm)	$a_p \times a_e$ (mm)	n (mm ⁻¹)	V_f (mm/min)	ℓ (mm)	a_p (mm)	$a_p \times a_e$ (mm)	n (mm ⁻¹)	V_f (mm/min)	ℓ (mm)	a_p (mm)	$a_p \times a_e$ (mm)	n (mm ⁻¹)	V_f (mm/min)
Aluminium Alloy 50-110HB	FZ05 DN103	50	8	32	17,900	5,370	60	8	40	14,300	6,440	75	8	50	11,500	5,180
		80	6	15	17,900	5,370	100	6	18	14,300	6,440	125	6	24	11,500	5,180
		130	4	6	14,300	4,290	160	4	8	11,500	5,180	200	4	10	9,200	4,140
Austenitic Stainless Steel	DS217	50	6	12	2,400	480	60	6	15	1,900	570	75	6	18	1,500	450
		80	5	8	2,400	480	100	5	10	1,900	570	125	5	12	1,500	450
		130	4	4	2,000	400	160	4	5	1,600	480	200	4	6	1,300	390
Titanium Alloy	DS217	50	6	12	1,600	260	60	6	15	1,300	310	75	6	18	1,000	240
		80	5	8	1,600	260	100	5	10	1,300	310	125	5	12	1,000	240
		130	4	4	1,200	190	160	4	5	1,000	240	200	4	6	760	180

Material	Grade	Tool dia. (mm)									
		25 / 28					30				
		4N					4N				
		ℓ (mm)	a_p (mm)	$a_p \times a_e$ (mm)	n (mm ⁻¹)	V_f (mm/min)	ℓ (mm)	a_p (mm)	$a_p \times a_e$ (mm)	n (mm ⁻¹)	V_f (mm/min)
Aluminium Alloy 50-110HB	FZ05 DN103	75	8	50	11,500	6,900	90	8	60	9,500	5,700
		125	6	24	11,500	6,900	150	6	30	9,500	5,700
		200	4	10	9,200	5,520	240	4	12	7,600	4,560
Austenitic Stainless Steel	DS217	75	6	18	1,500	600	90	6	21	1,300	520
		125	5	12	1,500	600	150	5	14	1,300	520
		200	4	6	1,300	520	240	4	7	1,100	440
Titanium Alloy	DS217	75	6	18	1,020	330	90	6	21	850	270
		125	5	12	1,020	330	150	5	14	850	270
		200	4	6	760	240	240	4	7	640	200

Material	Grade	Tool dia. (mm)									
		32 / 35					40 / 42				
		5N					6N				
		ℓ (mm)	a_p (mm)	$a_p \times a_e$ (mm)	n (mm ⁻¹)	V_f (mm/min)	ℓ (mm)	a_p (mm)	$a_p \times a_e$ (mm)	n (mm ⁻¹)	V_f (mm/min)
Aluminium Alloy 50-110HB	FZ05 DN103	100	8	64	9,000	6,750	100	8	80	6,000	5,400
		160	6	30	9,000	6,750	160	6	36	6,000	5,400
		260	4	12	7,200	5,400	260	4	16	4,800	4,320
Austenitic Stainless Steel	DS217	100	6	21	1,200	600	100	6	27	800	480
		160	5	14	1,200	600	160	5	18	800	480
		260	4	7	1,000	500	260	4	9	660	400
Titanium Alloy	DS217	100	6	21	800	320	100	6	27	530	250
		160	5	14	800	320	160	5	18	530	250
		260	4	7	600	240	260	4	9	400	190

Note) 1. The figure to be adjusted according to the machine rigidity or work rigidity.

2. In case of chatter occurring, recommended to reduce the depth of cut a_p or Spindle speed

3. If machine does not have enough power, recommend to reduce the depth of cut a_p or Spindle speed and Feed speed.

4. Use of water soluble cutting oil is recommended.

AERO CHIPPER

AMX/MAM Type

■ Recommended Cutting Conditions | Face Milling

● Bore Type

Material	Grade	Tool dia. (mm)									
		40					50				
		6N					7N				
		ℓ (mm)	ap (mm)	ae (mm)	n (mm ⁻¹)	Vf (mm/min)	ℓ (mm)	ap (mm)	ae (mm)	n (mm ⁻¹)	Vf (mm/min)
Aluminium Alloy 50-110HB	FZ05 DN103	100	5	28	6,000	5,400	100	5	35	5,700	5,990
		150	2.5	28	6,000	5,400	150	3.5	35	5,700	5,990
		200	1.5	28	4,800	4,320	200	2.5	35	4,600	4,830
Austenitic Stainless Steel	DS217	100	2	24	800	380	100	2	30	760	430
		150	1	24	800	380	150	1	30	760	430
		200	1	24	660	320	200	1	30	640	360
Titanium Alloy	DS217	100	2	24	530	190	100	2	30	510	210
		150	1	24	530	190	150	1	30	510	210
		200	1	24	400	140	200	1	30	380	160

Material	Grade	Tool dia. (mm)									
		63					80				
		8N					9N				
		ℓ (mm)	ap (mm)	ae (mm)	n (mm ⁻¹)	Vf (mm/min)	ℓ (mm)	ap (mm)	ae (mm)	n (mm ⁻¹)	Vf (mm/min)
Aluminium Alloy 50-110HB	FZ05 DN103	100	5	44	4,500	5,400	100	5	56	3,600	4,320
		150	5	44	4,500	5,400	150	5	56	3,600	4,320
		200	3	44	4,500	5,400	200	4	56	2,900	4,320
Austenitic Stainless Steel	DS217	100	2	38	610	390	100	2	48	480	310
		150	2	38	610	390	150	2	48	480	310
		200	1	38	610	390	200	2	48	480	310
Titanium Alloy	DS217	100	2	38	400	190	100	2	48	320	150
		150	2	38	400	190	150	2	48	320	150
		200	1	38	400	190	200	2	48	320	150

Note) 1. The figure to be adjusted according to the machine rigidity or work rigidity.

2. In case of chatter occurring, recommended to reduce the depth of cut ap or Spindle speed

3. If machine does not have enough power, recommend to reduce the depth of cut ap or Spindle speed and Feed speed.

4. Use of water soluble cutting oil is recommended.

Recommended Cutting Conditions | Face Milling

Modular Type + MSN Type carbide shank holder

Material	Grade	Tool dia. (mm)														
		16 / 18					20 / 22					25				
		2N					3N					3N				
		ℓ (mm)	a_p (mm)	a_e (mm)	n (mm ⁻¹)	V_f (mm/min)	ℓ (mm)	a_p (mm)	a_e (mm)	n (mm ⁻¹)	V_f (mm/min)	ℓ (mm)	a_p (mm)	a_e (mm)	n (mm ⁻¹)	V_f (mm/min)
Aluminium Alloy 50-110HB	FZ05 DN103	50	5	11	17,900	5,370	60	5	14	14,300	6,440	75	5	17.5	11,500	5,180
		80	2.5	11	17,900	5,370	100	2.5	14	14,300	6,440	125	2.5	17.5	11,500	5,180
		130	1	11	14,300	4,290	160	1	14	11,500	5,180	200	1	17.5	9,200	4,140
Austenitic Stainless Steel	DS217	50	2	10	2,400	380	60	2	12	1,900	460	75	2	15	1,500	360
		80	1	10	2,400	380	100	1	12	1,900	460	125	1	15	1,500	360
		130	1	10	2,000	320	160	1	12	1,600	380	200	1	15	1,300	310
Titanium Alloy	DS217	50	2	10	1,600	190	60	2	12	1,300	230	75	2	15	1,000	180
		80	1	10	1,600	190	100	1	12	1,300	230	125	1	15	1,000	180
		130	1	10	1,200	140	160	1	12	1,000	180	200	1	15	760	140

Material	Grade	Tool dia. (mm)									
		25 / 28					30				
		4N					4N				
		ℓ (mm)	a_p (mm)	a_e (mm)	n (mm ⁻¹)	V_f (mm/min)	ℓ (mm)	a_p (mm)	a_e (mm)	n (mm ⁻¹)	V_f (mm/min)
Aluminium Alloy 50-110HB	FZ05 DN103	75	5	17.5	11,500	6,900	90	5	21	9,500	5,700
		125	2.5	17.5	11,500	6,900	150	2.5	21	9,500	5,700
		200	1	17.5	9,200	5,520	240	1	21	7,600	4,560
Austenitic Stainless Steel	DS217	75	2	15	1,500	480	90	2	18	1,300	420
		125	1	15	1,500	480	150	1	18	1,300	420
		200	1	15	1,300	420	240	1	18	1,100	350
Titanium Alloy	DS217	75	2	15	1,000	240	90	2	18	850	200
		125	1	15	1,000	240	150	1	18	850	200
		200	1	15	760	180	240	1	18	640	150

Material	Grade	Tool dia. (mm)									
		32 / 35					40 / 42				
		5N					6N				
		ℓ (mm)	a_p (mm)	a_e (mm)	n (mm ⁻¹)	V_f (mm/min)	ℓ (mm)	a_p (mm)	a_e (mm)	n (mm ⁻¹)	V_f (mm/min)
Aluminium Alloy 50-110HB	FZ05 DN103	100	5	22.5	9,000	6,750	100	5	28	6,000	5,400
		160	2.5	22.5	9,000	6,750	160	2.5	28	6,000	5,400
		260	1	22.5	7,200	5,400	260	1	28	4,800	4,320
Austenitic Stainless Steel	DS217	100	2	19	1,200	480	100	2	24	800	380
		160	1	19	1,200	480	160	1	24	800	380
		260	1	19	1,000	400	260	1	24	660	320
Titanium Alloy	DS217	100	2	19	800	240	100	2	24	530	190
		160	1	19	800	240	160	1	24	530	190
		260	1	19	600	180	260	1	24	400	140

Note) 1. The figure to be adjusted according to the machine rigidity or work rigidity.


2. In case of chatter occurring, recommended to reduce the depth of cut a_p or Spindle speed

3. If machine does not have enough power, recommend to reduce the depth of cut a_p or Spindle speed and Feed speed.

4. Use of water soluble cutting oil is recommended.

Recommended Data for Profile Milling

Ramping




Tool dia. (mm)	Aluminium		Stainless steel		Titanium alloy		Max. Depth of cut (mm)
	Max. ramping angle (°)	Cutting length (mm)	Max. ramping angle (°)	Cutting length (mm)	Max. ramping angle (°)	Cutting length (mm)	
φDc	θ°	L	θ°	L	θ°	L	ap
20	16	28	10	45	10	45	8
25	11	41	9	51	9	51	8
28	9	51	7	65	7	65	8
30	8	57	6	76	6	76	8
32	7	65	6	76	6	76	8
35	6	76	6	76	6	76	8
40	5	91	5	91	5	91	8
50	4	114	4	114	4	114	8
63	3	153	3	153	3	153	8

Note

1. In case of ramping, apply 70% or less feed (Vf) from standard cutting condition table.
2. When cutting Titanium/Stainless steel, apply 0.005mm or less (fz) from standard cutting condition table.
3. Wet cutting is recommended.

Helical interpolation



- Calculation of tool pass dia.

$$\phi dc = \phi Dh - \phi Dc$$

Tool pass dia. Bore dia. Tool dia.


- Depth of cut per one circuit should not exceed max. depth of cut Ap
- Down cutting is recommended, tool pass rotation should be counterclockwise

Tool dia. (mm)	Min.bore dia. (mm)	Max. Bore dia. (mm)	Max.Depth of cut (mm)		
			Aluminium	Stainless steel	Titanium alloy
φDc	φDh min.	φDh max.			
20	35.8	38.6	15	9	9
25	45.8	48.6	13	11	11
28	51.8	54.6	12	10	10
30	55.8	58.6	11	10	10
32	59.8	62.6	11	10	10
35	65.8	68.6	11	11	11
40	75.8	78.6	10	10	10
50	96.8	98.6	10	10	10
63	122.8	124.6	10	10	10

Note

1. In case of helical interpolation, apply 70% or less feed (Vf) from standard cutting condition table.
2. When cutting Titanium/Stainless steel, apply 0.005mm or less (fz) from standard cutting condition table.
3. Wet cutting is recommended.

Drilling



Coner radius R (mm)	Max. depth of cut: Z (mm)
RE	Z
R2.5 or below	3
R3 / R3.2	2
R4	1.5

Note

1. Do not combine drilling and ramping together.
2. In case of drilling, apply 50% or less feed (Vf) from standard cutting condition table.
3. Long chips may come out in case of drilling, confirm safe operating conditions.

■ Recommended Cutting Conditions | Shoulder Milling

● Bore Type

Material	Grade	Tool dia. (mm)									
		50					63				
		4N					5N				
		ℓ (mm)	a_p (mm)	$a_p \times a_e$ (mm)	n (mm ⁻¹)	V_f (mm/min)	ℓ (mm)	a_p (mm)	$a_p \times a_e$ (mm)	n (mm ⁻¹)	V_f (mm/min)
Aluminium Alloy 50-110 HB	FZ05	100	15	150	5,700	4,560	100	15	225	4,500	4,500
		150	12	96	5,700	4,560	150	12	168	4,500	4,500
		200	9	54	5,700	4,560	200	9	108	4,500	4,500
Stainless Steel Below 250HB	JC5118	100	10	80	640	260	100	10	120	510	260
		150	8	48	640	260	150	8	88	510	260
		200	6	27	640	260	200	6	54	510	260
Titanium Alloy 35-43 HRC	JC5118	100	15	120	380	120	100	15	180	300	120
		150	12	72	380	120	150	12	132	300	120
		200	9	40	380	120	200	9	81	300	120

● Shank Type

Material	Grade	Tool dia. (mm)									
		20					25/28				
		2N					2N				
		ℓ (mm)	a_p (mm)	$a_p \times a_e$ (mm)	n (mm ⁻¹)	V_f (mm/min)	ℓ (mm)	a_p (mm)	$a_p \times a_e$ (mm)	n (mm ⁻¹)	V_f (mm/min)
Aluminium Alloy 50-110 HB	FZ05	35	12	40	14,300	1,430	50	15	75	11,500	4,600
		60	9	25	14,300	1,430	75	12	48	11,500	4,600
Stainless Steel Below 250HB	JC5118	35	2	12	1,590	160	50	10	40	1,270	250
		60	1.2	12	1,590	160	75	8	24	1,270	250
Titanium Alloy 35-43 HRC	JC5118	35	4	12	950	76	50	15	60	760	120
		60	2.5	12	950	76	75	12	36	760	120

Material	Grade	Tool dia. (mm)									
		32/35					40				
		2N					3N				
		ℓ (mm)	a_p (mm)	$a_p \times a_e$ (mm)	n (mm ⁻¹)	V_f (mm/min)	ℓ (mm)	a_p (mm)	$a_p \times a_e$ (mm)	n (mm ⁻¹)	V_f (mm/min)
Aluminium Alloy 50-110 HB	FZ05	50	15	120	9,000	3,600	80	15	125	7,200	4,320
		100	12	60	9,000	3,600	120	12	75	7,200	4,320
Stainless Steel Below 250HB	JC5118	50	10	60	990	200	80	10	65	800	240
		100	8	30	990	200	120	8	40	800	240
Titanium Alloy 35-43 HRC	JC5118	50	15	96	600	96	80	15	100	480	120
		100	12	48	600	96	120	12	60	480	120

Note

1. The figure to be adjusted according to the machine rigidity or work rigidity.
2. In case of chatter occurring, recommended to reduce the depth of cut a_p or Spindle speed
3. If machine does not have enough power, recommend to reduce the depth of cut a_p or Spindle speed and Feed speed.
4. Use of water soluble cutting oil is recommended when machining Aluminium alloy or Titanium alloy.

■ Recommended Cutting Conditions | Shoulder Milling

● Modular Type + MSN Type carbide shank holder

Material	Grade	Tool dia. (mm)									
		20					25/28				
		1N					2N				
		ℓ (mm)	a_p (mm)	$a_p \times a_e$ (mm)	n (mm ⁻¹)	V_f (mm/min)	ℓ (mm)	a_p (mm)	$a_p \times a_e$ (mm)	n (mm ⁻¹)	V_f (mm/min)
Aluminium Alloy 50-110 HB	FZ05	60	12	40	14,300	1,430	75	15	75	11,500	4,600
		100	9	18	14,300	1,430	125	12	36	11,500	4,600
		160	5	8	11,500	1,150	200	6	15	9,200	3,680
Stainless Steel Below 250HB	JC5118	60	8	20	1,590	160	75	10	40	1,270	250
		100	6	10	1,590	160	125	8	20	1,270	250
		160	3	4	1,270	130	200	4	8	1,020	200
Titanium Alloy 35-43 HRC	JC5118	60	12	32	950	76	75	15	60	760	120
		100	9	15	950	76	125	12	30	760	120
		160	5	6	760	61	200	6	12	610	98

Material	Grade	Tool dia. (mm)									
		30/32/35					40				
		2N					3N				
		ℓ (mm)	a_p (mm)	$a_p \times a_e$ (mm)	n (mm ⁻¹)	V_f (mm/min)	ℓ (mm)	a_p (mm)	$a_p \times a_e$ (mm)	n (mm ⁻¹)	V_f (mm/min)
Aluminium Alloy 50-110 HB	FZ05	100	15	96	9,000	3,600	100	15	120	6,000	3,600
		160	12	48	9,000	3,600	160	12	60	6,000	3,600
		260	6	18	7,200	2,880	260	6	24	4,800	2,880
Stainless Steel Below 250HB	JC5118	100	10	50	990	200	100	10	65	660	200
		160	8	24	990	200	160	8	32	660	200
		260	4	10	800	160	260	4	12	530	160
Titanium Alloy 35-43 HRC	JC5118	100	15	75	600	96	100	15	96	400	96
		160	12	36	600	96	160	12	45	400	96
		260	6	15	480	77	260	6	18	320	77

Note

1. The figure to be adjusted according to the machine rigidity or work rigidity.
2. In case of chatter occurring, recommended to reduce the depth of cut a_p or Spindle speed
3. If machine does not have enough power, recommend to reduce the depth of cut a_p or Spindle speed and Feed speed.
4. Use of water soluble cutting oil is recommended when machining Aluminium alloy or Titanium alloy.

Recommended Cutting Conditions | Face Milling

● Bore Type

Material	Grade	Tool dia. (mm)									
		50					63				
		4N					5N				
		ℓ (mm)	a_p (mm)	a_e (mm)	n (mm ⁻¹)	V_f (mm/min)	ℓ (mm)	a_p (mm)	a_e (mm)	n (mm ⁻¹)	V_f (mm/min)
Aluminium Alloy 50-110 HB	FZ05	100	6	35	5,700	4,560	100	7	44	4,500	4,500
		150	4	35	5,700	4,560	150	5	44	4,500	4,500
		200	2	35	5,700	4,560	200	3	44	4,500	4,500
Stainless Steel Below 250HB	JC5118	100	3	30	640	260	100	4	38	510	260
		150	2	30	640	260	150	2.5	38	510	260
		200	1	30	640	260	200	1.5	38	510	260
Titanium Alloy 35-43 HRC	JC5118	100	6	30	380	120	100	7	38	300	120
		150	4	30	380	120	150	5	38	300	120
		200	2	30	380	120	200	3	38	300	120

● Shank Type

Material	Grade	Tool dia. (mm)									
		20					25/28				
		1N					2N				
		ℓ (mm)	a_p (mm)	a_e (mm)	n (mm ⁻¹)	V_f (mm/min)	ℓ (mm)	a_p (mm)	a_e (mm)	n (mm ⁻¹)	V_f (mm/min)
Aluminium Alloy 50-110 HB	FZ05	35	4	14	14,300	1,430	50	6	17.5	11,500	4,600
		60	2.5	14	14,300	1,430	75	4	17.5	11,500	4,600
Stainless Steel Below 250HB	JC5118	35	2	12	1,590	160	50	3	15	1,270	250
		60	1.2	12	1,590	160	75	2	15	1,270	250
Titanium Alloy 35-43 HRC	JC5118	35	4	12	950	76	50	6	15	760	120
		60	2.5	12	950	76	75	4	15	760	120

Material	Grade	Tool dia. (mm)									
		32/35					40				
		2N					3N				
		ℓ (mm)	a_p (mm)	a_e (mm)	n (mm ⁻¹)	V_f (mm/min)	ℓ (mm)	a_p (mm)	a_e (mm)	n (mm ⁻¹)	V_f (mm/min)
Aluminium Alloy 50-110 HB	FZ05	50	7	22.5	9,000	3,600	80	6	28	7,200	4,320
		100	4	22.5	9,000	3,600	120	4	28	7,200	4,320
Stainless Steel Below 250HB	JC5118	50	4	19	990	200	80	3	24	800	240
		100	2	19	990	200	120	2	24	800	240
Titanium Alloy 35-43 HRC	JC5118	50	7	19	600	96	80	6	24	480	120
		100	4	19	600	96	120	4	24	480	120

Note

1. The figure to be adjusted according to the machine rigidity or work rigidity.
2. In case of chatter occurring, recommended to reduce the depth of cut a_p or Spindle speed
3. If machine does not have enough power, recommend to reduce the depth of cut a_p or Spindle speed and Feed speed.
4. Use of water soluble cutting oil is recommended when machining Aluminium alloy or Titanium alloy.

■ Recommended Cutting Conditions | Face Milling

● Modular Type + MSN Type carbide shank holder

Material	Grade	Tool dia. (mm)									
		20					25/28				
		1N					2N				
		ℓ (mm)	a_p (mm)	a_e (mm)	n (mm ⁻¹)	V_f (mm/min)	ℓ (mm)	a_p (mm)	a_e (mm)	n (mm ⁻¹)	V_f (mm/min)
Aluminium Alloy 50-110 HB	FZ05	60	4	14	14,300	1,430	75	6	17.5	11,500	4,600
		100	2	14	14,300	1,430	125	3	17.5	11,500	4,600
		160	0.8	14	11,500	1,150	200	1.2	17.5	9,200	3,680
Stainless Steel Below 250HB	JC5118	60	2	12	1,590	160	75	3	15	1,270	250
		100	1	12	1,590	160	125	1.5	15	1,270	250
		160	0.5	12	1,270	130	200	0.6	15	1,020	200
Titanium Alloy 35-43 HRC	JC5118	60	4	12	950	76	75	6	15	760	120
		100	2	12	950	76	125	3	15	760	120
		160	0.8	12	760	61	200	1.2	15	610	98

Material	Grade	Tool dia. (mm)									
		30/32/35					40				
		2N					3N				
		ℓ (mm)	a_p (mm)	a_e (mm)	n (mm ⁻¹)	V_f (mm/min)	ℓ (mm)	a_p (mm)	a_e (mm)	n (mm ⁻¹)	V_f (mm/min)
Aluminium Alloy 50-110 HB	FZ05	100	6	22.5	9,000	3,600	100	6	28	6,000	3,600
		160	3	22.5	9,000	3,600	160	3	28	6,000	3,600
		260	1.2	22.5	7,200	2,880	260	1.2	28	4,800	2,880
Stainless Steel Below 250HB	JC5118	100	3	19	990	200	100	3	24	660	200
		160	1.5	19	990	200	160	1.5	24	660	200
		260	0.6	19	800	160	260	0.6	24	530	160
Titanium Alloy 35-43 HRC	JC5118	100	6	19	600	96	100	6	24	400	96
		160	3	19	600	96	160	3	24	400	96
		260	1.2	19	480	77	260	1.2	24	320	77

Note


1. The figure to be adjusted according to the machine rigidity or work rigidity.
2. In case of chatter occurring, recommended to reduce the depth of cut a_p or Spindle speed
3. If machine does not have enough power, recommend to reduce the depth of cut a_p or Spindle speed and Feed speed.
4. Use of water soluble cutting oil is recommended when machining Aluminium alloy or Titanium alloy.

Carbide Modular Head Holder

MSN Type

MSN
TYPE

Solid Monoblock Carbide Body

Through
coolant
hole

Cat.No.	Stock	Dimensions(mm)						Weight (kg)
		ØDs	ℓ1	L	ØD1	MD	ØD2	
MSN-M6-12-S10C	●	10	12	60	9.7	M6	3	0.06
MSN-M6-30-S10C	●	10	30	80	9.7	M6	3	0.07
MSN-M6-50-S10C	●	10	50	100	9.7	M6	3	0.09
MSN-M6-80-S10C	●	10	80	130	9.7	M6	3	0.12
MSN-M6-120-S10C	●	10	120	170	9.7	M6	3	0.16
MSN-M6-170-S10C ※	●	10	170	220	9.7	M6	3	0.20
MSN-M6-15-S12C	●	12	15	60	11.5	M6	3	0.08
MSN-M6-30-S12C	●	12	30	80	11.5	M6	3	0.11
MSN-M6-50-S12C	●	12	50	100	11.5	M6	3	0.13
MSN-M6-80-S12C	●	12	80	130	11.5	M6	3	0.18
MSN-M6-120-S12C	●	12	120	170	11.5	M6	3	0.23
MSN-M6-170-S12C ※	●	12	170	220	11.5	M6	3	0.30
MSN-M6-30-S16C	●	16	30	80	13.5	M6	3	0.19
MSN-M6-50-S16C	○	16	50	100	13.5	M6	3	0.23
MSN-M6-80-S16C	●	16	80	130	13.5	M6	3	0.28
MSN-M8-20-S16C	●	16	20	75	15.5	M8	4	0.17
MSN-M8-40-S16C	●	16	40	95	15.5	M8	4	0.22
MSN-M8-60-S16C	●	16	60	115	15.5	M8	4	0.28
MSN-M8-80-S16C	●	16	80	135	15.5	M8	4	0.32
MSN-M8-120-S16C	●	16	120	175	15.5	M8	4	0.42
MSN-M8-152-S16C	●	16	152	207	15.5	M8	4	0.51
MSN-M10-20-S20C	●	20	20	80	19.5	M10	4	0.29
MSN-M10-40-S20C	●	20	40	100	19.5	M10	4	0.39
MSN-M10-70-S20C	●	20	70	130	19.5	M10	4	0.50
MSN-M10-90-S20C	●	20	90	150	19.5	M10	4	0.60
MSN-M10-140-S20C	●	20	140	200	19.5	M10	4	0.80
MSN-M10-160-S20C	●	20	160	220	19.5	M10	4	0.87
MSN-M10-210-S20C	●	20	210	270	19.5	M10	4	1.07

※ "MSN-M6-170-S10C" and "MSN-M6-170-S12C" are for high-feed cutting only.




Cat.No.	Stock	Dimensions(mm)						Weight (kg)
		øDs	ℓ1	L	øD1	MD	øD2	
MSN-M12-25-S25C	●	25	25	90	24	M12	6	0.53
MSN-M12-55-S25C	●	25	55	120	24	M12	6	0.72
MSN-M12-70-S25C	●	25	70	135	24	M12	6	0.81
MSN-M12-105-S25C	●	25	105	170	24	M12	6	1.03
MSN-M12-135-S25C	●	25	135	215	24	M12	6	1.30
MSN-M12-155-S25C	●	25	155	220	24	M12	6	1.34
MSN-M12-200-S25C	●	25	200	265	24	M12	6	1.58
MSN-M12-255-S25C	●	25	255	320	24	M12	6	1.91
MSN-M16-25-S32C	●	32	25	90	29	M16	8	0.85
MSN-M16-55-S32C	●	32	55	120	29	M16	8	1.13
MSN-M16-77-S32C	●	32	77	157	29	M16	8	1.47
MSN-M16-97-S32C	●	32	97	177	29	M16	8	1.64
MSN-M16-105-S32C	●	32	105	170	29	M16	8	1.59
MSN-M16-127-S32C	●	32	127	207	29	M16	8	1.89
MSN-M16-155-S32C	●	32	155	220	29	M16	8	2.04
MSN-M16-177-S32C	●	32	177	257	29	M16	8	2.32
MSN-M16-195-S32C	●	32	195	260	29	M16	8	2.40
MSN-M16-225-S32C	●	32	225	290	29	M16	8	2.57
MSN-M16-245-S32C	●	32	245	310	29	M16	8	2.74
MSN-M16-295-S32C	●	32	295	360	29	M16	8	3.17
MSN-M16-315-S32C	●	32	315	380	29	M16	8	3.34

Carbide Modular Head Holder

MSN Type

MSN-S
TYPE

Solid Monoblock Carbide Body



Cat.No.	Stock	Dimensions(mm)				Weight (kg)
		ØDs	L	MD	ØD2	
MSN-M6-67S-S9.8C	●	9.8	67	M6	3	0.06
MSN-M6-107S-S9.8C	●	9.8	107	M6	3	0.10
MSN-M6-82S-S10C	●	10	82	M6	3	0.08
MSN-M6-122S-S10C	●	10	122	M6	3	0.12
MSN-M6-167S-S10C	●	10	167	M6	3	0.16
MSN-M6-220S-S10C ※	●	10	220	M6	3	0.21
MSN-M6-80S-S11.8C	●	11.8	80	M6	3	0.11
MSN-M6-120S-S11.8C	●	11.8	120	M6	3	0.17
MSN-M6-90S-S12C	●	12	90	M6	3	0.13
MSN-M6-130S-S12C	●	12	130	M6	3	0.19
MSN-M6-170S-S12C	●	12	170	M6	3	0.25
MSN-M6-220S-S12C ※	●	12	220	M6	3	0.32
MSN-M8-87S-S14C	○	14	87	M8	4	0.16
MSN-M8-137S-S14C	●	14	137	M8	4	0.26
MSN-M8-97S-S15C	●	15	97	M8	4	0.21
MSN-M8-147S-S15C	●	15	147	M8	4	0.33
MSN-M8-197S-S15C	●	15	197	M8	4	0.44
MSN-M8-217S-S15C	●	15	217	M8	4	0.49
MSN-M8-107S-S16C	●	16	107	M8	4	0.27
MSN-M8-157S-S16C	●	16	157	M8	4	0.40
MSN-M8-220S-S16C	●	16	220	M8	4	0.57
MSN-M10-130S-S18C	●	18	130	M10	4	0.42
MSN-M10-190S-S18C	●	18	190	M10	4	0.62
MSN-M10-240S-S18C	●	18	240	M10	4	0.89
MSN-M10-270S-S18C	●	18	270	M10	4	0.90
MSN-M10-130S-S20C	●	20	130	M10	4	0.53
MSN-M10-190S-S20C	●	20	190	M10	4	0.78
MSN-M10-250S-S20C	●	20	250	M10	4	1.02
MSN-M10-270S-S20C	●	20	270	M10	4	1.13

※ "MSN-M6-220S-S10C" and "MSN-M6-220S-S12C" are for high-feed cutting only.




Cat.No.	Stock	Dimensions(mm)				Weight (kg)
		∅Ds	L	MD	∅D2	
MSN-M12-145S-S23C	○	23	145	M12	6	0.76
MSN-M12-185S-S23C	●	23	185	M12	6	0.98
MSN-M12-265S-S23C	●	23	265	M12	6	1.42
MSN-M12-185S-S24C	●	24	185	M12	6	1.07
MSN-M12-265S-S24C	●	24	265	M12	6	1.54
MSN-M12-320S-S24C	●	24	320	M12	6	1.85
MSN-M12-145S-S25C	●	25	145	M12	6	0.91
MSN-M12-215S-S25C	●	25	215	M12	6	1.36
MSN-M12-285S-S25C	●	25	285	M12	6	1.80
MSN-M12-320S-S25C	●	25	320	M12	6	2.06
MSN-M16-160S-S28C	●	28	160	M16	8	1.22
MSN-M16-230S-S28C	●	28	230	M16	8	1.77
MSN-M16-310S-S28C	●	28	310	M16	8	2.41
MSN-M16-157S-S32C	●	32	157	M16	8	1.61
MSN-M16-217S-S32C	●	32	217	M16	8	2.22
MSN-M16-287S-S32C	●	32	287	M16	8	2.94
MSN-M16-357S-S32C	●	32	357	M16	8	3.66
MSN-M16-380S-S32C	●	32	380	M16	8	3.98

Carbide Modular Head Holder


MSN Type

Through
coolant
holeMSN-T
TYPE


Solid Monoblock Carbide Body



Cat.No.	Stock	Dimensions(mm)							Weight (kg)
		ØDs	ℓ1	L	ØD1	θ°	MD	ØD2	
MSN-M6-35T-S12C	○	12	35	92	9.5	1°30'	M6	3	0.12
MSN-M6-57T-S12C	●	12	57	114	9.5	1°	M6	3	0.14
MSN-M6-65T-S16C	●	16	65	125	11.2	1°45'	M6	3	0.28
MSN-M8-40T-S20C	○	20	40	100	14.5	3°30'	M8	4	0.36
MSN-M8-77T-S20C	●	20	77	143	14.5	1°45'	M8	4	0.49
MSN-M8-90T-S25C	○	25	90	165	14.5	2°	M8	4	0.81
MSN-M10-40T-S20C	●	20	40	100	18.5	0°43'	M10	4	0.39
MSN-M10-90T-S20C	●	20	90	150	18.5	0°19'	M10	4	0.58
MSN-M10-140T-S20C	●	20	140	200	18.5	0°12'	M10	4	0.77
MSN-M10-115T-S32C	○	32	115	195	18.5	2°	M10	4	1.54
MSN-M12-100T-S32C	○	32	100	180	23.5	2°	M12	6	1.61
MSN-M16-117T-S32C	○	32	117	197	29	0°38'	M16	8	1.88
MSN-M16-127T-S32C	○	32	127	207	29	0°30'	M16	8	2.23
MSN-M16-177T-S32C	●	32	177	257	29	0°23'	M16	8	2.78
MSN-M16-197T-S32C	○	32	197	277	29	0°23'	M16	8	3.00






- 180° Flat face
- Able to drill without pilot hole, even on sloped surfaces & cross holes



■ Features

- 1 Easy tool management
- 2 Able to drill without pilot hole, even on sloped surfaces and cross holes.
- 3 Long tool life by adopting new grade JC7550 and improved coolant distribution system.
- 4 The most suitable for burr-less processing.

■ Applications



INDEXABLE FLAT DRILL

TLZD Type



TLZD
TYPE

Holder

● Depth of hole: $1.5 \times D_c$ Through
coolant
holeJC7500
Coating

Spot Facing

Drilling

 $DC \leq \phi 30$  $DC > \phi 30$ 

Cat.No.	Stock	DC		Dimensions (mm)					Parts	
		Min.	Max.	LU	LH	LS	OAL	DCON	Screw	Wrench
TLZD1400S16-SS	●	14.0	14.5	29	43	48	91	16	DSW-2045H	A-07
TLZD1500S20-SS	●	14.6	15.5	31	46	50	96	20		
TLZD1600S20-SS	●	15.6	16.5	33	49	50	99	20	TSW-2556H	A-08
TLZD1700S20-SS	●	16.6	17.5	35	52	50	102	20		
TLZD1800S20-SS	●	17.6	18.5	37	55	50	105	20	TSW-2567H	A-08
TLZD1900S25-SS	●	18.6	19.5	39	58	56	114	25		
TLZD2000S25-SS	●	19.6	20.5	41	61	56	117	25	DSW-307H	A-10
TLZD2100S25-SS	●	21.0	21.5	43	64	56	120	25		
TLZD2200S25-SS	●	22.0	22.5	45	67	56	123	25	DSW-309H	A-10
TLZD2300S25-SS	●	23.0	23.5	47	70	56	126	25		
TLZD2400S32-SS	●	24.0	24.5	49	73	60	133	32	TSW-3510H	A-15
TLZD2500S32-SS	●	25.0	25.5	51	76	60	136	32		
TLZD2600S32-SS	●	26.0	26.5	53	79	60	139	32	TSW-3512H	A-15
TLZD2700S32-SS	●	27.0	27.5	55	82	60	142	32		
TLZD2800S32-SS	●	28.0	28.5	57	85	60	145	32	TSW-3512H	A-15
TLZD2900S32-SS	●	29.0	29.5	59	88	60	148	32		
TLZD3000S32-SS	●	30.0	30.5	61	91	60	151	32	TSW-3512H	A-15
TLZD3100S32-SS	●	31.0	31.5	-	94	60	154	32		
TLZD3200S32-SS	●	32.0	-	-	97	60	157	32		


TLZD
TYPE**Modular Type**

● Depth of hole 0.7~1×Dc

Through
coolant
holeJC7500
Coating

Spot Facing

Drilling



Cat.No.	Stock	DC		Dimensions (mm)					Parts		MSN Carbide Shank
		Min.	Max.	LF	DCSFMS	MD	C	W	Screw	Wrench	
TLZD1400-M6	●	14.0	14.5	27.5	13.1	M6	7	10	DSW-2045H	A-07	MSN-M6-**-S16C
TLZD1500-M8	●	14.6	15.5	29.5	14	M8	8	12			MSN-M8-**-S14C
TLZD1600-M8	●	15.6	16.5	29.5	15	M8	8	12	TSW-2556H	A-08	MSN-M8-**-S15C
TLZD1700-M8	●	16.6	17.5	30.5	16	M8	8	12			MSN-M8-**-S16C
TLZD1800-M8	●	17.6	18.5	30.5	17	M8	8	12			MSN-M8-**-S16C
TLZD1900-M10	●	18.6	19.5	38.5	18	M10	9	14	TSW-2567H	A-08	MSN-M10-**-S18C
TLZD2000-M10	●	19.6	20.5	38.5	19	M10	9	14			MSN-M10-**-S20C
TLZD2100-M10	●	21.0	21.5	38.5	20	M10	9	14			MSN-M10-**-S20C
TLZD2200-M10	●	22.0	22.5	38.5	21	M10	9	14	DSW-307H	A-10	MSN-M10-**-S20C
TLZD2300-M10	●	23.0	23.5	38.5	22	M10	9	14			MSN-M10-**-S20C
TLZD2400-M12	●	24.0	24.5	43	23	M12	11	19			MSN-M12-**-S23C
TLZD2500-M12	●	25.0	25.5	43	24	M12	11	19	DSW-309H	A-10	MSN-M12-**-S25C
TLZD2600-M12	●	26.0	26.5	43	25	M12	11	19			MSN-M12-**-S25C
TLZD2700-M12	●	27.0	27.5	43	26	M12	11	19			MSN-M12-**-S25C
TLZD2800-M12	●	28.0	28.5	43	27	M12	11	19	TSW-3510H	A-15	MSN-M12-**-S25C
TLZD2900-M16	●	29.0	29.5	51	28	M16	12	22			MSN-M16-**-S28C
TLZD3000-M16	●	30.0	30.5	51	29	M16	12	22			MSN-M16-**-S32C
TLZD3100-M16	●	31.0	31.5	51	30	M16	12	22	TSW-3512H	A-15	MSN-M16-**-S32C
TLZD3200-M16	●	32.0	-	51	31	M16	14	26			MSN-M16-**-S32C



Screw	Torque (N.m)
DSW-2045H	0.9
TSW-2556H	1.2
TSW-2567H	1.2
DSW-307H	2.1
DSW-309H	2.1
TSW-3510H	3.0
TSW-3512H	3.0

INDEXABLE FLAT DRILL

TLZD Type

TLZ
TYPE

Insert - Grade JC7550



DC	Cat.No.	Stk	A	S	Holder
14.0	TLZ1400	●	10.6	4.5	TLZD14*
14.1	TLZ1410	●			
14.2	TLZ1420	●			
14.3	TLZ1430	●			
14.4	TLZ1440	●			
14.5	TLZ1450	●			
14.6	TLZ1460	●	11.3	4.8	TLZD15*
14.7	TLZ1470	●			
14.8	TLZ1480	●			
14.9	TLZ1490	●			
15.0	TLZ1500	●			
15.1	TLZ1510	●			
15.2	TLZ1520	●			
15.3	TLZ1530	●			
15.4	TLZ1540	●			
15.5	TLZ1550	●	12.1	5.0	TLZD16*
15.6	TLZ1560	●			
15.7	TLZ1570	●			
15.8	TLZ1580	●			
15.9	TLZ1590	●			
16.0	TLZ1600	●			
16.1	TLZ1610	●			
16.2	TLZ1620	●			
16.3	TLZ1630	●			
16.4	TLZ1640	●			
16.5	TLZ1650	●	12.6	5.5	TLZD17*
16.6	TLZ1660	●			
16.7	TLZ1670	●			
16.8	TLZ1680	●			
16.9	TLZ1690	●			
17.0	TLZ1700	●			
17.1	TLZ1710	●			
17.2	TLZ1720	●			
17.3	TLZ1730	●			
17.4	TLZ1740	●			
17.5	TLZ1750	●			
17.6	TLZ1760	●	13.2	5.8	TLZD18*
17.7	TLZ1770	●			
17.8	TLZ1780	●			
17.9	TLZ1790	●			
18.0	TLZ1800	●			
18.1	TLZ1810	●			
18.2	TLZ1820	●			

DC	Cat.No.	Stk	A	S	Holder
18.3	TLZ1830	●	13.2	5.8	TLZD18*
18.4	TLZ1840	●			
18.5	TLZ1850	●			
18.6	TLZ1860	●	13.6	6.0	TLZD19*
18.7	TLZ1870	●			
18.8	TLZ1880	●			
18.9	TLZ1890	●			
19.0	TLZ1900	●			
19.1	TLZ1910	●			
19.2	TLZ1920	●			
19.3	TLZ1930	●			
19.4	TLZ1940	●			
19.5	TLZ1950	●			
19.6	TLZ1960	●	14.6	6.5	TLZD20*
19.7	TLZ1970	●			
19.8	TLZ1980	●			
19.9	TLZ1990	●			
20.0	TLZ2000	●			
20.5	TLZ2050	●			
21.0	TLZ2100	●	15.2	6.7	TLZD21*
21.5	TLZ2150	●			
22.0	TLZ2200	●	15.9	7.5	TLZD22*
22.5	TLZ2250	●			
23.0	TLZ2300	●	16.7	7.5	TLZD23*
23.5	TLZ2350	●			
24.0	TLZ2400	●	17.4	8.0	TLZD24*
24.5	TLZ2450	●			
25.0	TLZ2500	●	18.3	8.0	TLZD25*
25.5	TLZ2550	●			
26.0	TLZ2600	●	18.8	8.5	TLZD26*
26.5	TLZ2650	●			
27.0	TLZ2700	●	19.5	8.5	TLZD27*
27.5	TLZ2750	●			
28.0	TLZ2800	●	20.3	9.0	TLZD28*
28.5	TLZ2850	●			
29.0	TLZ2900	●	21.1	9.0	TLZD29*
29.5	TLZ2950	●			
30.0	TLZ3000	●	21.5	9.5	TLZD30*
30.5	TLZ3050	●			
31.0	TLZ3100	●	22.3	10.0	TLZD31*
31.5	TLZ3150	●			
32.0	TLZ3200	●	23.1	10.0	TLZD32*

■ Recommended Cutting Conditions

● TLZD-SS type

Material	Mild Steel below 180HB	Carbon Steel below 280HB	Tool Steel below 255HB	Alloy Steel 280-350HB
Vc (m/min)	50 - 70 - 100	50 - 70 - 100	30 - 50 - 70	30 - 50 - 70
f (mm/rev)	0.06 - 0.20 (Dc14-16) 0.07 - 0.21 (Dc17-20) 0.08 - 0.22 (Dc21-25) 0.09 - 0.23 (Dc26-29) 0.10 - 0.24 (Dc30-32)	0.06 - 0.20 (Dc14-16) 0.07 - 0.21 (Dc17-20) 0.08 - 0.22 (Dc21-25) 0.09 - 0.23 (Dc26-29) 0.10 - 0.24 (Dc30-32)	0.06 - 0.20 (Dc14-16) 0.07 - 0.21 (Dc17-20) 0.08 - 0.22 (Dc21-25) 0.09 - 0.23 (Dc26-29) 0.10 - 0.24 (Dc30-32)	0.06 - 0.20 (Dc14-16) 0.07 - 0.21 (Dc17-20) 0.08 - 0.22 (Dc21-25) 0.09 - 0.23 (Dc26-29) 0.10 - 0.24 (Dc30-32)

Material	Mold Steel below 40HRC	Cast Iron	Stainless Steel	Aluminium Alloy
Vc (m/min)	20 - 30 - 40	50 - 70 - 100	80 - 100 - 120 - 140	50 - 100 - 150
f (mm/rev)	0.04 - 0.10 (Dc14-16) 0.04 - 0.11 (Dc17-18) 0.05 - 0.11 (Dc19-20) 0.05 - 0.12 (Dc21-25) 0.05 - 0.13 (Dc26-27) 0.06 - 0.13 (Dc28-29) 0.06 - 0.14 (Dc30-32)	0.06 - 0.20 (Dc14-16) 0.07 - 0.21 (Dc17-20) 0.08 - 0.22 (Dc21-25) 0.09 - 0.23 (Dc26-29) 0.10 - 0.24 (Dc30-32)	0.02 - 0.06 (Dc14-18) 0.03 - 0.07 (Dc19-25) 0.04 - 0.08 (Dc26-31) 0.05 - 0.09 (Dc32)	0.06 - 0.20 (Dc14-16) 0.07 - 0.21 (Dc17-20) 0.08 - 0.22 (Dc21-25) 0.09 - 0.23 (Dc26-29) 0.10 - 0.24 (Dc30-32)

Note

1. These cutting conditions are for drilling flat surface. when drilling angled surfaces, parameters should be adjusted.
For inclined angle under 30°, apply 40-80% of (Vf) and for inclined angle 30° or more , apply 20-50% of (Vf) from standard cutting conditions.
2. These cutting conditions are for drilling with water soluble coolant. when dry cutting , use air to remove chips.
3. Drilling depth over 1.5 x Dc is not recommended.
4. Side milling is not possible.
5. In case of long chips , adjust parameters by increasing (Vf) or using step feed for breaking chips.

■ Recommended Cutting Conditions

● TLZD-***-M** Modular Head type

Material	Mild Steel below 180HB	Carbon Steel below 280HB	Tool Steel below 255HB	Alloy Steel 280-350HB
Vc (m/min)	70	70	70	70
f (mm/rev)	0.04 - 0.06 (Dc14) 0.04 - 0.08 (Dc15-18) 0.04 - 0.09 (Dc19-23) 0.06 - 0.12 (Dc24-28) 0.06 - 0.14 (Dc29-32)	0.04 - 0.06 (Dc14) 0.04 - 0.08 (Dc15-18) 0.04 - 0.09 (Dc19-23) 0.06 - 0.12 (Dc24-28) 0.06 - 0.14 (Dc29-32)	0.03 - 0.05 (Dc14) 0.03 - 0.06 (Dc15-18) 0.04 - 0.07 (Dc19-23) 0.05 - 0.09 (Dc24-28) 0.06 - 0.11 (Dc29-32)	0.03 - 0.05 (Dc14) 0.03 - 0.06 (Dc15-18) 0.04 - 0.07 (Dc19-23) 0.05 - 0.09 (Dc24-28) 0.06 - 0.11 (Dc29-32)

Material	Mold Steel below 40HRC	Cast Iron	Stainless Steel	Aluminium Alloy
Vc (m/min)	40	100	100	100
f (mm/rev)	0.02 - 0.06 (Dc14) 0.03 - 0.07 (Dc15-18) 0.03 - 0.08 (Dc19-23) 0.04 - 0.10 (Dc24-28) 0.05 - 0.13 (Dc29-32)	0.02 - 0.07 (Dc14) 0.04 - 0.09 (Dc15-18) 0.02 - 0.10 (Dc19-23) 0.02 - 0.12 (Dc24-28) 0.02 - 0.13 (Dc29-32)	0.02 - 0.04 (Dc14-23) 0.03 - 0.04 (Dc24-32)	0.02 - 0.07 (Dc14) 0.04 - 0.09 (Dc15-18) 0.02 - 0.10 (Dc19-23) 0.02 - 0.12 (Dc24-28) 0.02 - 0.13 (Dc29-32)

Note

1. These cutting conditions are for drilling flat surface. when drilling angled surfaces, parameters should be adjusted.
for inclined angle under 30°, apply 40-80% of (Vf) and for inclined angle 30° or more , apply 20-50% of (Vf) from standard cutting conditions.
2. These cutting conditions are for drilling with water soluble coolant. when dry cutting , use air to remove chips.
3. Drilling depth over 1.0 x Dc is not recommended.
4. Side milling is not possible.
5. In case of long chips , adjust parameters by increasing (Vf) or using step feed for breaking chips.
when drilling stainless steel, increasing (Vf) is not recommended to break chips. Increase (Vc) and reduce (Vf) so that bellows-shaped chips can occur.

PROCEDURE FOR MOUNTING INSERT

1. Removing used insert

Make sure to remove any chips or dust off the tip before removing the used insert. Remove used insert and clean pocket using a brush or air blowing before loading new insert.

2. Loading new insert

Place new insert in pocket, lightly tighten two screws while pressing the top of the insert (see photo). After confirming there is no gap between the drill and insert, tighten the insert screw, starting with the same screw you first lightly tightened, to the recommended torque while still pressing the top of the insert.



"MOLY"
(Sold separately)


 Note:

Clamp screw needs to be changed out after replacing the insert approximately 10 times or if you see any issues with the screws.



Clamp screw

■ HOLE BOTTOM SHAPE



Tool dia. (mm)	Remains (mm)
$\phi 14 \sim \phi 20.5$	0.04~0.06
$\phi 21 \sim \phi 26.5$	0.05~0.07
$\phi 27 \sim \phi 32.0$	0.06~0.08

Feature 1 Drill Body Variations

L/D=3
 $\Phi 13.5 - 32.5$



L/D=5
 $\Phi 13.5 - 32.5$



L/D=8
 $\Phi 13.5 - 32.5$



NEW L/D=12
 $\Phi 13.5 - 22.5$




Modular Head
L/D=2D
 $\Phi 13.5 - 32.5$



carbide modular head holder MSN type

TEZD-M (Modular head) type

The combination of a modular head and a carbide shank holder enables stable drilling even with a long overhang.

**TEZDF type**

A high-rigidity flanged shank body enables stable and accurate hole making.

Conventional model



Hole Dia : $\Phi 17.013$

TEZDF-ML type



Hole Dia : $\Phi 17.005$



dia	: $\Phi 17$
tool	: TEZD1700S20F-ML
material	: SS400
Vc	: 75 m/min
f	: 0.15 mm/rev

Improved chip formation and hole accuracy!

Feature 2 Available in three insert types**TEZ type** - General purpose


Φ13.5 - 32.5




- PVD coating grade "**JC8050**"
- Suitable for all types of materials.

**TEZ-S type** - For Stainless Steel, Titanium Alloy



Φ13.5 - 20.5



- PVD coating grade "**JC7515**"
(for high thermal crack resistance & oxidation resistance)
- "**Small margins**" reduce cutting heat generated.
- "**Improved Centripetal centering**" geometry for Smooth drilling and Good chip evacuation.




Centripetal centering geometry

Competitor C
for heat-resistant alloyTEZ type
for heat-resistant alloyTEZ-S type
for heat-resistant alloy


Rifle mark

Good
surface finish**TEZ-H type** - For Mold Steel, Hardened Steel (up to 52 HRC)

Φ13.5 - 20.5




- PVD coating grade "**DH115**"
(for high hardness & heat resistance)
- "**Small margins**" reduce cutting heat generated.
- "**Optimized Tip and Corner geometry**" specially for hardened materials.
- "**Strong Drill Corner Edge**" prevents chipping.

Optimized Tip and Corner geometry
specially for hardened materials

TEZ-H type



Competitor




dia : Φ 16
 insert : TEZ-1600H
 grade : DH115
 material : NAK80(40HRC)
 Vc : 50 m/min
 f : 0.2 mm/rev

PROCEDURE FOR MOUNTING INSERT

1. Removing used insert

Make sure to remove any chips or dust off the tip before removing the used insert. Remove used insert and clean pocket using a brush or air blowing before loading new insert.



2. Loading new insert

Place new insert in pocket, lightly tighten two screws while pressing the top of the insert (see photo). After confirming there is no gap between the drill and insert, tighten the insert screw, starting with the same screw you first lightly tightened, to the recommended torque while still pressing the top of the insert.

**Note:**


Clamp screw need to be changed out after replacing the insert approximately 10 times or if you see any issues with the screws.




Clamp screw

IF USING LATHE MACHINE

1. Check run out of insert O.D. within 0.03mm (off set of center 0.015mm) and flute O.D. of shank side within approx. 0.03mm.
2. Due to large thrust of cutting forces, make sure drill is fully seated in holder.
3. Reduce the cutting speed and feed rate by 20% from standard cutting conditions.




TEZD-M
TYPE


Modular Type


Cat.No.	Stock	DC		Dimensions (mm)						Fig.	Parts	
		Min.	Max.	LF	PL	DCSFMS	MD	C	W		Screw	Wrench
TEZD1400-M8	●	13.5	14.5	38	2.3	13.4	M8	8	12	1	DSW-2045H	A-07
TEZD1500-M8	●	14.6	15.5	40.5	2.4	14	M8	8	12	2		
TEZD1600-M8	●	15.6	16.5	43	2.6	15	M8	8	12	2	TSW-2556H	A-08
TEZD1700-M8	●	16.6	17.5	45.5	2.7	16	M8	8	12	2		
TEZD1800-M8	●	17.6	18.5	48	2.9	17	M8	8	12	2	TSW-2567H	A-08
TEZD1900-M10	●	18.6	19.5	50.5	3.1	18	M10	9	14	2		
TEZD2000-M10	●	19.6	20.5	53	3.2	19	M10	9	14	2	DSW-307H	A-10
TEZD2100-M10	●	20.6	21.5	55.5	3.4	20	M10	9	14	2		
TEZD2200-M10	●	21.6	22.5	58	3.5	21	M10	9	14	2	DSW-309H	A-10
TEZD2300-M10	●	22.6	23.5	60.5	3.7	22	M10	9	14	2		
TEZD2400-M12	●	23.6	24.5	63	3.9	23	M12	11	19	2	TSW-3510H	A-15
TEZD2500-M12	●	24.6	25.5	65.5	4.0	24	M12	11	19	2		
TEZD2600-M12	●	25.6	26.5	68	4.2	25	M12	11	19	2	TSW-3512H	A-15
TEZD2700-M12	●	26.6	27.5	70.5	4.4	26	M12	11	19	2		
TEZD2800-M12	●	27.6	28.5	73	4.5	27	M12	11	19	2	TSW-3512H	A-15
TEZD2900-M16	●	28.6	29.5	75.5	4.7	28	M16	12	22	2		
TEZD3000-M16	●	29.6	30.5	78	4.8	29	M16	12	22	2	TSW-3512H	A-15
TEZD3100-M16	●	30.6	31.5	80.5	5.0	30	M16	12	22	2		
TEZD3200-M16	●	31.6	32.5	83	5.2	31	M16	14	26	2		


Clamp screw	Torque(N·m)
DSW-2045H	0.9
TSW-2556H	1.2
TSW-2567H	1.2
DSW-307H	2.1
DSW-309H	2.1
TSW-3510H	3.0
TSW-3512H	3.0

INDEXABLE DRILL

TEZD Type

TEZDF-MS
TYPE

Holder




Cat.No.	Stock	DC		Dimensions (mm)							Parts	
		Min.	Max.	LU	LH	LS	LF	PL	DCON	DCSFMS	Screw	Wrench
TEZD1400S16F-MS	●	13.5	14.5	53.5	67.5	48	113	2.3	16	20	DSW-2045H	A-07
TEZD1500S20F-MS	●	14.6	15.5	56.7	71.7	50	119	2.4	20	24.9		
TEZD1600S20F-MS	●	15.6	16.5	60.9	76.9	50	124	2.6	20	24.9	TSW-2556H	A-08
TEZD1700S20F-MS	●	16.6	17.5	64.1	81.1	50	128	2.7	20	24.9		
TEZD1800S20F-MS	●	17.6	18.5	68.3	86.3	50	133	2.9	20	24.9	TSW-2567H	A-08
TEZD1900S25F-MS	●	18.6	19.5	71.5	90.5	56	143	3.1	25	32		
TEZD2000S25F-MS	●	19.6	20.5	75.6	95.6	56	148	3.2	25	32	DSW-307H	A-10
TEZD2100S25F-MS	●	20.6	21.5	78.8	99.8	56	152	3.4	25	32		
TEZD2200S25F-MS	●	21.6	22.5	83.0	105.0	56	157	3.5	25	32	DSW-309H	A-10
TEZD2300S25F-MS	●	22.6	23.5	86.2	109.2	56	161	3.7	25	32		
TEZD2400S32F-MS	●	23.6	24.5	90.4	114.4	60	170	3.9	32	41.9	TSW-3510H	A-15
TEZD2500S32F-MS	●	24.6	25.5	93.5	118.5	60	174	4.0	32	41.9		
TEZD2600S32F-MS	●	25.6	26.5	97.7	123.7	60	179	4.2	32	41.9	TSW-3512H	A-15
TEZD2700S32F-MS	●	26.6	27.5	100.9	127.9	60	183	4.4	32	41.9		
TEZD2800S32F-MS	●	27.6	28.5	105.1	133.1	60	188	4.5	32	41.9	TSW-3512H	A-15
TEZD2900S32F-MS	●	28.6	29.5	108.3	137.3	60	192	4.7	32	41.9		
TEZD3000S32F-MS	●	29.6	30.5	112.5	142.5	60	197	4.8	32	41.9	TSW-3512H	A-15
TEZD3100S32F-MS	●	30.6	31.5	115.7	146.7	60	201	5.0	32	41.9		
TEZD3200S32F-MS	●	31.6	32.5	119.8	151.8	60	206	5.2	32	41.9		

Clamp screw	Torque(N·m)
DSW-2045H	0.9
TSW-2556H	1.2
TSW-2567H	1.2
DSW-307H	2.1
DSW-309H	2.1
TSW-3510H	3.0
TSW-3512H	3.0

TEZDF-ML
TYPE

Holder

Through
coolant
hole**5D**
L/D

Cat.No.	Stock	DC		Dimensions (mm)							Parts	
		Min.	Max.	LU	LH	LS	LF	PL	DCON	DCSFMS	Screw	Wrench
TEZD1400S16F-ML	●	13.5	14.5	82.5	99.5	48	145	2.3	16	20	DSW-2045H	A-07
TEZD1500S20F-ML	●	14.6	15.5	87.7	105.7	50	153	2.4	20	24.9		
TEZD1600S20F-ML	●	15.6	16.5	93.9	112.9	50	160	2.6	20	24.9	TSW-2556H	A-08
TEZD1700S20F-ML	●	16.6	17.5	99.1	120.1	50	167	2.7	20	24.9		
TEZD1800S20F-ML	●	17.6	18.5	105.3	126.3	50	173	2.9	20	24.9	TSW-2567H	A-08
TEZD1900S25F-ML	●	18.6	19.5	110.5	133.5	56	186	3.1	25	32		
TEZD2000S25F-ML	●	19.6	20.5	116.6	140.6	56	193	3.2	25	32	DSW-307H	A-10
TEZD2100S25F-ML	●	20.6	21.5	121.8	146.8	56	199	3.4	25	32		
TEZD2200S25F-ML	●	21.6	22.5	128.0	154.0	56	206	3.5	25	32	DSW-309H	A-10
TEZD2300S25F-ML	●	22.6	23.5	133.2	161.2	56	213	3.7	25	32		
TEZD2400S32F-ML	●	23.6	24.5	139.4	168.4	60	224	3.9	32	41.9	TSW-3510H	A-15
TEZD2500S32F-ML	●	24.6	25.5	144.5	174.5	60	230	4.0	32	41.9		
TEZD2600S32F-ML	●	25.6	26.5	150.7	181.7	60	237	4.2	32	41.9	TSW-3512H	A-15
TEZD2700S32F-ML	●	26.6	27.5	155.9	188.9	60	244	4.4	32	41.9		
TEZD2800S32F-ML	●	27.6	28.5	162.1	195.1	60	250	4.5	32	41.9	TSW-3512H	A-15
TEZD2900S32F-ML	●	28.6	29.5	167.3	202.3	60	257	4.7	32	41.9		
TEZD3000S32F-ML	●	29.6	30.5	173.5	209.5	60	264	4.8	32	41.9	TSW-3512H	A-15
TEZD3100S32F-ML	●	30.6	31.5	178.7	215.7	60	270	5.0	32	41.9		
TEZD3200S32F-ML	●	31.6	32.5	184.8	222.8	60	277	5.2	32	41.9		


Clamp screw	Torque(N·m)
DSW-2045H	0.9
TSW-2556H	1.2
TSW-2567H	1.2
DSW-307H	2.1
DSW-309H	2.1
TSW-3510H	3.0
TSW-3512H	3.0

INDEXABLE DRILL

TEZD Type

TEZDF-XL
TYPE

Holder



Cat.No.	Stock	DC		Dimensions (mm)							Parts	
		Min.	Max.	LU	LH	LS	LF	PL	DCON	DCSFMS	Screw	Wrench
TEZD1400S16F-XL	●	13.5	14.5	121.5	135.5	48	181	2.3	16	20	DSW-2045H	A-07
TEZD1500S20F-XL	●	14.6	15.5	130.7	145.7	50	193	2.4	20	24.9		
TEZD1600S20F-XL	●	15.6	16.5	138.9	154.9	50	202	2.6	20	24.9	TSW-2556H	A-08
TEZD1700S20F-XL	●	16.6	17.5	148.1	165.1	50	212	2.7	20	24.9		
TEZD1800S20F-XL	●	17.6	18.5	156.3	174.3	50	221	2.9	20	24.9	TSW-2567H	A-08
TEZD1900S25F-XL	●	18.6	19.5	165.5	184.5	56	237	3.1	25	32		
TEZD2000S25F-XL	●	19.6	20.5	173.6	193.6	56	246	3.2	25	32	DSW-307H	A-10
TEZD2100S25F-XL	●	20.6	21.5	182.8	203.8	56	256	3.4	25	32		
TEZD2200S25F-XL	●	21.6	22.5	191.0	213.0	56	265	3.5	25	32	DSW-309H	A-10
TEZD2300S25F-XL	●	22.6	23.5	200.2	223.2	56	275	3.7	25	32		
TEZD2400S32F-XL	●	23.6	24.5	208.4	232.4	60	288	3.9	32	41.9	TSW-3510H	A-15
TEZD2500S32F-XL	●	24.6	25.5	217.5	242.5	60	298	4.0	32	41.9		
TEZD2600S32F-XL	●	25.6	26.5	225.7	251.7	60	307	4.2	32	41.9	TSW-3512H	A-15
TEZD2700S32F-XL	●	26.6	27.5	234.9	261.9	60	317	4.4	32	41.9		
TEZD2800S32F-XL	●	27.6	28.5	243.1	271.1	60	326	4.5	32	41.9	TSW-3512H	A-15
TEZD2900S32F-XL	●	28.6	29.5	252.3	281.3	60	336	4.7	32	41.9		
TEZD3000S32F-XL	●	29.6	30.5	260.5	290.5	60	345	4.8	32	41.9	TSW-3512H	A-15
TEZD3100S32F-XL	●	30.6	31.5	253.7	300.7	60	355	5.0	32	41.9		
TEZD3200S32F-XL	●	31.6	32.5	261.8	309.8	60	364	5.2	32	41.9		

Clamp screw	Torque(N·m)
DSW-2045H	0.9
TSW-2556H	1.2
TSW-2567H	1.2
DSW-307H	2.1
DSW-309H	2.1
TSW-3510H	3.0
TSW-3512H	3.0


TEZDF-XXL
TYPE

NEW

Holder

Through
coolant
hole

12D
L/D



Cat.No.	Stock	DC		Dimensions (mm)							Parts	
		Min.	Max.	LU	LH	LS	LF	PL	DCON	DCSFMS	Screw	Wrench
TEZD1400S16F-XXL	●	13.5	14.5	177.5	191.5	48	237	2.3	16	20	DSW-2045H	A-07
TEZD1500S20F-XXL	●	14.6	15.5	190.7	205.7	50	253	2.4	20	24.9		
TEZD1600S20F-XXL	●	15.6	16.5	202.9	218.9	50	266	2.6	20	24.9	TSW-2556H	A-08
TEZD1700S20F-XXL	●	16.6	17.5	216.1	233.1	50	280	2.7	20	24.9		
TEZD1800S20F-XXL	●	17.6	18.5	228.3	246.3	50	293	2.9	20	24.9	TSW-2567H	A-08
TEZD1900S25F-XXL	●	18.6	19.5	241.5	260.5	56	313	3.1	25	32		
TEZD2000S25F-XXL	●	19.6	20.5	253.6	273.6	56	326	3.2	25	32	DSW-307H	A-10
TEZD2100S25F-XXL	●	20.6	21.5	266.8	287.8	56	340	3.4	25	32		
TEZD2200S25F-XXL	●	21.6	22.5	279.0	301.0	56	353	3.5	25	32		

Clamp screw	Torque(N·m)
DSW-2045H	0.9
TSW-2556H	1.2
TSW-2567H	1.2
DSW-307H	2.1



INDEXABLE DRILL

TEZD Type

TEZ
TYPE

Insert - Grade JC8050

● Suitable for General Steel





DC	Cat.No.	Stk	A	S	PL	Holder
13.5	TEZ1350	●	11.4	4.5	2.3	TEZD14*
13.6	TEZ1360	●				
13.7	TEZ1370	●				
13.8	TEZ1380	●				
13.9	TEZ1390	●				
14.0	TEZ1400	●				
14.1	TEZ1410	●				
14.2	TEZ1420	●				
14.3	TEZ1430	●				
14.4	TEZ1440	●				
14.5	TEZ1450	●	11.5	4.8	2.4	TEZD15*
14.6	TEZ1460	●				
14.7	TEZ1470	●				
14.8	TEZ1480	●				
14.9	TEZ1490	●				
15.0	TEZ1500	●				
15.1	TEZ1510	●				
15.2	TEZ1520	●				
15.3	TEZ1530	●				
15.4	TEZ1540	●				
15.5	TEZ1550	●	12.4	5.0	2.6	TEZD16*
15.6	TEZ1560	●				
15.7	TEZ1570	●				
15.8	TEZ1580	●				
15.9	TEZ1590	●				
16.0	TEZ1600	●				
16.1	TEZ1610	●				
16.2	TEZ1620	●				
16.3	TEZ1630	●				
16.4	TEZ1640	●				
16.5	TEZ1650	●	13.2	5.5	2.7	TEZD17*
16.6	TEZ1660	●				
16.7	TEZ1670	●				
16.8	TEZ1680	●				
16.9	TEZ1690	●				
17.0	TEZ1700	●				
17.1	TEZ1710	●				
17.2	TEZ1720	●				
17.3	TEZ1730	●				
17.4	TEZ1740	●				
17.5	TEZ1750	●	13.5	5.8	2.9	TEZD18*
17.6	TEZ1760	●				
17.7	TEZ1770	●				
17.8	TEZ1780	●				
17.9	TEZ1790	●				
18.0	TEZ1800	●				
18.1	TEZ1810	●				
18.2	TEZ1820	●				

DC	Cat.No.	Stk	A	S	PL	Holder
18.3	TEZ1830	●	13.5	5.8	2.9	TEZD18*
18.4	TEZ1840	●				
18.5	TEZ1850	●				
18.6	TEZ1860	●	14.2	6.0	3.1	TEZD19*
18.7	TEZ1870	●				
18.8	TEZ1880	●				
18.9	TEZ1890	●				
19.0	TEZ1900	●				
19.1	TEZ1910	●				
19.2	TEZ1920	●				
19.3	TEZ1930	●				
19.4	TEZ1940	●				
19.5	TEZ1950	●				
19.6	TEZ1960	●	15.1	6.5	3.2	TEZD20*
19.7	TEZ1970	●				
19.8	TEZ1980	●				
19.9	TEZ1990	●				
20.0	TEZ2000	●				
20.1	TEZ2010	●				
20.2	TEZ2020	●				
20.3	TEZ2030	●				
20.4	TEZ2040	●				
20.5	TEZ2050	●				
20.6	TEZ2060	●	15.7	6.7	3.4	TEZD21*
20.7	TEZ2070	●				
20.8	TEZ2080	●				
20.9	TEZ2090	●				
21.0	TEZ2100	●				
21.1	TEZ2110	●				
21.2	TEZ2120	●				
21.3	TEZ2130	●				
21.4	TEZ2140	●				
21.5	TEZ2150	●				
21.6	TEZ2160	●	16.6	7.5	3.5	TEZD22*
21.7	TEZ2170	●				
21.8	TEZ2180	●				
21.9	TEZ2190	●				
22.0	TEZ2200	●				
22.1	TEZ2210	●				
22.2	TEZ2220	●				
22.3	TEZ2230	●				
22.4	TEZ2240	●				
22.5	TEZ2250	●				
22.6	TEZ2260	●	17.4	7.5	3.7	TEZD23*
22.7	TEZ2270	●				
22.8	TEZ2280	●				
22.9	TEZ2290	●				
23.0	TEZ2300	●				

TEZ
TYPE**Insert - Grade JC8050**

● Suitable for General Steel



DC	Cat.No.	Stk	A	S	PL	Holder
23.1	TEZ2310	●	17.4	7.5	3.7	TEZD23*
23.2	TEZ2320	●				
23.3	TEZ2330	●				
23.4	TEZ2340	●				
23.5	TEZ2350	●				
23.6	TEZ2360	●	18.2	8.0	3.9	TEZD24*
23.7	TEZ2370	●				
23.8	TEZ2380	●				
23.9	TEZ2390	●				
24.0	TEZ2400	●				
24.1	TEZ2410	●				
24.2	TEZ2420	●				
24.3	TEZ2430	●				
24.4	TEZ2440	●				
24.5	TEZ2450	●	19.1	8.0	4.0	TEZD25*
24.6	TEZ2460	●				
24.7	TEZ2470	●				
24.8	TEZ2480	●				
24.9	TEZ2490	●				
25.0	TEZ2500	●				
25.1	TEZ2510	●				
25.2	TEZ2520	●				
25.3	TEZ2530	●				
25.4	TEZ2540	●				
25.5	TEZ2550	●	19.7	8.5	4.2	TEZD26*
25.6	TEZ2560	●				
25.7	TEZ2570	●				
25.8	TEZ2580	●				
25.9	TEZ2590	●				
26.0	TEZ2600	●				
26.1	TEZ2610	●				
26.2	TEZ2620	●				
26.3	TEZ2630	●				
26.4	TEZ2640	●				
26.5	TEZ2650	●	20.4	8.5	4.4	TEZD27*
26.6	TEZ2660	●				
26.7	TEZ2670	●				
26.8	TEZ2680	●				
26.9	TEZ2690	●				
27.0	TEZ2700	●				
27.1	TEZ2710	●				
27.2	TEZ2720	●				
27.3	TEZ2730	●				
27.4	TEZ2740	●				
27.5	TEZ2750	●	21.2	9.0	4.5	TEZD28*
27.6	TEZ2760	●				
27.7	TEZ2770	●				
27.8	TEZ2780	●				



DC	Cat.No.	Stk	A	S	PL	Holder
27.9	TEZ2790	●	21.2	9.0	4.5	TEZD28*
28.0	TEZ2800	●				
28.1	TEZ2810	●				
28.2	TEZ2820	●				
28.3	TEZ2830	●				
28.4	TEZ2840	●	22.1	9.0	4.7	TEZD29*
28.5	TEZ2850	●				
28.6	TEZ2860	●				
28.7	TEZ2870	●				
28.8	TEZ2880	●				
28.9	TEZ2890	●				
29.0	TEZ2900	●				
29.1	TEZ2910	●				
29.2	TEZ2920	●				
29.3	TEZ2930	●				
29.4	TEZ2940	●	22.5	9.5	4.8	TEZD30*
29.5	TEZ2950	●				
29.6	TEZ2960	●				
29.7	TEZ2970	●				
29.8	TEZ2980	●				
29.9	TEZ2990	●				
30.0	TEZ3000	●				
30.1	TEZ3010	●				
30.2	TEZ3020	●				
30.3	TEZ3030	●				
30.4	TEZ3040	●	23.4	10	5.0	TEZD31*
30.5	TEZ3050	●				
30.6	TEZ3060	●				
30.7	TEZ3070	●				
30.8	TEZ3080	●				
30.9	TEZ3090	●				
31.0	TEZ3100	●				
31.1	TEZ3110	●				
31.2	TEZ3120	●				
31.3	TEZ3130	●				
31.4	TEZ3140	●	24.3	10	5.2	TEZD32*
31.5	TEZ3150	●				
31.6	TEZ3160	●				
31.7	TEZ3170	●				
31.8	TEZ3180	●				
31.9	TEZ3190	●				
32.0	TEZ3200	●				
32.1	TEZ3210	●				
32.2	TEZ3220	●				
32.3	TEZ3230	●				
32.4	TEZ3240	●				
32.5	TEZ3250	●				

INDEXABLE DRILL

TEZD Type

TEZ-S
TYPE**Insert - Grade JC7515**

● for Stainless steel, Titanium alloy



Through
coolant
holeJC7500
Coating

DC	Cat.No.	Stk	A	S	PL	Holder
13.5	TEZ1350S	●	11.4	4.5	2.3	TEZD14*
13.6	TEZ1360S	●				
13.7	TEZ1370S	●				
13.8	TEZ1380S	●				
13.9	TEZ1390S	●				
14.0	TEZ1400S	●				
14.1	TEZ1410S	●				
14.2	TEZ1420S	●				
14.3	TEZ1430S	●				
14.4	TEZ1440S	●				
14.5	TEZ1450S	●	11.5	4.8	2.4	TEZD15*
14.6	TEZ1460S	●				
14.7	TEZ1470S	●				
14.8	TEZ1480S	●				
14.9	TEZ1490S	●				
15.0	TEZ1500S	●				
15.1	TEZ1510S	●				
15.2	TEZ1520S	●				
15.3	TEZ1530S	●				
15.4	TEZ1540S	●				
15.5	TEZ1550S	●	12.4	5.0	2.6	TEZD16*
15.6	TEZ1560S	●				
15.7	TEZ1570S	●				
15.8	TEZ1580S	●				
15.9	TEZ1590S	●				
16.0	TEZ1600S	●				
16.1	TEZ1610S	●				
16.2	TEZ1620S	●				
16.3	TEZ1630S	●				
16.4	TEZ1640S	●				
16.5	TEZ1650S	●	13.2	5.5	2.7	TEZD17*
16.6	TEZ1660S	●				
16.7	TEZ1670S	●				
16.8	TEZ1680S	●				
16.9	TEZ1690S	●				
17.0	TEZ1700S	●				
17.1	TEZ1710S	●				
17.2	TEZ1720S	●				
17.3	TEZ1730S	●				
17.4	TEZ1740S	●				
17.5	TEZ1750S	●	13.5	5.8	2.9	TEZD18*
17.6	TEZ1760S	●				
17.7	TEZ1770S	●				
17.8	TEZ1780S	●				
17.9	TEZ1790S	●				
18.0	TEZ1800S	●				
18.1	TEZ1810S	●				

DC	Cat.No.	Stk	A	S	PL	Holder
18.2	TEZ1820S	●	13.5	5.8	2.9	TEZD18*
18.3	TEZ1830S	●				
18.4	TEZ1840S	●				
18.5	TEZ1850S	●				
18.6	TEZ1860S	●	14.2	6.0	3.1	TEZD19*
18.7	TEZ1870S	●				
18.8	TEZ1880S	●				
18.9	TEZ1890S	●				
19.0	TEZ1900S	●				
19.1	TEZ1910S	●				
19.2	TEZ1920S	●				
19.3	TEZ1930S	●				
19.4	TEZ1940S	●				
19.5	TEZ1950S	●				
19.6	TEZ1960S	●	15.1	6.5	3.2	TEZD20*
19.7	TEZ1970S	●				
19.8	TEZ1980S	●				
19.9	TEZ1990S	●				
20.0	TEZ2000S	●				
20.5	TEZ2050S	●				

TEZ-H
TYPE**Insert - Grade DH115**

● for Mold steel, Hardened steel (up to 52 HRC)

Through
coolant
hole**DH**
Coating

DC	Cat.No.	Stk	A	S	PL	Holder
13.5	TEZ1350H	●	11.4	4.5	2.3	TEZD14*
14.0	TEZ1400H	●				
14.1	TEZ1410H	●				
14.2	TEZ1420H	●				
14.3	TEZ1430H	●				
14.5	TEZ1450H	●				
15.0	TEZ1500H	●	11.5	4.8	2.4	TEZD15*
15.1	TEZ1510H	●				
15.2	TEZ1520H	●				
15.3	TEZ1530H	●				
15.5	TEZ1550H	●				
15.8	TEZ1580H	●	12.4	5.0	2.6	TEZD16*
15.9	TEZ1590H	●				
16.0	TEZ1600H	●				
16.1	TEZ1610H	●				
16.2	TEZ1620H	●				
16.3	TEZ1630H	●				
16.5	TEZ1650H	●	13.2	5.5	2.7	TEZD17*
17.0	TEZ1700H	●				
17.1	TEZ1710H	●				
17.5	TEZ1750H	●	13.5	5.8	2.9	TEZD18*
17.6	TEZ1760H	●				
17.7	TEZ1770H	●				
17.8	TEZ1780H	●				
18.0	TEZ1800H	●				
18.1	TEZ1810H	●				
18.5	TEZ1850H	●				

DC	Cat.No.	Stk	A	S	PL	Holder
19.0	TEZ1900H	●	14.2	6.0	3.1	TEZD19*
19.5	TEZ1950H	●				
19.8	TEZ1980H	●	15.1	6.5	3.2	TEZD20*
20.0	TEZ2000H	●				
20.2	TEZ2020H	●				
20.5	TEZ2050H	●				
		●				

■ Recommended Cutting Conditions

● TEZ type JC8050

Material	Structural Steel , Carbon Steel below 280HB	Alloy Steel 280-350HB	Tool Steel below 255HB
Vc (m/min)	75 - 90	70 - 90	70 - 90
f (mm/rev)	0.30 - 0.35	0.22 - 0.25	0.22 - 0.25

Material	Stainless Steel	Grey Cast Iron	Nodular Cast Iron
Vc (m/min)	45	85 - 110	60 - 90
f (mm/rev)	0.25	0.30 - 0.40	0.15 - 0.28

● TEZ-S type JC7515

Material	Titanium Alloy	Stainless Steel
Vc (m/min)	35 - 60	45 - 80
f (mm/rev)	0.15 - 0.20	0.15 - 0.20

● TEZ-H type DH115

Material	Mold Steel 30 - 36HRC	Mold Steel 38 - 43HRC	Hardened Steel 42 - 52HRC
Vc (m/min)	50 - 70	40 - 60	40 - 60
f (mm/rev)	0.15 - 0.25	0.10 - 0.20	0.10 - 0.15

Note)

1. Use water-soluble coolant.
2. Adjust cutting conditions according to machine rigidity or work rigidity.
3. When using -XL (8D) type , reduce rpm & Vf by 20% from standard cutting conditions.
Pre-drilling of guide-hole (depth : 0.5D) is recommended.

GRADES



DIJET GRADES FOR MILLING TOOLS

Material		P					M					K			
Application		Finishing ← → Roughing					Finishing ← → Roughing					Finishing ← → Roughing			
ISO		P01	P10	P20	P30	P40	M01	M10	M20	M30	M40	K01	K10	K20	K30
PVD coating	DH	DH103 DH108 DH110 DH111 DH115						DH108 DH111				DH102 DH103 DH108 DH110 DH111 DH115			
	DP		DP117		DP150										
	DS1 for Titanium						DS108								
	DS2 for Heat resistant alloy							DS217 DS218		DS250					
	JC8000		JC8015 JC8118		JC8050		JC8015 JC8118 JC8050					JC8015 JC8118			
	JC7500						JC7515 JC7550 JC7560								
	JC5000		JC5015 JC5118 JC5240 JC5040				JC5015 JC5118					JC5015 JC5240			
DLC coating															
Diamond coating															
Uncoated												KT9 FZ15			
Cermet			CX75 CX90				CX75					CX75			
Super-High pressure sintered	CBN											JBN795 JBN500 JBN245			
	Diamond														


Material		N				S				H			
Application		Finishing		Roughing		Finishing		Roughing		Finishing		Roughing	
ISO		N01	N10	N20	N30	S01	S10	S20	S30	H01	H10	H20	H30
PVD coating	DH					DH102				DH102			
						DH103				DH103			
						DH108							
						DH110				DH110			
						DH111							
						DH115							
	DP										DP117		
PVD coating	DS1 for Titanium					DS108							
						DS118							
						DS150							
PVD coating	DS2 for Heat resistant alloy												
						DS217							
						DS218							
PVD coating						DS250							
	JC8000					JC8015				JC8015			
						JC8118				JC8118			
PVD coating						JC8050							
	JC7500					JC7515							
						JC7518							
PVD coating						JC7550							
						JC7560							
	JC5000					JC5015						JC5118	
PVD coating						JC5118							
DLC coating		DN103											
		JC20003											
			JC20015										
Diamond coating		JC10000											
Uncoated		FZ05								FZ05			
		KT9											
		FZ15				FZ15				FZ15			
		FC18											
Cermet													
Super-High pressure sintered	CBN									JBN795			
										JBN500			
Super-High pressure sintered	Diamond	JDA30											
		JDA10											







SPARE PARTS





®


SPARE PARTS



Geometry	Cat.No.	Dimensions						Wrench size
		A	B	C	D	E	α°	
	ADS-513	7.8	M5×0.5	13.0	5.0	—	—	AD-2080
	ADS-514	5.6	M5×0.5	14.5	6.5	—	—	AD-2080

Geometry	Cat.No.	Dimensions						Wrench size	Torque (N·m)
		A	B	C	D	E	α°		
	CSW-206	3.5	M2.5×0.45	5.0	2.4	—	55	T-8	0.9
	CSW-406H	5.0	M4×0.7	6.0	3.6	—	43	T-15	3.6
	CSW-407	5.0	M4×0.7	7.0	3.6	—	43	T-15	3.6
	CSW-408H	5.0	M4×0.7	8.0	3.6	—	43	T-15	3.6
	CSW-513H	7.0	M5×0.8	13.0	4.4	—	63	T-20	5.5
	CSW-510	6.4	M5×0.8	11.0	4.5	—	43	T-20	5.5
	DSW-1840H	2.5	M1.8×0.35	4.0	2.0	—	55	T-6	0.4
	DSW-2045H	3.0	M2×0.4	4.5	2.3	—	60	T-7	0.5
	DSW-2563H	3.45	M2.5×0.45	6.3	2.6	—	55	T-8	1.1
	DSW-306H	4.3	M3×0.5	6.5	3.2	—	55	T-10	1.8
	DSW-307	4.3	M3×0.5	7.5	2.8	—	55	T-10	1.4
	DSW-307H	4.3	M3×0.5	7.6	3.2	—	55	T-10	2.1
	DSW-309H	4.3	M3×0.5	9.0	3.2	—	55	T-10	2.1
	DSW-4075H	5.2	M4×0.7	7.5	3.5	—	55	T-15	3.6
	DSW-408	6.0	M4×0.7	8.5	3.6	—	55	T-15	3.6
	DSW-4085	5.3	M4×0.7	8.5	3.5	—	55	T-15	3.6
	DSW-410H	5.3	M4×0.7	10.0	3.7	—	55	T-15	3.6
	DSW-4510H	6.8	M4.5×0.75	10.0	4.7	—	55	T-20	6.0
	DSW-4512H	6.8	M4.5×0.75	12.5	5.2	—	55	T-20	6.0
	DSW-509	7.0	M5×0.8	9.5	4.9	—	55	T-20	6.1
	DSW-511H	7.0	M5×0.8	11.5	4.9	—	55	T-20	6.1
	ESW-206	3.6	M2.5×0.45	6.0	2.0	—	60	T-8	0.9
	ESW-304	4.0	M3×0.5	4.5	2.0	—	55	T-8	1.4
	ESW-306	4.0	M3×0.5	6.0	2.0	—	55	T-8	1.4
	ESW-307	4.0	M3×0.5	7.5	2.0	—	55	T-8	1.4
	ESW-405	5.3	M4×0.7	5.9	2.7	—	55	T-15	3.1
	ESW-406	5.3	M4×0.7	6.6	2.7	—	55	T-15	3.1
	ESW-408	5.3	M4×0.7	8.0	2.7	—	55	T-15	3.1
	ESW-410	5.3	M4×0.7	10.0	2.7	—	55	T-15	3.1
	ESW-507	6.8	M5×0.8	7.5	3.4	—	55	T-25	5.5
	ESW-508	6.8	M5×0.8	8.2	3.4	—	55	T-25	5.5
	ESW-510	6.8	M5×0.8	10.0	3.4	—	55	T-25	5.5
	FSW-2005H	2.5	M2×0.25	5.0	1.3	—	40	T-6	0.5
	FSW-2506H	3.0	M2.5×0.35	6.6	1.5	—	40	T-7	0.9
	FSW-3007H	3.8	M3×0.35	8.1	2.0	—	40	T-8	1.2
	FSW-3509H	4.7	M3.5×0.6	9.6	2.3	—	40	T-10	2.0
	FSW-4013H	5.8	M4×0.7	13.5	3.3	—	40	T-15	3.0
	FSW-5016H	6.8	M5×0.8	16.4	3.2	—	40	T-20	4.0
	FSW-6020	8.5	M6×1.0	20.0	4.3	—	40	T-30	6.0
	FSW-8025	11.0	M8×1.25	25.0	5.5	—	40	T-40	6.0
	FSW-8025S/KSW-8025	11.0	M8×1.25	25.0	5.5	—	40	T-30	6.0
	HSW-614H	10.0	M6×1.0	15.0	7.3	—	60	T-30	7.5


Geometry	Cat.No.	Dimensions						Wrench size	Torque (N•m)
		A	B	C	D	E	α°		
	TSW-2250	3.1	M2.2×0.45	5.0	2.3	—	60	T-7	0.6
	TSW-2556H	3.6	M2.5×0.45	5.6	2.7	—	60	T-8	1.1
	TSW-2567H	3.6	M2.5×0.45	6.7	2.7	—	60	T-8	1.1
	TSW-307H	4.3	M3×0.5	7.6	3.1	—	60	T-10	2.1
	TSW-3509H	5.3	M3.5×0.6	9.0	4.5	—	60	T-15	3.0
	TSW-3510H	5.3	M3.5×0.6	10.0	4.5	—	60	T-15	3.0
	TSW-3512H	5.3	M3.5×0.6	11.5	4.5	—	60	T-15	3.0
	TSW-408	5.5	M4×0.7	8.0	3.3	—	60	T-15	3.1
	TSW-410H	5.3	M4×0.7	10.0	3.6	—	60	T-15	3.5
	TSW-511	7.0	M5×0.8	11.0	5.0	—	60	T-20	5.5
	TSW-612	8.5	M6×1.0	12.0	4.8	—	60	T-25	7.5
	TSW-614H	8.5	M6×1.0	14.0	6.2	—	60	T-25	7.5


Geometry	Cat.No.	Dimensions						Wrench size	Torque (N•m)
		A	B	C	D	E	F		
	HCS4-10	7.0	M4×0.7	14.0	4.0	3.0	—	—	—
	HCS5-10	8.5	M5×0.8	15.0	5.0	4.0	—	—	—
	HSB-10	17.0	M10×1.5	56.0	10.0	8.0	13	—	—
	HSB-12	18.0	M12×1.75	62.0	12.0	10.0	—	—	—







Geometry	Cat.No.	Dimensions						Wrench size	Torque (N•m)
		A	B	C	D	E	F		
	SSW-535	6.3	M5×0.5	7.0	3.1	3.5	—	—	6.5


Geometry	Cat.No.	Dimensions						Wrench size	Torque (N•m)
		A	B	C	D	E	F		
	LS-101	4.6	M6×1.0	16.0	6.5	6.5	3.0	—	6.0
	LS-106	4.6	M6×1.0	14.5	6.5	5.0	3.0	—	6.0
	LS-107	4.6	M6×1.0	13.0	5.0	5.0	3.0	—	6.0
	LS-109	5.5	M7×0.75	19.0	7.5	8.0	—	T-25	7.0
	LS-110	4.8	M6×0.75	22.0	8.0	8.0	—	T-15	6.0



SPARE PARTS


Geometry	Cat. No	Dimensions						Wrench size	Torque (N•m)
		A	B	C	D	E	F		
	LS-113	3.7	No.10-32UNF	10.2	4.5	4.1	2.4	—	—

Geometry	Cat. No	Dimensions						Wrench size	Torque (N•m)
		A	B	C	D	E	F		
	SLS-3	6.0	M8×1.0	20.0	8.0	8.0	4.0	—	8.0

Geometry	Cat. No	Dimensions					Wrench size
		A	B	C	D	E	
	LW-020	52.0	15.0	—	—	2.0	—
	LW-025	59.5	18.0	—	—	2.5	—
	LW-030	67.0	20.0	—	—	3.0	—
	LW-035	71.5	22.5	—	—	3.5	—
	LW-040	75.0	25.0	—	—	4.0	—
	LW-050	80.0	28.0	—	—	5.0	—
	A-030	—	60.0	80.0	28.0	3.0	—
	A-07SD	4.0	60.0	80.0	—	—	T-7
	A-08SD	4.0	70.0	80.0	—	—	T-8
	A-10SD	4.0	70.0	95.0	—	—	T-10
	A-20SD	5.0	90.0	105.0	—	—	T-20
	A-25SD	5.0	100.0	105.0	—	—	T-25
	A-06	1.7	34.5	15.0	15.0	—	T-6
	A-07	2.0	34.5	15.0	15.9	—	T-7
	A-08	2.3	39.0	19.0	19.0	—	T-8
	A-10	3.0	40.0	40.0	20.0	—	T-10
	A-15	3.5	45.0	40.0	20.0	—	T-15
	A-20W	4.0	45.0	40.0	20.0	—	T-20
	A-15T	4.0	100.0	80.0	26.0	—	T-15
	A-20	4.0	100.0	100.0	32.0	—	T-20
	A-20L	5.5	200.0	100.0	32.0	—	T-20
	A-25	4.5	100.0	100.0	32.0	—	T-25
	A-27	5.5	100.0	100.0	32.0	—	T-27
	A-30	6.0	100.0	100.0	32.0	—	T-30
	AD-2080	2.0	45.0	35.0	—	—	—

Geometry	Cat. No	Dimensions						Wrench size	Torque (N•m)
		A	B	C	D	E	F		
	RSW-05008	—	M5×0.8	8.0	—	—	—	T-10	—

Geometry	Cat. No	Dimensions							Wrench size
		A	B	C	D	E	F	G	
	DCM-1	M5×0.8	13.8	13.8	6.8	2.0	8.5	2.5	—
	DCM-5	M6×1.0	17.0	16.5	8.9	2.0	10.0	3.0	—
	DCM-17	M4.5×0.75	11.7	18.0	10.5	5.0	10.0	—	T-20
	DCM-18	M3.5×0.6	10.0	13.0	7.6	3.0	7.2	—	T-15

Geometry	Cat. No	Dimensions					
		A	B	C	D	E	F
	DCM-2	M8×1.0	10.0	19.0	11.0	6.0	13.5

Shape	Cat. No
	MOLY

INDEX



INDEX

Cat.No	Name	Page
--------	------	------

A

A-06	Wrench for GMX/MXG07 PME MPM BNM/RNM06	A075 A076 A107 A108 A144 A154
A-07	Wrench for BNM08 RNM08 TLZD TEZD	A144 A154 A214 A215 A223~227
A-08	Wrench for MQT GMX/MXG QXP/MQX BNM/RNM10 XFG/MXF AMX/MAM TLZD TEZD	A032 A081~083 A092~094 A144 A154 A168 A169 A192 A193 A214 A215 A223~227
A-08SD	Wrench for SDH	A175
A-10	Wrench for SKG09 EXSKS05 EXSAP11 TLZD TEZD	A054 A055 A062 A063 A116~118 A144 A154 A214 A215 A223~227
A-15	Wrench for EXSKS07 EXSAP17 SSV BNM/RNM12&16 SDH MAL/ALXM TLZD TEZD	A027~030 A064 A065 A121 A122 A136 A137 A144 A145 A154 A175 A194 A195 A214 A215 A223~227
A-15T	Wrench for SKG10 EXSKS07 EXSAP17 SSV/SSVL HDM ALX	A042 A043 A064 A120 A136 A138 A174 A194
A-20	Wrench for SKG14 EXSKS09 EXSIX HDM HEP	A045 A066 A131 A174 A186
A-20W	Wrench for BNM/RNM20	A027~030 A145 A155
A-30	Wrench for BNM/RNM25 BNM/RNM30&32	A027~030 A145 A155
ALX○○○○○R-22	AERO CHIPPER	A194
ALXM○○○○○S○○	AERO CHIPPER	A194
AMX-○○○○○R-○○	AERO CHIPPER MINI	A192

B

B-○○	Blade for Torque Control Wrench	A150
BNM□-○○○○○○○S-S○○C	MIRROR BALL	A144
BNM□-○○○○○○○T-S○○C	MIRROR BALL	A144
BNM-○○○	Insert for MIRROR BALL - BNM/MBX type	A148 A149
BNM-○○○-S	Insert for MIRROR BALL - BNM/MBX type	A149
BNM-○○○-SS	Insert for MIRROR BALL - BNM/MBX type	A147
BNM-○○○-TG	Insert for MIRROR BALL - BNM/MBX type	A146
BNM-○○○-TS	Insert for MIRROR BALL - BNM/MBX type	A146

C

CSW-408H	Screw for SDH	A175
CSW-513H	Screw for SKG14 EXSKS09 EXSIX PNS-REBORN	A045 A066 A131 A183

D

DCM-17	Clamp set for HDM HEP	A174 A186
DCM-18	Clamp set for HDM	A174
DS-○○	Spanner	A145 A155
DSW-1840H	Screw for PME, MPM	A107 A108
DSW-2045H	Screw for TLZD TEZD	A214 A215 A223~227
DSW-2563H	Screw for MQT MQX QXP	A032 A092~094
DSW-306H	Screw for MSG09	A054
DSW-307H	Screw for SKG09 MSG09 TLZD TEZD	A054 A055 A214 A215 A223~227
DSW-309H	Screw for TLZD TEZD	A214 A215 A223~227
DSW-4075H	Screw for SSV SSVL ALXM	A136~138 A195
DSW-4085	Screw for ALX ALXM MAL	A194 A195
DSW-410H	Screw for HDM SDH	A174 175
DSW-4512H	Screw for HDM HEP	A174 A175 A186

Cat.No	Name	Page
--------	------	------

E

ENMU07T207ZER-○○	Insert for QM GII- GMX/MXG07 type	A077
ENMQ100312ZER	Insert for QMMAX GII- GMX/MXG type	A084
ENMU100○12ZER-○○	Insert for QMMAX GII- GMX/MXG type	A084
EOHW0602○○ZTR	Insert for QM MILL - PME/PME-LS/MPM type	A109
EOMT0602○○ZER	Insert for QM MILL - PME/PME-LS/MPM type	A109
EOMW060210ZER	Insert for QM MILL - PME/PME-LS/MPM type	A109
EPHW100316ZTR	Insert for QM MAX - MQX/QXP type	A096
EPMT1003○○ZER	Insert for QM MAX - MQX/QXP type	A096
EPMW100312Z□R	Insert for QM MAX - MQX/QXP type	A096
EXSAP-○○○○R-○○	EXTREME SAP 17	A120
EXSAP-○○○○-○○-S○○	EXTREME SAP 17	A121
EXSAP-○○○○-11-○○-S○○+A	EXTREME SAP 11	A117
EXSAP-○○○○R-11-○○	EXTREME SAP 11	A116
EXSIX-○○○○R-○○	SHOULDER SIX	A131
EXSKS-○○○○R-○○	SKS EXTREME 09	A066
EXSKS-○○○○R-07-○○	SKS EXTREME 07	A064
EXSKS-○○○○-07-○○-S○○	SKS EXTREME 07	A065
EXSKS-○○○○R-05-○○	SKS EXTREME 05	A062

F

FRM-○○○-R○○	Insert for MIRROR RADIUS ENDMILL - RNM/MRX type	A156 A157
FSW-2005H	Screw for BNM6 RNM6	A144 A154
FSW-2506H	Screw for BNM8 RNM8	A144 A154
FSW-3007H	Screw for BNM10 RNM10	A144 A145 A154 A155
FSW-4013H	Screw for BNM16 RNM16	A027~030 A145 A155
FSW-5016H	Screw for BNM20 RNM20	A027~030 A145 A155
FSW-6020	Screw for BNM25 RNM25	A027~030 A145 A155

G

GMX○○○○-07-○○-S○○+A	QM GII	A076
GMX-○○○○-○○-S○○	QMMAX GII	A082
GMX-○○○○R-○○	QMMAX GII	A081

H

HDM-○○○○-○○R-○○	SUPER DIEMSTER	A174
HEP-○○○○R-○○-○○	HEPTA MILL	A186
HRM-○○○-R○○	Insert for MIRROR RADIUS ENDMILL - RNM/MRX type	A158

K

KRM-○○○-R10-BR○○	Insert for MIRROR BARREL - MRX type	A027
KSW-3509	Screw for BNM12 RNM12	A144 A145 A154 A155
KSW-8025	Screw for BNM30 RNM30	A027 A030 A145 A155

INDEX

Cat.No	Name	Page
--------	------	------

L

LRM-○○○-R○○-BR○○	Insert for MIRROR BARREL - MBX type	A030
------------------	-------------------------------------	------

M

M10×1.5×25	ARBOR SET BOLT for EXSKS09 EXSIX HEP	A066 A131 A186
M10×1.5×35	ARBOR SET BOLT for SKG10/14	A042 A045
M12×1.75×30	ARBOR SET BOLT for SKG09/10 EXSAP11 EXSAP17 EXSIX SSV PNS	A042 A054 A116 A120 A131 A136 A182
M12×1.75×35	ARBOR SET BOLT for SKG14 EXSKS07	A045 A064
M12×1.75×40	ARBOR SET BOLT for EXSKS09 HEP	A066 A186
M16×2×25	ARBOR SET BOLT for EXSKS07 EXSAP17	A064 A120
M16×2×30	ARBOR SET BOLT for EXSIX SSV	A131 A136
M16×2×45	ARBOR SET BOLT for EXSKS09	A066
M20×2.5×40	ARBOR SET BOLT for EXSAP17 EXSIX SSV	A120 A131 A136
M20×2.5×45	ARBOR SET BOLT for EXSKS09 HEP	A066 A186
MAGNETISER	MAGNETISER	A109
MAL-○○○○-M○○	AERO-CHIPPER	A194
MAM-○○○○-M○○	AERO-CHIPPER	A193
MBX-○○○-M○○	MIRROR BALL	A030 A145
MEX-○○○○-07-M○○	SKS EXTREME 07	A064
MEX-○○○○-05-M○○	SKS EXTREME 05	A062
MPM-○○○○-M○○	QMMILL	A108
MPT-○○○○A00-M○○	HIGH PRECISION QMMILL	A108
MQT-○○○○A○○-M○○	HIGH PRECISION QMMAX	A032
MQX-○○○○-M○○	QMMAX	A094
MRX-○○○-M○○	MIRROR RADIUS	A027 A155
MSG-○○○○-09-M○○	SKS-GII 09	A054
MSG-○○○○-10-M○○	SKS-GII 10	A043
MSN-M○○-○○○○-S○○C	MSN Carbide Modular Head Holder	A208~A213
MSX-○○○○-11-M○○	EXTREME SAP 11	A118
MSX-○○○○-M○○	EXTREME SAP 17	A122
MTP-○○○-M○○	MIRROR BARREL	A028 A029
MXF-○○○○-M○○	DIEMASTER 5G	A169
MXG-○○○○-07-M○○	QM GII	A075
MXG-○○○○-M○○	QMMAX GII	A083

P

PME○○○○S○○	QMMill	A107
PME○○○○S○○-LS	QMMill	A107
PNS-○○○○R-19-○○	PNS-REBORN	A182
PNMU190720AER-○○	Insert for PNS-REBORN	A183

Q

QXPS○○○○S○○+A	QMMAX	A093
QXP-○○○○R	QMMAX	A092

Cat.No	Name	Page
--------	------	------

R

RD□T○○○○M□□	Insert for SUPER DIEMSTER - HDM/SDH type	A176
RDGT○○□○MOF-AL	Insert for SUPER DIEMSTER - HDM/SDH type	A176
RDMT○○○○MOE-ML	Insert for SUPER DIEMSTER - HDM/SDH type	A176
RDMW○○□○M□□	Insert for SUPER DIEMSTER - HDM/SDH type	A176
RNM□-○○○○○○S-S○○C	MIRROR RADIUS ENDMILL	A154
RNM□-○○○○○○U-S○○C	MIRROR RADIUS ENDMILL	A154
RNM-○○○-R○○	Insert for MIRROR RADIUS ENDMILL - RNM/MRX type	A159

S

SDET090312ZDER-SM	Insert for SKS-GII 09 type	A056
SDEW090312ZER	Insert for SKS-GII 09 type	A056
SDH-○○○○-R○○-M○○	SUPER DIEMSTER	A174
SKG-○○○○-○○-09-S○○	SKS-GII 09	A055
SKG-○○○○R-09-○○	SKS-GII 09	A054
SKG-○○○○R-10-○○	SKS-GII 10	A042
SKG-○○○○R-14-○○	SKS-GII 14	A045
SPET100415ZPER-SM	Insert for SKS-GII 10 type	A044
SPMT100415ZP○R-PM	Insert for SKS-GII 10 type	A044
SPMT100415ZP○R-SM	Insert for SKS-GII 10 type	A044
SPMT140520ZP○R-PM	Insert for SKS-GII 14 type	A046
SPNW100415ZTR	Insert for SKS-GII 10 type	A044
SPNW140515ZTR	Insert for SKS-GII 14 type	A046
SSV-○○○○-○○○-S○○+A	SIC-EVO	A137
SSV-○○○○-M○○	SIC-EVO	A136
SSV-○○○○R-○○	SIC-EVO	A136
SSVL-○○○○R-○○-○○	SIC-EVO LONG	A138

INDEX

Cat.No	Name	Page
--------	------	------

T

TEZ○○○○	Insert for TA-EZ Drill - TEZD type	A228 A229
TEZ○○○○S	Insert for TA-EZ Drill - TEZD type	A230
TEZ○○○○H	Insert for TA-EZ Drill - TEZD type	A231
TEZD○○○○-M○	TA-EZ Drill - Modular type	A223
TEZD○○○○S○○-ML	TA-EZ Drill 5D	A225
TEZD○○○○S○○-MS	TA-EZ Drill 3D	A224
TEZD○○○○S○○-XL	TA-EZ Drill 8D	A226
TEZD○○○○S○○-XXL	TA-EZ Drill 12D	A227
TLZ○○○○	Insert for TLZD Drill - TLZD type	A216
TLZD○○○○-M○	TLZD Drill - Modular type	A215
TLZD○○○○S○○-SS	TLZD Drill	A217
TNM-○○○○-NR○BR○○	Insert for MIRROR BARREL - MTP type	A228
TPM-○○○-NR2T30BR○○○	Insert for MIRROR BARREL - MTP type	A229
TQC-○○	Torque Control Wrench	A150
TSW-204H	Screw for GMX07/MXG07	A075 A076
TSW-2556H	Screw for MQT QXPS MQX SDH MAM TLZD TEZD	A032 A093 A094 A175 A193 A214 A215 A223~227
TSW-2567H	Screw for GMX MXG MXF/XFG AMX/MAM TLZD TEZD	A081~A083 A168 A169 A192 A193 A214 A215 A223~227
TSW-307H	Screw for EXSKS05 EXSAP11	A062~063 A116~118
TSW-3509H	Screw for SKG10	A042~043
TSW-3510H	Screw for TLZD, TEZD	A214 A215 A223~227
TSW-3512H	Screw for TLZD TEZD	A214 A215 A223~227
TSW-410H	Screw for EXSKS07 EXSAP17 EXTDM	A064~065 A120~122

W

WNHU04T310ZER	Insert for DIEMASTER 5G - MXF/XFG type	A169
WNMU050320ZER-○○	Insert for SKS EXTREME - EXSKS 05 type	A063
WNMU070620ZER-○○	Insert for SKS EXTREME - EXSKS 07 type	A064
WNMU090○○○ZER-○○	Insert for SKS EXTREME - EXSKS 09 type	A067

X

XDHW080610ZER-W	Insert for HEPTA MILL - HEP type	A186
XDM○080620Z○R	Insert for HEPTA MILL - HEP type	A186
XDMT080620ZER-ML	Insert for HEPTA MILL - HEP type	A186
XDMW080635ZTR-S	Insert for HEPTA MILL - HEP type	A186
XFG-○○○○R-○○	DIEMASTER 5G	A168
XOET0803○○PDFR	Insert for AERO CHIPPER - AMX/MAM type	A193
XOGT1605○○PD○R	Insert for AERO CHIPPER - ALX/MAL type	A195
XPH□100308ZER-R	Insert for HIGH PRECISION QM MAX - MQT type	A033

Cat.No	Name	Page
--------	------	------

Y

YCMU0907○○ZER-PM	Insert for SHOULDER SIX - EXSIX type	A132
YOHWO602○○ZER-12	Insert for QM MILL - PME/PME-LS/MPM MPT type	A109
YPHW1003○○ZER-15	Insert for QM MAX - MQX/QXP MQTtype	A033 A096
YPHW100308ZER-F	Insert for QM MAX - MQX/QXP MQTtype	A033 A096
YPHW100308ZTR-F1	Insert for QM MAX - MQX/QXP MQTtype	A033 A096
YPHW100320ZER-24	Insert for QM MAX - MQX/QXP type	A096

Z

ZNGU1105○○ZER○○	Insert for EXTREME SAP - EXSAP/MSX 11 type	A119
ZNGU1709○○ZER○○	Insert for EXTREME SAP - EXSAP/MSX 17 type	A123
ZOET1605○○ZFR-NL	Insert for SIC-EVO - SSV type	A139
ZOMT0602○○ZER-PL	Insert for QM MILL - PME/PME-LS/MPM MPT type	A109
ZOMT1605○○ZER-PM	Insert for SIC-EVO - SSV/SSVL type	A139
ZPMT1003○○ZER-NL	Insert for QM MAX - MQX/QXP type	A033 A096
ZPMT1003○○ZER-PL	Insert for QM MAX - MQX/QXP MQTtype	A033 A096
ZPMT1003○○ZER-SL	Insert for QM MAX - MQX/QXP type	A033 A096

PLANTS & OFFICES IN JAPAN



● OSAKA PLANT



● MIE POWDER PLANT (raw materials)



● MIE PLANT (carbide blanks)



● MIE PLANT (tools)



● TONDABAYASHI PLANT (raw materials)



Break Through



DIJET INDUSTRIAL CO., LTD.

Headquarters 2-1-18, Kami-Higashi, Hirano-ku, Osaka 547-0002, Japan Phone: 81-6-6791-6781 Fax: 81-6-6793-1221



JQA-2089



JQA-EM1580

DIJET GmbH (Europe)

Immermannstr.9 40210 Düsseldorf, Germany
Phone. 49-211-50088820, 50088822 Fax. 49-211-50088823

DIJET INDUSTRIAL CO., LTD. (Bangkok Representative Office)

699 Srinakarindr Road, Modernform Tower 15th Floor,
Kweang Suanluang, Khet Suanluang, Bangkok 10250, Thailand
Phone. 66-2-722-8258, 8259 Fax. 66-2-722-8260

DIJET INDUSTRIAL CO., LTD. (Shanghai Representative Office)

Room No.712 Tomson Commercial Building., 710 Dongfang Rd.,
Shanghai 200122, China
Phone. 86-21-5058-1698 Fax. 86-21-5058-1699

DIJET INDUSTRIAL CO., LTD. (Guandong Representative Office)

Rm.903, No.98, Zhenan East-Road, Changan Town, Dongguan City,
Guangdong Province 523850, China
Phone. 86-769-8188-6001 Fax. 86-769-8188-6608

DIJET INDUSTRIAL CO., LTD. (Chengdu Office)

RM.No.2015, No.1BLDG.A-B Stand, Hi-Tech Incubation Garden, No.1480
Tianfu Avenue North, Hi-Tech District, Chengdu City, Sichuan, P.R.CHINA
Phone. 86-28-8511-4585 Fax. 86-28-8511-2758

DIJET INDUSTRIAL CO., LTD. (Wuhan Office)

B-2513, Jiayu Jianyin Business Masion, No.10 Chuangye Road,
Wuhan Eco. & Tech. Development Zone, Wuhan City, Hubei 430056, China
Phone. 86-27-8773-8919 Fax. 86-27-8773-8959

DIJET INDUSTRIAL CO., LTD. (Mumbai Representative Office)

305, Mahant Chambers Plot No.315, Road No.34, Wagle Estate
MIDC Industrial Area, Thane (W),400604,India
Phone. 91-22-4012-1231 Fax.91-22-4024-0919

DIJET Incorporated (U.S.A.)

45807 Helm Street, Plymouth, MI 48170 U.S.A.
Phone. 1-734-454-9100 Fax. 1-734-454-9395